



OpenText™ Professional Performance Engineering

Error Codes Guide

May 2025

Legal Notices

© Copyright 2025 Open Text.

The only warranties for products and services of Open Text and its affiliates and licensors ("Open Text") are as may be set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Open Text shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Disclaimer

Certain versions of software accessible here may contain branding from Hewlett-Packard Company (now HP Inc.) and Hewlett Packard Enterprise Company. This software was acquired on September 1, 2017 by Micro Focus and is now offered by OpenText, a separately owned and operated company. Any reference to the HP and Hewlett Packard Enterprise/HPE marks is historical in nature, and the HP and Hewlett Packard Enterprise/HPE marks are the property of their respective owners.

Error code	Handle	Message\Additional information
\$ _protocolid\$.h		
-301999	\$ _protocolid\$ DEMO_TEXT_RESOURCE	This is a demo text resource for \$ _protocolid\$
AlertEngineRes.h		
-58999	ALERT_ENGINE_MSG_FORMATTED_MSG_HEADER	\n-----\n\n message START ----- \n\nProfile Name: %1\nAlert Name: %2\nSeverity: %3\n\n
-58998	ALERT_ENGINE_MSG_FORMATTED_MSG_FOOTER	\nUser Message: %1\nAdditional Details: \n-----\n\n message END ----- \n\n
-58997	ALERT_ENGINE_MSG_FORMATTED_SUBMESSAGE_HEADER	\n===== \n\nTriggered by: %1
-58996	ALERT_ENGINE_MSG_FORMATTED_SUBMESSAGE_FOOTER	\n===== \n
-58995	ALERT_ENGINE_MSG_SUBMESSAGE_INSTANCE_FORMAT	\n-----\nFor the following key: %1\nDescription: %2\n----- \n
-58994	ALERT_ENGINE_MSG_TRIGGERED_AT_LOCATION	\nTriggered at location : %1
-58993	ALERT_ENGINE_MSG_ON_TIME	\nOn %1
AmazonEC2.msgs.h		
-207099	REGION	Region
-207098	SUBNET	Subnet
-207097	VPC	VPC
-207096	IMAGE	AMI
-207095	INSTANCE_TYPE	Instance Type
-207094	SECURITY_GROUPS	Security Groups
-207093	KEY_PAIR	Key Pair
-207092	ELASTIC_IPS	Elastic IPs
-207091	SHUTDOWN_BEHAVIOR	Shutdown Behavior
-207090	SHUTDOWN_BEHAVIOR_TERMINATE	Terminate
-207089	SHUTDOWN_BEHAVIOR_STOP	Stop
-207088	DEFAULT_IN	Default in
-207087	SECURITY_GROUPS_DESC	A security group acts as a firewall that controls the traffic for one or more instances
-207086	SUBNET_DESC	A subnet is a range of IP addresses in your VPC
-207085	VPC_DESC	A virtual private cloud (VPC) is a virtual network dedicated to your AWS account
-207084	IMAGE_DESC	An AMI includes the following:\n* A template for the root volume for the instance (for example, an operating system, an application server, and applications)\n* Launch permissions that control which AWS accounts can use the AMI to launch instances\n* A block device mapping that specifies the volumes to attach to the instance when it's launched
-207083	KEY_PAIR_DESC	To log in to your instance, you must create a key pair, specify the name of the key pair when you launch the instance, and provide the private key when you connect to the instance
-207082	ELASTIC_IPS_DESC	An Elastic IP address (EIP) is a static IP address designed for dynamic cloud computing. With an EIP, you can mask the failure of an instance or software by rapidly remapping the address to another instance in your account
-207081	DEFAULT	default
-207080	REGION_DESC	Each region is a separate geographic area
-207079	INSTANCE_TYPE_DESC	The instance type that you specify determines the hardware of the host computer used for your instance
-207078	SHUTDOWN_BEHAVIOR_DESC	Shutdown Behavior
-207077	CREDENTIALS_HELP	Access key ID and Secret access key are AWS (Amazon Web Services) identifiers used to manage IAM (Identity and Access Management) in order to manage users and their security credentials across Amazon's EC2 (Elastic Compute Cloud). \n\nFor guidelines on how to obtain your AWS Access Identifiers, see the Help Center.
-207076	ACCESS_KEY_ID	Access Key Id
-207075	SECRET_ACCESS_KEY	Secret Access Key
-207074	NO_SECURITY_GROUP	security groups (%1%) are not configured for port %2%. Make sure your network profile is configured with the correct port number.
CALC.h		
-226999	CALC_RESULT	Result of division of % 1 f by % 2 f is % 3 f
-226998	CALC_DIV_BY_0	Division by zero!
CoAP.h		
-223999	CoAP_INVALID_METHOD	Invalid or Empty Method %1.
-223998	CoAP_ONLY_COAP_SUPPORTED	Only coap scheme supported.

Error code	Handle	Message\Additional information
-223997	CoAP_INVALID_TYPE	Invalid or Empty Type %1.
-223996	CoAP_NO_URL	No URL provided!
-223995	CoAP_INVALID_URL	Invalid URL provided. Error % 1 Id.
-223994	CoAP_NO_HOSTNAME	No hostname in the URL!
-223993	CoAP_REQUEST_FAILED	coap_request failed. Error: "%1".
-223992	CoAP_LOG_REQUEST	Request Object:\n%1
-223991	CoAP_LOG_RESPONSE	Response Object:\n%1
-223990	CoAP_SETOPTIONS_FAILED	coap_set_options failed. Error: "%1".
-223989	CoAP_INVALID_TIMEOUT_VALUE	coap_set_options invalid time out value passed.
-223988	CoAP_LOG_SETOPTIONS	coap_set_options: Option %1 value changed, New value %2
-223987	CoAP_LOG_RESPONSE_CODE	Response Code: %1
-223986	COAP_REGSAVEPARAM_ERROR	coap_reg_save_param Error: "%1".
-223985	CoAP_LOG_REGSAVEPARAM	coap_reg_save_param: Saving search for "%1".
-223984	CoAP_SEARCHPARAM_NOTFOUND	%1 Parameter "%2" not found in response.
-223983	CoAP_LOG_GETINTPROPERTY	coap_get_int_property: %1 = % 2 Id
-223982	CoAP_INVALID_REQUEST_TYPE	Invalid or Empty Request Type %1.
-223981	CoAP_UNSUPPORTED_REQUEST_TYPE	Unsupported Request Type %1.
-223980	CoAP_GETINTPROPERTY_ERROR	coap_get_int_property: Error: "%1".
DataFormatsEngine_res.h		
-208999	EXTENSION	Extension: %1 - %2\n
-208998	INTERNAL_ERROR_IN_RECURSIVE_CONVERT_FROM	Internal Error in recursiveConvertFrom(), mExtensionNames.size()=%1, mpFormatted=%2\n
-208997	DFE_RECURSIVE_CONVERT_FROM	DfeConvertFromFormatted::recursiveConvertFrom: extName: [%1], pExtension [%2].\n
-208996	EXTENSION_NOT_FOUND	Extension \"%1\" wasn't found\n
-208995	EXTENSION_FAILED_TO_CONVERT_GIVEN_DATA	Extension \"%1\" failed to convert the given data (code=% 2 Id)\n
-208994	CONVERT_EMPTY_STRING_RETURNED	Convert: Empty string returned from extension %1.\n
-208993	THE_GIVIN_FORMATTED_DATA_IS_NULL	The given formatted data is NULL\n
-208992	CONVERT_FROM_CALLED_WITH_EXTENSION_LIST	DfeConvertFromFormatted::convertFrom: called with extension list: [%1].\n
-208991	CONVERT_FROM_CALLED_WITH_NULL_EXTENSION	DfeConvertFromFormatted::convertFrom: called with NULL extension list.\n
-208990	FAILED_TO_EXTRACT_THE_EXTENSION_NAME	Failed to extract the extension name/s from the given formatted data\n
-208989	EXTENSION_RETURNED_NULL_POINTER	The extension returned NULL pointer for the conversion result\n
-208988	FAILED_TO_EXTRACT_EXTENSION_NAME	Failed to extract the extension name/s from the given formatted data (Convert-From Callback)\n
-208987	EXTENSION_RETURNED_NULL_POINTER_FROM_CALLBACK	The extension returned NULL pointer for the conversion result (Convert-From Callback)\n
-208986	CONVERT_FROM_CALLBACK_WRONG_USAGE	Convert-From callback wrong usage (in=%1, out=%2, context=%2)\n
-208985	INTERNAL_ERROR_IN_RELEASE_HTTP_ENTITY	Internal Error in releaseHTTPEntity() - failed to find HTTPEntity extension data\n
-208984	INTERNAL_ERROR_IN_RELEASE_BUFFER	Internal Error in releaseBuffer() - failed to find HTTPEntity extension data (#1)\n
-208983	INTERNAL_ERROR_IN_RELEASE_BUFFER_2	Internal Error in releaseBuffer() - failed to find HTTPEntity extension data (#2)\n
-208982	CONVERT_TO_INTERNAL_ERROR	Convert To: Internal error (usage).\n
-208981	CONVERT_TO_UNABLE_TO_LOAD_CHAIN	Convert To: Unable to load chain \"%1\", make sure all relevant chain and extensions files exist and configured correctly.\n
-208980	CONVERT_TO_CONVERSION_ERROR	Convert To: DFE \"%1\" conversion error.\n
-208979	CONVERT_TO_INTERNAL_ERROR_CUSTOM	Convert To: Internal error custom chain could not be created.\n
-208978	CONVERT_TO_INTERNAL_ERROR_DURING_UPDATE	Convert To: Internal error (during update of tags).\n
-208977	CONVERT_TO_INTERNAL_ERROR_DURING_CHAIN	Convert To: Internal error (during chain process).\n
-208976	CONVERT_TO_INTERNAL_ERROR_MEMORY_ALLOCATION	Convert To: Internal error (memory allocation failed).\n
-208975	CONVERT_TO_INTRNAL_ERROR_WRONG_PARAMETERS	Convert To: Internal error (wrong parameters - empty HTTPEntity).\n
-208974	CONVERT_TO_INTERNAL_ERROR_GET_LAST_USED_EXTENSION_INFO	Convert To: Internal error in getLastUsedExtensionInfo() 1\n
-208973	CONVERT_TO_INTERNAL_ERROR_GET_LAST_USED_EXTENSION_INFO_2	Convert To: Internal error in getLastUsedExtensionInfo() 2\n
-208972	VERIFICATION_INTERNAL_ERROR	Verification: Internal Error in verifyConversionResult(); mpOriginal=%1, mpFormatted=%2, mpExtension=%3, mpContexts=%4
-208971	VERIFICATION_INTERNAL_ERROR_VERIFY	Verification: Internal Error in verifyConversionResult(); pConvertFrom=%1
-208970	INTERNAL_ERROR_IN_VERIFY_NV_BUFFER_CONVERSION	Internal Error in verifyNVBufferConversionResult(); mpOriginal=%1, mpFormatted=%2, mpExtension=%3, mpContexts=%4
-208969	FAILED_TO_VERIFY_CORRECTNESS	Failed to verify the correctness of the formatted data generated by the extension \"%1\".\nRaw Data (starts with):\n%2\nFormatted Data (starts with):\n%3\n
-208968	FAILED_TO_VERIFY_CORRECTNESS_2	Failed to verify the correctness of the formatted data generated by the extension \"%1\".\nRaw Data (starts with):\n%2\nFormatted Data (starts with):\n%3\nRaw Data - after conversion (starts with):\n%4\n
DigitalOcean.msgs.h		
-207499	REGION	Region

Error code	Handle	Message\Additional information
-207498	REGION_DESC	Each region represents a specific datacenter in a geographic location.
-207497	TOKEN	OAuth token
-207496	TOKEN_DESC	You can generate OAuth token by visiting https://cloud.digitalocean.com/settings/applications . It contains both login and password encoded.
-207495	SIZE	Droplet's size
-207494	SIZE_DESC	Each size represents a plan that bundles together specific sets of resources. This includes the amount of RAM, the number of virtual CPUs, disk space, transfer and pricing details.
-207493	IMAGE	Image
-207492	IMAGE_DESC	The machine image contains the root file system for the droplet
-207491	SSH_KEY	SSH Key(s)
-207490	SSH_KEY_DESC	SSH Key can be used to log into droplet remotely instead of password
FtpReplayRes.h		
-205470	LRFTP_BAD_DELETE_OPTION	% 1 s is not ftp_delete valid option
-205469	LRFTP_BAD_DIR_OPTION	% 1 s is not ftp_dir valid option
-205468	LRFTP_BAD_GET_OPTION	% 1 s is not ftp_get valid option
-205467	LRFTP_BAD_LOGON_OPTION	% 1 s is not ftp_logon valid option
-205466	LRFTP_BAD_PUT_OPTION	% 1 s is not ftp_put valid option
-205465	LRFTP_BAD_RENDIR_OPTION	% 1 s is not ftp_rendir valid option
-205464	LRFTP_ACCEPT_FAILED	Accept command failed err number = % 1 ld
-205463	LRFTP_NO_PATH_SPECIFIED	At least one of SOURCE/Target path/file should be specified\r\n\r\n
-205462	LRFTP_CONTENT	content of % 1 s :\n
-205461	LRFTP_CREATE_DIR_FAILED	Create directory failed; % 1 s
-205460	LRFTP_CWD_FAILED	CWD failed; % 1 s
-205459	LRFTP_DELETE_FAILED	Delete failed; % 1 s
-205458	LRFTP_PASS_FAILED	Failed in PASS command; % 1 s
-205457	LRFTP_PWD_FAILED	Failed in PWD command; % 1 s
-205456	LRFTP_USER_FAILED	Failed in USER command; % 1 s
-205455	LRFTP_SFTP_CONN_FAILED	Failed to establish a secure FTP session.
-205454	LRFTP_CONNECTION_FAILED	Failed to establish connection to % 1 s:% 2 ld
-205453	LRFTP_SESSION_FAILED	Failed to establish FTP session.
-205452	LRFTP_READ_FAILED	Failed to open % 1 s for reading.
-205451	LRFTP_WRITE_FAILED	Failed to open % 1 s for writing.
-205450	LRFTP_OPEN_LOCAL_SERVICE_FAILED	Failed to open local service\r\n\r\n
-205449	LRFTP_OPEN_OUTPUT_FAILED	Failed to open output file\r\n\r\n
-205448	LRFTP_PUT_DATA_FAILED	Failed to put data: % 1 s
-205447	LRFTP_RETRIEVE_DATA_FAILED	Failed to retrieve data; % 1 s
-205446	LRFTP_USER_REQUEST_FAILED	Failed to send USER request; % 1 s
-205445	LRFTP_MKDIR_FAILED	Ftp Create dir % 1 s
-205444	LRFTP_MKDIR_SUCCESS	Ftp Create directory ended successfully.
-205443	LRFTP_DELETE_SUCCESS	Ftp Delete ended successfully.
-205442	LRFTP_DELETE_FILE	Ftp Deleting file % 1 s
-205441	LRFTP_DIR_SUCCESS	Ftp Dir ended successfully.
-205440	LRFTP_GET_SUCCESS	Ftp Get finished successfully.
-205439	LRFTP_GET_DESCRIPTION	Ftp Get: each item must specify source file to get.
-205438	LRFTP_LOGON_SUCCESS	Ftp Logon successful.
-205437	LRFTP_PUT_SUCCESS	Ftp Put ended successfully.
-205436	LRFTP_PUT2_SUCCESS	Ftp put of % 1 s finished successfully
-205435	LRFTP_RMDIR	Ftp Remove dir % 1 s
-205434	LRFTP_RMDIR_SUCCESS	Ftp Remove directory ended successfully.
-205433	LRFTP_RENAME_DIR_SUCCESS	Ftp Rename Dir ended successfully.
-205432	LRFTP_RENAME_DIR	Ftp Rename dir from % 1 s to % 2 s
-205431	LRFTP_SESSION_CLOSED	Ftp Session closed successfully.
-205430	LRFTP_GET_FAILED	Get failed; % 1 s
-205429	LRFTP_GET_FILE	Getting file % 1 s, passive mode set to % 2 ld
-205428	LRFTP_INVALID_COMMAND	Invalid command.
-205427	LRFTP_INVALID_URL	Invalid Ftp url entry (should be URL=ftp://username:password@server:port or URL=ftps://username:password@server:port).
-205426	LRFTP_BAD_DELETE_ARG	item must specify source file to delete.

Error code	Handle	Message\Additional information
-205425	LRFTP LOGON FAILED	Logon Session failed % 1 s
-205424	LRFTP BAD_MPUT_TARGET	mput target should be directory and not a file
-205423	LRFTP NOT_CONNECTED	Not connected.
-205422	LRFTP NOT_LOGGED_ON	Not logged on!
-205421	LRFTP PORT_FAILED	PORT failed; % 1 s
-205420	LRFTP PUT_FAILED	Put failed; % 1 s
-205419	LRFTP PUT_FILE	Putting file % 1 s in % 2 s, passive mode set to % 3 ld
-205418	LRFTP QUIT_FAILED	Quit command failed; % 1 s
-205417	LRFTP RMDIR_FAILED	Remove directory failed; % 1 s
-205416	LRFTP RENAME_DIR_FAILED	Rename directory from failed; % 1 s
-205415	LRFTP RENAME_DIR2_FAILED	Rename directory to failed; % 1 s
-205414	LRFTP NO_SOURCE_OR_TARGET_DIR	SOURCE and TARGET directories must be specified!
-205413	LRFTP TYPE_FAILED	TYPE failed; % 1 s
-205412	LRFTP NO_SESSION_OBJECT	Unable to obtain FTP user session object.
-205411	LRFTP FILE_LIST	% 1 s
-205410	LRFTP BIND_SOCKET	Binding socket to local address @ %s:0
-205409	LRFTP TOO_BIG_COMMAND	Command is too big
-205408	LRFTP COMMAND_TRANSFER_FAILED	Failed to transmit a command
-205407	LRFTP INVALID_OPTION	% 1 s is not a valid option
-205406	LRFTP SET_OPTION_SUCCESS	Setting FTP session option ended successfully
-205405	LRFTP SET_OPTION_FAILED	Failed to set FTP session option
-205404	LRFTP INVALID_ARG	Invalid argument
-205403	LRFTP COMMAND_FAILED	FTP command % 1 s failed
-205402	LRFTP EPRT_FAILED	EPRT failed; % 1 s
-205401	LRFTP NOT_SUPPORTED_IN_LINUX	This feature is not supported in Linux
-205400	LRFTP BAD_FILE_MASK	Bad file mask '%1'
-205399	LRFTP PASV_FAILED	Failed to establish passive data connection: '%1'
GoogleComputeEngine.msgs.h		
-207399	REGION	Region
-207398	LOGIN_HINT	Google login
-207397	LOGIN_HINT_DESC	Google email address with GCE enabled
-207396	PROJECT	Project ID
-207395	PROJECT_DESC	All Google Compute Engine resources belong to a project. Projects form the basis for enabling and using the Google Cloud Platform services, including managing APIs, enabling billing, adding and removing collaborators and enabling other Google services.\n\nThe Project resource is created using the Google Developers Console when you activate Google Compute Engine for a project
-207394	ZONE	Zone
-207393	ZONE_DESC	The zone determines what computing resources are available and where your data is stored and used.
-207392	MACHINE_TYPE	Machine type
-207391	MACHINE_TYPE_DESC	The machine type determines the CPU and memory your instance will have.
-207390	IMAGE	Image
-207389	IMAGE_DESC	The image determines the operating system installed on the instance.
-207388	NETWORK	Network
-207387	NETWORK_DESC	The network determines what network traffic the instance can access.
-207386	NO_PORT_OPEN	Network %%1%% is not configured for port %%2%%. Make sure your network profile is configured with the correct port number.
-207385	REFRESH_TOKEN	Refresh token
-207384	REFRESH_TOKEN_DESC	Will be set automatically
GwtDfe_res.h		
-110993	GWT_DFE_EXCEPTION_GENERAL_ERROR	GWT DFE ERROR:\n%1.
-110999	LRW_MSG_GWT_LOADED_WAR	The following WAR/JAR/folders were loaded %1
-110998	LRW_MSG_GWT_WAR_NOT_LOADED	The following WAR/JAR/folders were not found: %1
-110997	GWT_DFE_EXCEPTION_CLASS_NOT_FOUND	GWT DFE ERROR:\n\nThe following class is missing in the GWT DFE configuration: %1.\n\nMake sure the used GWT DFE chains are configured correctly, including all .JAR, .CLASS and .GWT.RPC files used by the GWT application.\nSee the Opentext Performance Engineering documentation for details.

Error code	Handle	Message\Additional information
-110996	GWT_DFE_EXCEPTION_MISSING_SERIALIZATION_POLICY	GWT DFE ERROR:\n\nThe correct GWT serialization policy could not be found.\n\nMake sure the used GWT DFE chains are configured correctly, including the up to date .GWT.RPC files used by the GWT application.\n\nSee the Opentext Performance Engineering documentation for details.
-110995	GWT_DFE_EXCEPTION_WAR_HANDLING	GWT DFE ERROR:\n\nFailed to handle WAR entry.\n\nMake sure the used GWT DFE chains are configured correctly, including all .JAR, .CLASS and .GWT.RPC files used by the GWT application.\n\nSee the Opentext Performance Engineering documentation for details."
-110994	GWT_DFE_EXCEPTION_MISSING_METHOD	GWT DFE ERROR:\n\nFailed to deserialize method.\n\nMake sure the used GWT DFE chains are configured correctly, including all .JAR, .CLASS and .GWT.RPC files used by the GWT application.\n\nSee the Opentext Performance Engineering documentation for details.
ImapReplayRes.h		
-205620	LRIMAP_MAIL_QUERY	% 1 s\n\nMailbox query: % 2 s
-205619	LRIMAP_APPEND_SUCCESS	Append message to mailbox % 1 s completed successfully.
-205618	LRIMAP_APPEND_FAILED	Append unsupported or arguments invalid.
-205617	LRIMAP_ATTRIBUTE	Attribute: % 1 s
-205616	LRIMAP_ATTRIBUTE2	Attribute: % 1 s % 2 s
-205615	LRIMAP_CANT_APPEND	Can't append to '% 1 s', error in flags or data/time or message text.
-205614	LRIMAP_CANT_EXPUNGE	Can't expunge messages, permission denied.
-205613	LRIMAP_CANT_FETCH	Can't fetch that data.
-205612	LRIMAP_CANT_LIST	Can't list reference '% 1 s', name '% 2 s'.
-205611	LRIMAP_COMPLETED	Completed.
-205610	LRIMAP_CONN_DENIED	Connection denied by IMap server.
-205609	LRIMAP_CONTAINS_MESSAGES	Contains % 1 s messages.
-205608	LRIMAP_CONTAINS_MESSAGES2	Contains % 1 s recent messages.
-205607	LRIMAP_COPY_FAILED	Copy command unsupported or arguments invalid.
-205606	LRIMAP_COPY_SUCCESS	Copy completed successfully.
-205605	LRIMAP_EXAMINED_MAILBOX	Examined mailbox '% 1 s':
-205604	LRIMAP_CUSTOM_REQUEST	Executing custom request '% 1 s'...
-205603	LRIMAP_EXPURGE_FAILED	Expunge unsupported or arguments invalid.
-205602	LRIMAP_CONN_FAILED	Failed to connect to % 1 s:% 2 ld.
-205601	LRIMAP_SECURE_CONN_FAILED	Failed to establish a secure IMap session.
-205600	LRIMAP_LOGON_FAILED	Failed to Logon (see message below): % 1 s\n\n
-205599	LRIMAP_APPEND_CONTINUATION_FAILED	Failed to receive continuation response from the server for APPEND request.
-205598	LRIMAP_RECV_CAPS_FAILED	Failed to receive IMap capabilities, response timed out.
-205597	LRIMAP_RECV_WELCOME_FAILED	Failed to receive IMap welcome message from % 1 s:% 2 ld.
-205596	LRIMAP_RECV_LOGON_STATUS_FAILED	Failed to receive logon status, response timed out.
-205595	LRIMAP_FETCH_SUCCESS	Fetch completed successfully.
-205594	LRIMAP_FETCH_FAILED	Fetch unsupported or arguments invalid.
-205593	LRIMAP_LOGON_SUCCESS	IMap Logon successful.
-205592	LRIMAP_LOGON_START	IMap start logon to % 1 s:% 2 ld.
-205591	LRIMAP_PREAUTH_SUCCESS	User pre-authenticated successfully.
-205590	LRIMAP_NOTICE	IMap Notice: Appending message to currently selected mailbox '% 1 s'.
-205589	LRIMAP_SESSION_CLOSED	IMap Session closed.
-205588	LRIMAP_CANT_COPY	Can't copy those messages or to that name.
-205587	LRIMAP_INVALID_APPEND_RESPONCE	Append operation did not receive a valid response.
-205586	LRIMAP_AUTH_UNSUPPORTED	Authentication scheme % 1 s is not supported, reverting to LOGIN authentication.
-205585	LRIMAP_BAD_OPTION	Unrecognized option '% 1 s', expecting 'Mailbox=<name>'.
-205584	LRIMAP_BAD_COMMAND	Invalid % 1 s command or arguments: '% 2 s' '% 3 s'
-205583	LRIMAP_BAD_URL	Invalid IMap url entry (should be URL=imap://username:password@emailserver or URL=imaps://username@emailserver).
-205582	LRIMAP_BAD_OPTION2	Invalid mailbox option.
-205581	LRIMAP_CRAM_MD5_NOT_SUPPORTED	Login authentication scheme 'CRAM-MD5' not supported by server.
-205580	LRIMAP_LOGIN_FAILED	Login request failed, server terminated connection.
-205579	LRIMAP_LOGON_FAILED2	Logon failed.
-205578	LRIMAP_SELECT_SUCCESS	Mailbox '% 1 s' % 2 s successfully with % 3 s access.
-205577	LRIMAP_MAILBOX_NOT_EXIST	Mailbox '% 1 s' does not exist, create mailbox first.
-205576	LRIMAP_MAILBOX_NOT_SELECTED	Mailbox not selected.
-205575	LRIMAP_MAILBOX_STATUS	Mailbox status: % 1 s
-205574	LRIMAP_MAILBOX_EMPTY_ERROR	Message content to append must not be empty.
-205573	LRIMAP_MAILBOX_NOT_SPECIFIED	No mailbox specified, and no default mailbox selected.

Error code	Handle	Message\Additional information
-205572	LRIMAP_NO_STATUS	No status available for '%_1_s'
-205571	LRIMAP_NOT_LOGGED_ON	Not logged on!
-205570	LRIMAP_RESPONSE_TIMEOUT	Response timed out (connection terminated).
-205569	LRIMAP_RESPONSE_UNRECOGNIZED	Response unrecognized.
-205568	LRIMAP_SEARCH_ERROR	Search error, can't search that criteria.
-205567	LRIMAP_SEARCH_FAILED	Search unsupported or arguments invalid.
-205566	LRIMAP_SELECTED_MAILBOX	Selected mailbox '%_1_s' :
-205565	LRIMAP_STORE_FAILED	Store unsupported or arguments invalid.
-205564	LRIMAP_SELECT_FAILED	Unable to %_1_s mailbox '%_2_s' (error: %_3_s)
-205563	LRIMAP_CONN_LOST	Unable to check server capabilities (connection lost).
-205562	LRIMAP_CREATE_SESSION_FAILED	Unable to create an IMap user session object.
-205561	LRIMAP_OBTAIN_SESSION_FAILED	Unable to obtain IMap user session object.
-205560	LRIMAP_FILE_RETRIEVAL_FAILED	Unable to retrieve message file '%_1_s'. Check if the file exists, and you have permissions.
-205559	LRIMAP_CONNECTION_LOST2	Unable to submit request (connection lost).
-205558	LRIMAP_MAILBOX_ACTIVATED	Mailbox '%_1_s' subscribed/activated.
-205557	LRIMAP_CANT_SUBSCRIBE	Can not subscribe to mailbox '%_1_s'.
-205556	LRIMAP_CANT_UNSUBSCRIBE	Can not unsubscribe from mailbox '%_1_s'.
-205555	LRIMAP_INVALID_MAILBOX	Invalid mailbox name '%_1_s'
-205554	LRIMAP_MAILBOX_UNSUBSCRIBED	Mailbox '%_1_s' un-subscribed.
-205553	LRIMAP_MAILBOX_CREATED	Mailbox '%_1_s' successfully created.
-205552	LRIMAP_CANT_CREATE_MAILBOX	IMap Error: Unable to create mailbox '%_1_s', check name.
-205551	LRIMAP_MAILBOX_DELETED	Mailbox '%_1_s' successfully deleted.
-205550	LRIMAP_MAILBOX_DELETE_FAILED	IMap Error: Unable to delete mailbox '%_1_s', check name.
-205549	LRIMAP_MAILBOX_CHECKED	Mailbox checked.
-205548	LRIMAP_CHECKPOINT_FAILED	Checkpoint request not supported by server.
-205547	LRIMAP_NOOP_FAILED	NOOP request not supported by server.
-205546	LRIMAP_MAILBOX_CLOSED	Mailbox closed.
-205545	LRIMAP_STARTTLS_FAILED1	Server didn't response to STARTTLS, connection was lost.
-205544	LRIMAP_STARTTLS_FAILED2	Response to STARTTLS timed out.
-205543	LRIMAP_PARAM_ALLOC_FAILED	Failed to allocate %_1_id bytes for parameter storage.
LrTcLogger_res.h		
-205250	LRWEB2LOG_MSGID_LOG_STATUS_LINE	Status Line
-205249	LRWEB2LOG_MSGID_LOG_INTERNAL_LOCK_TRACE	
-205248	LRWEB2LOG_MSGID_LOG_INTERNAL_FUNC_TRACE	
-205247	LRWEB2LOG_MSGID_LOG_INTERNAL_HTTP_TRACE	
-205246	LRWEB2LOG_MSGID_LOG_INTERNAL_NOTIFICATION	NOTIFICATION
-205245	LRWEB2LOG_MSGID_LOG_INTERNAL_MEASUREMENT	
-205244	LRWEB2LOG_MSGID_LOG_INTERNAL_GENERIC	
-205243	LRWEB2LOG_MSGID_LOG_HTTP_REQUEST_HEADERS	
-205242	LRWEB2LOG_MSGID_LOG_HTTP_REQUEST_BODY	
-205241	LRWEB2LOG_MSGID_LOG_HTTP_RESPONSE_HEADERS	
-205240	LRWEB2LOG_MSGID_LOG_HTTP_RESPONSE_BODY	
-205239	LRWEB2LOG_MSGID_LOG_HTTP_TRACE	
-205238	LRWEB2LOG_MSGID_LOG_NTLM_INFORMATION	
-205237	LRWEB2LOG_MSGID_LOG_SSL_INFORMATION	
-205236	LRWEB2LOG_MSGID_LOG_AUT_NON_ERROR	AUT non-error
-205235	LRWEB2LOG_MSGID_LOG_AUT_ERROR	AUT error
-205234	LRWEB2LOG_MSGID_LOG_PARAMETER_SUBSTITUTION	
-205200	LRWEB2LOG_MSGID_LOG_EXTENDED_GENERIC	
-205180	LRWEB2LOG_MSGID_LOG_STANDARD	Standard log
-205179	LRWEB2LOG_MSGID_LOG_WARNING	Warning
-205178	LRWEB2LOG_MSGID_LOG_INTERNAL_PROBLEM	Internal problem
-205177	LRWEB2LOG_MSGID_LOG_ERROR	Error
-205176	LRWEB2LOG_MSGID_LOG_INTERNAL_ERROR	Internal Error
-205175	LRWEB2LOG_MSGID_LOG_FATAL_ERROR	Fatal Error
-205174	LRWEB2LOG_MSGID_LOG_INVALID_MSGTYPE	[Error: Invalid message type]

Error code	Handle	Message\Additional information
-205099	RUNLOGIC ERR CONST PACE NO TIME ENTRY	Run-time settings pacing error: No setting for the fixed delay after the previous iteration ends.
-205098	RUNLOGIC CONST PACE TIME IS	Pacing in node %1 is set to start every %2 seconds.
-205097	RUNLOGIC CONST PACE IS NEGATIVE	Run-time settings pacing error: Fixed delay after the previous iteration is set to be a negative number (%1).
-205096	RUNLOGIC WAITING SECS FOR PACING	Waiting %1 seconds for iteration pacing.
-205095	RUNLOGIC WARNING ITERATION PACING CANNOT BE REACHED	Iteration pacing cannot be reached (pace time = %1, actual time = %2).
-205094	RUNLOGIC ERR RAND MIN MAX	Run-time setting pacing error: Minimum value of the random interval (%1) for pacing is greater than maximum value (%2).
-205093	RUNLOGIC ERR RAND PACE NO MAX TIME ENTRY	Run-time settings pacing error: No setting for maximum value at random interval pacing.
-205092	RUNLOGIC ERR BEFORE FIRST PACE NO MAX TIME ENTRY	Command line does not contain the maximal value of the pacing before first iteration.
-205091	RUNLOGIC ERR AFTER PACE NO MAX TIME ENTRY	Run-time settings pacing error: No setting for maximum range of the random delay after the previous iteration ends.
-205090	RUNLOGIC ERR RAND PACE NO MIN TIME ENTRY	Run-time settings pacing error: No setting for minimum value at random interval pacing.
-205089	RUNLOGIC ERR BEFORE FIRST NO MIN TIME ENTRY	Command line does not contain the minimal value of the pacing before first iteration.
-205088	RUNLOGIC ERR AFTER PACE NO MIN TIME ENTRY	Run-time settings pacing error: No setting for minimum range of the random delay after the previous iteration ends.
-205087	RUNLOGIC ERR RAND PACE MAX GT ZERO	Run-time settings pacing error: Maximum value of interval for the random pacing must be greater than 0.
-205086	RUNLOGIC ERR RAND PACE MIN GT ZERO	Run-time settings pacing error: Minimum value of interval for the random pacing must be greater than 0.
-205085	RUNLOGIC ERR BEFORE FIRST PACE MIN GT MAX	Run-time setting pacing error: Minimum value of the random interval for pacing is greater than maximum value.
-205084	RUNLOGIC ERR BEFORE FIRST PACE MIN GT ZERO	Minimum value for pacing before first iteration must be greater than 0.
-205083	RUNLOGIC ERR AFTER PACE MAX GT ZERO	Run-time settings pacing error: Maximum value of interval for the random delay after the previous iteration ends must be greater than 0.
-205082	RUNLOGIC ERR AFTER PACE MIN GT ZERO	Run-time settings pacing error: Minimum value of interval for the random delay after the previous iteration ends must be greater than 0.
-205081	RUNLOGIC ERR RAND PACE MIN GT MAX	Run-time setting pacing error: Minimum value of the random interval for pacing is greater than maximum value.
-205080	RUNLOGIC ERR AFTER PACE MIN GT MAX	Run-time setting pacing error: Maximum value of range for the random delay after the previous iteration ends cannot be smaller than minimum.
-205079	RUNLOGIC RAND PACE INIT DEBUG	Each iteration will be started at random interval every %1 - %2 seconds.
-205078	RUNLOGIC AFTER PACE INIT DEBUG	Each iteration will be started with random delay of %1 - %2 seconds after the previous iteration ends.
-205077	RUNLOGIC OBJECT SON TYPE UNDEFINED	Type attribute in node %1 undefined.
-205076	RUNLOGIC OBJECT SON RUN MODE UNDEFINED	Run mode of node %1 undefined.
-205075	RUNLOGIC OBJECT PACE TYPE RAND	Pace type is 'Start each iteration at random interval' in block %1.
-205074	RUNLOGIC OBJECT PACE TYPE CONST	Pace type is 'Start each iteration at fixed interval' in block %1.
-205073	RUNLOGIC OBJECT PACE TYPE HPS	Pace type is hps in block %1.
-205072	RUNLOGIC OBJECT PACE TYPE AFTER	Pace type is 'Start each iteration with random delay after the previous iteration ends' in block %1.
-205071	RUNLOGIC OBJECT ITERATIONS	Number of iterations for block %1 is %2.
-205070	RUNLOGIC OBJECT ITERATIONS WARNING	Illegal number of iterations %1 in block %2, value set to 1 iteration.
-205069	RUNLOGIC OBJECT START ITERATION	Starting iteration %1.
-205068	RUNLOGIC OBJECT START SCRIPT	Virtual User Script started at %1
-205067	RUNLOGIC OBJECT SCRIPT VERSION	Script was last modified in version %1
-205066	RUNLOGIC OBJECT END SCRIPT	Ending Vuser...
-205065	RUNLOGIC OBJECT END ITERATION	Ending iteration %1.
-205064	RUNLOGIC OBJECT RUNNING VUSER	Running Vuser...
-205063	RUNLOGIC OBJECT VUSER TERMINATED	Vuser Terminated.
-205062	RUNLOGIC ACTION RUNNING ACTION	Running action %1.
-205061	RUNLOGIC RANDOM IS NULL	Random pool is NULL
-205060	RUNLOGIC PERCENT IS NULL	Percent for node %1 is NULL.
-205059	RUNLOGIC PERCENT ERROR	Percent error in node %1 (sum over 100).
-205058	RUNLOGIC PERCENT ERROR2	Sum of random object (%1) pct has to be 100.
-205057	RUNLOGIC ERROR CANNOT OPEN RUNLOGIC FILE	Cannot open file %1.
-205056	RUNLOGIC ERROR RUN SECTION DOES NOT EXIST	Run Section does not exist.
-205055	RUNLOGIC ERROR RAND POOL IS NULL	Random Generator is NULL
-205054	RUNLOGIC ERROR RUN MODE NOT SUPPORTED	Run mode %1 not supported.
-205053	RUNLOGIC RANDOM ORDER IS NULL	Random order pool is NULL
-205052	RUNLOGIC STARTING ACTION	Starting action %1.
-205051	RUNLOGIC ENDING ACTION	Ending action %1.
-205050	RUNLOGIC ERR CONST AFTER PACE NO TIME ENTRY	Run-time settings pacing error: No value was set for the fixed delay after the previous iteration ends.
-205049	RUNLOGIC CONST AFTER PACE TIME IS	After pace interval in node %1 a constant was set to %2 seconds.
-205048	RUNLOGIC CONST AFTER PACE IS NEGATIVE	Run-time settings error: Fixed delay after the previous iteration is a negative number (%1). The delay must be positive.
-205047	RUNLOGIC WAITING CONST SECS FOR PACING	Waiting a constant interval of %1..2f seconds between iterations.
-205046	RUNLOGIC OBJECT PACE TYPE CONST AFTER	Pace type is to wait a constant interval after the iteration in block %1.
-205045	RUNLOGIC ERR EXIT ITERATION FAILED	User called an "Exit" command with "Fail" status
-205044	RUNLOGIC ERR EXIT ACTION FAILED	User called an "Exit" command on an action with "Fail" status
-205043	RUNLOGIC ERR GENERIC ACTION ABORTED	Abort was called from an action

Error code	Handle	Message\Additional information
-205042	RUNLOGIC_ERR_ABNORMAL_TERMINATION	Application process (mdrv.exe) encountered an error and terminated
-204899	LRWEB2REPLAY_MSGID_GET_PARAMETER	Notify: Getting Parameter "%1" = "%2".
-204898	LRWEB2REPLAY_MSGID_TRUCLIENT_DESC_DATE_TIME	TruClient Replay (build %6) for OpenText Professional Performance Engineering %1, build %3. OS: %2, initialized on %4 at %5\n
-204897	LRWEB2REPLAY_MSGID_TRUCLIENT_DESC_FF_MOBILE	Mobile Device: %1\n
-204896	LRWEB2REPLAY_MSGID_START_RTS	Selected Run-Time Settings:
-204895	LRWEB2REPLAY_MSGID_END_RTS	End of selected Run-Time Settings\n
-204894	LRWEB2REPLAY_MSGID_RTS_SIMULATE_NEW_USER	Simulate a new user on each iteration.....: %1
-204893	LRWEB2REPLAY_MSGID_RTS_RESET_REPLAY_STATE	Reset replay state at the end of each iteration.....: %1
-204892	LRWEB2REPLAY_MSGID_RTS_NO_PROXY	NO proxy (direct connection to the Internet)
-204891	LRWEB2REPLAY_MSGID_SYSTEM_PROXY	Using system proxy settings
-204890	LRWEB2REPLAY_MSGID_RTS_MANUAL_PROXY	MANUAL proxy configuration:
-204889	LRWEB2REPLAY_MSGID_RTS_NO_PROXY_FOR	Do not use a proxy for (exceptions).....: "%1"
-204888	LRWEB2REPLAY_MSGID_RTS_PROXY_ALL	Proxy for all.....: %1%2
-204887	LRWEB2REPLAY_MSGID_RTS_PROXY_HTTP	Proxy for HTTP.....: %1%2
-204886	LRWEB2REPLAY_MSGID_RTS_PROXY_HTTPS	Proxy for HTTPS.....: %1%2
-204885	LRWEB2REPLAY_MSGID_RTS_PAC_URL	AUTOMATIC proxy configuration (PAC) URL.....: "%1"
-204884	LRWEB2REPLAY_MSGID_RTS_HOME	Home page URL.....: %1
-204883	LRWEB2REPLAY_MSGID_RTS_CHECK_CACHE_IESTART	Check for newer versions of stored pages: %1 (Every time I start the browser)
-204882	LRWEB2REPLAY_MSGID_RTS_CHECK_CACHE_ALWAYS	Check for newer versions of stored pages: %1 (Every time I visit the web page)
-204881	LRWEB2REPLAY_MSGID_RTS_CHECK_CACHE_NEVER	Check for newer versions of stored pages: %1 (Never)
-204880	LRWEB2REPLAY_MSGID_RTS_CHECK_CACHE_AUTO	Check for newer versions of stored pages: %1 (Automatically)
-204879	LRWEB2REPLAY_MSGID_RTS_COMPARE_CACHE_ONCE	Compare the page in cache to the page on the network: % 1 _ld (once)
-204878	LRWEB2REPLAY_MSGID_RTS_COMPARE_CACHE_EVERY	Compare the page in cache to the page on the network: % 1 _ld (every time)
-204877	LRWEB2REPLAY_MSGID_RTS_COMPARE_CACHE_NEVER	Compare the page in cache to the page on the network: % 1 _ld (never)
-204876	LRWEB2REPLAY_MSGID_RTS_COMPARE_CACHE_OUTDATE	Compare the page in cache to the page on the network: % 1 _ld (when out-of-date)
-204875	LRWEB2REPLAY_MSGID_RTS_KEEP_ALIVE	Keep-Alive.....: %1
-204874	LRWEB2REPLAY_MSGID_RTS_PROXY_KEEP_ALIVE	Proxy Keep-Alive.....: %1
-204873	LRWEB2REPLAY_MSGID_RTS_KEEP_ALIVE_TIMEOUT	Keep-Alive timeout (ms).....: %1
-204872	LRWEB2REPLAY_MSGID_RTS_KEEP_ALIVE_TIMEOUT_SEC	Keep-Alive timeout (sec).....: % 1 _ld
-204871	LRWEB2REPLAY_MSGID_RTS_HTTP_VERSION	HTTP Version.....: %1
-204870	LRWEB2REPLAY_MSGID_RTS_PROXY_HTTP_VERSION	Proxy HTTP Version.....: %1
-204869	LRWEB2REPLAY_MSGID_RTS_DNS_CACHE_TIMEOUT	DNS cache timeout (ms).....: %1
-204868	LRWEB2REPLAY_MSGID_RTS_DNS_CACHE_ENTRIES	DNS cache entries.....: %1
-204867	LRWEB2REPLAY_MSGID_RTS_FILE	Run-Time Settings file.....: "%1"
-204866	LRWEB2REPLAY_MSGID_TRUCLIENT_VUSER_DIR	Vuser directory.....: "%1"
-204865	LRWEB2REPLAY_MSGID_TRUCLIENT_VUSER_OUT_DIR	Vuser output directory.....: "%1"
-204864	LRWEB2REPLAY_MSGID_LOG_README	Please refer to the ReadMe file in the Installation Guide for notes about measurements and logging.
-204863	LRWEB2REPLAY_MSGID_WARNING_INIT_CONTAINS_STEPS_WHEN_SIM_NE_W_USR_ON	The "vuser_init" section contains step(s) when the "Simulate a new user on each iteration" Run-Time Setting is ON. This may produce unpredictable results with multiple iterations.
LrXmiRes.h		
-109999	LRXML_MSG_STEP_SUCCEEDED	<CENTER>%1 succeeded</CENTER>
-109998	LRXML_MSG_STEP_FAILED	<CENTER>%1 execution failed</CENTER>
-109997	LRXML_MSG_STEP_FAILED_NO_MATCH	<CENTER>%1 did not find any matches</CENTER>
-109996	LRXML_STEP_SUCCEEDED	%1 succeeded
-109995	LRXML_STEP_SUCCEEDED_EX	%1 succeeded, % 2 _ld %3 processed
-109994	LRXML_STEP_FAILED	%1 execution failed
-109993	LRXML_STEP_FAILED_NO_MATCH	%1 did not find any matches
LrwCs_res.h		
-27999	LRW_MSG_CS_NO_MEM_FOR_BLOCK	Not enough memory (% 1 _ld bytes) for a memory block for %2
-27998	LRW_MSG_CS_NO_MEM	Not enough memory (% 1 _ld bytes) for %2
-27997	LRW_MSG_CS_INTERNAL_ERROR	Internal Error - %1
-27996	LRW_MSG_CS_NO_MEM_FOR_FRAME_NAME	Not enough memory (% 1 _ld bytes) for frame name
-27995	LRW_MSG_CS_LINK_NOT_FOUND	Requested link ("Text=%1") not found
-27994	LRW_MSG_CS_LINKING_TO	Linking to "%1", Target Frame="%2"
-27993	LRW_MSG_CS_IMAGE_LINKING_TO	Image-linking to "%1", Target Frame="%2"

Error code	Handle	Message\Additional information
-27992	LRW_MSG_CS_PRINT_STR_LEN_VAL	(*Debug*) "%1": Length=% 2 Id, Value=%3%4%5
-27991	LRW_MSG_CS_PRINT_ELEM_GENERIC	(*Debug*) Element "%1" at %2, ptParsedPage=%3, ptNextElemAtSameLevel=%4, eType=% 5 Id
-27990	LRW_MSG_CS_PRINT_ELEM_WITHIN_FORM	(*Debug*) eElemFormSubtype=% 1 Id, ptContainingElem FORM=%2
-27989	LRW_MSG_CS_PRINT_START	(*Debug*) Start debug print %1
-27988	LRW_MSG_CS_PRINT_END	(*Debug*) End debug print %1
-27987	LRW_MSG_CS_IMAGE_NOT_FOUND	Requested image not found
-27986	LRW_MSG_CS_REGEX_NOT_SUPPORTED	Regular expressions are not supported
-27985	LRW_MSG_CS_NO_HTML_CONTEXT	There is no context for HTML-based functions. A previous function may not have used "Mode=HTML" or downloaded only non-HTML page(s), or the context has been reset (e.g., due to a GUI-based function)
-27984	LRW_MSG_CS_UNCHECK_RADIO_DISALLOWED	Radio group "%1" cannot be unchecked, as "%2" was initially checked
-27983	LRW_MSG_CS_READONLY_NAMED	Attempting to modify "readonly" field "%1"
-27982	LRW_MSG_CS_READONLY_UNNAMED	Attempting to modify an unnamed "readonly" %1 field
-27981	LRW_MSG_CS_READONLY_IMAGE	Attempting to set coordinates of a "readonly" <INPUT TYPE=image> field (src=%1")
-27980	LRW_MSG_CS_TRUNC_TO_MAXLENGTH	Value of "%1" (length % 2 Id) truncated due to maxlength=% 3 Id
-27979	LRW_MSG_CS_FORM_NOT_FOUND	Requested form not found
-27978	LRW_MSG_CS_SUBMITTING_FORM_TO	Submitting form to "%1", Target Frame="%2"
-27977	LRW_MSG_CS_BLOCK_SIZE_TOO_LARGE	Memory block size (% 1 Id) requested for %2 exceeds limit of % 3 Id bytes
-27976	LRW_MSG_CS_PRINT_FORM	(*Debug*) _ptFirstElemWithinForm=%1, _ptLastElemWithinForm=%2, _ptFirstSubmitElem=%3, _ptLastSubmitElem=%4, _ptFirstRadioGroup=%5, _ptLastRadioGroup=%6, bMultipartFormSubmit=% 7 Id, usiMatchCount=% 8 Id
-27975	LRW_MSG_CS_PRINT_IMG	(*Debug*) ptContainingElem_A=%1
-27974	LRW_MSG_CS_UNSELECT_DISALLOWED	Unselect ("<OFF>") disallowed for a combo box (SELECT with "size" omitted or <= 1)
-27973	LRW_MSG_CS_REGEX_ERR_COMP	Error when compiling regular expression "%1": %2 mic_regex_compile rc=% 3 Id
-27972	LRW_MSG_CS_REGEX_ERR_EXEC	Error when executing compiled regular expression "%1": %2 mic_regex_exec rc=% 3 Id
-27971	LRW_MSG_CS_JS_OBJECT_ALLOC	Allocation of "%1" JavaScript object failed
-27970	LRW_MSG_CS_JS_GET_PRIVATE_DATA	Failed to get private data of JavaScript object
LrwDomFactory_res.h		
-35399	LRW_MSG_DOM_FACTORY_INTERNAL_ERROR	Internal Error - %1
LrwJsw_res.h		
-26299	LRW_MSG_JSW_INTERNAL_ERROR	Internal Error - %1
-26298	LRW_MSG_JSW_BEGIN_EVALUATING_JS_SCRIPT	JavaScript evaluating begins
-26297	LRW_MSG_JSW_FINISH_EVALUATING_JS_SCRIPT	Evaluating JavaScript was completed successfully
-26296	LRW_MSG_JSW_EVALUATING_JS_SCRIPT_FAILED	Failed to evaluate JavaScript code due to an error in an internal function (%1)
-26295	LRW_MSG_JSW_ERROR_WHILE_EVALUATING_JS_SCRIPT	JavaScript error in line % 1 Id: %2
-26294	LRW_MSG_JSW_CALLING_JS_FUNCTION_FAILED	JavaScript evaluation error when executing function %1
-26293	LRW_MSG_JSW_UNSUPPORTED_JS_TYPE	JavaScript evaluation: Attempt to use an unsupported JavaScript data type, % 1 Id
-26292	LRW_MSG_JSW_NOT_ENOUGH_MEM	Not enough memory (% 1 Id bytes) for %2
-26291	LRW_MSG_JSW_PROPERTY_IS_NOT_SUPPORTED	JavaScript property is not supported: %1 (for object %2)
-26290	LRW_MSG_JSW_NO_PROPERTIES_FOR_WINDOW	No properties for this window
-26289	LRW_MSG_JSW_WARNING_WHILE_EVALUATING_JS_SCRIPT	JavaScript warning in line % 1 Id: %2
-26288	LRW_MSG_JSW_AUTOMATION_ERROR	ActiveX-related automation error: %1 %2 (HRESULT=%3)
-26287	LRW_MSG_JSW_TYPE_MISMATCH_IN_NEW_ACTIVEXOBJECT	Type mismatch in "new ActiveXObject"
-26286	LRW_MSG_JSW_LOCATION_PARAMETER_IS_NOT_SUPPORTED_IN_NEW_ACTIVEXOBJECT	location parameter is not supported in "new ActiveXObject"
-26285	LRW_MSG_JSW_COMPILING_JS_SCRIPT_FAILED	Failed to compile JavaScript code
-26284	LRW_MSG_JSW_EXECUTING_JS_SCRIPT_FAILED	Failed to execute JavaScript code
-26283	LRW_MSG_JSW_EVALUATING_JS_SCRIPT_FAILED_PREV	Failed to evaluate JavaScript code. See previous message(s)
-26282	LRW_MSG_JSW_CALLING_JS_METHOD_FAILED	JavaScript evaluation error when executing method %1
-26281	LRW_MSG_JSW_WARNING_CALLING_ONERROR_HANDLER	JavaScript error in line % 1 Id: %2 - calling onerror handler
-26280	LRW_MSG_JSW_BEGIN_EVALUATING_INTERNAL_JS_SCRIPT	Internal JavaScript evaluating begins
-26279	LRW_MSG_JSW_FINISH_EVALUATING_INTERNAL_JS_SCRIPT	Evaluating Internal JavaScript was completed successfully
-26278	LRW_MSG_JSW_UNSUPPORTED_ACTIVE_X	Running ActiveX objects disallowed for this Vuser type. Use the "AJAX (Click and Script)" protocol
-26277	LRW_MSG_JSW_ACCESSING_DELETED_OBJECT	Attempting to access an object that has been deleted
-26276	LRW_MSG_JSW_ERROR_WHILE_EVALUATING_JS_SCRIPT_WITH_MSG_ID	JavaScript error (id=% 1 Id) in line % 2 Id: %3
-26275	LRW_MSG_JSW_WARNING_WHILE_EVALUATING_JS_SCRIPT_WITH_MSG_ID	JavaScript warning (id=% 1 Id) in line % 2 Id: %3

Error code	Handle	Message\Additional information
-26274	LRW_MSG_JSW_ERROR_WHILE_EVALUATING_JS_SCRIPT_WITH_MSG_ID_IGNORED	Ignoring JavaScript error (id=%_1_id) in line %_2_id: %3
-26273	LRW_MSG_JSW_WARNING_WITH_MSG_ID_CALLING_ONERROR_HANDLER	JavaScript error (id=%_1_id) in line %_2_id: %3 - calling onerror handler
LrwLogicMgr2_res.h		
-35099	LRW_MSG_LOGIC_EXECUTE_WITHOUT_TIMER_WAITING	Executing setTimeout/setInterval with TimerID=%_1_id without waiting
-35098	LRW_MSG_LOGIC_MGR_LOCATION_META_REFRESH	Refreshing due to a "META" element. URL="%1"
-35097	LRW_MSG_LOGIC_MGR_DOWNLOADING_DUE_TO_META_REFRESH	Downloading "%1" due to a refresh specified by a "META" element
-35096	LRW_MSG_LOGIC_WAITING_META_REFRESH	Waiting for %1 seconds for a refresh specified by a "META" element. Timestamps: current=%_2_id, expiration=%_3_id
-35095	LRW_MSG_LOGIC_EXECUTE_META_REFRESH_WITHOUT_WAITING	Refreshing due to a "META" element without waiting
-35094	LRW_MSG_LOGIC_MGR_DOWNLOADING_BEHAVIOR_FILE	Downloading behavior file with URL="%1"
-35093	LRW_MSG_LOGIC_MGR_DOWNLOADING_JAVA_DATA	Downloading Java Applet data URL="%1"
-35092	LRW_MSG_LOGIC_MGR_VERIFICATION_FAILED_BROWSER_TITLE	Browser title verification failed (expected: "%1", found: "%2")
-35091	LRW_MSG_LOGIC_MGR_VERIFICATION_FAILED_CONTAINS_TEXT	"Contains text" verification failed (expected: "%1", found: "%2")
-35090	LRW_MSG_LOGIC_MGR_VERIFICATION_FAILED_DOES_NOT_CONTAIN_TEXT	"Does not contain text" verification failed ("%1" found in "%2")
-35089	LRW_MSG_LOGIC_MGR_VERIFICATION_FAILED_TEXT	"Exact text" verification failed (expected: "%1", found: "%2")
-35088	LRW_MSG_LOGIC_MGR_DOWNLOADING_DUE_TO_SHOW_DOCUMENT	Downloading "%1" due to a 'showDocument' method call from a Java Applet
-35087	LRW_MSG_LOGIC_MGR_VERIFICATION_PASSED_BROWSER_TITLE	Browser title verification passed
-35086	LRW_MSG_LOGIC_MGR_VERIFICATION_PASSED_CONTAINS_TEXT	"Contains text" verification passed
-35085	LRW_MSG_LOGIC_MGR_VERIFICATION_PASSED_DOES_NOT_CONTAIN_TEXT	"Does not contain text" verification passed
-35084	LRW_MSG_LOGIC_MGR_VERIFICATION_PASSED_TEXT	"Exact text" verification passed
-35083	LRW_MSG_LOGIC_MGR_RADIOGROUP_FIREEVENT	Firing an "%1" event on the first radio in the group
-35082	LRW_MSG_LOGIC_MGR_LOCATION_RELOAD_MODAL_DIALOG	'window.showModalDialog()' invoked. URL="%1"
-35081	LRW_MSG_LOGIC_MGR_MODAL_NOT_FOUND	Modal dialog not found in browser
-35080	LRW_MSG_LOGIC_MGR_SAP_IVIEW_NOT_FOUND	SAP iView not found
-35079	LRW_MSG_LOGIC_MGR_SAP_FRAME_NOT_FOUND	SAP frame not found
-35078	LRW_MSG_LOGIC_MGR AJAX NOT FOUND	"%1" not found
-35077	LRW_MSG_LOGIC_MGR_EXTEND_SELECT_FOR_NON_MULTIPLE	"ExtendSelect" invalid when the SELECT element does not specify "multiple"
-35076	LRW_MSG_LOGIC_MGR_DESELECT_FOR_NON_MULTIPLE	"DeSelect" invalid when the SELECT element does not specify "multiple"
-35075	LRW_MSG_LOGIC_MGR AJAX AUTOCOMPLETE SAME_VALUE	Setting an autocomplete to the same value as it already had
-35074	LRW_MSG_LOGIC_MGR AJAX UNSUPPORTED_FRAMEWORK	The specified AJAX framework ("%1") is not supported
-35073	LRW_MSG_LOGIC_MGR AJAX UNSUPPORTED_CONTROL	The specified AJAX framework ("%1") does not support the "%2" control
-35072	LRW_MSG_LOGIC_MGR AJAX UNSUPPORTED_USER_ACTION	The "%1" UserAction is not supported on the specified AJAX control ("%2")
-35071	LRW_MSG_LOGIC_MGR_ELEMENT_DISABLED_PERFORMING_NON_EVAL	The acted-on "%1" element is disabled. Performing the action anyway
-35070	LRW_MSG_LOGIC_MGR_ELEMENT_DISABLED_PERFORMING_EVAL	The acted-on "%1" element is disabled. Performing the "EvalJavaScript" action anyway
-35069	LRW_MSG_LOGIC_MGR_ELEMENT_DISABLED_PERFORMING_RTS	The acted-on "%1" element is disabled. Performing the action anyway, as requested by the "Ignore acted-on element being disabled" Runtime Setting (in Preferences / Options)
-35068	LRW_MSG_LOGIC_MGR_ELEMENT_DISABLED_NOT_PERFORMING	The acted-on "%1" element is disabled. Action not performed. Please verify that the correct element is being described. If yes, consider using the "Ignore acted-on element being disabled" Runtime Setting (in Preferences / Options)
-35067	LRW_MSG_LOGIC_MGR_LIMIT_NO_NETWORK_TIMERS_EXCEEDED	"Limit no-network timers at end of step" Runtime Setting (%_1_id) exceeded. Not evaluating any more setTimeout/setInterval-specified scripts in this step
-35066	LRW_MSG_LOGIC_MGR_RETRY_TIMEOUT	Retrying due to the "RetryInterval" argument has caused the step download timeout (%_1_id seconds) to be exceeded
-35065	LRW_MSG_LOGIC_MGR DFE FAILURE	Failed to convert the data argument (error code = %_1_id)
-35064	LRW_MSG_LOGIC_MGR DFE IS NOT SET	Step '%1' requires that Data Format Extensions be enabled in the Runtime Settings
-35063	LRW_MSG_LOGIC_MGR DFE_LIST_ARGUMENT_IS_INVALID	The "%1" argument is invalid. Check that the provided extensions have their configuration files defined well
-35062	LRW_MSG_LOGIC_MGR_DFE_EMPTY_RESULT	Data Format Extension mechanism returned an empty buffer. Check that the provided extensions (%1) are able to convert the response. Also, check that the search filters defined to pass only the responses that are relevant to search
-35061	LRW_MSG_LOGIC_MGR_DFE_PARAM_NO_MATCH	No match found for the requested parameter "%1". Either the specified boundaries were not found in the response or the matched text is longer than current max html parameter size of %_2_id bytes. The total length of the response is %_3_id bytes. You can use "%4" to increase the max parameter size.
-35060	LRW_MSG_LOGIC_MGR DFE PARAM NO MATCH XPATH	No matches were found for the specified query: "%1"
-35059	LRW_MSG_LOGIC_MGR_SAVE_OFFSET_TOO_BIG	SaveOffset (%_1_id) exceeds the found value length (%_2_id) for parameter "%3". An empty string is saved
-35058	LRW_MSG_LOGIC_MGR_SAVE_LEN_TOO_BIG	SaveOffset (%_1_id) plus SaveLen (%_2_id) exceeds the found value length (%_3_id) for parameter "%4". SaveLen=%_5_id is used
-35057	LRW_MSG_LOGIC_MGR_FOUND_INSTANCE_TOO_LONG	A parameterization candidate was found, however it was not saved because itâ€™s length (%_1_id) exceeds the maximum allowable (%_2_id). To increase the maximum allowable parameter length, insert a web_max_html_param_len step or modify an existing one

Error code	Handle	Message\Additional information
-35056	LRW_MSG_LOGIC_MGR_DFE_NOT_CONVERTED	Raw data was not converted, no data was saved for parameter %1
-35055	LRW_MSG_LOGIC_MGR_REG_EXP_COMPILATION_ERR	Invalid regular expression
-35054	LRW_MSG_LOGIC_MGR_REG_EXP_WITHOUT_CAPTURE_GROUP	No substring to be saved in regular expression. Enclose part of the RE in parentheses "()" to save it to the parameter or use "Group=0" argument to save the entire RE match.
-35053	LRW_MSG_LOGIC_MGR_REG_EXP_CAPTURE_GROUP_BIGGER_THAN_AVAILABLE	The requested group number is greater than the number of groups found
-35052	LRW_MSG_LOGIC_MGR_JS_IS_NOT_SET	Step '%1' requires that JavaScript engine be enabled in the Runtime Settings
-35051	LRW_MSG_LOGIC_MGR_JS_RUN_FAILURE	Failed to run the JavaScript code
-35050	LRW_MSG_LOGIC_MGR_SYNC_ON_PARAM_FAILURE	Parameter '%1' was not defined and the time to wait for it has elapsed. This timeout can be set by passing argument 'RetryTimeoutMs' or by changing '%2 retry timeout' in Runtime Settings.
-35049	LRW_MSG_LOGIC_MGR_REG_EXP_PARAM_NO_MATCH	No match found for the requested parameter "%1". Check whether the requested regular expression exists in the response data
-35048	LRW_MSG_LOGIC_MGR_ATTRIBUTE_PARAM_NO_MATCH	No match found for the requested parameter "%1". Check whether the tag with specific attributes exists in the response data
-35047	LRW_MSG_LOGIC_MGR_WEBSOCKET_ENABLE_SOCKET_REPLAY	WebSocket api "%1" only supports socket replay
-35046	LRW_MSG_LOGIC_MGR_WEBSOCKET_ID_NOT_CONNECTED	The WebSocket whose ID is "%1" is not connected
-35045	LRW_MSG_LOGIC_MGR_WEBSOCKET_CANNOT_OPEN_FILE_FOR_SEND	Cannot open the file "%1" for %2
-35044	LRW_MSG_LOGIC_MGR_WEBSOCKET_SEND_ERROR_FOR_FILE	Failed to send the file "%1" for the WebSocket whose ID is "%2"
-35043	LRW_MSG_LOGIC_MGR_STREAM_TIME_REPORT	Stream id=%1, play time: %2, buffering time: %3
-35042	LRW_MSG_LOGIC_MGR_STREAM_BUFFERING_TIMEOUT	Stream(id=%1) closed due to buffering timeout. timeout setting: % 2 ld s, buffering time: % 3 ld s.
-35041	LRW_MSG_LOGIC_MGR_STREAM_VIDEO_DURATION	Stream id=%1, video duration: % 2 ld s
-35040	LRW_MSG_LOGIC_MGR_STREAM_CANNOT_RESOLVE_VIDEO_HEADER	Stream id=%1, mvhd atom cannot be found.
-35039	LRW_MSG_LOGIC_MGR_STREAM_PERCENT_ERROR_LIVE	Stream id=%1. "Percent" wait cannot work for live video.
-35038	LRW_MSG_LOGIC_MGR_STREAM_PROGRESS_OVER_TIME	Stream id=%1. The time you set was over the duration of the video.
-35037	LRW_MSG_LOGIC_MGR_STREAM_NOT_PLAYING	Stream id=%1. "Progress" wait cannot work if video/audio is not playing.
-35036	LRW_MSG_LOGIC_MGR_STREAM_SETP_TIME_OUT	Stream id=%1 failed. Step download timed out (% 2 ld seconds).
LrwLogicMgr_res.h		
-26249	LRW_MSG_LOGIC_MGR_INTERNAL_ERROR	Internal Error - %1
-26248	LRW_MSG_LOGIC_MGR_TEXT_LINKING_TO	Text-linking to "%1"
-26247	LRW_MSG_LOGIC_MGR_IMAGE_LINKING_TO	Image-linking to "%1"
-26246	LRW_MSG_LOGIC_MGR_MAP_AREA_LINKING_TO	Map-area-linking to "%1"
-26245	LRW_MSG_LOGIC_MGR_SUBMITTING_FORM_TO	Submitting form to "%1"
-26244	LRW_MSG_LOGIC_MGR_LOCATION_SET_TO	'document.location.href' (or 'document.location') has been set. URL="%1"
-26243	LRW_MSG_LOGIC_MGR_OPENING_WINDOW	Opening a window with URL="%1"
-26242	LRW_MSG_LOGIC_MGR_DOWNLOADING_IMAGE	Downloading an image with URL="%1" (the src property of the "IMG" element was changed by JavaScript execution)
-26241	LRW_MSG_LOGIC_MGR_DOWNLOADING_FRAME	Downloading a frame with URL="%1"
-26240	LRW_MSG_LOGIC_MGR_UNRESOLVED_PARAM	Parameter(s) referenced by the "URL" argument (number %_1_ld) and/or the "Referer" argument (number %_2_ld) within EXTRARES have not been resolved. Resource "%3" not downloaded
-26239	LRW_MSG_LOGIC_MGR_PARAM_STR_FAIL	Failed to save parameter "%1" (Parameter_SaveString rc=%_2_ld)
-26238	LRW_MSG_LOGIC_MGR_FAIL_TO_SET_COOKIE	document.cookie="%1" failed for document of URL "%2"
-26237	LRW_MSG_LOGIC_MGR_DO_PEOPLE_SOFT_FOCUS	Invoking additional focus event, on edit-field "%1"
-26236	LRW_MSG_LOGIC_MGR_NAVIGATING	Navigating to URL="%1"
-26235	LRW_MSG_LOGIC_WAITING_UNEXPIRED_TIMEOUT	Waiting for %1 seconds for unexpired setTimeout/setInterval (TimerID=%_2_ld). Timestamps: current=%_3_ld, expiration=%_4_ld
-26234	LRW_MSG_LOGIC_WAIT_UNEXPIRED_TIMEOUT_ENDED	Waiting ended (after %1 seconds) with %2 rc=%_3_ld. Timestamp=%_4_ld
-26233	LRW_MSG_LOGIC_MGR_LOCATION_RELOAD_TRUE	'document.location.reload(true)' invoked. URL="%1"
-26232	LRW_MSG_LOGIC_MGR_LOCATION_RELOAD_FALSE	'document.location.reload()' invoked (with no arguments or with 'false'). URL="%1"
-26231	LRW_MSG_LOGIC_MGR_ABORTING	Aborting download of URL "%1"
-26230	LRW_MSG_LOGIC_MGR_LOCATION_DOWNLOADING	Downloading "%1" due to the above operation on 'document.location'
-26229	LRW_MSG_LOGIC_MGR_ARG_MISSING_OR_INVALID	The "%1" argument is missing or invalid
-26228	LRW_MSG_LOGIC_MGR_TEXT_LINK_NOT_FOUND	Text-link ("%1") not found
-26227	LRW_MSG_LOGIC_MGR_IMAGE_NOT_FOUND	Image not found
-26226	LRW_MSG_LOGIC_MGR_BUTTON_NOT_FOUND	Button not found
-26225	LRW_MSG_LOGIC_MGR_BUTTON_DISABLED	Button is disabled. Performing the action anyway
-26224	LRW_MSG_LOGIC_MGR_EDIT_FIELD_NOT_FOUND	Edit field not found
-26223	LRW_MSG_LOGIC_MGR_FILE_FIELD_NOT_FOUND	File field not found
-26222	LRW_MSG_LOGIC_MGR_RADIO_GROUP_NOT_FOUND	Radio item not found (name="%1", value not specified)
-26221	LRW_MSG_LOGIC_MGR_CHECK_BOX_NOT_FOUND	Check-box not found
-26220	LRW_MSG_LOGIC_MGR_CHECK_BOX_ALREADY_CHECKED	Check-box already checked. No action taken

Error code	Handle	Message\Additional information
-26219	LRW MSG LOGIC MGR CHECK BOX ALREADY UNCHECKED	Check-box already unchecked. No action taken
-26218	LRW MSG LOGIC MGR SELECT NOT FOUND	List ("SELECT" element) not found
-26217	LRW MSG LOGIC MGR OPTION NOT FOUND	Option ("OPTION" element) not found in the specified list ("SELECT" element)
-26216	LRW MSG LOGIC MGR OPTION ALREADY SELECTED	Option to be selected was selected already. No action taken
-26215	LRW MSG LOGIC MGR OPTION ALREADY DESELECTED	Option to be deselected was deselected already. No action taken
-26214	LRW MSG LOGIC MGR TEXT AREA NOT FOUND	Text-area not found
-26213	LRW MSG LOGIC MGR MAP NOT FOUND	Map "%1" not found
-26212	LRW MSG LOGIC MGR AREA NOT FOUND	Area not found in map
-26211	LRW MSG LOGIC MGR EVAL EXPRESSION FAILED	JavaScript evaluation of the "Expression" argument failed
-26210	LRW MSG LOGIC MGR EVAL EXPRESSION UNSUPPORTED TYPE	Unsupported data type (% 1 Id) returned by JavaScript evaluation of the "Expression" argument
-26209	LRW MSG LOGIC MGR CLICK OK CANCEL	The "Click" argument must specify either "OK" or "Cancel"
-26208	LRW MSG LOGIC MGR COORD IGNORED	Non-empty coordinates ("%1") ignored by image-link when "IsMap" is false
-26207	LRW MSG LOGIC MGR COORD INVALID	Invalid coordinates ("%1") for an image-link
-26206	LRW MSG LOGIC MGR WINDOW NOT FOUND	Browser/frame not found
-26205	LRW MSG LOGIC MGR ELEMENT FOUND IN SUB_FRAME	Warning: %1 element found in a SUB-FRAME ("%2") of the frame described/IMPLIED by the Vuser script function
-26204	LRW_MSG_LOGIC_MGR_NO_GUI_CONTEXT	There is no context for GUI-based functions. A web_browser(... "Navigate=" ...) may be missing, or the context has been reset (e.g., all windows closed or an HTML-based function called)
-26203	LRW MSG LOGIC MGR DOWNLOADING INPUT TYPE IMAGE	Downloading an image with URL="%1" (the src property of an "INPUT" element of type "image" was changed by JavaScript execution)
-26202	LRW MSG LOGIC MGR NOT FOUND PARAMETER	Value of the "%1" parameter could not be obtained (Parameter_GetParameterExt rc=% 2 Id)
-26201	LRW MSG LOGIC MGR SKIPPING LOG SEARCH	"%1" is ignored when log file search is disabled. To enable log file search, specify "EnableLogSearch=1" in the .cfg file
-26200	LRW MSG LOGIC MGR UNHANDLED EXTRARES	At least one of the resources specified by EXTRARES has not been downloaded due to the above error(s)
-26199	LRW MSG LOGIC MGR SKIPPING GET SOCKET INFO	%1 is ignored when get socket info is disabled. To enable getting socket info, specify "EnableGetSocketsInfo=1" in the .cfg file
-26198	LRW MSG LOGIC MGR WRONG INFO TYPE	InfoType parameter ("%1") of %2 function is missing/misspelled
-26197	LRW MSG LOGIC MGR HISTORY DOWNLOADING	Downloading "%1" due to a History operation (e.g., back/forward/go)
-26196	LRW MSG LOGIC MGR FOUND TEXT ALERT AED	Alert ContentCheck Rule "%1" in Application "%2" triggered. Text "%3" matched in alert(): "%4"
-26195	LRW MSG LOGIC MGR FOUND PFX SFX ALERT AED	Alert ContentCheck Rule "%1" in Application "%2" triggered. Text Pfx="%3" and Sfx="%4" matched in alert(): "%5"
-26194	LRW MSG LOGIC MGR NOT FOUND TEXT ALERT AED	Alert ContentCheck Rule "%1" in Application "%2" triggered. Text "%3" not matched in alert(): "%4"
-26193	LRW MSG LOGIC MGR NOT FOUND PFX SFX ALERT AED	Alert ContentCheck Rule "%1" in Application "%2" triggered. Text Pfx="%3" and Sfx="%4" not matched in alert(): "%5"
-26192	LRW MSG LOGIC MGR ADD COOKIE FAILED	Failed to add Cookie "%1"
-26191	LRW MSG LOGIC METHOD START DOWNLOAD DOWNLOADING	Downloading "%1" specified by a startDownload call
-26190	LRW MSG LOGIC MGR WEB ELEMENT NOT FOUND	Web element not found (Tag is "%1", Text is "%2")
-26189	LRW MSG LOGIC MGR TAG NOT SUPPORTED	Tag ("%1") not supported
-26188	LRW MSG LOGIC MGR DOWNLOADING LINK	Downloading a resource of a "LINK" element with URL="%1"
-26187	LRW MSG LOGIC MGR PAUSE SUCCESS ON UNIQUE ID	The "%1" with ID "%2" was successful
-26186	LRW MSG LOGIC MGR PAUSE SUCCESS ON NON UNIQUE ID	Pausing all "%1" with non unique ID "%2" - % 3 Id verifications
-26185	LRW MSG LOGIC MGR PAUSE ID UNDECLARED	"%1" failed - undeclared ID "%2"
-26184	LRW MSG LOGIC MGR PAUSE ALREADY PAUSED	"%1" with ID "%2" is already paused - ignoring pause request
-26183	LRW MSG LOGIC MGR RESUME SUCCESS ON UNIQUE ID	The "%1" request with ID "%2" was successful
-26182	LRW MSG LOGIC MGR RESUME SUCCESS ON NON UNIQUE ID	Resuming all "%1" with non unique ID "%2" - % 3 Id verifications
-26181	LRW MSG LOGIC MGR RESUME ID UNDECLARED	"%1" failed - undeclared ID "%2"
-26180	LRW MSG LOGIC MGR RESUME ALREADY ACTIVE	"%1" with ID "%2" is already active - ignoring resume request
-26179	LRW MSG LOGIC MGR BROWSER DOWNLOAD	Downloading "%1" specified by web_browser(..., "Download=", ...)
-26178	LRW MSG LOGIC MGR NO MATCH OF THAT TYPE	No %1 object found in the browser/frame
-26177	LRW MSG LOGIC MGR FOUND X MATCHES OF THAT TYPE	Found % 1 Id %2 object(s) in the browser/frame:
-26176	LRW MSG LOGIC MGR NO MATCH FOR INPUT	No "INPUT" element of type "%1" found in the browser/frame
-26175	LRW MSG LOGIC MGR FOUND X MATCHES FOR INPUT TAG	Found % 1 Id "INPUT" element(s) of type "%2" in the browser/frame:
-26174	LRW MSG LOGIC MGR RADIO GROUP NOT FOUND WITH VALUE	Radio item not found (name="%1", value="%2")
-26173	LRW MSG LOGIC MGR FOUND X MATCHES FOR RADIO	Found % 1 Id radio group(s) in the browser/frame:
-26172	LRW MSG LOGIC MGR WINDOW NAVIGATE	'window.navigate()' invoked. URL="%1"
-26171	LRW MSG LOGIC MGR DOWNLOADING XML FILE	Downloading XML file with URL="%1"
-26170	LRW MSG LOGIC MGR DOWNLOADING SCRIPT	Downloading a script with URL="%1" (the src property of the "SCRIPT" element was changed by JavaScript execution)
-26169	LRW MSG LOGIC MGR REFRESH IS NOT SUPPORTED	"UserAction=Refresh" not supported. No action taken
-26168	LRW MSG LOGIC MGR EDIT FIELD SAME VALUE UNENCR	Setting an edit-field to the same value as it already had ("%1")
-26167	LRW MSG LOGIC MGR EDIT FIELD SAME VALUE ENCR	Setting an edit-field to the same value as it already had
-26166	LRW MSG LOGIC MGR RADIO BUTTON ALREADY SELECTED	Selecting a radio button which was already selected
-26165	LRW MSG LOGIC MGR TEXT AREA WITH SAME VALUE	Setting a text-area to the same value as it already had ("%1")
-26164	LRW_MSG_LOGIC_MGR_FILE_WITH_SAME_PATH	Setting a file edit field to the same value as it already had ("%1")

Error code	Handle	Message\Additional information
-26163	LRW_MSG_LOGIC_MGR_OPTION_ALREADY_SELECTED_DESELECTS_OTHERS	Option to be selected was selected already. Deselecting all other options in the multiple-selection list ("SELECT" element)
-26162	LRW_MSG_LOGIC_MGR_LOCATION_REPLACE	'document.location.replace()' invoked. URL="%1"
-26161	LRW_MSG_LOGIC_MGR_FRAME_NOT_FOUND	Frame not found in browser/dialog
-26160	LRW_MSG_LOGIC_MGR_BROWSER_NOT_FOUND	Browser not found
-26159	LRW_MSG_LOGIC_MGR_NO_FRAME_MATCH	No FRAME/IFRAME object found in the specified browser
-26158	LRW_MSG_LOGIC_MGR_X_FRAMES_MATCH	Found % 1 Id FRAME/IFRAME object(s) in the browser
-26157	LRW_MSG_LOGIC_MGR_FOUND_BROWSERS	Found % 1 Id browser(s)
-26156	LRW_MSG_LOGIC_MGR_DOWNLOADING_IFRAME	Downloading an inline frame with URL="%1"
-26155	LRW_MSG_LOGIC_MGR_TABLE_NOT_FOUND	Table not found
-26154	LRW_MSG_LOGIC_MGR_INVALID_DATE_FORMAT	Parameter "%1" ("%2") date format is invalid.
-26153	LRW_MSG_LOGIC_MGR_NAVIGATING_TO_HOMR_PAGE	Navigating to home page at URL="%1"
-26152	LRW_MSG_LOGIC_MGR_LOCATION_RELOAD_MODELESS_DIALOG	'window.showModelessDialog()' invoked. URL="%1"
-26151	LRW_MSG_LOGIC_MGR_DOWNLOADING_DUE_TO_WINDOW	Downloading "%1" due to the above window function (e.g., navigate, showModalDialog, showModelessDialog)
-26150	LRW_MSG_LOGIC_MGR_POPUP_NOT_FOUND	Pop-up window not found
-26149	LRW_MSG_LOGIC_MGR_MODELESS_NOT_FOUND	Modeless dialog not found in browser
LrwMessageCategories_res.h		
-34699	LRW_MSG_CAT_HTML_ERROR	HTML Error
-34698	LRW_MSG_CAT_DECOMPRESSION_ERROR	Decompression Error
-34697	LRW_MSG_CAT_PAC_ERROR	Proxy Automatic Configuration (PAC) Error
LrwNetRur_res.h		
-26099	LRW_MSG_NET_RUR_INTERNAL_ERROR	Internal Error - %1
-26098	LRW_MSG_NET_RUR_NOT_ENOUGH_MEM	Not enough memory (% 1 Id bytes) for %2
-26097	LRW_MSG_NET_RUR_RRS_MSG	[message number reserved to Replay-Recorded-Session (RRS) and never used in FormatGenericMessage]
LrwNetSocket_res.h		
-27799	LRW_MSG_NET_SOCKET_PRT_FTP_CTL	% 1 Id-byte FTP control connection data for "%2"
-27798	LRW_MSG_NET_SOCKET_PRT_SPDY_DATA	% 1 Id-byte SPDY data for "%2"
-27797	LRW_MSG_NET_SOCKET_PRT_HTTP2_DATA	% 1 Id-byte HTTP2 data for "%2"
-27796	LRW_MSG_NET_SOCKET_PRT_HTTP2_SETTINGS	% 1 Id-byte HTTP2 settings frame received from "%2"
-27795	LRW_MSG_NET_SOCKET_PRT_SPDY_PUSH	% 1 Id-byte SPDY server push stream from "%2"
-27794	MSG_COULD_NOT_RESOLVE	Could not resolve address of host %1 Additional information: • Try to access the application with a browser from the host machine and from another machine (such as the recording machine). • Check that you accurately specified the correct host name and port. • Ping the host/port. • Check the DNS server configuration on the recording machine and the injector machine. • If you are using a name server(s), check whether the server host(s) are up (e.g. try to ping the server(s)). • Try to resolve another hostname that you know should work, to check that the name resolution server application is running. • Replace the host name with the IP address.
-27793	MSG_FAILED_TO_CONNECT	Failed to connect to server "%1:% 2 Id".
-27792	MSG_FAILED_TO_CONNECT_REASON	Failed to connect to server "%1:% 2 Id": %3
-27791	MSG_PROXY_SHUT_CONNECTION	Proxy "%1" has shut the connection
-27790	MSG_READ_FROM_PROXY_FAILED	Read from proxy "%1" failed
-27789	MSG_PROXY_FAILED_TO_CONNECT	Proxy "%1" failed to connect to server "%2" -- returned status code % 3_Id %4 Additional information: • Try to access the application with a browser from the injector machine and from another machine (such as the recording machine). • Check that you accurately specified the correct host name and port. • Ping the host/port. • Check if the server application you are trying to access is running. • If you used a hostname, check if it was resolved to the correct address. • Check if the server application is listening to the right port.
-27788	MSG_SEND_FAILED	Failed to transmit data to network

Error code	Handle	Message\Additional information
-27787	MSG_PREMATURE_SHUTDOWN	Server "%1" has shut down the connection prematurely. Additional information: • Ping the remote host to which you were connected. If it does not respond, it may be offline or there may be a network problem. Try again later. • Ping a local host to verify that your local network is still functioning. • Ping your local router address. • Ping a host on the same subnet as the remote host to which you were connected (if you know of one). This will verify that the destination network is functional. • Send a "traceroute" command to the remote host. This will not reveal the problem unless you know the router addresses at the remote end, but it may help you determine if the problem is somewhere along the network path.
-27786	MSG_RECV_FAILED	Failed to read data from server "%1" Additional information: • Ping the remote host to which you were connected. If it does not respond, it may be off-line or there may be a network problem. • Increase the socket buffer size using the TCP_BUFFER_SIZE option in web_set_sockets_option.
-27785	MSG_MISSING_PASSIVE_REPLY	Missing passive socket "%1" Additional information: Check the server reply and try to solve the problem accordingly.
-27784	MSG_UNPARSABLE_PASSIVE_RESPONSE	Unable to find address of passive FTP port in server response: %1 Additional information: Check the server reply and try to solve the problem accordingly.
-27783	MSG_FTP_TRANSIENT_ERROR	FTP server "%1" returned transient error code %_2_id : %3 Additional information: Check the server reply and try to solve the problem accordingly.
-27782	MSG_FTP_FATAL_ERROR	FTP server "%1" returned error code %_2_id : %3 Additional information: Check the server status code against FTP RFC.
-27781	MSG_FTP_SERVER_SHUT_CONNECTION	FTP server "%1" has shut the connection
-27780	MSG_BUSYWAIT	Busy-wait detected in state %1 for URL "%2"
-27779	MSG_CONNECT_TIMEOUT	Timeout (%_1_id seconds) exceeded while attempting to establish connection to host "%2" Additional information: • If you used an IP address for the destination, verify that it is a valid IP address. • If you used a hostname, check that it was resolved to the correct address. • If you have a router configured, check that the router is running (check by pinging it, and then ping an address on the other side of it). Send a 'traceroute' command to the destination address to check that all the routers are functional. • Check your subnet mask. If you don't have the proper subnet mask, your network system may treat a local address as a remote address (so it forwards addresses on the local subnet to the router, rather than broadcasting an ARP request locally), or visa versa. • Increase the HTTP-request connect timeout in Runtime Settings > Internet Protocol > Preferences > Options.
-27778	MSG_RECV_TIMEOUT	Timeout (%_1_id seconds) exceeded while waiting to receive data for URL "%2"
-27777	MSG_GENERAL_TIMEOUT	Timeout (%_1_id seconds) exceeded in state %2 for URL "%3" Additional information: • Ping the remote host to which you were connected. If it does not respond, it may be off-line or there may be a network problem. • Verify that the server application you are trying to access is running.. • Increase the HTTP-request connect timeout in Runtime Settings > Internet Protocol > Preferences > Options.
-27776	MSG_SSL_OPERATION_FAILED	[GENERAL_MSG_CAT_SSL_ERROR]%1 to host "%2" failed
-27775	MSG_SSL_NEEDS_CLIENT_CERT	No client certificates were sent to server %1. Use "%2" to specify a suitable one.
-27774	MSG_SSL_PROTOCOL_ERROR	SSL protocol error when attempting to %1 with host "%2"
-27773	MSG_UNKNOWN_SSL_ERROR	Unknown SSL error when attempting to negotiate connection with host "%1" Additional information: A client certificate was not specified. Use web_set_certificate_ex to specify a certificate.
-27772	MSG_SSL_CONNECTION_CLOSED_DURING_CONNECT	Server "%1" shut connection during attempt to negotiate SSL session
-27771	MSG_MISSING_CERTIFICATE_FILE_TYPE	No certificate file type. Additional information: Specify a certificate file type by adding the "CertFormat=X" to web_set_certificate_ex. X can be "PEM" or "ANS1".

Error code	Handle	Message\Additional information
-27770	MSG_UNSUPPORTED_CERTIFICATE_FILE_TYPE	[GENERAL_MSG_CAT_SSL_ERROR]Unsupported certificate file format "%1", only PEM and ASN1 are currently supported. Additional information: Use PEM or ASN1 certificate format. Use the OpenSSL tool to convert pkcs12 certificates to PEM certificates. Use the Winlnet replay mode. In Runtime Settings > Internet Protocol:Preferences node, check the Winlnet replay instead of Sockets (Windows only) option in the Advanced section.
-27769	MSG_CERT_PATH_TOO_LONG	Full path length %_1_Id for Certificate File exceeds %_2_Id Additional information: The maximum size for the certificate file was exceeded. Move the certificate file to the script directory or use a relative path.
-27768	MSG_KEY_PATH_TOO_LONG	Full path length %_1_Id for Key File exceeds %_2_Id Additional information: The maximum size for the key file was exceeded. Move the key file to the script directory or use a relative path.
-27767	MSG_CANT_SET_CERTIFICATE	Cannot set Certificate File "%1". File format is probably invalid (should be ASN1 or PEM).
-27766	MSG_CANT_SET_KEY	Cannot set Key File for certificate "%1". Please check file format (should be PEM), password correctness, and matching to the certificate file.
-27765	MSG_UNSUPPORTED_PROTOCOL	Unsupported protocol: Only http, https and FTP are supported
-27764	MSG_NO_HOSTNAME	No hostname provided
-27763	MSG_SOCKET_FAIED	Failed to create socket
-27762	MSG_WSACREATEEVENT_FAILED	WSACreateEvent failed
-27761	MSG_UNSUPPORTED_AUTHENTITHICATION	%1 authentication not supported in Socket replay -- Try replaying in Winlnet mode.
-27760	MSG_REQUEST_FAILED	Request "%1" failed
-27759	MSG_OUT_OF_FTP_SOCKETS	Unable to allocate socket for FTP data connection, try increasing the number of connections in the runtime setting tab
-27758	MSG_ILLEGAL_MAXCONNECTIONS	Invalid value (%_1_Id) specified for MAX_TOTAL_CONNECTIONS: Must be between between %_2_Id and %_3_Id Additional information: Choose a number between the minimum and maximum number of connections per host.
-27757	MSG_BAD_OPTION	Unknown option: %1 Additional information: An unsupported option was specified for web_set_sockets_option. Add a web_set_sockets_option function with the "HELP" option. Specify an empty string for its value, in order to send information about the available options to the Replay log.
-27756	MSG_OUT_OF_MEMORY	Out of memory Additional information: Close other applications running on the same machine. Reduce the number of virtual users on the current machine.
-27755	MSG_BAD_SSL_VER	Unknown SSL version %1: use one of '2', '3', '2&3', 'TLS', 'TLS1.1', 'TLS1.2', 'TLS1.3' Additional information: An unsupported version was specified for the SSL_VERSION argument in web_set_sockets_option
-27754	MSG_IP_UNAVAILABLE	The user IP address %1:%_2_Id is not available for this machine. Using default address instead.
-27753	MSG_BAD_IP_FORMAT	Can not parse ip address %1 Additional information: An invalid Internet address was used in web_set_sockets_option (for example, a portion of an "a.b.c.d" address exceeds 255 characters). Check the IP address and correct it.
-27752	MSG_FAILED_TO_GET_LOCAL_NAME	Failed to obtain local host name. Using default address instead.
-27751	MSG_NEEDS_INT	%1 takes an integer value Additional information: An invalid integer value was used in web_set_sockets_option
-27750	MSG_BAD_SHUTDOWN_MODE	Illegal %1: %2 -- use FAST, GRACEFUL or ABRUPT Additional information: Correct the second parameter in web_set_sockets_option("SHUTDOWN_MODE") with "FAST", "GRACEFUL" or "ABRUPT" as second parameter.
-27749	MSG_PRIVATE_KEY_NEEDS_PASSWORD	User's private key requires a password.
-27748	MSG_BUFFER_OVERFLOW	Buffer Overflow when generating HTTP request. Try to increase the "network buffer size" in the Runtime Settings.
-27747	MSG_PAGE_DOWNLOAD_TIMEOUT	Page download timeout (%_1_Id seconds) has expired.
-27746	MSG_FAILED_TO_INITIALIZE_SSL	Failed to initialize SSL operation: %1
-27745	MSG_WRONG_SSL_CIPHER_FOR_HTTP2	Cipher %1 used by current SSL connection is not supported by HTTP2. Use web_set_sockets_option to supply suitable ciphers.
-27744	LRW_MSG_NET_SOCKET_NOT_ENOUGH_MEM	Not enough memory (%_1_Id bytes) for %2 Additional information: Close other applications running on the same machine. Reduce the number of virtual users on the current machine.
-27743	MSG_SEND_TIMEOUT	Timeout (%_1_Id seconds) exceeded after transmitting %_2_Id %3 bytes out of %_4_Id for URL %5
-27742	MSG_USER_NEEDED_FOR_NTLM	DOMAIN\user and password needed for NTLM authentication
-27741	MSG_FAILED_TO_CREATE_RESPONSE_OBJECT	Failed to register response object

Error code	Handle	Message\Additional information
-27740	MSG_FAILED_TO_SET_CIPHER_LIST	Failed to set SSL cipher list to "%2", reason %1
-27739	MSG_INTERNAL_ERROR_CONNECTION_CLOSED	Internal Error - connection to "%1" is closed in state %2
-27738	MSG_INVALID_TASK	Internal Error - xfiLrwNetWaitForTaskOK called with invalid task
-27737	MSG_NO_HTASK	Internal Error - xfiLrwNetWaitForTaskOK called with task which has not been registered in NetSocket
-27736	MSG_WAIT_NOT_ASYNC	Internal Error - xfiLrwNetWaitForTaskOK called in synchronous mode
-27735	MSG_OVERLAPPED_SEND_FAILED	Overlapped transmission of request to "%1" for URL "%2" failed
-27734	MSG_MISSING_CERT_PATH_OR_INDEX	Using the "%1"() function, either specify a certificate file PATH via the "CertFilePath=" argument or a certificate INDEX via "CertIndex=" argument (valid only on Windows NT/2000/XP using socket replay or on any Windows platform using Wininet replay)
-27733	MSG_INVALID_ENVIRONMENT	Using Windows certificates by index is impossible in this environment (see trace file for details). Please, use "%1"() with "CertFilePath=" argument instead
-27732	MSG_INVALID_ENVIRONMENT_SSL	Preparation for SSL connection failed
-27731	MSG_INVALID_CERT_INDEX	Can't find a certificate by the input CertIndex
-27730	MSG_CERT_INDEX_OUT_OF_RANGE	The certificate index value (% 1 Id) is bigger than the maximum possible value (% 2 Id)
-27729	MSG_SSL_STX_USE_CERTIFICATE_FAILED	SSL context certificate initialization failed for certificate with index=% 1 Id. Please, use "%2"() with "CertFilePath=" argument instead
-27728	MSG_SSL_STX_USE_PRIVATE_KEY_FAILED	SSL context private key initialization failed for certificate with index=% 1 Id. Please, use "%2"() with "CertFilePath=" argument instead
-27727	LRW_MSG_NET_SOCKET_INTERNAL_ERROR	Internal Error - %1
-27726	MSG_DIGEST_AUTH_INT_UNSUPPORTED	Digest authentication with Integrity Protection requested by server, but not implemented in Opentext Performance Engineering
-27725	MSG_USER_NEEDED_FOR_DIGEST	User and password needed for digest authentication
-27724	MSG_DIGEST_NO_NONCE	Server did not provide nonce for digest authentication
-27723	MSG_WAIT_FOR_TASK_TIMEOUT	Timeout of % 2 Id expired when waiting for the completion of URL "%1"
-27722	MSG_USER_DATAPOINT_FAILED	Reporting user data point "%1" failed (Transaction UserDataPoint rc=% 2 Id)
-27721	MSG_STEP_DOWNLOAD_TIMEOUT_NON_RESOURCES	Step download timeout (% 1 Id seconds) has expired when downloading resource "%2"
-27720	MSG_STEP_DOWNLOAD_TIMEOUT_RESOURCES	Step download timeout (% 1 Id seconds) has expired when downloading resource "%2". Set the "Step Timeout caused by resources is a warning" Runtime Setting to Yes/No to have this message as a warning/error, respectively
-27719	LRW_MSG_FIND_PROXY_FOR_URL_FUNC_EXECUTION_FAILED	Executing the Proxy Automatic Configuration (PAC) script function (FindProxyForUrl) failed for URL="%1" and is ignored
-27718	LRW_MSG_FIND_PROXY_FOR_URL_FUNC_BAD_RET_VAL	The Proxy Automatic Configuration (PAC) function (FindProxyForUrl) return value is not a string and is ignored for URL="%1" (internal type=% 2 Id, address=%3, length=% 4 Id)
-27717	LRW_MSG_NET_SOCKET_PAC_FAILED_FOR_ALL_PROXIES	Resolve/connect failed for the following proxies specified in the automatic configuration script: "%1". Requested URL is "%2".
-27716	LRW_MSG_NET_SOCKET_PAC_PROXY_BAD_FORMAT	One of the proxy specifications is invalid in the string returned by the FindProxyForURL function in the automatic configuration script (neither "PROXY host:port" nor just "host:port")
-27715	MSG_FAILED_TO_SIGN_WITH_CERTIFICATE	Failed to sign with the Certificate
-27714	MSG_INDEX_ONE_BASED	%1 takes a one-based index
-27713	MSG_HOST_PORT_NOT_FOUND	Failed to obtain host:port entry for %1:% 2 Id
-27712	LRW_MSG_NET_SOCKET_VERIFY_FILE_NOT_FOUND	Requested verify file (%1) not found.
-27711	LRW_MSG_NET_SOCKET_LOAD_VERIFY_LOCATIONS_FAILED	Load verify locations failed : %1 (%2)
-27710	LRW_MSG_NET_SOCKET_INVALID_NTLM_TYPE2_HEADER	Invalid NTLM type 2 message: "%1"
-27709	LRW_MSG_NET_SOCKET_CERTIFICATE_FILE_NOT_FOUND	Certificate File ("%1") not found.
-27708	LRW_MSG_NET_SOCKET_KEY_FILE_NOT_FOUND	Key File for certificate ("%1") not found.
-27707	LRW_MSG_NET_SOCKET_CERTIFICATE_FILE_NO_READ_PERMISSION	Insufficient permission to read Certificate File ("%1").
-27706	LRW_MSG_NET_SOCKET_KEY_FILE_NO_READ_PERMISSION	Insufficient permission to read Key File ("%1").
-27705	LRW_NET_SOCKET_INVALID_KRB5_HOST	Kerberos can not recognize hostname %1.
-27704	LRW_NET_SOCKET_INVALID_KRB5_PRINC	Kerberos can not use credentials %1/%2.
-27703	LRW_NET_SOCKET_WSA_IO_PENDING	"WSA_IO_PENDING"
-27702	LRW_NET_SOCKET_WSABASEERR	"[0] No Error"
-27701	LRW_NET_SOCKET_WSAEINTR	"[10004] Interrupted system call"
-27700	LRW_NET_SOCKET_WSAEBADF	"[10009] Bad file number"
-27699	LRW_NET_SOCKET_WSAEACCES	"[10013] Permission denied"
-27698	LRW_NET_SOCKET_WSAEFAULT	"[10014] Bad address"
-27697	LRW_NET_SOCKET_WSAEINVAL	"[10022] Invalid argument"
-27696	LRW_NET_SOCKET_WSAEMFILE	"[10024] Too many open files"
-27695	LRW_NET_SOCKET_WSAEWOULDLOCK	"[10035] Operation would block"
-27694	LRW_NET_SOCKET_WSAEINPROGRESS	"[10036] Operation now in progress"
-27693	LRW_NET_SOCKET_WSAEALREADY	"[10037] Operation already in progress"
-27692	LRW_NET_SOCKET_WSAENOTSOCK	"[10038] Socket operation on non-socket"
-27691	LRW_NET_SOCKET_WSAEDESTADDRREQ	"[10039] Destination address required"
-27690	LRW_NET_SOCKET_WSAEMSGSIZE	"[10040] Message too long"
-27689	LRW_NET_SOCKET_WSAEPROTOTYPE	"[10041] Protocol wrong type for socket"

Error code	Handle	Message\Additional information
-27688	LRW_NET_SOCKET_WSAENOPROTOOPT	"[10042] Bad protocol option"
-27687	LRW_NET_SOCKET_WSAEPROTONOSUPPORT	"[10043] Protocol not supported"
-27686	LRW_NET_SOCKET_WSAESOCKTNOSUPPORT	"[10044] Socket type not supported"
-27685	LRW_NET_SOCKET_WSAEOPNOTSUPP	"[10045] Operation not supported on socket"
-27684	LRW_NET_SOCKET_WSAEPFNOSUPPORT	"[10046] Protocol family not supported"
-27683	LRW_NET_SOCKET_WSAEAFNOSUPPORT	"[10047] Address family not supported by protocol family"
-27682	LRW_NET_SOCKET_WSAEADDRINUSE	"[10048] Address already in use\r\nTry changing the registry value \\r\nHKEY_LOCAL_MACHINE\\System\\CurrentControlSet\\Services\\Tcpip\\Parameters\\TcpTimedWaitDelay to 30\r\nand HKEY_LOCAL_MACHINE\\System\\CurrentControlSet\\Services\\Tcpip\\Parameters\\MaxUserPort to 65534\r\nand rebooting the machine\r\nSee the readme.doc file for more information"
-27681	LRW_NET_SOCKET_WSAEADDRNOTAVAIL	"[10049] Can't assign requested address"
-27680	LRW_NET_SOCKET_WSAENETDOWN	"[10050] Network is down"
-27679	LRW_NET_SOCKET_WSAENETUNREACH	"[10051] Network is unreachable"
-27678	LRW_NET_SOCKET_WSAENETRESET	"[10052] Net dropped connection or reset"
-27677	LRW_NET_SOCKET_WSAECONNABORTED	"[10053] Software caused connection abort"
-27676	LRW_NET_SOCKET_WSAECONNRESET	"[10054] Connection reset by peer\r\nThis is probably because the SSL protocol version is not supported. Try switching the TLS/SSL version using "web_set_sockets_option" API."
-27675	LRW_NET_SOCKET_WSAENOBUFS	"[10055] No buffer space available\r\nTry changing the registry value \\r\nHKEY_LOCAL_MACHINE\\System\\CurrentControlSet\\Services\\Tcpip\\Parameters\\TcpTimedWaitDelay to 30\r\nand HKEY_LOCAL_MACHINE\\System\\CurrentControlSet\\Services\\Tcpip\\Parameters\\MaxUserPort to 65534\r\n"
-27674	LRW_NET_SOCKET_WSAEISCONN	"[10056] Socket is already connected"
-27673	LRW_NET_SOCKET_WSAENOTCONN	"[10057] Socket is not connected"
-27672	LRW_NET_SOCKET_WSAESHUTDOWN	"[10058] Can't send after socket shutdown"
-27671	LRW_NET_SOCKET_WSAETOOMANYREFS	"[10059] Too many references, can't splice"
-27670	LRW_NET_SOCKET_WSAETIMEDOUT	"[10060] Connection timed out"
-27669	LRW_NET_SOCKET_WSAECONNREFUSED	"[10061] Connection refused"
-27668	LRW_NET_SOCKET_WSAELOOP	"[10062] Too many levels of symbolic links"
-27667	LRW_NET_SOCKET_WSAENAMETOOLONG	"[10063] File name too long"
-27666	LRW_NET_SOCKET_WSAEHOSTDOWN	"[10064] Host is down"
-27665	LRW_NET_SOCKET_WSAEHOSTUNREACH	"[10065] No Route to Host"
-27664	LRW_NET_SOCKET_WSAENOTEMPTY	"[10066] Directory not empty"
-27663	LRW_NET_SOCKET_WSAEPROCLIM	"[10067] Too many processes"
-27662	LRW_NET_SOCKET_WSAEUSERS	"[10068] Too many users"
-27661	LRW_NET_SOCKET_WSAEDQUOT	"[10069] Disc Quota Exceeded"
-27660	LRW_NET_SOCKET_WSAESTALE	"[10070] Stale NFS file handle"
-27659	LRW_NET_SOCKET_WSAEREMOTE	"[10071] Too many levels of remote in path"
-27658	LRW_NET_SOCKET_WSASYSNOTREADY	"[10091] Network SubSystem is unavailable"
-27657	LRW_NET_SOCKET_WSAVERNOTSUPPORTED	"[10092] WINSOCK DLL Version out of range"
-27656	LRW_NET_SOCKET_WSA_NOTINITIALIZED	"[10093] Successful WSASTARTUP not yet performed"
-27655	LRW_NET_SOCKET_RECEIVE_FAILED	Receive ("%1") failed for URL="%2", rc=% 3 Id, LastError=% 4 Id%5%6
-27654	MSG_NO_NATIVE_NTLM_ON_UNIX	Can not use Windows native NTLM authentication on non-Windows platform
-27653	MSG_NATIVE_NTLM_TYPE1_ERROR	Error during creation of Type1 token using Windows native NTLM implementation: %1
-27652	MSG_NATIVE_NTLM_TYPE3_ERROR	Error during creation of Type3 token using Windows native NTLM implementation: %1
-27651	LRW_NET_SOCKET_RETAIN_CROSS_STEP_DOWNLOAD	Retaining cross-step download of URL="%1" (RelFrameId=%2, Internal ID=% 3 Id)
-27650	LRW_NET_SOCKET_ABORTING_CROSS_STEP_DOWNLOAD	Aborting cross-step download of URL="%1" (RelFrameId=%2, Internal ID=% 3 Id)
-27649	LRW_NET_SOCKET_ABORTING_NON_CROSS_STEP_DOWNLOAD	Aborting pending download of URL="%1" (RelFrameId=%2, Internal ID=% 3 Id)
-27648	MSG_STEP_DOWNLOAD_TIMEOUT_NO_DOWNLOAD	Step download timeout (% 1 Id seconds) has expired when no download was active)
-27647	LRW_NET_SOCKET_KEEP_ALIVE_TIMEOUT	Connection to %1:% 2 Id closed after being inactive for % 3 Id seconds, exceeding the "HTTP Keep-Alive timeout" Runtime Setting (% 4 Id seconds). URL="%5"
-27646	LRW_NET_SOCKET_READ_UNCONNECTED_SOCKET	Attempted read from an unconnected socket%1%2. URL="%3"
-27645	LRW_NET_SOCKET_REGEX_ERROR	Failed to compile regular expression "%1". Internal error code % 2 Id
-27644	MSG_STEP_DOWNLOAD_TIMEOUT_ONLY_CROSS_STEP	Step download timeout (% 1 Id seconds) has expired when only cross-step downloads (% 2 Id) were active
-27643	MSG_MAXCONNECTIONS_BELOW_USED	MAX_TOTAL_CONNECTIONS is specified as % 1 Id when % 2 Id connections are already in use. MAX_TOTAL_CONNECTIONS is set to % 3 Id
-27642	CHIL_ENGINE_CANT_FIND	Cannot find the CHIL engine. Please check your OpenSSL version.
-27641	CHIL_ENGINE_CANT_LOAD	Cannot load the CHIL engine. Please check whether the file nfhwcrhk.dll is in PATH environment variable.
-27640	SPDY_RST_FRAME	Server "%1" has sent the SPDY RST_STREAM frame with the status code "%2". The stream % 3 Id is closed.

Error code	Handle	Message\Additional information
-27639	SPDY_GOAWAY_FRAME	Server %1" has sent the SPDY GOAWAY frame with the status code "%2". The stream % 3 _id is closed.
-27638	SPDY_REPLAY_HEADER_PRINT	The server %1" has replied with headers:
-27637	SPDY_REQUEST_HEADER_PRINT	The request to server %1" is done with headers:
-27636	SPDY_REQUEST_BODY_PRINT	The request to server "%1" is done with body:
-27635	HTTP2_RST_FRAME	Server "%1" has sent the HTTP2 RST_STREAM frame with the status code "%2".
-27634	HTTP2_GOAWAY_FRAME	Server %1" has sent the HTTP2 GOAWAY frame with the status code "%2".
-27633	HTTP2_PUSH_PROMISE	Server %1" has sent the HTTP2 PUSH_PROMISE frame which is not supported.
-27632	LRW_NET_SOCKET_RETAIN_WEBSOCKET_CONNECTION	Retaining websocket connection of URI="%1" (RelFrameId=%2, Internal ID=% 3 _id)
-27631	LRW_NET_SOCKET_CLOSING_WEBSOCKET_CONNECTION	Closing websocket connection of URI="%1" (RelFrameId=%2, Internal ID=% 3 _id)
-27630	LRW_NET_SOCKET_SSL_CONNECTION_INFORMATION	\\r\\n[SSL:] Connection information:\\r\\n%1\\r\\n\\nversion : %2\\r\\ncipher : %3 (ver. %4) % 5 _id bits\\r\\nServer certificate:\\r\\n\\nname : %6\\r\\n\\nversion : %7\\r\\n\\npublic key: % 8 _id bits\\r\\n\\nSession information:\\r\\n\\nmaster key: %9\\r\\n\\nSession id: %10\\r\\n\\nSession ctx : %11\\r\\n\\n
-27629	LRW_NET_SOCKET_SSL_REUSED_SESSION	reused session
-27628	LRW_NET_SOCKET_SSL_NEW_SESSION	new session
-27627	LRW_NET_SOCKET_SSL_X509_ERROR	[SSL:] X509 certificate error % 1 _id: %2\\r\\n\\nfor certificate "%3"\\r\\n\\ndepth=% 4 _id, x509_ctx=%5, x509_ctx->ctx=%6, preverify_ok=% 7 _id, current_cert=%8, subject_name=%9
-27626	LRW_NET_SOCKET_SSL_RECEIVED	[SSL:] Received callback about handshake completion
-27625	LRW_NET_SOCKET_SSL_GET1_SESSION_FAILED	[SSL:] Incrementing a session reference count (SSL_get1_session) failed
-27624	LRW_NET_SOCKET_SSL_SESSION_FREEING_IN_CALLBACK	[SSL:] Freeing the global SSL session in a callback
-27623	LRW_NET_SOCKET_SSL_SESSION_ESTABLISHED_IN_CALLBACK	[SSL:] Established a global SSL session in a callback
-27622	LRW_NET_SOCKET_SSL_NEW_SSL	[SSL:] New SSL
-27621	LRW_NET_SOCKET_SSL_ESTABLISHING	[SSL:] %1 attempt to establish the reuse of the global SSL session (SSL_set_session rc=% 2 _id).
-27620	LRW_NET_SOCKET_SSL_SUCCESS	Successful
-27619	LRW_NET_SOCKET_SSL_FAIL	Failed
-27618	LRW_NET_SOCKET_SSL_HANDSHAKE_COMPLETE	[SSL:] Handshake complete
-27617	LRW_NET_SOCKET_SSL_ESTABLISH_AS_NEW_SESSION	[SSL:] Considering establishing the above as a new global SSL session: bSslRessionReuseGlobal=% 1 _id, _ptSSL=%2, ptConnectedSslSession=%3. Global session (_ptGlobalSslSession=%4), HTTP2=%5 :
-27616	LRW_NET_SOCKET_SSL_SESSION_FREEING	[SSL:] Freeing the global SSL session
-27615	LRW_NET_SOCKET_SSL_SESSION_ESTABLISHED	[SSL:] Established a global SSL session
-27614	LRW_NET_SOCKET_ERROR_IN_PRINT_MTLN_MSG	Error in printing NTLM Message:%1
-27613	LRW_NET_SOCKET_NTLM_TYPE2_MSG	Using NTLM type2 message: "%1"
-27612	LRW_NET_SOCKET_GEN_TYPE3_NATIVE	generating type 3 native
-27611	LRW_NET_SOCKET_NO_SOCKET_AVAILABLE	No socket (out of % 1 _id) is CURRENTLY available for a regular connection for URL="%2"
-27610	LRW_NET_SOCKET_REG_REDIRECTED_SYNC	Registered redirected synchronous download of URL="%1". Synchronous downloads count=% 2 _id
-27609	LRW_NET_SOCKET_SYNC_DOWNLOAD_END	Synchronous download ended/terminated with any other pending request(s). Synchronous downloads count=% 1 _id
-27608	LRW_NET_SOCKET_END_SYNC_DOWNLOAD	Ended synchronous download of URL="%1"
-27607	LRW_NET_SOCKET_REPORT_USER_DATA_POINT	reporting user data point %1
-27606	LRW_NET_SOCKET_RENEGOTIATE_HTTPS	Re-negotiating https connection [% 1 _id] to %2, as the server has requested client certificate
-27605	LRW_NET_SOCKET_CONNECT_SOCKET	Connected socket [% 1 _id] from %2:% 3 _id to %4:% 5 _id in % 6 _id ms
-27604	LRW_NET_SOCKET_COMPLETION_RT_CALLED	completion_rt_called % 1 _id bytes transferred
-27603	LRW_NET_SOCKET_SERVER_SHUTDOWN_CONNECTION_ON_USED_CONN	Server %1 has shut down connection [% 2 _id] prematurely (after sending request on a used connection)
-27602	LRW_NET_SOCKET_SERVER_SHUTDOWN_CONNECTION_ON_UNUSED_CONN	Server %1 has shut down connection [% 2 _id] prematurely (after sending request on an unused connection)
-27601	LRW_NET_SOCKET_FTPSERVER_SHUTDOWN_CONNECTION	FTP server %1 [% 2 _id] has shut data connection
-27600	LRW_NET_SOCKET_FTPSERVER_RETURN_CODE	FTP server %1 returned code % 2 _id : %3
-27599	LRW_NET_SOCKET_CLOSE_CONN_AFTER_WAITING	Warning: Closing connection [% 1 _id] after waiting % 2 _ids for body for % 3 _id response for URL "%4"
-27598	LRW_NET_SOCKET_SELECT_RETURN	select returned % 1 _id
-27597	LRW_NET_SOCKET_INACTIVE_SOCKET_CLOSED	Inactive socket [% 1 _id] was closed by %2:% 3 _id, probably due to Keep-Alive timeout
-27596	LRW_NET_SOCKET_FINDPROXYFORURL_RETURNED	FindProxyForURL has returned proxy %1:% 2 _id, which comprises a direct connection for URL="%3"
-27595	LRW_NET_SOCKET_AUTOPROXY_SELECT_DIRECT_CONN	Auto-proxy configuration selected a direct connection (%1:% 2 _id) for URL="%3"
-27594	LRW_NET_SOCKET_AUTOPROXY_SELECT_PROXY	Auto-proxy configuration selected proxy %1:% 2 _id for URL="%3"
-27593	LRW_NET_SOCKET_IGNORE_DIRECT_CONN	Ignoring direct connection (%1:% 2 _id) selected by auto-proxy configuration but marked as "bad" due to a previous attempt to connect to it. URL="%3"
-27592	LRW_NET_SOCKET_IGNORE_PROXY	Ignoring proxy %1:% 2 _id selected by auto-proxy configuration but marked as "bad" due to a previous attempt to connect to it. URL="%3"
-27591	LRW_NET_SOCKET_AUTOPROXT_RESULT_CACHE	Automatic Proxy Result Cache for %1:% 2 _id is marked as "BAD". Re-evaluating FindProxyForURL for URL="%3"
-27590	LRW_NET_SOCKET_RELEASE_DOWNLOAD_AFTER_WAITING	Releasing %1 download of URL="%2" after waiting for a connection for % 3 _idms

Error code	Handle	Message\Additional information
-27589	LRW_NET_SOCKET_START_DOWNLOAD	Started %1 download of URL="%2"
-27588	LRW_NET_SOCKET_EXCEED_BYTE_LIMIT_CONTINUE	ResourceByteLimit exceeded, but only % 1 Id bytes of "%2" remain to be read. Continuing to read
-27587	LRW_NET_SOCKET_EXCEED_BYTE_LIMIT_ABORT	ResourceByteLimit exceeded, aborting download of "%1"
-27586	LRW_NET_SOCKET_EXCEED_BYTE_LIMIT_CANCEL	ResourceByteLimit exceeded, canceling download of "%1"
-27585	LRW_NET_SOCKET_MODEM_SPEED_EMU_NOT_ENABLED	Modem speed emulation not enabled
-27584	LRW_NET_SOCKET_SETTING_IREADSIZE	setting iReadSize=% 1 Id because maximum modem sleep time of % 2 Id was requested
-27583	LRW_NET_SOCKET_MAXNUM_OF_OPEN_CONN_CHANGED	Maximum number of open connections changed from % 1 Id to % 2 Id
-27582	LRW_NET_SOCKET_MAX_UPLOAD_CHUNK_SIZE_CHANGED	Changing the maximum upload chunk size from % 1 Id bytes to % 2 Id bytes
-27581	LRW_NET_SOCKET_MAX_UPLOAD_CHUNK_SIZE_UNLIMITED	Changing the maximum upload chunk size from % 1 Id bytes to unlimited
-27580	LRW_NET_SOCKET_DESPAIR_TIMEOUT_CHANGED	Changing despair_TIMEOUT form % 1 Idms to % 2 Idms
-27579	LRW_NET_SOCKET_FAILED_TO_OPEN_PAC_FILE	Error: Failed to open PAC file %1, : %2
-27578	LRW_NET_SOCKET_PAC_FILE_NOT_IMPLEMENTED	PAC file by URL is not yet implemented, supply a file path instead
-27577	LRW_NET_SOCKET_BAD_FILE_LENGTH_FOR_PAC_FILE	Error: Bad file length % 1 Id for PAC file %2
-27576	LRW_NET_SOCKET_FAILED_TO_COMPILE_PAC_FILE	Error: failed to compile PAC file %1
-27575	LRW_NET_SOCKET_PROXY_NAME_TOO_LONG	Proxy name %1... too long
-27574	LRW_NET_SOCKET_FAILED_TO_CONN_PROXY	Failed to connect to proxy %1:% 2 Id - %3. Retrying with next proxy
-27573	LRW_NET_SOCKET_FIND_PROXY_FOR_URL_RETURNED	FindProxyForURL returned "%1" for URL="%2"
-27572	LRW_NET_SOCKET_CANNOT_REUSE	Connection [% 1 Id] to %2:% 3 Id via proxy %4:% 5 Id cannot be reused for HTTPS access to %6:% 7 Id
-27571	LRW_NET_SOCKET_ALREADY_CONNECTED_TO	Already connected [% 1 Id] to %2:% 3 Id
-27570	LRW_NET_SOCKET_REPORHOSTINFO_NOT_INCLUDING	ReportHostInfo: Not including URL="%1"
-27569	LRW_NET_SOCKET_FAILED_TO_OBTAIN_X509	Failed to obtain X509 from cert
-27568	LRW_NET_SOCKET_FAILED_TO_CREATE_INPUT_BIO	Failed to create input BIO. Msg="%1"
-27567	LRW_NET_SOCKET_FAILED_TO_CREATE_PKCS7	Failed to create PKCS7. Msg="%1"
-27566	LRW_NET_SOCKET_FAILED_TO_CREATE_OUTPUT_BIO	Failed to create output BIO. Msg="%1"
-27565	LRW_NET_SOCKET_FAILED_TO_CREATE_BASE64_BIO	Failed to create base64 BIO. Msg="%1"
-27564	LRW_NET_SOCKET_FAILED_TO_OBTAIN_PTR	Failed to obtain pointer to BUF_MEM.
-27563	LRW_NET_SOCKET_FAILED_TO_SAVE_SIGNED_STRING	Failed to save signed string to parameter.
-27562	LRW_NET_SOCKET_CLOSE_CONN_AFTER_REQUESTS	Closed connection [% 1 Id] to %2:% 3 Id after completing % 4 Id request(s)
-27561	LRW_NET_SOCKET_PACJS_BAD_ARGUMENTS	Bad arguments for %1
-27560	LRW_NET_SOCKET_PACJS_REQUIRE_STRING_ARG	%1 requires a string argument
-27559	LRW_NET_SOCKET_PACJS_ENUM_ARG	%1: Arg0: %2 Arg1: %3 Arg2: %4
-27558	LRW_NET_SOCKET_PACJS_CANNOT_RESOLVE_HOSTNAME	Can not resolve hostname %1
-27557	LRW_NET_SOCKET_PACJS_NOTIFY_ALERT	Notify: Alert: %1
-27556	LRW_NET_SOCKET_STATE_WAIT_BEFORE_REFRESH	Waiting % 1 f seconds before refresh to URL "%2"
-27555	LRW_NET_SOCKET_STATE_SKIPPING_URL	Skipping URL "%1": disallowed host
-27554	LRW_NET_SOCKET_STATE_CANNOT_REUSE	Connections to %1:%_2_Id and %3:%_4_Id share the same IP address, but connection [%_5_Id] to %6:%_7_Id cannot be reused for HTTPS access to %8:%_9_Id
-27553	LRW_NET_SOCKET_STATE_SHARE_SAME_IP	Hosts %1 and %2 share the same IP address -- maintaining existing connection [% 3 Id]
-27552	LRW_NET_SOCKET_STATE_CONNECT_TO_HOST	Connecting [% 1 Id] to host %2:% 3 Id
-27551	LRW_NET_SOCKET_STATE_SERVER_SHUTDOWN	Server %1 has shut down the connection [% 2 Id]
-27550	LRW_NET_SOCKET_STATE_SERVER_SHUTDOWN_PREMATURELY	Server %1 has shut down the connection [% 2 Id] prematurely %3. %4%5
-27549	LRW_NET_SOCKET_STATE_SERVER_SHUTDOWN_PREMATURELY2	Server %1 has shut down connection [% 2 Id] prematurely (after receiving complete response of previous request)
-27548	LRW_NET_SOCKET_STATE_CONSIDER_RETRY	Considering retry
-27547	LRW_NET_SOCKET_STATE_NO_RETRY_ATTEMPTED	No retry attempted
-27546	LRW_NET_SOCKET_STATE_DUE_TO_OPTION	due to "%1"/("IGNORE_PREMATURE_SHUTDOWN", ...)
-27545	LRW_NET_SOCKET_STATE_CLOSE_CONN	Closing connection [% 1 Id] to server %2 - %3
-27544	LRW_NET_SOCKET_STATE_CLOSE_CONN_WITH_CODE	Closing connection [% 1 Id] to %2 after receiving status code % 3 Id
-27543	LRW_NET_SOCKET_STATE_REQUEST_DONE	Request done "%1"
-27542	LRW_NET_SOCKET_STATE_WAIT_RETRY_DELAY	Waiting a retry delay of % 1 Id ms for URL="%2" (Internal ID=% 3 Id)
-27541	LRW_NET_SOCKET_SETOPTIONS_SET_TCP_NODELAY	Set setsockopt(TCP_NODELAY, 1) -> % 1 Id
-27540	LRW_NET_SOCKET_SETOPTIONS_TCP_NODELAY_UNDEFINED	TCP_NODELAY undefined on this platform
-27539	LRW_NET_SOCKET_SETOPTIONS_SET_TCP_RFC1323	Set setsockopt(TCP_RFC1323, 1) -> % 1 Id
-27538	LRW_NET_SOCKET_SETOPTIONS_TCP_RFC1323_NOT_SUPPORTED	ERROR TCP_RFC1323 not supported
-27537	LRW_NET_SOCKET_SETOPTIONS_CHANGE_BUFF_SIZE	Changing TCP/IP buffer size from % 1 Id to % 2 Id bytes
-27536	LRW_NET_SOCKET_SETOPTIONS_FAILED_TO_CALL_FUNC	%1 failed, rc=% 3 Id error=% 4 Id
-27535	LRW_NET_SOCKET_DESC_WARNING_READ_DATA	WARNING: read data from %1:% 2 Id which we do not know what to do with
-27534	LRW_NET_SOCKET_OPTION_LOAD_VERIFY_FILE	A PEM formatted file containing list of Certificate Authorities

Error code	Handle	Message\Additional information
-27533	LRW_NET_SOCKET_OPTION_DEFAULT_VERIFY_PATH	A directory containing a list of Certificate Authority files (in PEM format)
-27532	LRW_NET_SOCKET_OPTION_SSL_VERSION	SSL version preference (2, 3, 2&3, TLS, TLS1.1, TLS1.2)
-27531	LRW_NET_SOCKET_OPTION_SSL_CIPHER_LIST	A list of colon delimited SSL ciphers to use for SSL connection.
-27530	LRW_NET_SOCKET_OPTION_SO_REUSE_ADDRESS	Enable reuse of ports
-27529	LRW_NET_SOCKET_OPTION_USER_IP_ADDRESS	Set preferred IP address of client <ip_addr>[:<port>]
-27528	LRW_NET_SOCKET_OPTION_IP_ADDRESS_BY_INDEX	Set IP address of client to be the nth address on the client machine
-27527	LRW_NET_SOCKET_OPTION_SHUTDOWN_MODE	Controls how ports are shutdown: FAST (default), GRACEFUL, or ABRUPT
-27526	LRW_NET_SOCKET_OPTION_TCP_BUFFER_SIZE	Set TCP send and receive buffer size
-27525	LRW_NET_SOCKET_OPTION_SYNCHRONOUS_CONNECT	Specify blocking connect
-27524	LRW_NET_SOCKET_OPTION_PRINT_USER_IP_ADDRESS_LIST	Print a list of ip addresses available on a given machine
-27523	LRW_NET_SOCKET_OPTION_PRINT_SSL_INFO	Print information about SSL connections
-27522	LRW_NET_SOCKET_OPTION_TRACE_SSL_IO	Trace raw IO from SSL requests
-27521	LRW_NET_SOCKET_OPTION_DISALLOW_HOSTS	causes all requests to the listed servers to be ignored
-27520	LRW_NET_SOCKET_OPTION_ALLOW_ONLY_HOSTS	causes requests to servers not in the list to be ignored
-27519	LRW_NET_SOCKET_OPTION_STRONG_PRNG	use strong random number generator to generate SSL keys
-27518	LRW_NET_SOCKET_OPTION_MAX_CONNECTIONS_PER_HOST	maximum number of simultaneous connections per host
-27517	LRW_NET_SOCKET_OPTION_MAX_TOTAL_CONNECTIONS	maximum number of simultaneous connections per vuser
-27516	LRW_NET_SOCKET_OPTION_CLOSE_KEEPALIVE_CONNECTIONS	close all open connections
-27515	LRW_NET_SOCKET_OPTION_SSL_NO_PROXY_TUNNEL	Do not tunnel SSL through proxy
-27514	LRW_NET_SOCKET_OPTION_PROXY_INITIAL_BASIC_AUTH	Send basic authentication to proxy server before receiving an HTTP 407 error
-27513	LRW_NET_SOCKET_OPTION_INITIAL_BASIC_AUTH	Send basic authentication to server before receiving an HTTP 401 error
-27512	LRW_NET_SOCKET_OPTION_PROXY_INITIAL_AUTH	Use preemptive authentication for proxy server before receiving an HTTP 407 error. To use this authentication, select "BASIC", "NTLM", or "KERBEROS". To disable preemptive authentication, select "NONE".
-27511	LRW_NET_SOCKET_OPTION_INITIAL_AUTH	Use preemptive authentication for server before receiving an HTTP 401 error. To use this authentication, select "BASIC", "NTLM", or "KERBEROS". To disable preemptive authentication, select "NONE".
-27510	LRW_NET_SOCKET_OPTION_DESPAIR_TIMEOUT	limit amount of time to wait for body of redirect and error message
-27509	LRW_NET_SOCKET_OPTION_USE_SELECT	Replace Mercury response with select calls
-27508	LRW_NET_SOCKET_OPTION_NO_DELAY	Disable Nagle algorithm
-27507	LRW_NET_SOCKET_OPTION_RFC1323	Implement RFC1323 -- TCP Extensions for High Performance
-27506	LRW_NET_SOCKET_OPTION_UPLOAD_CHUNK_SIZE	set maximum chunk size for large request body
-27505	LRW_NET_SOCKET_OPTION_OVERLAPPED_SEND	disable=0, force=1 overlapped sends
-27504	LRW_NET_SOCKET_OPTION_NEW_BEHAVIOR_OF_OVERLAPPED_SEND	default behavior=0, new behavior=1 of overlapped sends
-27503	LRW_NET_SOCKET_OPTION_OVERLAPPED_SEND_FAILURE_AS_WARNING	in case overlapped transmission fails, issue a warning instead of an error
-27502	LRW_NET_SOCKET_OPTION_NO_STARVATION	avoid starvation of TCP/IP sockets due to modem speed emulation
-27501	LRW_NET_SOCKET_OPTION_MODEM_SPEED_SLEEP_TIME	sets maximum time (in ms) modem speed emulation can be in non-responsive sleep
-27500	LRW_NET_SOCKET_OPTION_CHECK_CONNECTION_ABORT_DURING_RECEIVE	checks WSAECONNABORTED if recv fails
-27499	LRW_NET_SOCKET_OPTION_IGNORE_PREMATURE_SHUTDOWN	ignore premature shutdown by server
-27498	LRW_NET_SOCKET_OPTION_EMULATE_CLIENT_PROCESSING_TIME	When receiving large amounts of data emulate the time it will take the application an extended amount of time to process.
-27497	LRW_NET_SOCKET_OPTION_EMULATE_CLIENT_PROCESSING_TIME_INTERVAL	the think time we need to emulate if EMULATE_CLIENT_PROCESSING_TIME is on in milliseconds
-27496	LRW_NET_SOCKET_OPTION_EMULATE_CLIENT_PROCESSING_TIME_THRESHOLD	the amount of data after which we need to emulate think time in case EMULATE_CLIENT_PROCESSING_TIME is on in KBytes
-27495	LRW_NET_SOCKET_OPTION_NTLM_USE_REAL_CLIENT_HOST_NAME	Use client real host name instead of 'dummy_host' in NTLM Authentication
-27494	LRW_NET_SOCKET_OPTION_HELP	Print information about available options
-27493	LRW_NET_SOCKET_OPTION_BYPASS_MACHINE_CACHE	Bypass the machine cache and query the DNS server for the following requests
-27492	LRW_NET_SOCKET_OPT_SNI	The Server Name Indication (SNI) extension configuration. One of: "1" - Enable extension (default), "0" - Disable extension, "server_name" - If a server name is specified, that server name is used once: for the next handshake. After the next handshake, the option reverts to the previous setting, "1" or "0".
-27491	LRW_NET_SOCKET_OPTION_HTTP2_SERVER_PUSH	Disable(0) or enable(1) server push for HTTP2
-27490	LRW_NET_SOCKET_TRY_TO_SET_SNI_WITH_SN	Trying to set SNI with servername %1
-27489	LRW_NET_SOCKET_SET_IP_ADDRESS	Setting IP address %1
-27488	LRW_NET_SOCKET_SET_SNI_WITH_SN_SUCCESSFUL	Setting SNI was succesful
LrwNetSocket.txt.h		
-34599	LRW_TXT_NET_SOCKET_IDENTITY	1%

Error code	Handle	Message\Additional information
-34598	LRW_TXT_NET_SOCKET_COMPOSE	%1: %2
LrwNetWPS_res.h		
-234999	LRW_MSG_NET_WPS_CONNECTING_TO_GATEWAY	Connecting to %1 on port %2 in %3 mode %4 security . . .
-234998	LRW_MSG_NET_WPS_CONNECTED_TO_GATEWAY_SUCC	Connected successfully to %1
-234997	LRW_MSG_NET_WPS_CONNECTED_TO_GATEWAY_FAILED	Failed to connect to %1 (%2)
-234996	LRW_MSG_NET_WPS_CO_CONNECTION_FAILED	Failed to establish session (%1)
-234995	LRW_MSG_NET_WPS_DISCONNECTING_FROM_GATEWAY	Disconnecting from %1 . . .
-234994	LRW_MSG_NET_WPS_DISCONNECTED_FROM_GATEWAY_SUCC	Disconnected successfully from Gateway
-234993	LRW_MSG_NET_WPS_REDIRECTED_TO_GATEWAY	Redirected to %1 on port %2
-234992	LRW_MSG_NET_WPS_RESPONSE_STATUS_CODE_ERR	WSP transaction returned illegal status code (0x%1)
-234991	LRW_MSG_NET_WPS_PUSH_MSG_RECEIVED	A Push message was received: %1-bytes headers , %2-bytes body
-234990	LRW_MSG_NET_WPS_PUSH_PULL_MSG	Retrieving message . . .
LrwNetWinl_res.h		
-27449	LRW_MSG_NET_WINI_UNSUPP_SCHEME	Scheme in URL="%1" is not supported by the Winlnet replay mechanism. Only "http:" and "https:" are supported. Additional information: The Winlnet Replay does not support the specified scheme (portion of a URL before "://"). For example, URLs starting with "ftp://". Use the Sockets Replay: In VuGen or Controller, select Runtime Settings > Internet Protocol: Preferences, and clear the Winlnet replay instead of Sockets (Windows only) checkbox. If the URL is explicitly specified in the script (e.g., in web_url), comment out or remove the function referring to it.
-27448	LRW_MSG_NET_WINI_TIMEOUT	Timed out while processing %1 Additional information: See message for error code 27447.
-27447	LRW_MSG_NET_WINI_TIMEOUT_CLOSE_HANDLE	Timed out while closing handle on behalf of %1 Additional information: • Check that your network connection is still active (ping the server). • Check that the URL or the application being tested is accessible from a browser on the same machine. • Rerun the scenario, and concurrently try to access the URL or the application being tested from a browser on another machine. If the response time is excessive, the server or the server application probably cannot sustain such loads. Analyze the server or the server application for bottlenecks and optimize to improve performance. • Run the scenario on Controller, and use the Analysis results to locate whether the bottlenecks are on the server, DNS, or the network. Optimize the system to improve performance. • Increase the runtime timeout settings: In VuGen or Controller, select Runtime Settings > Internet Protocol: Preferences, click the Options button, and increase the "HTTP-request connect timeout" or "HTTP-request receive" timeout values.
-27446	LRW_MSG_NET_WINI_INTERNAL_ERROR	Internal Error - %1
-27445	LRW_MSG_NET_WINI_CONNECT_FAILED	InternetConnect failed. Windows error code %_1_id. %2 Additional information: Refer to the Windows Error Code tables for Winlnet, Win32, or WinSocket, and search for the value specified in the error code.
-27444	LRW_MSG_NET_WINI_HTTP_SEND_REQUEST_FAILURE	"%1" failed (Windows error code=%_2_id) following an HttpSendRequest failure (Windows error code=%_3_id) for %4
-27443	LRW_MSG_NET_WINI_AUTHENTICATION_FAILURE	Client authentication certificate needed but is not available. Use "%1" or "%2" to specify a certificate. Additional information: An authentication certificate is required by the server application, but a valid certificate was not specified. If there is no preceding web_set_certificate, or web_set_certificate_ex with CertIndex argument, add it. Check that the certificate at the specified index on the current machine is the same certificate as on the machine where the script runs successfully. If it is not, change the order of the certificates using import/export.
-27442	LRW_MSG_NET_WINI_RETRY_LIMIT_EXCEEDED	"%1" failed, Windows error code=%_2_id%3%4 and retry limit (%_5_id) exceeded for %6 Additional information: See message for error code 27441.

Error code	Handle	Message\Additional information
-27441	LRW_MSG_NET_WINI_HTTP_SEND_REQUEST_ERROR	Attempting "HttpSendRequest" retry due to Windows error code=%_1_id%2%3 for %4 Additional information: Change the default timeout setting for the Wininet replay engine. In the Registry Editor, open HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Internet Settings, and change the default time (30 seconds) to 180 seconds: "SendTimeOut"=dword:0002bf20 "ReceiveTimeOut"=dword:0002bf20
-27440	LRW_MSG_NET_WINI_CERTIFICATE_INDEX_MISSING_INVALID	Missing certificate's index or thumbprint
-27439	LRW_MSG_NET_WINI_CERTIFICATE_THUMBPRINT_MISSING	Can't find a certificate by the input CertThumbprint. Additional information: An authentication certificate is required by the server application, but a valid certificate was not specified. If there is no preceding web_set_certificate, or web_set_certificate_ex with CertIndex argument, add it. Check that the certificate at the specified index on the current machine is the same certificate as on the machine where the script runs successfully. If it is not, change the order of the certificates using import/export.
-27438	LRW_MSG_NET_WINI_READ_INTERNET_FILE_ERROR	InternetReadFile failed. Windows error code=%_1_id. %2 Additional information: To identify the problem, refer to the Windows Error Code tables for WinINet, Win32, and WinSocket, and search for the value specified in the error code.
-27437	LRW_MSG_NET_WINI_SOCKETS_OPTION_NO_EFFECT	"%1" has no effect on Wininet replay. Additional information: The web_set_sockets_option script function is intended for use by the Sockets replay only, and has no effect when using the Wininet replay. Ignore this message if the usage of the web_set_sockets_option is not significant for you (e.g., TRACE_SSL_IO). Switch to the Sockets replay: In VuGen or Controller, select Runtime Settings > Internet Protocol: Preferences, and clear the Wininet replay instead of Sockets (Windows only) check box.
-27436	LRW_MSG_NET_WINI_ERRORS_SUPPRESSED	Aborting Wininet replay
-27435	LRW_MSG_NET_WINI_CANNOT_SET_MAX_CONNECTION	Wininet connection limit(s) could not be set (InternetSetOption for %1 failed, Windows error code %2). The Internet Explorer version may be lower than 5.0
-27434	LRW_MSG_NET_WINI_REGISTRY_INADEQUATE	The "MaxConnectionsPerServer" and "MaxConnectionsPer1_0Server" Wininet registry settings are inadequate for load testing with the Wininet replay. Additional information: Open HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Internet Settings in the Registry Editor, and change the Value data for "MaxConnectionsPerServer" and "MaxConnectionsPer1_0Server" to "30000".
-27433	LRW_MSG_NET_WINI_REGISTRY_MODIFIED	Registry settings "MaxConnectionsPerServer" and "MaxConnectionsPer1_0Server" have now been changed to %_1_id (under "HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Internet Settings")
-27432	LRW_MSG_NET_WINI_REGISTRY_BROWSER	Note: The new registry values may cause Internet Explorer to run faster than when its defaults are used (as it can open more concurrent connections)
-27431	LRW_MSG_NET_WINI_REGISTRY_COMPARE	If you want to compare the browser with the Wininet replay, delete the above registry keys (using regedit/regedt32)
-27430	LRW_MSG_NET_WINI_REGISTRY_NEXT	The new registry settings apply from the next run only. Please re-run
-27429	LRW_MSG_NET_WINI_REGISTRY_FAIL	Failed to modify "MaxConnectionsPerServer" and/or "MaxConnectionsPer1_0Server" (under "HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Internet Settings") Additional information: Open HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Internet Settings in the Registry Editor, and change the Value data for "MaxConnectionsPerServer" and "MaxConnectionsPer1_0Server" to "30000".
LrwNetWinI_txt.h		
-27399	LRW_MSG_NET_WINI_URL	URL="%1"
-27398	LRW_MSG_NET_WINI_HOST_PORT	Host="%1", Port=%_2_id
-27397	LRW_MSG_NET_WINI_ACTIVITY_ON_BEHALF	"%1" on behalf of "%2"
-27396	LRW_MSG_NET_WINI_RETRY_REASON_SERVER_NAME	(server name not resolved)
-27395	LRW_MSG_NET_WINI_RETRY_REASON_INVALID_SERVER_RESPONSE	(invalid server response)
-27394	LRW_MSG_NET_WINI_RETRY_REASON_SECURITY_CHANNEL_ERROR	(security channel error)
-27393	LRW_MSG_NET_WINI_RETRY_REASON_CONNECTION_ABORTED	(connection aborted)
-27392	LRW_MSG_NET_WINI_RETRY_REASON_CONNECTION_FAILURE	(cannot connect)
-27391	LRW_MSG_NET_WINI_RETRY_REASON_AUTHENTICATION_NEEDED	(client authentication certificate needed)
-27390	LRW_MSG_NET_WINI_RETRY_REASON_INVALID_CERTIFICATION_AUTHORITY	(invalid Certification Authority)
-27389	LRW_MSG_NET_WINI_RETRY_REASON_CERTIFICATE_REVOKED	(certificate revoked)

Error code	Handle	Message\Additional information
LrwObjMgr_res.h		
-35999	LRW_MSG_OBJ_MGR_INTERNAL_ERROR	Internal Error - %1
-35998	LRW_MSG_OBJ_MGR_NO_INNER_HTML	"%1" does not have an innerHTML property
-35997	LRW_MSG_OBJ_MGR_SET_TIMEOUT_SINGLE_THRESHOLD	setTimeout/setInterval interval (%_1_id milliseconds) exceeds the "Single setTimeout/setInterval threshold" Runtime Setting (%_2_id seconds) and is ignored. TimerID=%_3_id, script="%4"
-35996	LRW_MSG_OBJ_MGR_SET_TIMEOUT_ACCUMULATIVE_THRESHOLD	setTimeout/setInterval is accepted (TimerID=%_1_id), but deactivated until the beginning of the next Action-type function, as it would exceed the "Accumulative setTimeout/setInterval threshold" Runtime Setting (%_2_id seconds). Interval=%_3_id milliseconds, script="%4"
-35995	LRW_MSG_OBJ_MGR_SET_TIMEOUT_ACCEPTED	setTimeout/setInterval accepted (TimerID=%_1_id), Interval=%_2_id milliseconds. A timer for this will be registered at the end of the current script. Timestamps: current=%_3_id, expiration=%_4_id, script="%5"
-35994	LRW_MSG_OBJ_MGR_SET_TIMEOUT_REGISTERING	Registering a timer for setTimeout/setInterval with TimerID=%_1_id. Timestamps: current=%_2_id, expiration=%_3_id, interval=%_4_id
-35993	LRW_MSG_OBJ_MGR_SET_TIMEOUT_UNREGISTERING	Unregistering the timer for setTimeout/setInterval with TimerID=%_1_id
-35992	LRW_MSG_OBJ_MGR_SET_TIMEOUT_PREPARING	Preparing the script for setTimeout/setInterval with TimerID=%_1_id for execution. Timestamps: effective=%_2_id, expiration=%_3_id, real=%_4_id, script="%5"
-35991	LRW_MSG_OBJ_MGR_SET_TIMEOUT_RECURSIVE	The script for setTimeout/setInterval with TimerID=%_1_id is ignored: reached the execution stage when the script for TimerID=%_2_id is still executing
-35990	LRW_MSG_OBJ_MGR_SET_TIMEOUT_NOT_FOUND	clearTimeout/clearInterval TimerID (%_1_id) not found
-35989	LRW_MSG_OBJ_MGR_SET_FILE_VALUE_HTML	HTML-specified value ("%1") for an "INPUT" element of type "file" is ignored. The field name is "%2" or not set yet (e.g., when "value=" precedes "name=" in the HTML)
-35988	LRW_MSG_OBJ_MGR_SET_FILE_VALUE_JS	A JavaScript attempt to set the value of an input object (name="%1") having type=file is ignored
-35987	LRW_MSG_OBJ_MGR_EVAL_FAILED	JavaScript evaluation failed for the script listed above
-35986	LRW_MSG_OBJ_MGR_NON_FUNC_HANDLER	Ignoring an attempt to assign a non-function to an event handler
-35985	LRW_MSG_OBJ_MGR_DUPLICATE_LISTENER	"%1" event handler already specified
-35984	LRW_MSG_OBJ_MGR_EVENT_UNSUPPORTED_FOR_OBJECT	Event %1 is not supported for %2
-35983	LRW_MSG_OBJ_MGR_SETTING_UNSUPPORTED	Setting the value of "%1" is not supported yet
-35982	LRW_MSG_OBJ_MGR_FRAME_CONTENT_UNAVAILABLE	The contents of the frame are unavailable. Probably the frame was downloaded before "Show Vuser" was activated, or not downloaded at all.
-35981	LRW_MSG_OBJ_MGR_SELECTED_ALREADY	The item to be selected is selected already
-35980	LRW_MSG_OBJ_MGR_DESELECTED_ALREADY	The item to be deselected is deselected already
-35979	LRW_MSG_OBJ_MGR_NON_MULTIPLE_SELECT	Deselect or ExtendedSelect attempted for a non-multiple SELECT
-35978	LRW_MSG_OBJ_MGR_GET_ITEM_INDEX	Attempting to get the item with index %_1_id (zero-based) from a collection of length %_2_id
-35977	LRW_MSG_OBJ_MGR_SET_ITEM_INDEX	Attempting to set the item with index %_1_id (zero-based) in a collection of length %_2_id
-35976	LRW_MSG_OBJ_MGR_REG_CONFIRM	Missing registration function before the current function: Add 'web_reg_dialog(DESCRIPTION, "Type=Confirm","Message=%1", ACTION, "Click=<OK_or_Cancel>", LAST);',\nunchanging "Click=<OK_or_Cancel>" to either "Click=OK" or "Click=Cancel". Using default='OK'
-35975	LRW_MSG_OBJ_MGR_REG_PROMPT	Missing registration function before the current function: Add 'web_reg_dialog(DESCRIPTION, "Type=Prompt","Message=%1", ACTION, "SetText=<Text>", LAST);',\nreplacing "<Text>" by the appropriate text to be entered as the response to the message. For example, "SetText=John Doe"
-35974	LRW_MSG_OBJ_MGR_LINK_NO_EFFECT	Clicking on a link that has no href/onclick
-35973	LRW_MSG_OBJ_MGR_SET_INTERVAL_REESTABLISHED	setInterval with TimerID=%_1_id reestablished
-35972	LRW_MSG_OBJ_MGR_SET_INTERVAL_NOT_REESTABLISHED	setInterval with TimerID=%_1_id not reestablished
-35971	LRW_MSG_OBJ_MGR_HISTORY_DISABLED	Back/Forward/Go referenced when "history" is disabled. Please refer to the "History support" Runtime Setting (in "Internet Protocol" / "Preferences" / "Options...")
-35970	LRW_MSG_OBJ_MGR_HISTORY_ITEM_NOT_FOUND	"%1" %_2_id items in the history list is not available
-35969	LRW_MSG_OBJ_MGR_INVOKING_UNSUPPORTED_OBJECT_METHOD	Attempting to invoke a method of an unsupported object, classid="%1"
-35968	LRW_MSG_OBJ_MGR_NOT_TRUNC_TO_MAXLENGTH	Length (%_1_id bytes) of value assigned to "%2" exceeds maxlength (%_3_id), but is not truncated
-35967	LRW_MSG_OBJ_MGR_CONTROLLER_SYNC_FILE_PROBLEM	Failed to open console sync file ("%1") for output. Internal error code (errno) was %_2_id
-35966	LRW_MSG_OBJ_MGR_UPDATE_CORRELATION_INDEX_FILE_FAILURE	Could not update correlation index file
-35965	LRW_MSG_OBJ_MGR_RT_VIEWER_EXCEP	Exception raised in Run Time Viewer in %1
-35964	LRW_MSG_OBJ_MGR_GO_0_UNSUPP	history.go(0) not fully supported. Results may be unpredictable if page was initially downloaded with a POST. URL="%1".
-35963	LRW_MSG_OBJ_MGR_MULTIPLE_SUBMIT	An attempt to resubmit form (Action URL="%1")
-35962	LRW_MSG_OBJ_MGR_ALREADY_COLLECTION_MEMBER	An object that is already a member of a collection is assigned by a JavaScript to the same or to another collection
-35961	LRW_MSG_OBJ_MGR_NO_PROPERTY	"%1" does not have a "%2" property
-35960	LRW_MSG_OBJ_MGR_REASSIGN_INPUT_TYPE	An attempt to assign type "%1" to an INPUT element of type "%2" is ignored
-35959	LRW_MSG_OBJ_MGR_INVOKING_UNSUPPORTED_APPLET_METHOD	Attempting to invoke a method of an unsupported applet, code="%1"
-35958	LRW_MSG_OBJ_MGR_INVALID_METHOD_ARGS	Invalid argument(s) specified for the "%1" method
-35957	LRW_MSG_OBJ_MGR_START_DOWNLOAD_EMPTY_URL	startDownload called with an empty URL and ignored
-35956	LRW_MSG_OBJ_MGR_INVALID_OBJ_ARG	Argument number %_1_id to function "%2" is not an object of the required type

Error code	Handle	Message\Additional information
-35955	LRW_MSG_OBJ_MGR_FUNC_FAILED	Function "%1" failed
-35954	LRW_MSG_OBJ_MGR_EXEC_SCRIPT_VBSCRIPT	VBScript execScript not evaluated
-35953	LRW_MSG_OBJ_MGR_CONVERSION_FAILED	Failed to convert argument number % 1_Id of "%2" (internal information: address=%3, length=% 4_Id, type=% 5_Id)
-35952	LRW_MSG_OBJ_MGR_SET_COLLECTION_NEGATIVE_INDEX	Referencing a collection item with a negative index (% 1_Id)
-35951	LRW_MSG_OBJ_MGR_UNSUPP_REMOVE_ATTR	%1.removeAttribute("%2") is not supported and is ignored
-35950	LRW_MSG_OBJ_MGR_FRAME_NOT_FOUND	Frame not found
-35949	LRW_MSG_OBJ_MGR_BROWSERS_CREATED	% 1_Id empty browser(s) with title="%2" created for matching Ordinal=% 3_Id
-35948	LRW_MSG_OBJ_MGR_COMBINE_URL_FAILED	Failed to combine URL="%1" and URL="%2" for "%3"
-35947	LRW_MSG_OBJ_MGR_UNSUPPORTED_ARG	"%1" not supported for "%2"
-35946	LRW_MSG_OBJ_MGR_INVALID_APPLY_ELEMENT	%1.applyElement(%2) is invalid
-35945	LRW_MSG_OBJ_MGR_UNSUPPORTED_APPLY_ELEMENT	The applyElement method is not supported for an element that is not connected to the DOM and for an argument that IS connected already or has children
-35944	LRW_MSG_OBJ_MGR_INVALID_PROPERTY_SET	Setting of the "%1" property is invalid for an object of type "%2"
-35943	LRW_MSG_OBJ_MGR_UNSUPPORTED_EVENT_FOR_OBJECT	%1 does not support event "%2"
-35942	LRW_MSG_OBJ_MGR_SET_ATTR_READ_ONLY	setAttribute failed for read-only attribute "%1" of "%2"
-35941	LRW_MSG_OBJ_MGR_REMOVE_ATTR_PERMANENT	removeAttribute ignored for permanent attribute "%1" of "%2"
-35940	LRW_MSG_OBJ_MGR_REGISTERED_RESPONSE_CANCEL	Registered "Cancel" response used for "%1" message "%2"
-35939	LRW_MSG_OBJ_MGR_REGISTERED_RESPONSE_OK_NO_TEXT	Registered "OK" response used for "%1" message "%2"
-35938	LRW_MSG_OBJ_MGR_REGISTERED_RESPONSE_OK_SET_TEXT	Registered "OK" response with text="%1" used for "%2" message "%3"
-35937	LRW_MSG_OBJ_MGR_SET_INTERVAL_LAST_IN_STEP	setInterval with TimerID=% 1_Id reestablished for the last time in the step
-35936	LRW_MSG_OBJ_MGR_METHOD_FAILED_ARG_STR_1	%1("%2") failed
-35935	LRW_MSG_OBJ_MGR_ANOTHER_DOCUMENT	%1 called with an object from another document or with NULL
-35934	LRW_MSG_OBJ_MGR_RANDOM_SELECTION	Occurrence number % 1_Id selected out of % 2_Id matching alternatives for %3=Random
-35933	LRW_MSG_OBJ_MGR_EVAL_SUCCESSFUL	JavaScript evaluation was successful for the script listed above
-35932	LRW_MSG_OBJ_MGR_SCRIPT_NOT_EVALUATABLE	Unsupported language ("%"1") or type ("%"2") for a script. The script will not be evaluated
-35931	LRW_MSG_OBJ_MGR_SET_TIMEOUT_ADJUSTING_TIMER	Adjusting timer for setTimeout/setInterval with TimerID=% 1_Id. Timestamps: current=% 2_Id, expiration=% 3_Id, interval=% 4_Id
-35930	LRW_MSG_OBJ_MGR_BROWSER_NOT_FOUND	Browser not found
-35929	LRW_MSG_OBJ_MGR_PENDING_USER_REGISTRARTION_STEP	% 1_Id registered dialog response(s) (web_reg_dialog) have not been referenced within the step and are deleted
-35928	LRW_MSG_OBJ_MGR_PENDING_USER_REGISTRARTION_NOT_STEP	% 1_Id registered dialog response(s) (web_reg_dialog) detected at the end of iteration / vuser_init section / vuser_end section / showModalDialog callback, and are deleted
-35927	LRW_MSG_OBJ_MGR_WINDOW_ITEM_FAILED	frames()/window() reference (with ROUND parentheses) failed: %1
-35926	LRW_MSG_OBJ_MGR_TRUNCATE_COMMENT_FROM_SCRIPT	Last non-empty script line ("%"1") ignored (ends with "-->")
-35925	LRW_MSG_OBJ_MGR_UNSUPPORTED_APPLET	Running applets disallowed for this Vuser type. Use the "AJAX (Click and Script)" protocol
-35924	LRW_MSG_OBJ_MGR_UNSUPPORTED_ACTIVE_X	Running ActiveX controls disallowed for this Vuser type. Use the "AJAX (Click and Script)" protocol
-35923	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_EVALUATION_FAILED	Failed to evaluate the script in URL="%1"
-35922	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_NAVIGATED	A navigation to the %1 has been issued by the script in URL="%1"
-35921	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_DOCUMENT_DELETED	The document of the %1 has been deleted during evaluation of the script in URL="%1"
-35920	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_OBJECT_DELETED	The %1 has been deleted during evaluation of the script in URL="%1"
-35919	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_WINDOW_DELETED_BEFORE_WRITE	The %1 has been deleted before writing the value returned by the script in URL="%2"
-35918	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_VOID	No value returned by the script in URL="%1"
-35917	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_NOT_STR	An invalid value (length=% 1_Id, internal type=% 2_Id) returned by the script in URL="%3"
-35916	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_EMPTY	An empty value returned by the script in URL="%1"
-35915	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_RESULT_IGNORED	For %1, ignoring the value returned by the script in URL="%2"
-35914	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_RESULT_WRITING_DOCUMENT	The script in URL="%1" returned "%2". Writing it to the document of the %3
-35913	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_RESULT_WRITING_OBJECT	The script in URL="%1" returned "%2". Writing it to the %3
-35912	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_EMPTY_SCRIPT_TEXT	Using empty text for the %1 with src="%2"
-35911	LRW_MSG_OBJ_MGR_JAVASCRIPT_SCHEME_WINDOW_CLOSED_BEFORE_WRITE	The %1 has been closed before writing the value returned by the script in URL="%2"
LrwRTBSyncObject_txt.h		
-27349	LRW_MSG_RTBSYNC_OBJECT_WEB_STEP_SUCCEEDED	<CENTER>Step completed successfully</CENTER>
-27348	LRW_MSG_RTBSYNC_OBJECT_WEB_STEP_FAILED	<CENTER>Step failed</CENTER>
-27347	LRW_MSG_RTBSYNC_OBJECT_STEP_CREATION_FAILED	<CENTER>Step creation failed</CENTER>
-27346	LRW_MSG_RTBSYNC_OBJECT_IMAGE_LOADED	<CENTER>Image loaded successfully</CENTER>
-27345	LRW_MSG_RTBSYNC_OBJECT_JAVA_APPLET_LOADED	<CENTER>Java applet loaded successfully</CENTER>

Error code	Handle	Message\Additional information
-27344	LRW_MSG_RTb_SYNC_OBJECT_JAVA_APPLET_PAGE	<HTML> <h2><CENTER>Java applet cannot be displayed</HTML>
-27343	LRW_MSG_RTb_SYNC_OBJECT_RESOURCE_SUCCESSFULLY	<CENTER>Resource of content type ""%1"" loaded successfully</CENTER>
-27342	LRW_MSG_RTb_SYNC_OBJECT_RESOURCE_UNKNOWN_TYPE_SUCCESSFULLY	<CENTER>Resource loaded successfully</CENTER>
-27341	LRW_MSG_RTb_SYNC_OBJECT_RESOURCE_PAGE	<HTML> <h2><CENTER>Resource cannot be displayed</HTML>
-27340	LRW_MSG_RTb_SYNC_OBJECT_REGISTER_ACTION_STEP	<CENTER>%1 registered successfully</CENTER>
-27339	LRW_MSG_RTb_SYNC_OBJECT_SUCCEEDED_MSG	<CENTER>%1</CENTER>
-27338	LRW_MSG_RTb_SYNC_OBJECT_FAILED_MSG	<CENTER>%1</CENTER>
LrwReplayMain_res.h		
-27299	LRW_MSG_REPLAY_MAIN_RESOURCE_NOT_LOADED	Resource "%1" not downloaded (resource downloading not requested) Additional information: The "Download non-HTML resources" option was not selected in the runtime settings. Enable this in the Browser Emulation runtime settings.
-27298	LRW_MSG_REPLAY_MAIN_ARG_MORE_THAN_ONCE	The "%1" argument (number %_2_id) is specified more than once Additional information: Check which instance should remain and delete the other one.
-27297	LRW_MSG_REPLAY_MAIN_SUBARG_MORE_THAN_ONCE	"%1" (sub-argument number %_2_id) is specified more than once for the "%3" argument (number %_4_id) Additional information: Check which instance of the sub-argument should remain, and delete the other one.
-27296	LRW_MSG_REPLAY_MAIN_INVALID_SUBARG	Sub-argument number %_1_id of the "%2" argument (number %_3_id) is invalid Additional information: Enter a valid value for the offending argument.
-27295	LRW_MSG_REPLAY_MAIN_MISSING_EQ	Missing or misplaced equals sign (=) in the "%1" argument (number %_2_id) Additional information: Place the equalssign (=) in the appropriate position of the specified argument.
-27294	LRW_MSG_REPLAY_MAIN_FILE_WO_MULTIPART	""File=yes" specified (argument number %1) without "EncType=multipart/form-data"" Additional information: Delete the "File=Yes" argument, or specify the argument "EncType=multipart/form-data".
-27293	LRW_MSG_REPLAY_MAIN_FUNC_FAILED_NO_RC	"%1" failed
-27292	LRW_MSG_REPLAY_MAIN_FUNC_FAILED_RC	"%1" failed, rc=%_2_id
-27291	LRW_MSG_REPLAY_MAIN_FILE_LINE_INVALID	Cannot obtain script file/line for generating automatic transaction names. File name "%1" is invalid
-27290	LRW_MSG_REPLAY_MAIN_ARG_NULL	The "%1" argument (number %_2_id) is NULL Additional information: Supply a non-empty string for the offending argument.
-27289	LRW_MSG_REPLAY_MAIN_ARG_UNRECOG_VAL	Unrecognized value ("%1") for the "%2" argument (number %_3_id) Additional information: Enter a valid value for the offending argument.
-27288	LRW_MSG_REPLAY_MAIN_ARG_NOT_NUM	The "%1" argument (number %_2_id) does not specify a valid number Additional information: If the value specified is not a number, change it to a number. If the value specified is a number, check that it is within the valid range.
-27287	LRW_MSG_REPLAY_MAIN_ARG_OUT_RANGE	The "%1" argument (number %_2_id) is out of range (%3 through %4) Additional information: Use a number within the range specified in the error message.
-27286	LRW_MSG_REPLAY_MAIN_ARG_NULL_EMPTY	The "%1" argument (number %_2_id) is NULL or empty Additional information: Supply a non-empty string for the offending argument.
-27285	LRW_MSG_REPLAY_MAIN_SETTING_TIMEOUT_FAILED	Setting the timeout value failed Additional information: • Check that the timeout value specified is within the valid range (the range is usually from 1 to 120). • Delete the problematic web_set_timeout call from the script. • Change the required timeout: In VuGen, choose Runtime Settings > Internet Protocol: Preferences, click the Options button, and change the required timeout value. The new timeout value will be applied to the whole script.
-27284	LRW_MSG_REPLAY_MAIN_REG_FIND_FAIL_NOT_FOUND	No match found for "%1" string "%2", and "Fail" was set to "NotFound" ("%3" has no effect here)
-27283	LRW_MSG_REPLAY_MAIN_REG_FIND_IGNORE_NOT_FOUND	No match found for "%1" string "%2" ("%3" has no effect here)

Error code	Handle	Message\Additional information
-27282	LRW_MSG_REPLAY_MAIN_EMPTY_BOUNDARY_ORD	Ordinal must be 1 when the left and/or right boundaries are empty. Additional information: Specify non-empty left and right boundaries, or delete the offending "Ordinal" (or "Ord") argument, or change its value to 1. This is only applicable if the first occurrence of the requested parameter is required. If not, specify non-empty boundaries.
-27281	LRW_MSG_REPLAY_MAIN_CORRELATION_IDX_FILE	Could not update correlation index file (iteration dir)
-27280	LRW_MSG_REPLAY_MAIN_FAILED_ITER	os_mkdir failed (rc=% 1 Id) for iteration number % 2 Id
-27279	LRW_MSG_REPLAY_MAIN_INTERNAL_ERROR	Internal Error - %1
-27278	LRW_MSG_REPLAY_MAIN_OBTAIN_RESULT_DIR	Cannot obtain result directory name. Additional information: The result directory already exists and cannot be overwritten. The result directory is used for one (or more) of the following features: Correlations, runtime viewer, and the Summary report. Disable correlation in the recording options or see the previous message.
-27277	LRW_MSG_REPLAY_MAIN_DIR_EXIST	Result directory already exists. Additional information: The result directory already exists and cannot be overwritten. The result directory is used for one (or more) of the following features: Correlations, runtime viewer, and the Summary report. Disable correlation in the recording options or see the previous message.
-27276	LRW_MSG_REPLAY_MAIN_CTRL_FILE	Could not create console sync file. Additional information: Failed to create Controller sync file. This file is required for activating the runtime viewer feature. The file should be created in the Vuser result directory. • Check for other processes using the iteration directory. • Check that the iteration directory has the correct write permissions. • Disable the runtime viewer in VuGen.
-27275	LRW_MSG_REPLAY_MAIN_CONDITION_SEVER	Condition(s) of severity "%1" raised for a virtual user in the current PROCESS, but not necessarily in the current THREAD. Additional information: See message for error code 27273.
-27274	LRW_MSG_REPLAY_MAIN_CONDITION_ENABLE	To see the message(s) for these condition(s), rerun with logging enabled for this severity. Additional information: See message for error code 27273.
-27273	LRW_MSG_REPLAY_MAIN_FILE	See the message(s) for these condition(s) in file "%1". Additional information: If logging is enabled, check that it is set at the required level. Check the log file for messages that may help resolve the error. To see the extended log, enable it in the runtime settings.
-27272	LRW_MSG_REPLAY_MAIN_ARG_MISSING_EMPTY	The "%1" argument is missing or empty. Additional information: If logging is enabled, check that it is set at the required level. Check the log file for messages that may help resolve the error. To see the extended log, enable it in the runtime settings.
-27271	LRW_MSG_REPLAY_MAIN_CONCURRENT_GRP_END_INIT	A concurrent group is active at the end of the vuser_init section. Add the missing web_end_concurrent_group call to the relevant place in the Init section.
-27270	LRW_MSG_REPLAY_MAIN_CONCURRENT_GRP_END_VUSER	A concurrent group is active at the end of the Virtual User run. Add the missing web_end_concurrent_group call to the relevant place in the Init section.
-27269	LRW_MSG_REPLAY_MAIN_CONCURRENT_GRP_END_ITER	A concurrent group is active at the end of iteration number %_1_Id. Add the missing web_end_concurrent_group call to the relevant place in the Init section.
-27268	LRW_MSG_REPLAY_MAIN_WEB_REQ_END_INIT	Pending Web requests detected at the end of the vuser_init section and will be aborted. Additional information: See message for error code 27266.
-27267	LRW_MSG_REPLAY_MAIN_WEB_REQ_END_VUSER	Pending Web requests detected at the end of the Virtual User run and will be aborted. Additional information: See message for error code 27266.
-27266	LRW_MSG_REPLAY_MAIN_WEB_REQ_END_ITER	Pending Web requests detected at the end of iteration and will be aborted. Additional information: The specified iteration number ended, but there are still active web requests that were not performed during the iteration. This situation is allowed within a concurrent group, but there is no concurrent group active. Check which requests were not performed. If a pending (unperformed) request is not critical, include "Resource=1" in one of its parameters, or delete the request from the script.
-27265	LRW_MSG_REPLAY_MAIN_FUNC_UNAVAIL	xfvLrwNetDeleteUnhandledItems function unavailable. Pending items cannot be deleted
-27264	LRW_MSG_REPLAY_MAIN_PEND_ITEM	Unhandled pending items will be deleted
-27263	LRW_MSG_REPLAY_MAIN_MSS_ADDUSER	MSS_AddUser failed, rc=% 1 Id

Error code	Handle	Message\Additional information
-27262	LRW_MSG_REPLAY_MAIN_PEND_GRP_END_INIT	Pending concurrent group detected and reset at the end of the vuser_init section. Additional information: Add the missing web_end_concurrent_group call to the relevant place in the Init section.
-27261	LRW_MSG_REPLAY_MAIN_PEND_GRP_END_VUSER	Pending concurrent group detected and reset at end of the virtual user
-27260	LRW_MSG_REPLAY_MAIN_PEND_GRP_END_ITER	Pending concurrent group detected and reset at the end of iteration number %_1_Id. Additional information: Add the web_end_concurrent_group call to the relevant section in the script.
-27259	LRW_MSG_REPLAY_MAIN_PEND_PARAM_END_INIT	Pending %1/%2/%3/%4 request(s) detected and reset at the end of the vuser_init section. Additional information: The Init section ended, but there are still active web_reg_save_param / reg_find / create_html_param[_ex] requests that were not performed during the Init section. Check which requests were not performed. If an unperformed request is not critical, delete it from the script.
-27258	LRW_MSG_REPLAY_MAIN_PEND_PARAM_END_VUSER	Pending %1/%2/%3/%4 request(s) detected and reset at the end of the Vuser run. Additional information: The Init section ended, but there are still active web_reg_save_param / reg_find / create_html_param[_ex] requests that were not performed during replay. Check which requests were not performed. If an unperformed request is not critical, delete it from the script.
-27257	LRW_MSG_REPLAY_MAIN_PEND_PARAM_END_ITER	Pending %1/%2/%3/%4 request(s) detected and reset at the end of iteration number %_5_Id. Additional information: The specified iteration number ended, but there are still active web_reg_save_param/ reg_find / create_html_param[_ex] requests that were not performed during the iteration. Check which requests were not performed. If an unperformed request is not critical, delete it from the script.
-27256	LRW_MSG_REPLAY_MAIN_HEADER_NAME	Header name is NULL or empty. Additional information: Provide a non-empty string for the header name argument.
-27255	LRW_MSG_REPLAY_MAIN_HEADER_VALUE	Header value is NULL. Additional information: Provide a non-empty string for the header name value.
-27254	LRW_MSG_REPLAY_MAIN_PARAM_NAME	Parameter name is NULL or empty. Additional information: Provide a non-empty string for the parameter name argument.
-27253	LRW_MSG_REPLAY_MAIN_INVALID_LB_RB	Invalid left and/or right boundary. Additional information: Provide a non-NULL string for the left and/or right boundary. arguments.
-27252	LRW_MSG_REPLAY_MAIN_INVALID_ORD	Invalid ordinal. Additional information: Enter an "Ordinal" argument value that is greater than 0.
-27251	LRW_MSG_REPLAY_MAIN_PARAM_SAVESTR_FAIL	Parameter_SaveString failed (rc=%_1_Id) when emptying "%2". Additional information: Check that the parameter length is within a valid range.
-27250	LRW_MSG_REPLAY_MAIN_TASK_LIST	Pending Web requests detected and deleted
-27249	LRW_MSG_REPLAY_MAIN_THINK_TIME	Sleeping for %1 second(s) of Automatic Think Time (between %_2_Id and %_3_Id milliseconds)
-27248	LRW_MSG_REPLAY_MAIN_PARAM_STR_FAIL	Parameter_SaveString failed (rc=%_1_Id) for "%2" Additional information: Check that the parameter length is within a valid range.
-27247	LRW_MSG_REPLAY_MAIN_INVALID_PROXY	Invalid proxy port. Additional information: Check that the first argument in the web_set_proxy function is specified in the format proxy_host:port or proxy_host. If no port is defined in the first argument, the default proxy port is used.
-27246	LRW_MSG_REPLAY_MAIN_DISALLOWED_CONCURRENT	Function not allowed within a concurrent group Additional information: Move the function outside the concurrent group.
-27245	LRW_MSG_REPLAY_MAIN_END_NOT_IN_CONCURRENT	%1 without a prior %2 Additional information: There is no corresponding web_concurrent_start for the web_concurrent_end call. Add the web_concurrent_start function before the call to web_concurrent_end or delete the offending call to web_concurrent_end from the script

Error code	Handle	Message\Additional information
-27244	LRW_MSG_REPLAY_MAIN_START_IN_CONCURRENT	%1 detected within a concurrent group. A previous %2 may be missing Additional information: The error occurs when no web_concurrent_end call is found before the consequent web_concurrent_start call. A concurrent group cannot exist within another concurrent group. Split the nested concurrent group by adding the web_concurrent_end call before the consequent web_concurrent_start call, or delete the nested web_concurrent_start call from the script.
-27243	LRW_MSG_REPLAY_MAIN_INVALID_PORT	Invalid port Additional information: See previous message.
-27242	LRW_MSG_REPLAY_MAIN_HOST_NAME	Host name is empty Additional information: Check that the third argument in the web_set_user function is specified in the format "host:port" or "host". The host must be a non-empty string. The port must be either a number greater than 0 or unspecified (in which case the default port will be used).
-27241	LRW_MSG_REPLAY_MAIN_NOT_ENOUGH_ALLOCA_MEM	Not enough OS_ALLOCA memory (%_1_id bytes) for host name Additional information: • Check the machine's memory resources, and close any unnecessary processes running on the machine. • Restart the computer and replay the script again. • If the problem persists, reduce the number of virtual users that you are running on the same machine.
-27240	LRW_MSG_REPLAY_MAIN_ADDAUTHENTRY	AddAuthEntry failed Additional information: Check that the "username" and the "host:port" arguments are specified as non-empty strings.
-27239	LRW_MSG_REPLAY_MAIN_EMPTY_AFTER_PARAM	The "%1" argument (number %_2_id) is empty after parameterization
-27238	LRW_MSG_REPLAY_MAIN_NAME_WITHOUT_VALUE	A name specified without a value
-27237	LRW_MSG_REPLAY_MAIN_COOKIE	Cookie is NULL or empty Additional information: Specify the "Cookie" argument in web_add_cookie as a non-empty string.
-27236	LRW_MSG_REPLAY_MAIN_EMPTY_HOST	Host is NULL or empty Additional information: Specify the third argument in the web_set_user function in the format "host:port" or "host". The host must be a non-empty string. The port must be either a number greater than 0 or unspecified (in which case the default port will be used).
-27235	LRW_MSG_REPLAY_MAIN_NULL_USER_OR_PASSWORD	NULL user and/or password Additional information: Specify the "username" and "password" arguments as non-NULL strings.
-27234	LRW_MSG_REPLAY_MAIN_ADD_COOKIE_FAILED	Adding the cookie failed Additional information: Check that the "Cookie" argument format is valid.
-27233	LRW_MSG_REPLAY_MAIN_SCRIPT_FUNC_UNSUPP	Function not currently supported under Turbo Replay. For the old replay, specify ForceOldReplay=1 in the configuration file (e.g., default.cfg)
-27232	LRW_MSG_REPLAY_MAIN_WITHOUT_PRIOR_REQ	No prior requests have been successfully registered Additional information: Delete the concurrent group, or add web requests to this group.
-27231	LRW_MSG_REPLAY_MAIN_ARG_NOT_NULL	The "%1" argument (number %_2_id) is not NULL Additional information: Ensure that the specified argument in web_concurrent_end is NULL.
-27230	LRW_MSG_REPLAY_MAIN_ARG_1_2_COMB_INVALID	Argument number 1 is not NULL and argument number 2 is neither NULL nor LAST Additional information: Specify the first argument as NULL, or set the first argument as a non-NULL string, and the second argument as NULL or LAST.
-27229	LRW_MSG_REPLAY_MAIN_SAVE_HEADER_DISABLED	"%1"("%2") is turned off. Saving headers is not supported within concurrent groups Additional information: The web_save_header function cannot be performed for web requests within a concurrent group. Move the web_save_header function after the web_concurrent_end call.
-27228	LRW_MSG_REPLAY_MAIN_INVALID_ORDINAL	Invalid Ordinal Additional information: Enter an "Ordinal" argument value that is greater than 0.
-27227	LRW_MSG_REPLAY_MAIN_MUST_BE_1_OR_0	The "%1" argument (number %_2_id) must be "1" or "0" Additional information: Change the offending argument to "1" or "0".

Error code	Handle	Message\Additional information
-27226	LRW_MSG_REPLAY_MAIN_ARG_UNRECOG	The "%1" argument (number %_2_id) is unrecognized or misplaced Additional information: See previous message.
-27225	LRW_MSG_REPLAY_MAIN_ARG_UNRECOG_WITHIN	The "%1" argument (number %_2_id) is not recognized within "%3" Additional information: Check that the argument is spelled correctly. If the argument group is not NULL, check that the offending argument is specified within the correct group in the argument list.
-27224	LRW_MSG_REPLAY_MAIN_INVALID_SNAPSHOT	Invalid Snapshot argument (number %_1_id). The "t<number>.inf" is incorrectly formatted Additional information: The argument specifying the Snapshot filename is invalid. If the snapshot is not essential, remove it from the argument list.
-27223	LRW_MSG_REPLAY_MAIN_INVALID_INFO_TYPE	Invalid Info Type (argument number 1) Additional information: The first argument in the web_get_int_property function is not of a supported type.
-27222	LRW_MSG_REPLAY_MAIN_REMOVE_COOKIE_FAILED	Removing the cookie failed
-27221	LRW_MSG_REPLAY_MAIN_INVALID_VALUE	Invalid value for the "%1" argument (number %_2_id) Additional information: The value of the argument specified is invalid. Specify a valid value.
-27220	LRW_MSG_REPLAY_MAIN_SAVESTR_FAIL_SETTING	Parameter_SaveString failed (rc=%_1_id) when setting "%2" to "0" Additional information: Check that the parameter length is within a valid range.
-27219	LRW_MSG_REPLAY_MAIN_PARAM_LEN_EXCEEDS_MAX	Length of parameter name exceeds maximum (%_1_id) for "Ord=ALL" Additional information: Shorten the parameter name to a permitted length.
-27218	LRW_MSG_REPLAY_MAIN_SAVE_PARAM_TYPE	Saved parameter type must be "RESPONSE" or "REQUEST"
-27217	LRW_MSG_REPLAY_MAIN_ARG_MORE_THAN_ONCE_ITEM	The "%1" argument (number %_2_id) is specified more than once for the same item Additional information: The function requires only one instance of this argument. The argument has already been specified in the argument list. The argument Id specifies the position of the argument in the argument list.
-27216	LRW_MSG_REPLAY_MAIN_INVALID_ARG	Invalid argument (number %_1_id) Additional information: Check that the argument is spelled correctly and that the offending argument is specified within the correct group in the argument list.
-27215	LRW_MSG_REPLAY_MAIN_EMPTY_NULL_AFTER_PARAM	The "%1" argument (number %_2_id) is NULL or empty after parameterization
-27214	LRW_MSG_REPLAY_MAIN_PARAM_LEN	The length of a saved parameter name cannot exceed %1 bytes Additional information: Shorten the parameter name specified by the "param" argument in the web_save_header function.
-27213	LRW_MSG_REPLAY_MAIN_UNSUPPORTED_VAL	Unsupported value for the "%1" argument (number %_2_id) Additional information: The value of the argument specified is unsupported. The argument Id specifies the position of the argument in the argument list.
-27212	LRW_MSG_REPLAY_MAIN_MISSING_NAME_OR_VAL	"Name" and/or "Value" missing before the "%1" argument (number %_2_id) Additional information: Add the missing "Name" and/or "Value" arguments, and delete the offending "ENDITEM" argument.
-27211	LRW_MSG_REPLAY_MAIN_ACTION_MISSING_EMPTY	The "Action" argument (which specifies the URL) is missing or empty Additional information: Add a non-empty "Action" argument (with a value specifying the HTTP address of the action to perform) when submitting the data.
-27210	LRW_MSG_REPLAY_MAIN_ARG_MISSING	Missing "%1" before argument number %_2_id Additional information: Add the missing argument before the argument in the position denoted by the argument Id.
-27209	LRW_MSG_REPLAY_MAIN_ARG_EMPTY	The "%1" argument (number %_2_id) is empty Additional information: Enter a non-empty string for the offending argument.
-27208	LRW_MSG_REPLAY_MAIN_ARG_SPECIFIED_ALREADY	The "%1" argument (number %_2_id) has already been specified in argument number %_3_id Additional information: The argument has already been specified in the argument list in the position denoted by 'argument Id 2'. The function requires only one instance of this argument.

Error code	Handle	Message\Additional information
-27207	LRW_MSG_REPLAY_MAIN_IMAGE_MUTUALLY_EXCL	The XCoord/YCoord arguments are mutually exclusive with the AreaAlt/AreaOrdinal/MapName arguments Additional information: Either specify "XCoord" and "YCoord", or any of the "AreaAlt", "AreaOrdinal", "MapName" arguments in the argument list.
-27206	LRW_MSG_REPLAY_MAIN_BOTH_COORD	Either both, or neither of the XCoord/YCoord arguments should be specified Additional information: Specify both "XCoord" and "YCoord", or neither of them in the argument list.
-27205	LRW_MSG_REPLAY_MAIN_NON_NUMERIC_COORD	XCoord and YCoord should be valid numbers between 0 and %_1_id Additional information: Specify "XCoord" and "YCoord" argument values between '0' and the maximum value specified.
-27204	LRW_MSG_REPLAY_MAIN_MAP_NAME_MISSING	"AreaAlt" and/or "AreaOrdinal" are invalid when "MapName" is missing or empty Additional information: Enter a non-empty string for the "MapName" argument.
-27203	LRW_MSG_REPLAY_MAIN_MAP_NAME_DIESE	"MapName" must not start with '#' Additional information: Fix the "MapName" argument so that it does not start with '#'. Non-zero NameRegExp/ValueRegExp not supported
-27202	LRW_MSG_REPLAY_MAIN_MAP_REGEX_NAME_VALUE	Additional information: Specify a value of '0' for the "NameRegExp" and "ValueRegExp" arguments.
-27201	LRW_MSG_REPLAY_MAIN_NOT_ENOUGH_MEM	Not enough memory (%_1_id bytes) for %2 Additional information: See message 27160.
-27200	LRW_MSG_REPLAY_MAIN_INVALID_MODE_FOR.CG	"Mode=%1" (argument number %_2_id) is invalid within a concurrent group Additional information: Change the "Mode" to "HTTP" or move the function including the offending "Mode" arguments outside the concurrent group.
-27199	LRW_MSG_REPLAY_MAIN_HTML_CONTEXT_DESTROYED	HTML context now destroyed due to an "action" function with "Mode=%1"
-27198	LRW_MSG_REPLAY_MAIN_UNSUPPORTED_KEYWORD	Unsupported keyword "%1" for argument number %_2_id Additional information: Check that the argument is spelled correctly and that the offending argument is specified within the correct group in the argument list.
-27197	LRW_MSG_REPLAY_MAIN_SKIPPING_STEP	Verification checks not enabled. %1 is skipped. See the 'Runtime settings/Preferences/Checks' Additional information: To enable the verification checks, select Runtime Settings > Preferences, and select Enable Image and text check.
-27196	LRW_MSG_REPLAY_MAIN_WEB_FIND_REPORT_OK	"%1" successful. %_2_id occurrence(s) of "%3" found (RightOf="%4", LeftOf="%5") Additional information: This is an Informational message only. Verify that the results are as expected.
-27195	LRW_MSG_REPLAY_MAIN_WEB_FIND_REPORT_FAIL	"%1" failed. %_2_id occurrence(s) of "%3" found (RightOf="%4", LeftOf="%5") Additional information: If a wrong page was received, try to resolve why (for example, check if a previous request navigated to a wrong page, or the page was changed). If the matching criteria were not accurate enough, adjust the arguments of web_find (e.g., specify a more unique text). Use the web_reg_find function for verification.
-27194	LRW_MSG_REPLAY_MAIN_REG_SAVE_PARAM_ELEM	Allocating a new LrwUtilSearchElem failed, probably not enough memory Additional information: • Check the machine's memory resources, and close any unnecessary processes running on the machine. • Restart the computer and replay the script again. • If the problem persists, reduce the number of virtual users that you are running on the same machine.
-27193	LRW_MSG_REPLAY_MAIN_INVALID_ALT_SRC	The "Alt" and "Src" arguments are missing or empty Additional information: Specify the "Alt" and "Src" arguments "as non-NULL strings.
-27192	LRW_MSG_REPLAY_MAIN_WEB_IMAGE_CHECK_REPORT_OK	"%1" succeeded (%_2_id occurrence(s) found. Alt="%3", Src="%4") Additional information: Verify that the results are as expected.
-27191	LRW_MSG_REPLAY_MAIN_WEB_IMAGE_CHECK_REPORT_FAIL	"%1" failed (%_2_id occurrence(s) found. Alt="%3", Src="%4") Additional information: If a wrong page was received, try to resolve why (for example, check if a previous request navigated to a wrong page, or the page was changed). If the matching criteria were not accurate enough, Modify the arguments of web_image_check to specify a more unique text. Use the web_reg_find function for verification.

Error code	Handle	Message\Additional information
-27190	LRW_MSG_REPLAY_MAIN_PARAM_NO_MATCH	No match found for the requested parameter "%1". Check whether the requested boundaries exist in the response data. Also, if the data you want to save exceeds % 2_ld bytes, use "%3" to increase the parameter size Additional information: Check whether the requested boundaries exist in the response data. If the data you want to save exceeds the amount of bytes denoted in the error message, use web_set_max_html_param_len to increase the parameter size.
-27189	LRW_MSG_REPLAY_MAIN_PARAM_MULTIPLE	Requested parameter "%1" found in % 2_ld different pages/frames. Use web_reg_save_param with more restrictive LB/RB/RelFrameId
-27188	LRW_MSG_REPLAY_MAIN_PARAM_SAVED_ID	Parameter "%1" saved from "RelFrameId=%2" (URL="%3")
-27187	LRW_MSG_REPLAY_MAIN_NOT_FOUND_BYTE_COUNT	The above "not found" error(s) may be explained by header and body byte counts being % 1_ld and % 2_ld, respectively.
-27186	LRW_MSG_REPLAY_MAIN_REG_FIND_FAIL_FOUND_COUNT	% 1_ld match(es) found for %2 string "%3" and "Fail" was set to "Found" Additional information: If a wrong page was received, try to resolve why (for example, check if a previous request navigated to a wrong page, or the page was changed). If the matching criteria were not accurate enough, adjust the arguments of web_reg_find (e.g., specify a more unique text).
-27185	LRW_MSG_REPLAY_MAIN_REG_FIND_IGNORE_FOUND_COUNT	% 1_ld match(es) found for %2 string "%3"
-27184	LRW_MSG_REPLAY_MAIN_REL_FRAME_ID_ALL_ORD_NOT_ALL	When "RelFrameId=ALL" is specified, "Ord" (argument number % 1_ld) must be omitted or "ALL" Additional information: Searching for a specific occurrence in each HTML page is not supported. Specifying "RelFrameId=ALL" in web_reg_save_param requests that all the HTML pages downloaded by the following "action" function be searched. The "Ord" (or "Ordinal") argument can specify the occurrence number in a GIVEN "RelFrameId" only. • To search all HTML pages for all occurrences, (which is the default for "RelFrameId=ALL"), omit the "Ord" argument, or explicitly specify "Ord=ALL". • To search for a specific occurrence within a given HTML page, specify its relative frame ID (e.g., "RelFrameId=1.1") along with the occurrence number ("e.g., "Ord=3"). • To search for a specific occurrence within any URL, whether HTML or not, omit the "RelFrameId" argument, and specify only the occurrence number.
-27183	LRW_MSG_REPLAY_MAIN_UNSUPP_ARG_IGNORED	Argument "%1" (number % 2_ld) is not supported anymore and is ignored
-27182	LRW_MSG_REPLAY_MAIN_FUNC_TERM_DONE_SUC	%1 was successful
-27181	LRW_MSG_REPLAY_MAIN_FUNC_TERM_DONE_HSL	%1 highest severity level was "%2"
-27180	LRW_MSG_REPLAY_MAIN_FUNC_TERM_REG_SUC	Registering %1 was successful
-27179	LRW_MSG_REPLAY_MAIN_FUNC_TERM_REG_HSL	Registering %1 highest severity level was "%2"
-27178	LRW_MSG_REPLAY_MAIN_FUNC_TERM_CNT_HSL	%1 highest severity level was "%2", % 3_ld body bytes, % 4_ld header bytes
-27177	LRW_MSG_REPLAY_MAIN_FUNC_TERM_CNT_HSL_CHUNK	%1 highest severity level was "%2", % 3_ld body bytes, % 4_ld header bytes, % 5_ld chunking overhead bytes
-27176	LRW_MSG_REPLAY_MAIN_FUNC_TERM_CNT_SUC	%1 was successful, % 2_ld body bytes, % 3_ld header bytes
-27175	LRW_MSG_REPLAY_MAIN_FUNC_TERM_CNT_SUC_CHUNK	%1 was successful, % 2_ld body bytes, % 3_ld header bytes, % 4_ld chunking overhead bytes
-27174	LRW_MSG_REPLAY_MAIN_PARAM_SAVED_RESOURCE	Parameter "%1" saved from a resource (URL="%2")
-27173	LRW_MSG_REPLAY_MAIN_METHOD_NOT_GET_POST	Method ("%1") is neither GET nor POST. The specified value will be used as is Additional information: This is a warning message only. The "Method" argument specifies a request which is neither GET nor POST. This may still be a valid request, either defined in the HTTP protocol or specific to the server application. However, it may be a typing error. If the request is successful, you can ignore this message. Otherwise, check that the intended Method was specified.
-27172	LRW_MSG_REPLAY_MAIN_METHOD_GET_MULTIPART	"Method=GET" specified with "EncType=multipart/form-data". "Method=POST" will be used instead Additional information: This is a warning message only. The "Method" argument specifies "GET", but the "EncType" argument specifies "multipart/form-data", which is applicable only to POST. Check the corresponding request in the recording log, and change the Method to "POST", or change/omit the "EncType" specification accordingly.
-27171	LRW_MSG_REPLAY_MAIN_PROXY_DIRECT	No proxy is used (direct connection to the Internet)
-27170	LRW_MSG_REPLAY_MAIN_PROXY_HOST_PORT	%1 proxy address is %2:% 3_ld
-27169	LRW_MSG_REPLAY_MAIN_PROXY_INITIAL_START	Initial proxy settings listing:
-27168	LRW_MSG_REPLAY_MAIN_PROXY_INITIAL_END	End of the initial proxy settings listing
-27167	LRW_MSG_REPLAY_MAIN_PROXY_DONT_USE_LOCAL	Not using a proxy for local (Intranet) addresses
-27166	LRW_MSG_REPLAY_MAIN_PROXY_DONT_USE_ADDRESSES	Not using a proxy for addresses beginning with: %1
-27165	LRW_MSG_REPLAY_MAIN_PROXY_USER_NAME	Proxy user name="%1"
-27164	LRW_MSG_REPLAY_MAIN_PROXY_NO_USER_NAME	No proxy user name is specified
-27163	LRW_MSG_REPLAY_MAIN_PROXY_PASSWORD	A password is specified (not shown) for the proxy
-27162	LRW_MSG_REPLAY_MAIN_PROXY_NO_PASSWORD	No password is specified for the proxy

Error code	Handle	Message\Additional information
-27161	LRW_MSG_REPLAY_MAIN_ILLEGAL_ARGUMENT	Illegal search argument to %1. Additional information: Try to use another search function (e.g., switch between web_reg_save_param, web_create_html_param, web_create_html_param_ex). Try to use other arguments for the same function. If that fails, contact customer support
-27160	LRW_MSG_REPLAY_MAIN_OUT_OF_MEMORY	Out of memory. Additional information: • Check the machine's memory resources, and close any unnecessary processes running on the machine. • Restart the computer and replay the script again. • If the problem persists, reduce the number of virtual users that you are running on the same machine.
-27159	LRW_MSG_REPLAY_MAIN_TOO_MANY_SEARCHES	%1 failed: Too many simultaneous searches. Additional information: • Reduce the number of search functions that apply to the failing script functions (that come before it in the script without any intervening "action" function). • Deactivate some ContentCheck Applications/Rules or the entire ContentCheck feature. • If that fails, contact customer support and provide them with an explanation of the problem, and the internal error message returned.
-27158	LRW_MSG_REPLAY_MAIN_UNKNOWN_PE_FAILURE	Internal error in %1. Additional information: • Try to comment out some search functions that apply to the failing script functions (that come before it in the script without any intervening "action" function). • Deactivate some ContentCheck Applications/Rules or the entire ContentCheck feature. • If the issue remains, contact customer support and provide them with an explanation of the problem, and the internal error message returned.
-27157	LRW_MSG_REPLAY_MAIN_INVALID_WHEN_MODE	"%1" is invalid when "Mode=%2" is specified or defaulted (e.g., within a concurrent group) Additional information: Remove the offending argument.
-27156	LRW_MSG_REPLAY_MAIN_BODY_FILE_EXCL	The BodyFilePath argument is mutually exclusive with Body, BodyBinary, BodyUnicode, RAW_BODY_START and Binary=1 Additional information: • If the body of the request should be taken from a file, leave the BodyFilePath argument and remove all the other listed arguments. • If the body of the request is specified by the function arguments, remove the BodyFilePath argument.
-27155	LRW_MSG_REPLAY_MAIN_EMPTY_OR_WHITE_SPACES	"%1" (argument number %_2_Id) is empty or all white spaces Additional information: Check the intended value for this argument. If the intended value is empty or you do not need this argument, remove it. Then specify a non-empty value consisting of at least one non-space character.
-27154	LRW_MSG_REPLAY_MAIN_NAME_PFX_SFX_EXCL	"Name" and "NamePfx"/"NameSfx" are mutually exclusive (before the "%1" argument number %_2_Id) Additional information: Remove either the "Name" argument, or "NamePfx" and/or "NameSfx" argument(s).
-27153	LRW_MSG_REPLAY_MAIN_MISSING_NAME_OR_PFX_SFX	Either "Name" or at least one of "NamePfx" and "NameSfx" should be non-empty (before the "%1" argument number %_2_Id) Additional information: Add either a "Name" argument, or "NamePfx" and/or "NameSfx" argument(s).
-27152	LRW_MSG_REPLAY_MAIN_MISSING_VAL	"Value" should be specified, even as an empty string (before the "%1" argument number %_2_Id) Additional information: Add a "Value" argument, specifying an empty or a non-empty string.
-27151	LRW_MSG_REPLAY_MAIN_MISSING_URL	The "URL" argument is missing or empty (before the "%1" argument number %_2_Id) Additional information: • Add a non-empty "URL" argument immediately before the specified position in the argument list. • Delete any arguments within the item ending at the specified position, including the "ENDITEM" itself.
-27150	LRW_MSG_REPLAY_MAIN_UNRESOLVED_PARAM	Parameter(s) referenced by the "URL" argument (number %_1_Id) and/or the "Referer" argument (number %_2_Id) within EXTRARES have not been resolved. Resource "%3" not downloaded
-27149	LRW_MSG_REPLAY_MAIN_ARG_DISALLOWED_CONCURRENT	The "%1" argument (number %_2_Id) is not allowed within a concurrent group Additional information: Some arguments (e.g., EXTRARES) are not allowed within a concurrent group (i.e., between web_concurrent_start and the nearest following web_concurrent_end). Perform one or more of the following: • Undo any manual changes made to the function. • Move the function having EXTRARES outside of the concurrent group. • Split the function having EXTRARES into multiple web_url function calls and then remove the entire EXTRARES group from the original function. • Remove the concurrent group statements (web_concurrent_start and the nearest following web_concurrent_end)
-27148	LRW_MSG_REPLAY_MAIN_PENDING_PE_NOT_FOUND	Pending web_reg_save_param/reg_find/create_html_param[ex] request(s) are deleted and will be handled as "not found"

Error code	Handle	Message\Additional information
-27147	LRW_MSG_REPLAY_MAIN_UNREF_FRAME_ID	No buffer having "RelFrameID=%1" has been received. The web_reg_save_param/reg_find request(s) specifying this RelFrameID will be handled as "not found"
-27146	LRW_MSG_REPLAY_MAIN_EXTRA_RES_BASE_DIR_INVALID	The "%1" argument (number %_2_id) does not start with "http://" or "https://", or the host name is missing or invalid Additional information: The argument must start with a valid "scheme" (http or https) followed by "://" and a valid server name and another slash (e.g., "https://www.anyco.com/").
-27145	LRW_MSG_REPLAY_MAIN_EXTRA_RES_BASE_DIR_SLASH	The "%1" argument (number %_2_id) does not end with a slash ('/'). An ending slash is added Additional information: The specified argument is invalid as a base directory name. It should end with a slash (e.g., "https://www.anyco.com/").
-27144	LRW_MSG_REPLAY_MAIN_EXTRA_RES_IGNORED	Resource downloading not requested, so "%1" (argument number %_2_id) and all arguments within it are ignored
-27143	LRW_MSG_REPLAY_MAIN_VN	Web Turbo Replay of Opentext Performance Engineering %1 (%2 %3)
-27142	LRW_MSG_REPLAY_MAIN_RTS_START	Some of the Runtime Settings:
-27141	LRW_MSG_REPLAY_MAIN_RTS_FILE	Runtime Settings file: "%1"
-27140	LRW_MSG_REPLAY_MAIN_RTS_FILE_UNAVAIL	Runtime Settings file name unavailable
-27139	LRW_MSG_REPLAY_MAIN_TEXT_OR_PFX_SFX	Specify non-empty value(s) for EITHER just "Text" OR both "TextPfx" and "TextSfx" Additional information: In the web_reg_find and web_global_verification functions, you can either specify the "Text" argument, or, alternatively, the pair of "TextPfx" and "TextSfx". You cannot mix between these or specify only ONE of "TextPfx" and "TextSfx". Remove the extra arguments or add the missing ones.
-27138	LRW_MSG_REPLAY_MAIN_VERIF_FAIL_NOT_FOUND	No %1 match found for Text "%2" or TextPfx "%3" and TextSfx "%4" (ID="%5")
-27137	LRW_MSG_REPLAY_MAIN_VERIF_IGNORE_NOT_FOUND	No %1 match found for Text "%2" or TextPfx "%3" and TextSfx "%4" (ID="%5")
-27136	LRW_MSG_REPLAY_MAIN_VERIF_FAIL_FOUND	%_1_id %2 match(es), such as "%3%4%5", found for Text "%6" or TextPfx "%7" and TextSfx "%8" (ID="%9")
-27135	LRW_MSG_REPLAY_MAIN_VERIF_IGNORE_FOUND	%_1_id %2 match(es), such as "%3%4%5", found for Text "%6" or TextPfx "%7" and TextSfx "%8" (ID="%9")
-27134	LRW_MSG_REPLAY_MAIN_UNSUPP_WAP	%1 is unsupported for WAP replay
-27133	LRW_MSG_REPLAY_MAIN_FOUND_TEXT_AED	ContentCheck Rule "%1" in Application "%2" triggered. Text "%3" matched (count=%_4_id)
-27132	LRW_MSG_REPLAY_MAIN_FOUND_PFX_SFX_AED	"ContentCheck Rule "%1" in Application "%2" triggered. Text Pfx="%3" and Sfx="%4" matched, match (#%_5_id) is "%6" Additional information: • If it is just an informational message, ignore it.. • Try to see whether a wrong page has been received, an error has occurred, or the Rule definition is inaccurate or not applicable.. • If a wrong page has been received, or an error has occurred, try to see what caused this (for example, incorrect argument to some previous "action" function, or missing/invalid cookie/header). • If the ContentCheck Rule is inaccurate or inapplicable, modify or delete it.. Note: a match count exceeding one can result from the matching criteria defined for this Rule being too general.
-27131	LRW_MSG_REPLAY_MAIN_NOT_FOUND_TEXT_AED	ContentCheck Rule "%1" in Application "%2" triggered. Text "%3" not matched
-27130	LRW_MSG_REPLAY_MAIN_NOT_FOUND_PFX_SFX_AED	ContentCheck Rule "%1" in Application "%2" triggered. Text Pfx="%3" and Sfx="%4" not matched
-27129	LRW_MSG_REPLAY_MAIN_FOUND_TEXT_VERIF	"Text=%1" found (for %2, count=%_3_id)
-27128	LRW_MSG_REPLAY_MAIN_FOUND_PFX_SFX_VERIF	""TextPfx=%1" and "TextSfx=%2" found for %3%4, match (#%_5_id) is "%6" Additional information: • If the verification check was successful, you can ignore this message. • If the verification check failed, try to see whether a wrong page has been received, an error has occurred, or the web_reg_find or web_global_verification function is inaccurate or not applicable. • If a wrong page has been received, or an error has occurred, try to see what caused this (for example, incorrect argument to some previous "action" function, or missing/invalid cookie/header). • If the web_reg_find or web_global_verification function is inaccurate or inapplicable, modify it or delete it, respectively.
-27127	LRW_MSG_REPLAY_MAIN_NOT_FOUND_TEXT_VERIF	"Text=%1" not found (for %2)
-27126	LRW_MSG_REPLAY_MAIN_NOT_FOUND_PFX_SFX_VERIF	"TextPfx=%1" and "TextSfx=%2" not found (for %3)
-27125	LRW_MSG_REPLAY_MAIN_ENABLED_HTTP09	Enabled acceptance of HTTP/0.9 responses
-27124	LRW_MSG_REPLAY_MAIN_DISABLED_HTTP09	Disabled acceptance of HTTP/0.9 responses
-27123	LRW_MSG_REPLAY_MAIN_SEARCH_CONCURRENT	Pending %1/%2/%3/%4 request(s) before %5 apply to the first Action function within the group, not to the entire group Additional information: This is a warning message only. Searches that were initiated by functions such as web_reg_save_param, web_reg_find, web_create_html_param, and web_create_html_param_ex that precede a concurrent group. • If you want a search to apply to the first "action" function within a concurrent group, place it immediately before that function, within the group. (web_concurrent_start) apply only to the first "action" function within the group. • If you want a search to apply to the entire concurrent group, copy and paste it immediately before each function within the group.
-27122	LRW_MSG_REPLAY_MAIN_AUTO_TRANS_START	Starting Automatic Transaction "%1" failed (rc=%_2_id)
-27121	LRW_MSG_REPLAY_MAIN_AUTO_TRANS_PROP	Setting properties for Automatic Transaction "%1" failed (rc=%_2_id)
-27120	LRW_MSG_REPLAY_MAIN_AUTO_TRANS_END	Ending Automatic Transaction failed (rc=%_1_id)

Error code	Handle	Message\Additional information
-27119	LRW_MSG_REPLAY_MAIN_SAVE_OFFSET	SaveOffset (% 1_Id) exceeds the found value length (% 2_Id) for parameter "%3". An empty string is saved.
-27118	LRW_MSG_REPLAY_MAIN_SAVE_LEN	SaveOffset (% 1_Id) plus SaveLen (% 2_Id) exceeds the found value length (% 3_Id) for parameter "%4". SaveLen=% 5_Id is used Additional information: Possible reasons include: • The found value is not the intended one, due to inaccurate arguments to web_reg_save_param. • The found value is not the intended one, due to navigating to a wrong page, or a different page being returned. • The specified SaveOffset is incorrect. Check if the found value is the intended one, and that it is in the correct page and check the values of SaveOffset and SaveLen.
-27117	LRW_MSG_REPLAY_BINARY_UNICODE_BINARY_BODY_EXCL	Binary=1 is mutually exclusive with BodyBinary, BodyUnicode and RAW_BODY_START Additional information: Remove the Binary=1 specification, and, if you have a Body argument, change it to BodyBinary.
-27116	LRW_MSG_REPLAY_SUBARGS_IC DIG_EXCL	Sub-arguments /IC and /DIG are mutually exclusive
-27115	LRW_MSG_REPLAY_MAIN_NET_UNCHANGED	The "%1" Net layer is already active and is retained
-27114	LRW_MSG_REPLAY_MAIN_NET_NOT_INITIALIZED	The "%1" Net layer has not been initialized
-27113	LRW_MSG_REPLAY_MAIN_SUC_TEXT_VERIF	Registered %1 successful for "Text=%2" (count=% 3_Id)
-27112	LRW_MSG_REPLAY_MAIN_SUC_PFX_SFX_VERIF	Registered %1 successful for "TextPfx=%2" and "TextSfx=%3" (count=% 4_Id)
-27111	LRW_MSG_REPLAY_MAIN_NOT_FOUND_REQ_TEXT_VERIF	Registered %1 successful for "Text=%2"
-27110	LRW_MSG_REPLAY_MAIN_NOT_FOUND_REQ_PFX_SFX_VERIF	Registered %1 successful for "TextPfx=%2" and "TextSfx=%3"
-27109	LRW_MSG_REPLAY_MAIN_WEB_DEBUG_PRINT_USAGE	Invalid argument number %1. Usage: web_debug_print(Title, %2, LAST)
-27108	LRW_MSG_REPLAY_MAIN_NO_AUTH_ENTRY	No user-name / password to be deleted for the specified server
-27107	LRW_MSG_REPLAY_MAIN_URL_NON_URL_MUTUALLY_EXCL	The Uri* arguments are mutually exclusive with the Scheme, Host*, Port, Path*, Query* and FragmentID* arguments Additional information: The "Uri" or "UriPrefix" arguments cannot be specified with any of the other arguments detailed in the message. Specify either a "URL", "URLPrefix", or one or more of the other arguments only.
-27106	LRW_MSG_REPLAY_MAIN_HOST_SUFFIX_PREFIX_MUTUALLY_EXCL	The Host, HostSuffix and HostPrefix arguments are mutually exclusive Additional information: Specify one fragment-related argument only.
-27105	LRW_MSG_REPLAY_MAIN_PATH_SUFFIX_PREFIX_MUTUALLY_EXCL	The Path, PathSuffix and PathPrefix arguments are mutually exclusive Additional information: Specify one fragment-related argument only.
-27104	LRW_MSG_REPLAY_MAIN_URL_PREFIX_MUTUALLY_EXCL	The Uri and UriPrefix arguments are mutually exclusive Additional information: Specify one fragment-related argument only.
-27103	LRW_MSG_REPLAY_MAIN_QUERY_PREFIX_MUTUALLY_EXCL	The Query, QueryPrefix and QuerySuffix arguments are mutually exclusive Additional information: Specify one fragment-related argument only.
-27102	LRW_MSG_REPLAY_MAIN_FRAGMENT_PREFIX_MUTUALLY_EXCL	The FragmentId, FragmentIdPrefix and FragmentIdSuffix arguments are mutually exclusive Additional information: Specify one fragment-related argument only.
-27101	LRW_MSG_REPLAY_MAIN_NOT_FOUND_PARAMETER	Value of the "%1" parameter could not be obtained (Parameter_GetParameterExt rc=% 2_Id)
-27100	LRW_MSG_REPLAY_MAIN_ARG_NOT_SPECIFIED	Argument "%1" not specified
-27099	LRW_MSG_REPLAY_MAIN_PAC_UNSUPPORTED_SCHEME_RTS	Address (URL="%1") of the proxy automatic configuration script does not start with "http:" / "https:" / "ftp:". Additional information: Correct the URL in the runtime settings or the default browser's settings.
-27098	LRW_MSG_REPLAY_MAIN_PAC_INVALID_ADDRESS_RTS	Could not download the proxy automatic configuration script (URL="%1"). Additional information: • Check the runtime settings: Navigate to Runtime Settings > Internet Protocol: Proxy, and ensure that Use custom proxy, Use automatic configuration script Address are selected, and that the correct path and name of a proxy automatic configuration (pac) script are specified. • Check the default browser's settings: Navigate to Runtime Settings > Internet Protocol: Proxy, and ensure that Use the default HTTP proxy settings is selected. To see the default settings go to Control Panel > Network and Internet > Internet Options > Connections tab > LAN settings button.
-27097	LRW_MSG_REPLAY_MAIN_PAC_START_DOWNLOAD	Starting to download the proxy automatic configuration script, URL="%1"
-27096	LRW_MSG_REPLAY_MAIN_PAC_END_DOWNLOAD	Proxy automatic configuration script (URL="%1") downloaded and evaluated successfully

Error code	Handle	Message\Additional information
-27095	LRW_MSG_REPLAY_MAIN_PAC_FAILED_TO_COMPILE	Failed to compile proxy automatic configuration script (URL="%1") Additional information: Correct the automatic proxy configuration script. Alternatively, deactivate the custom proxy option. Navigate to Runtime Settings > Internet Protocol: Proxy, and deactivate Use custom proxy.
-27094	LRW_MSG_REPLAY_MAIN_PROXY_USING_PROXY	Using custom proxy with following setting:
-27093	LRW_MSG_REPLAY_MAIN_PROXY_OBTAINING_SETTING_FROM_BROWSER	Obtaining the proxy settings from the default browser:
-27092	LRW_MSG_REPLAY_MAIN_SET_CERT_WIN32_ONLY	The "%1" function is supported under Windows only. Use the "%2" function instead
-27091	LRW_MSG_REPLAY_MAIN_FILTERING_ARGUMENT_MISSING	No filtering argument specified Additional information: Add filtering criteria to the function or remove the function call.
-27090	LRW_MSG_REPLAY_MAIN_RAW_BODY_INACCESSIBLE	The raw body arguments, char * address=%1 and int length=%_2_Id, following the RAW_BODY_START argument number %_3_Id, are missing or specify an inaccessible storage area Additional information: The RAW_BODY_START argument should be followed by two arguments — a "char *" expression and an "int" expression. Either one of these has not been specified, or the memory referenced by the address and the length is inaccessible. Check that the two expressions are valid, and that they are in the correct order.
-27089	LRW_MSG_REPLAY_MAIN_RAW_BODY_END_MISSING	RAW_BODY_END, which should be argument number %_1_Id (following RAW_BODY_START, char * address and int length) is missing or not accessible Additional information: The RAW_BODY_START argument should be followed by two arguments (a "char *" expression and an "int" expression), and then RAW_BODY_END. The RAW_BODY_END argument has not been specified, or was misplaced (e.g., missing address and/or length).
-27088	LRW_MSG_REPLAY_MAIN_FAILED_TO_LOAD_CORELLATION_CALLBACK_LIBRARY	Failed to load the "%1" auto-correlation callback library. %2 Additional information: Unable to load the specified auto-correlation callback library. Installation may not complete successfully. Verify that the specified library exists in the <installdir>\bin directory and/or in the PATH. If that fails, contact customer support.
-27087	LRW_MSG_REPLAY_MAIN_FAILED_TO_GET_CORELLATION_CALLBACK_FUNC	Auto-correlation callback function "%1" not found in library "%2"
-27086	LRW_MSG_REPLAY_MAIN_CORELLATION_CALLBACK_FUNC_FAILED	Auto-correlation callback function "%1" failed (rc=%_2_Id) for parameter "%3"
-27085	LRW_MSG_REPLAY_MAIN_PAC_WININET_UNSUPPORTED	Proxy automatic configuration is not supported in the Wininet replay mode. Please use the Sockets replay mode or disable proxy automatic configuration
-27084	LRW_MSG_REPLAY_MAIN_AUTO_CORR_DLL_WITHOUT_FUNCTION	"AutoCorrDll" (argument number %_1_Id) specified without "AutoCorrFunction"
-27083	LRW_MSG_REPLAY_MAIN_AUTO_TOO_MANY_CORR_DLLS	%_1_Id (maximum) auto-correlation libraries are loaded already
-27082	LRW_MSG_REPLAY_MAIN_CORR_DLL_LEN	Invalid "AutoCorrDll" (argument number %_1_Id) length (%_2_Id). Maximum length is %_3_Id
-27081	LRW_MSG_REPLAY_MAIN_SERVICE_AUTO_CORR_FUNC_NOT_FOUND	Service function "%1" not found in auto-correlation callback library "%2"
-27080	LRW_MSG_REPLAY_MAIN_ADD_REG_COOKIE_SUCCESSFUL	Cookie "%1" added successfully (registered via %2)
-27079	LRW_MSG_REPLAY_MAIN_ADD_REG_COOKIE_FAILED	Adding cookie "%1" failed (registered via %2) Additional information: The syntax of the cookie is probably incorrect. The most common errors are in the "expires" field. Look for a previous web_reg_add_cookie call specifying the cookie, and perform the correction there.
-27078	LRW_MSG_REPLAY_MAIN_FORM_ELEM_VAL_EXCEEDS_MAX_LENGTH	Length (%_1_Id) of the value of form element "%2" exceeds maximum (%_3_Id)
-27077	LRW_MSG_REPLAY_MAIN_INIT_NOT_EMPTY_NEW_USER	The "vuser_init" section contains web function(s) when the "Simulate a new user on each iteration" Runtime Setting is ON. This may produce unpredictable results with multiple iterations Additional information: The "Simulate a new user on each iteration" runtime setting distinguishes between these possibilities. When it is "ON", the Init Section should be empty. When it is "OFF", the first web function in the Action Section probably assumes that some preparations (e.g., "login") have been performed in the Init Section. This works fine in the first iteration, but before the second (and any following) iteration, any "context" is reset, and the script may fail.
-27076	LRW_MSG_REPLAY_MAIN_VALUE_ENCRYPTED_VALUE_EXCL	"Value" and "EncryptedValue" are mutually exclusive (before the "%1" argument number %_2_Id)
-27075	LRW_MSG_REPLAY_MAIN_WININET_UNDER_UNIX	"Wininet replay instead of Sockets" requested under Unix and ignored. Some features may not function as expected (e.g., "%1")
-27074	LRW_MSG_REPLAY_MAIN_NETSCAPE_JS	Emulating a Netscape browser is not supported for a Virtual User of this type. Refer to "Runtime settings/Browser/Browser Emulation/User-Agent (browser to be emulated)". Aborting
-27073	LRW_MSG_REPLAY_MAIN_PAC_FAILED_BROWSER	Note: The URL of the proxy automatic configuration script was obtained from the default browser (as requested in "Runtime settings/Internet Protocol/Proxy"). Using the alternative proxy options
-27072	LRW_MSG_REPLAY_MAIN_PAC_FAILED_RTS	The URL of the proxy automatic configuration script was explicitly specified in "Runtime settings/Internet Protocol/Proxy". Aborting
-27071	LRW_MSG_REPLAY_MAIN_WININET_UNSUPP_PAC	"Use automatic configuration script" (in "Runtime settings/Internet Protocol/Proxy") is not supported by the Wininet Replay and is ignored
-27070	LRW_MSG_REPLAY_MAIN_WININET_UNSUPP_CBD	Replay statistic collection is not supported by the Wininet Replay and is ignored

Error code	Handle	Message\Additional information
-27069	LRW_MSG_REPLAY_MAIN_WININET_UNSUPP_STEP_TIMEOUT	"Step download timeout" (in "Runtime settings/Preferences/Options") is not supported by the Wininet Replay and is ignored
-27068	LRW_MSG_REPLAY_MAIN_WININET_UNSUPP_CONTENT_CACHE	"Cache URLs requiring content" (in "Runtime settings/Browser/Browser Emulation") is not supported by the Wininet Replay and is ignored
-27067	LRW_MSG_REPLAY_MAIN_WININET_UNSUPP_GUI_MODE	"GUI Run Mode" (in "Runtime settings/Preferences/Options") is not supported by the Wininet Replay. Aborting
-27066	LRW_MSG_REPLAY_MAIN_RRS_NOTE	Note: This is a Replay Recorded Session (RRS) run. StartRecordingGMT="%1" (time offset=% 2 _ld)
-27065	LRW_MSG_REPLAY_MAIN_RUR_NOTE	Note: This is a Replay Under Recorder (RUR) run. StartRecordingGMT="%1" (time offset=% 2 _ld). RurVersion=% 3 _ld
-27064	LRW_MSG_REPLAY_MAIN_RUR_WITHOUT_TIMESTAMP	Replay Under Recorder (RUR) run without "StartRecordingGMT=yyyy/mm/dd HH:mm:ss" in the rur_default.cfg file. You can take the date/time from a "\\Date:\\\" header in the Generation Log. Continuing, but error(s) may occur
-27063	LRW_MSG_REPLAY_MAIN_RRS_WITHOUT_TIMESTAMP	Replay Recorded Session (RRS) run without "StartRecordingGMT=yyyy/mm/dd HH:mm:ss" in the Runtime Settings file. You can take the date/time from a "\\Date:\\\" header in the Generation Log. Continuing, but error(s) may occur
-27062	LRW_MSG_REPLAY_MAIN_RRS_SAVING_TIME_OFFSET	Replay Recorded Session (RRS): Saved time offset at the start of the first iteration (% 1 _ld)
-27061	LRW_MSG_REPLAY_MAIN_RRS_RESTORING_TIME_OFFSET_OK	Replay Recorded Session (RRS): Restored time offset to the start of the first iteration (% 1 _ld)
-27060	LRW_MSG_REPLAY_MAIN_RRS_RESTORING_TIME_OFFSET_FAILED	Replay Recorded Session (RRS): Failed to restore time offset to the start of the first iteration (% 1 _ld). Continuing, but error(s) may occur
-27059	LRW_MSG_REPLAY_MAIN_GUI_CONTEXT	The context for GUI-based functions is reset due to an HTML-Mode function expecting an HTML response (%1)
-27058	LRW_MSG_REPLAY_MAIN_ALNUM_SUBARGS_EXCL	The /ALNUMIC, /ALNUMLC and /ALNUMUC sub-arguments of "%1" are mutually exclusive
-27057	LRW_MSG_REPLAY_MAIN_NON_FILE_CONTENT_TYPE	"Content-Type" (argument number % 1 _ld) ignored for a non-File item
-27056	LRW_MSG_REPLAY_MAIN_WEB_SET_OPTION_NO_EFFECT	"%1" with %2 ("%3") has no effect where "Continue on error" applies
-27055	LRW_MSG_REPLAY_MAIN_DEFAULT_VAL_ORD_ALL	"DefaultValue" (argument number % 1 _ld) is mutually exclusive with "Ord=ALL" (argument number % 2 _ld)
-27054	LRW_MSG_REPLAY_MAIN_SWITCH_MATCHES_LIST_LOG	"%1 "TextPfx=%2" and "TextSfx=%3" matches beyond the first % 4 _ld will be issued as informational messages. Refer to "Runtime settings/Preferences/Options/Max number of error matches issued as ERRORS"
-27053	LRW_MSG_REPLAY_MAIN_SWITCH_MATCHES_LIST_LOG_AED	"ContentCheck Rule "%1" in Application "%2" matches beyond the first % 3 _ld will be issued as informational messages. Refer to "Runtime settings/Preferences/Options/Max number of error matches issued as ERRORS"
-27052	LRW_MSG_REPLAY_MAIN_VUSER_DIR	Vuser directory: "%1"
-27051	LRW_MSG_REPLAY_MAIN_VUSER_DIR_UNAVAIL	Vuser directory unavailable
-27050	LRW_MSG_REPLAY_MAIN_OUTPUT_DIR	Vuser output directory: "%1"
-27049	LRW_MSG_REPLAY_MAIN_OUTPUT_DIR_UNAVAIL	Vuser output directory unavailable
-27048	LRW_MSG_REPLAY_MAIN_CWD	Operating system's current working directory: "%1"
-27047	LRW_MSG_REPLAY_MAIN_CWD_UNAVAIL	Operating system's current working directory unavailable
-27046	LRW_MSG_REPLAY_MAIN_VERIFICATION_ID_NOT_UNIQUE	"The ID ("%1") specified in "%2" is already used by other search functions.Note that applying "%3" or "%4" on this ID will also affect other global searches with same ID."
-27045	LRW_MSG_REPLAY_MAIN_LOCALE	Current locale is "%1", code page % 2 _ld, preferred charset name "%3", Unicode converter name="%4", CRT locale string="%5"
-27044	LRW_MSG_REPLAY_MAIN_FAILED	Failed
-27043	LRW_MSG_REPLAY_MAIN_PASS	Pass
-27042	LRW_MSG_REPLAY_MAIN_ABORTED	Aborted
-27041	LRW_MSG_REPLAY_MAIN_SCRIPT_ABORTED	Script Aborted!
-27040	LRW_MSG_REPLAY_MAIN_DFE_LOGGER	Data Format Extension: %1
-27039	LRW_MSG_REPLAY_MAIN_INVALID_CONVERS_ID	The "%1" argument (number % 2 _ld) must not start with an underscore and must not have leading/trailing white spaces (nor any byte < 0x20)
-27038	LRW_MSG_REPLAY_MAIN_PAC_UNSUPPORTED_SCHEME_API	Address (URL="%1") of the proxy automatic configuration script does not start with "http:" / "https:" / "ftp:".
-27037	LRW_MSG_REPLAY_MAIN_PAC_INVALID_ADDRESS_API	Could not download the proxy automatic configuration script (URL="%1"). See previous messages.
-27036	LRW_MSG_REPLAY_MAIN_PAC_RTS_CREDENTIALS_OVERRIDEN	Credentials set by "%1" for PAC proxies override authentication defined in the Runtime Settings.
-27035	LRW_MSG_REPLAY_MAIN_DNS_CACHE	DNS caching: %1
-27034	LRW_MSG_REPLAY_MAIN_SIMULATE_BROWSER_CACHE	Simulate browser cache: %1
-27033	LRW_MSG_REPLAY_MAIN_CACHE_URL_REQUIRING_CONTENT	Cache URLs requiring content (e.g., HTMLs): %1
-27032	LRW_MSG_REPLAY_MAIN_ADDITIONAL_URL_REQUIRING_CONTENT	Additional URLs requiring content: %1
-27031	LRW_MSG_REPLAY_MAIN_CHECK_NEWER_VERSIONS	Check for newer versions every visit to the page: %1
-27030	LRW_MSG_REPLAY_MAIN_PAGE_DOWNLOAD_TIMEOUT	Page download timeout (sec): % 1 _ld
-27029	LRW_MSG_REPLAY_MAIN_PAGE_TIMEOUT_IS_WARNING	Resource Page Timeout is a Warning: %1
-27028	LRW_MSG_REPLAY_MAIN_CONTENT_CHECK_ENABLED	ContentCheck enabled: %1
-27027	LRW_MSG_REPLAY_MAIN_CONTENT_CHECK_FILE	ContentCheck script-level file: "%1"
-27026	LRW_MSG_REPLAY_MAIN_ENABLE_WEB_BREAKDOWN	Enable Web Page Breakdown: %1
-27025	LRW_MSG_REPLAY_MAIN_SIEBEL_SARM_ID	Siebel SARM ID: % 1 _ld
-27024	LRW_MSG_REPLAY_MAIN_SIEBEL_DB_BREAKDOWN	Siebel DB Breakdown: %1
-27023	LRW_MSG_REPLAY_MAIN_CONNECTION_DATA_POINTS	Enable connection data points: %1
-27022	LRW_MSG_REPLAY_MAIN_PROCESS_SOCKETS_AFTER_RESCHEDULE	Process socket after reschedule: %1
-27021	LRW_MSG_REPLAY_MAIN_SNAPSHOT_ERROR	Snapshot on error: %1
-27020	LRW_MSG_REPLAY_MAIN_STEP_IS_TRANSACTION	Define each step as a transaction: %1
-27019	LRW_MSG_REPLAY_MAIN_AUTO_TRANS_FILE_LINE	File and line in automatic transaction names: %1
-27018	LRW_MSG_REPLAY_MAIN_DOWNLOAD_NON_HTML	Download non-HTML resources: %1

Error code	Handle	Message\Additional information
-27017	LRW_MSG_REPLAY_MAIN_VERIFICATION_CHECK	Verification checks: %1
-27016	LRW_MSG_REPLAY_MAIN_CONVERT_UTF	Convert from/to UTF-8: %1
-27015	LRW_MSG_REPLAY_MAIN_CONVERT_UTF_OVERRIDDEN_BY_CHARSET	Convert from/to UTF-8 (overridden by 'Charset conversions by HTTP' for Click-and-Script steps): %1
-27014	LRW_MSG_REPLAY_MAIN_CONVERT_HTTP	Charset conversions by HTTP (overrides by 'Convert from/to UTF-8' for Click-and-Script steps): %1
-27013	LRW_MSG_REPLAY_MAIN_REPARSE_META_CHANGE	Reparse when META changes charset: %1
-27012	LRW_MSG_REPLAY_MAIN_DOM_DEFAULT_BLOCK_SIZE	Default block size for DOM memory allocations: % 1 _ld
-27011	LRW_MSG_REPLAY_MAIN_DOM_MEMORY_MANAGE	Memory Manager for dynamically-created DOM objects: %1
-27010	LRW_MSG_REPLAY_MAIN_OPTIMIZE_TIMERS	Optimize timers at end of step: %1
-27009	LRW_MSG_REPLAY_MAIN_NEW_USER_EACH_ITR	Simulate a new user each iteration: %1
-27008	LRW_MSG_REPLAY_MAIN_NON_CRITICAL_ERROR_IS_WARNING	Non-critical item errors as warnings: %1
-27007	LRW_MSG_REPLAY_MAIN_HTTP_ERROR_IS_WARNING	HTTP errors as warnings: %1
-27006	LRW_MSG_REPLAY_MAIN_WINNET_REPLAY	Wininet replay instead of Sockets: %1
-27005	LRW_MSG_REPLAY_MAIN_HTTP_VERSION	HTTP version: %1
-27004	LRW_MSG_REPLAY_MAIN_HTTP_KEEP_ALIVE	Keep-Alive HTTP connections: %1
-27003	LRW_MSG_REPLAY_MAIN_MAX_META_REFRESH	Max self Meta refresh updates: % 1 _ld
-27002	LRW_MSG_REPLAY_MAIN_AUTO_CONFIG_SCRIPT	Use automatic configuration script: %1
-27001	LRW_MSG_REPLAY_MAIN_AUTO_CONFIG_SCRIPT_ADDRESS	Automatic configuration script address: %1
-27000	LRW_MSG_REPLAY_MAIN_PROXY_SERVER	Use proxy server: %1
-26999	LRW_MSG_REPLAY_MAIN_PARSE_HTML	Parse HTML Content-Type: %1
-26998	LRW_MSG_REPLAY_MAIN_GRAPH_HITS	Graph hits per second and HTTP status codes: %1
-26997	LRW_MSG_REPLAY_MAIN_GRAPH_RESPONSE	Graph response bytes per second: %1
-26996	LRW_MSG_REPLAY_MAIN_GRAPH_PAGES	Graph pages per second: %1
-26995	LRW_MSG_REPLAY_MAIN_WEB_RECORDER_VERSION	Web recorder version ID: % 1 _ld
-26994	LRW_MSG_REPLAY_MAIN_READ_BEYOND_CONTENT	Read beyond Content-Length: %1
-26993	LRW_MSG_REPLAY_MAIN_RUN_MODE	Run mode: %1
-26992	LRW_MSG_REPLAY_MAIN_UTC_START_DATE_TIME	UTC (GMT) start date/time : %1
-26991	LRW_MSG_REPLAY_MAIN_LOCAL_START_DATE_TIME	LOCAL start date/time : %1
-26990	LRW_MSG_REPLAY_MAIN_LOCAL_DAY_LIGHT_SAVINGS_TIME	Local daylight-Savings-Time : %1
-26989	LRW_MSG_REPLAY_MAIN_MAXIUM_NUMBER_OF_CONCURRENT_CONNECTIONS	Maximum number of concurrent connections per server: %1
-26988	LRW_MSG_REPLAY_MAIN_USER_AGENT	Replay user agent: %1
-26987	LRW_MSG_REPLAY_MAIN_FILE_NAME_VALUE_CANNOT_DEFINE_AT_THE_SAME_ITEM	FileName and Value attributes cannot be defined at the same item "%1" argument (number % 2 _ld)
-26986	LRW_MSG_REPLAY_MAIN_MISSING_NAME_OR_VAL_OR_FILE_NAME	"Name" and/or ("Value" or "FileName") are missing before the "%1" argument (number % 2 _ld)
-26985	LRW_MSG_REPLAY_MAIN_REST_START_IGNORE	***** web_add_header is called internally from web_rest. The following messages are from web_add_header *****
-26984	LRW_MSG_REPLAY_MAIN_REST_END_OF_IGNORE	***** End of messages from web_add_header *****
-26983	LRW_MSG_REPLAY_MAIN_VN_WITH_ENV_INFO	Web Turbo Replay of Opentext Performance Engineering %1 for %2; build %3 (%4 %5)
LrwReplayMain_txt.h		
-26899	LRW_MSG_REPLAY_MAIN_SEV_LVL_PX_INFO	
-26898	LRW_MSG_REPLAY_MAIN_SEV_LVL_PX_WARNING	Warning
-26897	LRW_MSG_REPLAY_MAIN_SEV_LVL_PX_CONTINUING_AFTER_ERROR	Continuing after Error
-26896	LRW_MSG_REPLAY_MAIN_SEV_LVL_PX_ERROR	Error
-26895	LRW_MSG_REPLAY_MAIN_SEV_LVL_PX_FATAL_ERROR	Fatal Error
-26894	LRW_MSG_REPLAY_MAIN_FROM_FILE_LINE	[issued at %1(% 2 _ld)]
-26893	LRW_MSG_REPLAY_MAIN_HTTP_INFO_RETURN_CODE	<CENTER>HTTP return code : %1</CENTER>
-26892	LRW_MSG_REPLAY_MAIN_HTTP_INFO_DOWNLOAD_SIZE	<CENTER>Download size : %1 bytes</CENTER>
-26891	LRW_MSG_REPLAY_MAIN_HTTP_INFO_TOTAL_REQUEST_STAT	<CENTER>Total request size : %1 bytes</CENTER>
-26890	LRW_MSG_REPLAY_MAIN_HTTP_INFO_TOTAL_RESPONSE_STAT	<CENTER>Total response size : %1 bytes</CENTER>
-26889	LRW_MSG_REPLAY_MAIN_HTTP_INFO_DOWNLOAD_TIME	<CENTER>Download time : %1 milliseconds</CENTER>
-26888	LRW_MSG_REPLAY_MAIN_HTTP_INFO_ERROR	<CENTER>Error: Information not available</CENTER>
-26887	LRW_MSG_REPLAY_MAIN_RESOLVE_TIMEOUT	<CENTER>Maximum time for resolving the host name set to %1 seconds</CENTER>
-26886	LRW_MSG_REPLAY_MAIN_CONNECT_TIMEOUT	<CENTER>Maximum time for connecting to the web server set to %1 seconds</CENTER>
-26885	LRW_MSG_REPLAY_MAIN_RECEIVE_TIMEOUT	<CENTER>Maximum time for next portion of data to arrive from the server set to %1 seconds</CENTER>

Error code	Handle	Message\Additional information
-26884	LRW_MSG_REPLAY_MAIN_START_SAVE_RESPONSE	<CENTER>Start saving response headers into parameter: %1</CENTER>
-26883	LRW_MSG_REPLAY_MAIN_STOP_SAVE_RESPONSE	<CENTER>Stop saving response headers</CENTER>
-26882	LRW_MSG_REPLAY_MAIN_START_SAVE_REQUESTS	<CENTER>Start saving request headers into parameter: %1</CENTER>
-26881	LRW_MSG_REPLAY_MAIN_STOP_SAVE_REQUESTS	<CENTER>Stop saving request headers</CENTER>
-26880	LRW_MSG_REPLAY_MAIN_MAX_HTTP_CONNECTIONS	<CENTER>Maximum number of simultaneous connections set to %1</CENTER>
-26879	LRW_MSG_REPLAY_MAIN_SET_CERTIFICATE	<CENTER>Use certificate number %1 from Internet Explorer registry</CENTER>
-26878	LRW_MSG_REPLAY_MAIN_MAX_HTML_PARAM_LEN	<CENTER>Maximum length of a HTML string that can be retrieved and saved set to %1 characters</CENTER>
-26877	LRW_MSG_REPLAY_MAIN_BYPASS_LOCAL	<CENTER>Proxy was set to bypass local addresses</CENTER>
-26876	LRW_MSG_REPLAY_MAIN_DONT_BYPASS_LOCAL	<CENTER>Proxy was set not to bypass local addresses</CENTER>
-26875	LRW_MSG_REPLAY_MAIN_SET_USER	<CENTER>User name=%1 Password = %2 Host : Port = %3</CENTER>
-26874	LRW_MSG_REPLAY_MAIN_PROXY_BYPASS	<CENTER>Bypass proxy for these URLs : %1</CENTER>
-26873	LRW_MSG_REPLAY_MAIN_SET_PROXY	<CENTER>Direct all subsequent HTTP requests to %1 proxy server</CENTER>
-26872	LRW_MSG_REPLAY_MAIN_ADD_HEADER	<CENTER>Add the following header to the next HTTP request : %1: %2</CENTER>
-26871	LRW_MSG_REPLAY_MAIN_CREATE_HTML_PARAM	<CENTER>ParamName =%1 Left Boundary = %2 Right Boundary = %3</CENTER>
-26870	LRW_MSG_REPLAY_MAIN_CREATE_HTML_PARAM_EX	<CENTER>ParamName =%1 Left Boundary = %2 Right Boundary = %3 Instance = %4</CENTER>
-26869	LRW_MSG_REPLAY_MAIN_ADD_AUTO_HEADER	<CENTER>Add the following header to all subsequent HTTP requests : %1: %2</CENTER>
-26868	LRW_MSG_REPLAY_MAIN_CLEANUP_AUTO_HEADERS	<CENTER>Stop adding customized headers to subsequent HTTP requests</CENTER>
-26867	LRW_MSG_REPLAY_MAIN_ENABLE_KEEP_ALIVE	<CENTER>Enable the Vuser to re-use HTTP connections</CENTER>
-26866	LRW_MSG_REPLAY_MAIN_DISABLE_KEEP_ALIVE	<CENTER>Disable the Vuser from re-using HTTP connections</CENTER>
-26865	LRW_MSG_REPLAY_MAIN_CLEANUP_COOKIES	<CENTER>Remove all the cookies that are currently stored by the Vuser</CENTER>
-26864	LRW_MSG_REPLAY_MAIN_REMOVE_COOKIE	<CENTER>Remove the following cookie: %1</CENTER>
-26863	LRW_MSG_REPLAY_MAIN_ADD_COOKIE	<CENTER>Add the following cookie: %1</CENTER>
-26862	LRW_MSG_REPLAY_MAIN_CLEANUP_CACHE	<CENTER>Clear the contents of the cache simulator</CENTER>
-26861	LRW_MSG_REPLAY_MAIN_SET_SECURE_PROXY	<CENTER>Direct all subsequent HTTP requests to %1 secure proxy server</CENTER>
-26860	LRW_MSG_REPLAY_MAIN_SET_EMPTY_PROXY	<CENTER>Submit all subsequent HTTP requests directly to the server</CENTER>
-26859	LRW_MSG_REPLAY_MAIN_SET_USER_NO_PORT	<CENTER>User name = %1 Password = %2 Host = %3</CENTER>
-26858	LRW_MSG_REPLAY_MAIN_PROXY_BYPASS_LOCAL	<CENTER>Bypass proxy for local URLs</CENTER>
-26857	LRW_MSG_REPLAY_MAIN_PROXY_BYPASS_LOCAL_AND_MORE	<CENTER>Bypass proxy for local URLs and these URLs : %1</CENTER>
-26856	LRW_MSG_REPLAY_MAIN_PROXY_BYPASS_EMPTY	<CENTER>Reset all bypass settings</CENTER>
-26855	LRW_MSG_REPLAY_MAIN_SET_SOCKETS_OPTION	<CENTER>Set socket option %1 with value %2</CENTER>
-26854	LRW_MSG_REPLAY_MAIN_SET_MAX_RETRIES	<CENTER>Set maximum number of retries to %1</CENTER>
-26853	LRW_MSG_REPLAY_MAIN_REQ_SAVE_PARAM	<CENTER>ParamName =%1 Left Boundary = %2 Right Boundary = %3 Instance = %4</CENTER>
-26852	LRW_MSG_REPLAY_MAIN_SET_CERTIFICATE_EX	<CENTER>Use certificate from a file</CENTER>
-26851	LRW_MSG_REPLAY_MAIN_SET_CONN_LIMIT	<CENTER>Set limit of connections to %1</CENTER>
-26850	LRW_MSG_REPLAY_MAIN_REG_FIND	<CENTER>%1</CENTER>
-26849	LRW_MSG_REPLAY_MAIN_CONCURRENT_START	<CENTER>Concurrent Group started</CENTER>
-26848	LRW_MSG_REPLAY_MAIN_CONCURRENT_END	<CENTER>Concurrent Group ended</CENTER>
-26847	LRW_TXT_REPLAY_MAIN_REMOVE_AUTO_HEADER	<CENTER>Remove/revert %1 header, implicit generation: %2</CENTER>

Error code	Handle	Message\Additional information
-26846	LRW_MSG_REPLAY_MAIN_SJIS_TO_EUC_PARAM	<CENTER>Saved EUC value in parameter "%1</CENTER>"
-26845	LRW_TXT_REPLAY_MAIN_LIST_STR	%1: %2
-26844	LRW_TXT_REPLAY_MAIN_LIST_NUM	%1: % 2 Id
-26843	LRW_MSG_REPLAY_MAIN_SET_OPTION	<CENTER>Set option %1 with value %2</CENTER>
-26842	LRW_TXT_REPLAY_MAIN_LIST_STR_QUOTED	%1: "%2"
-26841	LRW_TXT_REPLAY_MAIN_SWITCHED_NET	<CENTER>Switched Net Layer to %1</CENTER>
-26840	LRW_TXT_REPLAY_MAIN_FILTER_ADDED	<CENTER>URL filter added</CENTER>
-26839	LRW_TXT_REPLAY_MAIN_AUTO_FILTER_ADDED	<CENTER>Auto URL filter added (ID="%1")</CENTER>
-26838	LRW_TXT_REPLAY_MAIN_AUTO_FILTER_REMOVED	<CENTER>Auto URL filter removed (ID="%1")</CENTER>
-26837	LRW_TXT_REPLAY_MAIN_CONVERT_PARAM	<CENTER>ParamName = %1</CENTER>
-26836	LRW_MSG_REPLAY_MAIN_STEP_TIMEOUT	<CENTER>Maximum time for the step timeout %1 seconds</CENTER>
-26835	LRW_MSG_REPLAY_MAIN_ARG_2_MUST_BE_LAST	Argument number 2 must be "LAST"
-26834	LRW_TXT_REPLAY_MAIN_REG_COOKIE	<CENTER>Cookie=%1</CENTER> <CENTER>Text=%2</CENTER>
-26833	LRW_MSG_REPLAY_MAIN_SEV_LVL_PX_NOTIFY	Notify
-26832	LRW_MSG_REPLAY_MAIN_SET_PROXY_PAC	<CENTER>Set automatic configuration script URL to %1</CENTER>
-26831	LRW_MSG_REPLAY_MAIN_STREAM_INFO_STATE	<CENTER>Stream id=%1, current state: %2</CENTER>
-26830	LRW_MSG_REPLAY_MAIN_STREAM_INFO_BYTES_SEND	<CENTER>Stream id=%1, sent bytes: %2</CENTER>
-26829	LRW_MSG_REPLAY_MAIN_STREAM_INFO_BYTES_RECEIVED	<CENTER>Stream id=%1, received bytes: %2</CENTER>
-26828	LRW_MSG_REPLAY_MAIN_STREAM_INFO_ERROR	<CENTER>Error: Stream id=%1. Information not available</CENTER>
-26827	LRW_MSG_REPLAY_MAIN_STREAM_INFO_CURRENT_TIME	<CENTER>Stream id=%1, current play time: %2</CENTER>
-26826	LRW_MSG_REPLAY_MAIN_STREAM_INFO_CURRENT_BUFFERING_TIME	<CENTER>Stream id=%1, current buffering time: %2</CENTER>
-26825	LRW_MSG_REPLAY_MAIN_STREAM_INFO_TOTAL_BUFFERING_TIME	<CENTER>Stream id=%1, total buffering time: %2</CENTER>
-26824	LRW_MSG_REPLAY_MAIN_STREAM_INFO_BUFFERED_TIME	<CENTER>Stream id=%1, buffered time: %2</CENTER>
-26823	LRW_MSG_REPLAY_MAIN_STREAM_INFO_DURATION	<CENTER>Stream id=%1, duration: %2</CENTER>
-26822	LRW_MSG_REPLAY_MAIN_STREAM_INFO_URL	<CENTER>Stream id=%1, URL: %2</CENTER>
-26821	LRW_MSG_REPLAY_MAIN_STREAM_INFO_PROTOCOL	<CENTER>Stream id=%1, Protocol: %2</CENTER>
-26820	LRW_MSG_REPLAY_MAIN_STREAM_INFO_SERVER_IP	<CENTER>Stream id=%1, Server IP: %2</CENTER>
-26819	LRW_MSG_REPLAY_MAIN_STREAM_INFO_BANDWIDTH	<CENTER>Stream id=%1, Bandwidth: %2</CENTER>
-26818	LRW_MSG_REPLAY_MAIN_STREAM_INFO_BUFFERINGTIMEOUT	<CENTER>Stream id=%1, Buffering time out: %2</CENTER>
-26817	LRW_MSG_REPLAY_MAIN_STREAM_INFO_SPEED	<CENTER>Stream id=%1, Play speed: %2</CENTER>
LrwSAPLogicMgr_res.h		
-34999	LRW_MSG_SAP_LOGIC_MGR_ELEMENT_FOUND_IN_SUB_FRAME	Warning: %1 element found in a SUB-FRAME ("%2") of the frame described/implied by the Vuser script function
-34998	LRW_MSG_SAP_LOGIC_MGR_BUTTON_NOT_FOUND	SAP Button not found
-34997	LRW_MSG_SAP_LOGIC_MGR_FRAME_NOT_FOUND	SAP Frame not found
-34996	LRW_MSG_SAP_LOGIC_MGR_SAP_BUTTON_DISABLED	SAP Button is disabled
-34995	LRW_MSG_SAP_LOGIC_MGR_SAP_MENU_ITEM_NOT_FOUND	SAP Menu Item "%1" not found
-34994	LRW_MSG_SAP_LOGIC_MGR_EDIT_NOT_FOUND	SAP Edit not found
-34993	LRW_MSG_SAP_LOGIC_MGR_SAP_EDIT_DISABLED	SAP Edit is disabled. Performing the action anyway
-34992	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_NOT_FOUND	SAP iView not found
-34991	LRW_MSG_SAP_LOGIC_MGR_DROPDOWNMENU_NOT_FOUND	SAP DropDownMenu not found
-34990	LRW_MSG_SAP_LOGIC_MGR_SAP_BUTTON_ELEMENT_DISABLED	SAP Button is disabled. Performing the action anyway
-34989	LRW_MSG_SAP_LOGIC_MGR_SAP_NODE_DISABLED	Menu item is disabled in menu path: %1
-34988	LRW_MSG_SAP_LOGIC_MGR_SAP_NODE_CLOSED	Menu is closed in menu path: %1
-34987	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_NOT_FOUND	SAP Portal not found
-34986	LRW_MSG_SAP_LOGIC_MGR_RADIO_GROUP_NOT_FOUND	SAP RadioGroup not found
-34985	LRW_MSG_SAP_LOGIC_MGR_RADIO_GROUP_ALREADY_SELECTED	Selecting a radio button which was already selected
-34984	LRW_MSG_SAP_LOGIC_MGR_RADIO_GROUP_ITEM_NOT_FOUND	Radio item not found (value="%1")
-34983	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_INVALID_NAVIGATION_LEVEL	Invalid navigation level %1 in SAP portal
-34982	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_TOP_NAVIGATION_BAR_FIRST_LEVEL_TAB_CONTAINER	Top navigation bar not found in first level tab container
-34981	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_TOP_NAVIGATION_TAB_CONTAINER	Top navigation tab container not found
-34980	LRW_MSG_SAP_LOGIC_MGR_INTERNAL_ERROR	Internal Error - %1
-34979	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_TAB_NOT_FOUND	Tab %1 not found in SAP portal

Error code	Handle	Message\Additional information
-34978	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_TAB_ALREADY_ACTIVE	Tab %1 already active
-34977	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_MAIN_SEARCH_BAR_NOT_FOUND	Main search bar not found in SAP portal
-34976	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_MAIN_SEARCH_EDIT_NOT_FOUND	Search edit not found
-34975	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_MAIN_SEARCH_BUTTON_NOT_FOUND	Search button not found
-34974	LRW_MSG_SAP_LOGIC_MGR_SAP_CHECKBOX_NOT_FOUND	SAP Check Box not found
-34973	LRW_MSG_SAP_LOGIC_MGR_SAP_CHECKBOX_DISABLED	SAP Check Box is disabled
-34972	LRW_MSG_SAP_LOGIC_MGR_SAP_CHECKBOX_CHECKED	SAP Check Box is already checked
-34971	LRW_MSG_SAP_LOGIC_MGR_SAP_CHECKBOX_UNCHECKED	SAP Check Box is already unchecked
-34970	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_MAIN_MIN_MAX_BUTTON_NOT_FOUND	iView main min max of button not found
-34969	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_IS_ALREADY_MINIMIZED	iView is already minimized
-34968	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_IS_ALREADY_MAXIMIZED	iView is already maximized
-34967	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_CONTAINING_TABLE_NOT_FOUND	Containing table of iView not found
-34966	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_MENU_BUTTON_NOT_FOUND	iView menu button not found
-34965	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_MENU_FRAME_NOT_FOUND	iView menu frame not found
-34964	LRW_MSG_SAP_LOGIC_MGR_SAP_IVIEW_MENU_ITEM_NOT_FOUND	iView menu item %1 not found
-34963	LRW_MSG_SAP_LOGIC_MGR_TREE_VIEW_NOT_FOUND	SAP TreeView not found
-34962	LRW_MSG_SAP_LOGIC_MGR_TREE_VIEW_ITEM_NOT_FOUND	SAP TreeView item "%1" not found
-34961	LRW_MSG_SAP_LOGIC_MGR_SAP_PORTAL_DETAILED_NAVIGATION_NOT_FOUND	SAP Portal Detailed Navigation not found
-34960	LRW_MSG_SAP_LOGIC_MGR_SAP_FRAME_NOT_FOUND	SAP frame not found
-34959	LRW_MSG_SAP_LOGIC_MGR_MENU_NOT_FOUND	SAP frame not found
-34958	LRW_MSG_SAP_LOGIC_MGR_NAVIGATION_BAR_NOT_FOUND	SAP navigation bar not found
-34957	LRW_MSG_SAP_LOGIC_MGR_OK_CODE_NOT_FOUND	SAP ok code not found
-34956	LRW_MSG_SAP_LOGIC_MGR_OK_CODE_INVALID_PARENT	Invalid parent for SAP Ok Code
-34955	LRW_MSG_SAP_LOGIC_MGR_OK_CODE_INVALID_GRAND_PARENT	Invalid grand parent for SAP Ok Code
-34954	LRW_MSG_SAP_LOGIC_MGR_OK_CODE_TOGGLE_NOT_FOUND	SAP toggle Ok code field not found
-34953	LRW_MSG_SAP_LOGIC_MGR_STATUS_BAR_NOT_FOUND	SAP status bar not found
-34952	LRW_MSG_SAP_LOGIC_MGR_TAB_STRIP_NOT_FOUND	SAP tab strip not found
-34951	LRW_MSG_SAP_LOGIC_MGR_TAB_STRIP_NO_SUCH_TAB_INDEX	SAP tab index is too large. There are only %1 tabs in the tab strip
-34950	LRW_MSG_SAP_LOGIC_MGR_TAB_STRIP_TABS_NOT_FOUND	No tabs found in this tab strip
-34949	LRW_MSG_SAP_LOGIC_MGR_TAB_STRIP_TAB_NOT_FOUND	Tab not found in tab strip
-34948	LRW_MSG_SAP_LOGIC_MGR_TAB_STRIP_CLICKABLE_ELEMENT_NOT_FOUND_ON_TAB	Clickable element not found on tab
-34947	LRW_MSG_SAP_LOGIC_MGR_SAP_LIST_ITEM_NOT_FOUND	SAP list item %1 not found
-34946	LRW_MSG_SAP_LOGIC_MGR_SAP_LIST_NOT_FOUND	SAP list not found
-34945	LRW_MSG_SAP_LOGIC_MGR_SAP_LIST_BUTTON_NOT_FOUND	SAP list button not found
-34944	LRW_MSG_SAP_LOGIC_MGR_SAP_LIST_ACTION_NOT_SUPPORTED	%1 not applicable to non-multiple SAP list
-34943	LRW_MSG_SAP_LOGIC_MGR_TABLE_NOT_FOUND	SAP Table not found
-34942	LRW_MSG_SAP_LOGIC_MGR_TABLE_CELL_NOT_FOUND	Cell was not found inside the sap table
-34941	LRW_MSG_SAP_LOGIC_MGR_SAP_EDIT_FIELD_OPEN_POSSIBLE_ENTRIES_BUTTON_NOT_FOUND	Button not found to open possible entries
-34940	LRW_MSG_SAP_LOGIC_MGR_EXECUTE_WITHOUT_TIMER_WAITING	Executing setTimeout/setInterval with TimerID=%_1_Id without waiting for SAP step
-34939	LRW_MSG_SAP_LOGIC_MGR_TAB_STRIP_ARROW_NOT_FOUND	Arrow not found in tab strip
LrwSAPObjMgr_res.h		
-34899	LRW_MSG_SAP_OBJ_MGR_SAP_BUTTON_DISABLED	SAP Button is disabled
-34898	LRW_MSG_SAP_OBJ_MGR_SAP_NODE_DISABLED	Menu item is disabled in menu path: %1
-34897	LRW_MSG_SAP_OBJ_MGR_SAP_NODE_NOT_FOUND	Menu item not found in menu path: %1
-34896	LRW_MSG_SAP_OBJ_MGR_SAP_NODE_CLOSED	Menu is closed in menu path: %1
-34895	LRW_MSG_SAP_OBJ_MGR_SAP_IVIEW_MAIN_MIN_MAX_BUTTON_NOT_FOUND	iView main min max of button not found
-34894	LRW_MSG_SAP_OBJ_MGR_SAP_IVIEW_IS_ALREADY_MINIMIZED	iView is already minimized

Error code	Handle	Message\Additional information
-34893	LRW_MSG_SAP_OBJ_MGR_SAP_IVIEW_IS_ALREADY_MAXIMIZED	iView is already maximized
LrwSAPScriptApi_res.h		
-34799	LRW_MSG_SAP_SCRIPT_API_ONLY_ONE_OF_4_ARG_MUST_BE_SPECIFIED	Only one argument out of "%1"/"%2"/"%3"/"%4" must be specified
LrwScriptApi_res.h		
-26399	LRW_MSG_SCRIPT_API_INTERNAL_ERROR	Internal Error - %1
-26398	LRW_MSG_SCRIPT_API_ARG_SPECIFIED_ALREADY	The "%1" argument (number % 2 Id) has already been specified in argument number % 3 Id
-26397	LRW_MSG_SCRIPT_API_ARG_MISSING_EMPTY	The "%1" argument is missing or empty
-26396	LRW_MSG_SCRIPT_API_ARG_UNRECOG	The "%1" argument (number % 2 Id) is unrecognized or misplaced
-26395	LRW_MSG_SCRIPT_API_2_ARGS_EXCL	The arguments "%1"/"%2" are mutually exclusive
-26394	LRW_MSG_SCRIPT_API_3_ARGS_EXCL	The arguments "%1"/"%2"/"%3" are mutually exclusive
-26393	LRW_MSG_SCRIPT_API_MAIN_NOT_ENOUGH_MEM	Not enough memory (% 1 Id bytes) for (%2)
-26392	LRW_MSG_SCRIPT_API_FUNC_TERM_DONE_SUC	%1 was successful
-26391	LRW_MSG_SCRIPT_API_FUNC_TERM_DONE_HSL	%1 highest severity level was "%2"
-26390	LRW_MSG_SCRIPT_API_FUNC_TERM_REG_SUC	Registering %1 was successful
-26389	LRW_MSG_SCRIPT_API_FUNC_TERM_REG_HSL	Registering %1 highest severity level was "%2"
-26388	LRW_MSG_SCRIPT_API_FUNC_TERM_CNT_HSL	%1 highest severity level was "%2", % 3 Id body bytes, % 4 Id header bytes
-26387	LRW_MSG_SCRIPT_API_FUNC_TERM_CNT_HSL_CHUNK	%1 highest severity level was "%2", % 3 Id body bytes, % 4 Id header bytes, % 5 Id chunking overhead bytes
-26386	LRW_MSG_SCRIPT_API_FUNC_TERM_CNT_SUC	%1 was successful, % 2 Id body bytes, % 3 Id header bytes
-26385	LRW_MSG_SCRIPT_API_FUNC_TERM_CNT_SUC_CHUNK	%1 was successful, % 2 Id body bytes, % 3 Id header bytes, % 4 Id chunking overhead bytes
-26384	LRW_MSG_SCRIPT_API_ARG_ISMAP_IS 1	The "ClickCoordinates" ACTION argument must be specified when DESCRIPTION specifies "IsMap=1"
-26383	LRW_MSG_SCRIPT_API_ARG_ISMAP_IS 0	The argument "ClickCoordinates" must not be specified when the argument "IsMap=0"
-26382	LRW_MSG_SCRIPT_API_ARG_ONE_OF_2_MUST_BE_SPECIFIED	One of the arguments "%1"/"%2" must be specified
-26381	LRW_MSG_SCRIPT_API_ARG_ONE_OF_3_MUST_BE_SPECIFIED	One of the arguments "%1"/"%2"/"%3" must be specified
-26380	LRW_MSG_SCRIPT_API_ARG_NOT_BOOLEAN	The "%1" argument (number % 2 Id) does not specify a valid boolean literal (e.g., "true", "false", "on", "off", "yes", "no", "1", "0")
-26379	LRW_MSG_SCRIPT_API_PENDING_PE_NOT_FOUND	Pending %1/%2/%3/%4 request(s) are deleted and will be handled as "not found"
-26378	LRW_MSG_SCRIPT_API_UNREF_FRAME_ID	No buffer having "RelFrameID=%1" has been received. The %2/%3 request(s) specifying this RelFrameID will be handled as "not found"
-26377	LRW_MSG_SCRIPT_API_PARAM_NO_MATCH	No match found for the requested parameter "%1". Either the specified boundaries were not found in the response or the matched text is longer than current max html parameter size of % 2 Id bytes. The total length of the response is % 3 Id bytes. You can use "%4" to increase the max parameter size.
-26376	LRW_MSG_SCRIPT_API_PARAM_MULTIPLE	Requested parameter "%1" found in % 2 Id different pages/frames. Use "%3" with more restrictive LB/RB/RelFrameId
-26375	LRW_MSG_SCRIPT_API_PARAM_SAVED_ID	Parameter "%1" saved from "RelFrameId=%2" (URL="%3")
-26374	LRW_MSG_SCRIPT_API_NOT_FOUND_BYTE_COUNT	The above "not found" error(s) may be explained by header and body byte counts being % 1 Id and % 2 Id, respectively.
-26373	LRW_MSG_SCRIPT_API_PARAM_SAVED_RESOURCE	Parameter "%1" saved from a resource (URL="%2")
-26372	LRW_MSG_SCRIPT_API_FOUND_TEXT_AED	ContentCheck Rule "%1" in Application "%2" triggered. Text "%3" matched (count=% 4 Id)
-26371	LRW_MSG_SCRIPT_API_FOUND_PFX_SFX_AED	"ContentCheck Rule "%1" in Application "%2" triggered. Text Pfx="%3" and Sfx="%4" matched, match (#% 5 Id) is "%6""
-26370	LRW_MSG_SCRIPT_API_NOT_FOUND_TEXT_AED	ContentCheck Rule "%1" in Application "%2" triggered. Text "%3" not matched
-26369	LRW_MSG_SCRIPT_API_NOT_FOUND_PFX_SFX_AED	ContentCheck Rule "%1" in Application "%2" triggered. Text Pfx="%3" and Sfx="%4" not matched
-26370	LRW_MSG_SCRIPT_API_FOUND_TEXT_VERIF	"Text=%1" found for %2%3 (count=% 4 Id)
-26367	LRW_MSG_SCRIPT_API_FOUND_PFX_SFX_VERIF	""TextPfx=%1" and "TextSfx=%2" found for %3%4, match (#% 5 Id) is "%6""
-26366	LRW_MSG_SCRIPT_API_NOT_FOUND_TEXT_VERIF	"Text=%1" not found for %2%3
-26365	LRW_MSG_SCRIPT_API_NOT_FOUND_PFX_SFX_VERIF	"TextPfx=%1" and "TextSfx=%2" not found for %3%4
-26364	LRW_MSG_SCRIPT_API_SUC_TEXT_VERIF	Registered %1%2 successful for "Text=%3" (count=% 4 Id)
-26363	LRW_MSG_SCRIPT_API_SUC_PFX_SFX_VERIF	Registered %1%2 successful for "TextPfx=%3" and "TextSfx=%4" (count=% 5 Id)
-26362	LRW_MSG_SCRIPT_API_SUC_REQ_TEXT_VERIF	Registered %1%2 successful for "Text=%3"
-26361	LRW_MSG_SCRIPT_API_SUC_REQ_PFX_SFX_VERIF	Registered %1%2 successful for "TextPfx=%3" and "TextSfx=%4"
-26360	LRW_MSG_SCRIPT_API_PARAM_STR_FAIL	Parameter SaveString failed (rc=% 1 Id) for "%2"
-26359	LRW_MSG_SCRIPT_API_DISALLOWED_CONCURRENT	Function not allowed within a concurrent group
-26358	LRW_MSG_SCRIPT_API_TASK_LIST	Pending web requests detected and deleted
-26357	LRW_MSG_SCRIPT_API_BOTH_ARGS	Either both or none of the "%1" and "%2" arguments should be specified
-26356	LRW_MSG_SCRIPT_API_INVALID_SNAPSHOT	Invalid Snapshot (argument number % 1 Id). The "t<number>.inf" is incorrectly formatted
-26355	LRW_MSG_SCRIPT_API_FUNC_START	%1 started
-26354	LRW_MSG_SCRIPT_API_UNSUPPORTED_VALUE	Unsupported value for the "%1" argument (number % 2 Id)
-26353	LRW_MSG_SCRIPT_API_NOT_GUI_MODE	%1 cannot be used in a Virtual User of this type
-26352	LRW_MSG_SCRIPT_API_CS_CONTEXT	The context for HTML-based functions is reset due to a GUI-based function being called (%1)

Error code	Handle	Message\Additional information
-26351	LRW_MSG_SCRIPT_API_INVALID_VALUE	Invalid value for the "%1" argument (number % 2 _ld)
-26350	LRW_MSG_SCRIPT_API_ARG_NULL_EMPTY	The "%1" argument (number % 2 _ld) is NULL or empty
-26349	LRW_MSG_SCRIPT_API_HINT_SECOND_ITER_ERR	Note: A possible cause for an error such as an element or frame not being found is that the\current action section cannot run from the point in the application at which the previous iteration/action\ended. A navigation statement to that point in the application may be missing at the end of the last\action section that ran before the section in which the error occurred
-26348	LRW_MSG_SCRIPT_API_ARG_MISSING	Required argument ("%1") omitted or misplaced
-26347	LRW_MSG_SCRIPT_API_1_ARG_EXCL	When the "%1" argument is specified, it must be the only argument in the ACTION section
-26346	LRW_MSG_SCRIPT_API_ARG_ONE_OF_4_MUST_BE_SPECIFIED	One of the arguments "%1"/"%2"/"%3"/"%4" must be specified
-26345	LRW_MSG_SCRIPT_API_4_ARGS_EXCL	The arguments "%1"/"%2"/"%3"/"%4" are mutually exclusive
-26344	LRW_MSG_SCRIPT_API_ARGS_NOT_ALLOWED_IF_NOT_DOWNLOAD	The "Referer"/"Method"/"Body"/"BodyBinary"/"EncType"/"Target"/"TargetOrdinal" arguments are allowed only when the "Download" argument is specified
-26343	LRW_MSG_SCRIPT_API_ARG_IS_EMPTY	The "%1" argument, when specified, must not be empty
-26342	LRW_MSG_SCRIPT_API_ARG_REGEXP_NOT_SUPPORTED	Regular expression (/RE) not supported for the "%1" argument (number % 2 _ld)
-26341	LRW_MSG_SCRIPT_API_ARG_CLICK_COORDINATES	The "ClickCoordinates" argument (number % 1 _ld) must be in the format "x,y", where x and y are non-negative integers, up to % 2 _ld digits each, without any spaces within the value
-26340	LRW_MSG_SCRIPT_API_1_2_EXCL_3_4	When "%1=%2" is specified, "%3"/"%4" must not be specified
-26339	LRW_MSG_SCRIPT_API_ARGS_NOT_ALLOWED_IF_NOT_FIRE_EVENT	The "EventX"/"EventY"/"EventOffsetX"/"EventOffsetY"/"EventKeyCode"/"EventCtrlKey" arguments are allowed only when the "FireEvent" argument is specified
-26338	LRW_MSG_SCRIPT_API_ARGS_EVENT_KEY_CODE_LEN_NOT_ONE	"EventKeyCode" must specify at most one byte
-26337	LRW_MSG_SCRIPT_API_PREDEF_FRAME_NAME	Predefined frame names, such as top, blank, self and parent, are not allowed for "%1"
-26336	LRW_MSG_SCRIPT_API_BODY_FOR_GET	Non-empty "Body=" or "BodyBinary=" specified (and will be used) when "Method=GET" is specified or defaulted
-26335	LRW_MSG_SCRIPT_API_ARG_DISALLOWED	The "%1" argument (number % 2 _ld) is not allowed for this function
-26334	LRW_MSG_SCRIPT_API_ARGS_NOT_ALLOWED_IF_NOT_EVAL_JAVA_SCRIPT	The "FrameName"/"FrameOrdinal" arguments are allowed only when the "EvalJavaScript" argument is specified or on verifications. For "Download=", use the "Target"/"TargetOrdinal" arguments instead
-26333	LRW_MSG_SCRIPT_API_ARG_ONE_OF_5_MUST_BE_SPECIFIED	One of the arguments "%1"/"%2"/"%3"/"%4"/"%5" must be specified
-26332	LRW_MSG_SCRIPT_API_5_ARGS_EXCL	The arguments "%1"/"%2"/"%3"/"%4"/"%5" are mutually exclusive
-26331	LRW_MSG_SCRIPT_API_ARG1_VALID_ONLY_IF_ARG2_EXIST	The "%1" argument can be specified with the "%2" argument only
-26330	LRW_MSG_SCRIPT_API_ARG_OPTIONAL_EMPTY	The "%1" argument, if specified, must not be empty
-26329	LRW_MSG_SCRIPT_API_ARG_SPECIFIED_ALREADY_NO_ARGNUM	The "%1" argument (number % 2 _ld) has already been specified
-26328	LRW_MSG_SCRIPT_API_1_2_EXCL_3	When "%1=%2" is specified, "%3" must not be specified
-26327	LRW_MSG_SCRIPT_API_1_2_EXCL_3_4_5	When "%1=%2" is specified, "%3"/"%4"/"%5" must not be specified
-26326	LRW_MSG_SCRIPT_API_ARG_ONE_OF_6_MUST_BE_SPECIFIED	One of the arguments "%1"/"%2"/"%3"/"%4"/"%5"/"%6" must be specified
-26325	LRW_MSG_SCRIPT_API_6_ARGS_EXCL	The arguments "%1"/"%2"/"%3"/"%4"/"%5"/"%6" are mutually exclusive
-26324	LRW_MSG_SCRIPT_API_ARG_REQUIRED_NOT_EMPTY_ASYNC	A non-empty value is required for the "%1" argument in Asynchronous Mode
-26323	LRW_MSG_SCRIPT_API_ARG_IGNORED_NOT_ASYNC	The "%1" argument (number % 2 _ld) is ignored when not in Asynchronous Mode
-26322	LRW_MSG_SCRIPT_API_ARG_AT_LEAST_ONE_OF_3_EVEN_EMPTY	At least one of the arguments "%1"/"%2"/"%3" must be specified (can be empty)
-26321	LRW_MSG_SCRIPT_API_PARAM_ERROR	Unable to retrieve value from parameter "%1", make sure parameter exists
-26320	LRW_MSG_SCRIPT_API_ORD_MUST_BE_1	Ordinal must be 1 when the left and/or right boundaries are empty
-26319	LRW_MSG_SCRIPT_API_ORD_MUST_BE_1_WHEN_ID_SPECIFIED	Ordinal must be 1 when id attribute is specified
-26318	LRW_MSG_SCRIPT_API_1_IS_2_IGNORE_3	When "%1=%2", "%3" is ignored
-26317	LRW_MSG_SCRIPT_API_1_IS_NOT_2_IGNORE_3	When "%1" is not "%2", "%3" is ignored
-26316	LRW_MSG_SCRIPT_API_1_IS_2_THEN_3_MUST_BE_4	When "%1=%2" is specified, "%3" argument must be "%4"
-26315	LRW_MSG_SCRIPT_API_1_IS_2_THEN_3_MUST_BE_OMITTED_OR_4	When "%1=%2" is specified, "%3" argument must be omitted or "%4"
-26314	LRW_MSG_SCRIPT_API_INVALID_CONVERS_ID	The "%1" argument (number % 2 _ld) must not start with an underscore and must not have leading/trailing white spaces (nor any byte < 0x20)
-26313	LRW_MSG_SCRIPT_API_VAL_EXCEEDS_RTS_NUM	The value (% 1 _ld milliseconds) of the "%2" argument (number % 3 _ld) exceeds the "Step download timeout" runtime setting (% 4 _ld seconds) and "CrossStep=No" is specified
-26312	LRW_MSG_SCRIPT_API_ARG_OPTION_INVALID	"%1" unrecognized/unsupported for the "%2" argument (number % 3 _ld)
-26311	LRW_MSG_SCRIPT_API_ARG_OPTION_INVALID_EXPLAINED	Problem with %1 for the "%2" argument, (number % 3 _ld). Please make sure %4 in argument %5 is ended with " \\n"
-26310	LRW_MSG_SCRIPT_API_ARG_OPTION_MORE_THAN_ONCE	"%1" specified more than once in the "%2" argument (number % 3 _ld)
-26309	LRW_MSG_SCRIPT_API_WEBSOCKET_CLOSE_CODE_ERROR	Close code should be an integer between 1000 and 1011
-26308	LRW_MSG_SCRIPT_API_DUPLICATED_STREAM_ID	Another streaming with the same ID "%1" has already been registered. Please set a new ID not registered
-26307	LRW_MSG_SCRIPT_API_WEB_STREAM_ID_FAILURE	Failed to find stream ID "%1"
-26306	LRW_MSG_SCRIPT_API_WEB_STREAM_CLOSED	Stream id "%1" has previously been closed or failed.
-26305	LRW_MSG_SCRIPT_API_WEB_STREAM_SEEK_LIVE	Stream id=%1. "Seek" cannot work for live video.
LrwScriptApi_txt.h		
-35299	LRW_TXT_SCRIPT_API_CONVERT_PARAM	<CENTER>ParamName = %1</CENTER>

Error code	Handle	Message\Additional information
-35298	LRW_TXT_SCRIPT_API_HINT_SECOND_ITER_ERR_PS	. For example, if the vuser_init section\l\Inconsists of the PeopleSoft log-in only, you can try adding:\l\Inweb_text_link("Back Home", DESCRIPTION, "Text=Home", "FrameName=UniversalHeader", LAST);
-35297	LRW_TXT_SCRIPT_API_ADD_COOKIE_EX	Added the following cookie(s): %1
-35296	LRW_TXT_SCRIPT_API_REG_DIALOG_SUCCESS	%1 dialog registered.
-35295	LRW_TXT_SCRIPT_API_REG_DIALOG_FAILURE	Failed to register %1 dialog.
-35294	LRW_TXT_SCRIPT_API_REG_CROSS_STEP_SUCCESS	URL="%1"%2 is registered for considering as cross-step download
-35293	LRW_TXT_SCRIPT_API_REG_CROSS_STEP_FAILURE	Failed to register URL="%1"%2 for considering as cross-step download
-35292	LRW_TXT_SCRIPT_API_CONVERT_FROM_FORMATTED	<CENTER>TargetParam = %1</CENTER>
-35291	LRW_TXT_SCRIPT_API_CONVERT_TO_FORMATTED	<CENTER>TargetParam = %1</CENTER>
-35290	LRW_TXT_SCRIPT_API_REG_SAVE_PARAM_EX	<CENTER>TargetParam = %1 Left Boundary = %2 Right Boundary = %3 Instance = %4</CENTER>
-35289	LRW_TXT_SCRIPT_API_REG_SAVE_PARAM_XPATH	<CENTER>ParamName = %1 QueryString = %2</CENTER>
-35288	LRW_TXT_SCRIPT_API_REG_SAVE_PARAM_REG_EXP	<CENTER>ParamName = %1 RegExp = %2 Instance = %3</CENTER>
-35287	LRW_TXT_SCRIPT_API_JS_RUN	<CENTER>Code = %1 Result Param = %2</CENTER>
-35286	LRW_TXT_SCRIPT_API_REG_CONVERS_INFO_SUCCESS	Conversation Information with ID=%1 registered (Pattern=%2)
-35285	LRW_TXT_SCRIPT_API_REG_CONVERS_INFO_FAILURE	Failed to register Conversation Information with ID=%1 (Pattern=%2)
-35284	LRW_TXT_SCRIPT_API_SYNC_ON_PARAM	<CENTER>ParamName = %1</CENTER>
-35283	LRW_TXT_SCRIPT_API_CONVERS_ABORT_SUCCESS	Successfully stopped Conversation with ID=%1
-35282	LRW_TXT_SCRIPT_API_CONVERS_ABORT_FAILURE	Failed to stop Conversation with ID=%1
-35281	LRW_TXT_SCRIPT_API_WEBSOCKET_CONNECT_SUCCESS	WebSocket successfully connected with ID=%1, URI=%2
-35280	LRW_TXT_SCRIPT_API_WEBSOCKET_CONNECT_FAILURE	WebSocket failed to connect with ID=%1, URI=%2
-35279	LRW_TXT_SCRIPT_API_WEBSOCKET_SEND_SUCCESS	WebSocket of ID=%1 successfully send Buffer=%2
-35278	LRW_TXT_SCRIPT_API_WEBSOCKET_SEND_FAILURE	WebSocket of ID=%1 failed to send Buffer=%2
-35277	LRW_TXT_SCRIPT_API_WEBSOCKET_CLOSE_SUCCESS	WebSocket of ID=%1 successfully closed
-35276	LRW_TXT_SCRIPT_API_WEBSOCKET_CLOSE_FAILURE	WebSocket of ID=%1 failed to close
-35275	LRW_TXT_SCRIPT_API_REG_SAVE_PARAM_JSON	<CENTER>ParamName = %1 QueryString = %2</CENTER>
-35274	LRW_TXT_SCRIPT_API_WEB_STREAM_OPEN_SUCCESS	Stream ID=%1, URL="%2" opened
-35273	LRW_TXT_SCRIPT_API_WEB_STREAM_OPEN_FAILURE	Failed to open stream ID=%1, URL="%2"
-35272	LRW_TXT_SCRIPT_API_WEB_STREAM_WAIT_SUCCESS	Wait time=% 1 Id for stream ID=%2
-35271	LRW_TXT_SCRIPT_API_WEB_STREAM_WAIT_FAILURE	Failed to wait time=% 1 Id for stream ID=%2
-35270	LRW_TXT_SCRIPT_API_WEB_STREAM_CLOSE_SUCCESS	Stream ID=%1 closed
-35269	LRW_TXT_SCRIPT_API_WEB_STREAM_CLOSE_FAILURE	Failed to close stream ID=%1
-35268	LRW_TXT_SCRIPT_API_WEB_STREAM_PLAY_SUCCESS	Stream ID=%1 started palying
-35267	LRW_TXT_SCRIPT_API_WEB_STREAM_PLAY_FAILURE	Failed to paly stream ID=%1
-35266	LRW_TXT_SCRIPT_API_WEB_STREAM_PAUSE_SUCCESS	Stream ID=%1 paused
-35265	LRW_TXT_SCRIPT_API_WEB_STREAM_PAUSE_FAILURE	Failed to pause stream ID=%1
-35264	LRW_TXT_SCRIPT_API_WEB_STREAM_SEEK_SUCCESS	Stream ID=%1 sought to %2
-35263	LRW_TXT_SCRIPT_API_WEB_STREAM_SEEK_FAILURE	Failed to seek %2, stream ID=%1
-35262	LRW_TXT_SCRIPT_API_WEB_STREAM_STOP_SUCCESS	Stream ID=%1 stoped
-35261	LRW_TXT_SCRIPT_API_WEB_STREAM_STOP_FAILURE	Failed to stop stream ID=%1
-35260	LRW_TXT_SCRIPT_API_REG_SAVE_PARAM_ATTRIB	<CENTER>ParamName = %1 TagName = %2 Extract = %3</CENTER>
LrwSrvNet2_res.h		
-35199	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_251	HTTP Status-Code=% 1 Id (%2) for "%3"
-35198	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_252	HTTP Status-Code=% 1 Id (%2) for "%3"
-35197	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_255	HTTP Status-Code=% 1 Id (%2) for "%3"
-35196	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_449	HTTP Status-Code=% 1 Id (%2) for "%3"
-35195	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_451	HTTP Status-Code=% 1 Id (%2) for "%3"
-35194	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_552	HTTP Status-Code=% 1 Id (%2) for "%3"
-35193	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_553	HTTP Status-Code=% 1 Id (%2) for "%3"
-35192	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_554	HTTP Status-Code=% 1 Id (%2) for "%3"

Error code	Handle	Message\Additional information
-35191	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_561	HTTP Status-Code=% 1_Id (%2) for "%3"
-35190	LRW_MSG_SRV_NET_DOWNLOADING_TABLE_BACKGROUND	Downloading TABLE background="%1"
-35189	LRW_MSG_SRV_NET_DOWNLOADING_TD_BACKGROUND	Downloading TD background="%1"
-35188	LRW_MSG_SRV_NET_DOWNLOADING_TH_BACKGROUND	Downloading TH background="%1"
-35187	LRW_MSG_SRV_NET_REDIR_WITHOUT_BODY_SIZE	The server's response is a redirection specifying neither Content-Length nor chunked Transfer-Encoding. This causes closing of the connection and ignoring the body of URL="%1"
-35186	LRW_MSG_SRV_NET_DOWNLOADING_XML_IN_HTML	Downloading XML file "%1" (detected in HTML)
-35185	LRW_MSG_SRV_NET_HISTORY_WITHOUT_CACHE	A history operation (e.g., back/forward/go) is attempted, but the "Simulate browser cache" Runtime Setting is unchecked (under Browser / Browser Emulation). The operation cannot be completed. (This message may be issued more than once for a single operation)
-35184	LRW_MSG_SRV_NET_REPARSING	Reparsing the HTML of URL="%1" due to a charset change by a META tag
-35183	LRW_MSG_SRV_NET_RESPONSE_CODE_PAGE_CONV	Conversion from "%1" (code page % 2_Id, preferred charset=%3, Unicode converter name="%4") will be performed for response of URL="%5"
-35182	LRW_MSG_SRV_NET_PRT_RESP_DEFERRING_HANDLING	%4Deferring handling of % 1_Id-byte response body for "%2" (RelFrameId=%3, Internal ID=% 5_Id)
-35181	LRW_MSG_SRV_NET_TARGET_WINDOW_NOT_CHANGED	Target window remains unchanged
-35180	LRW_MSG_SRV_NET_EMPTY_SCRIPT_TEXT	Using an empty text for the script
-35179	LRW_MSG_SRV_NET_FRAME_BASE_URL_AS_PARENT	Not issuing download for %1, as it has the same URL as of a parent window ("%2")
-35178	LRW_MSG_SRV_NET_CROSS_STEP_ALLOWED	URL="%1" is considered as a cross-step download
-35177	LRW_MSG_SRV_NET_CROSS_STEP_SYNC	URL="%1" is now requested synchronously, so that it is no longer considered as a cross-step download
-35176	LRW_MSG_SRV_NET_ATTR_YES_OVERRIDDEN_STRING	Attribute "%1" has previously been specified for ID="%2" as "%3", but is now overridden with "%4"
-35175	LRW_MSG_SRV_NET_ATTR_NOT_OVERRIDDEN_STRING	Attribute "%1" has previously been specified for ID="%2" as "%3", and is NOT overridden with "%4"
-35174	LRW_MSG_SRV_NET_ATTR_YES_OVERRIDDEN_NUMBER	Attribute "%1" has previously been specified for ID="%2" as "% 3_Id", but is now overridden with "% 4_Id"
-35173	LRW_MSG_SRV_NET_ATTR_NOT_OVERRIDDEN_NUMBER	Attribute "%1" has previously been specified for ID="%2" as "% 3_Id", and is NOT overridden with "% 4_Id"
-35172	LRW_MSG_SRV_NET_CONVERS_INFO_ATTRS_SET	% 1_Id attribute(s) set within Conversation Information with ID="%2"
-35171	LRW_MSG_SRV_NET_USED_FOR_URL	%1 now applied to URL="%2" (RelFrameId=%3, Internal ID=% 4_Id)
-35170	LRW_MSG_SRV_NET_CONVERS_ID_DUP	Another Conversation Information with the same ID="%1" has already been registered in %2(% 3_Id). Specified Conversation Information not registered
-35169	LRW_MSG_SRV_NET_ISSUING_LONG_POLL	Issuing a "LONG-POLL" request for conversation with ID="%1", URL="%2"
-35168	LRW_MSG_SRV_NET_ISSUING_POLL	Issuing a "POLL" request for conversation with ID="%1" and "PollIntervalMs=% 2_Id". Scheduling due at t=% 3_Id, URL="%4"
-35167	LRW_MSG_SRV_NET_ASYNC_URL_NOT_SEARCHED	Requested search(es) are not performed when Async and/or Cross-Step are specified or implied for URL="%1"
-35166	LRW_MSG_SRV_NET_ABORTING_CONVERS_TASK	Aborting download of URL "%1" (RelFrameId=%2, Internal ID=% 3_Id) of conversation with ID="%4"
-35165	LRW_MSG_SRV_NET_CONVERS_ABORT_GENERIC	Deleting Conversation Information with ID="%1"
-35164	LRW_MSG_SRV_NET_WEBSOCKET_ID_ALREADY_EXIST	The WebSocket ID = "%1" already exists
-35163	LRW_MSG_SRV_NET_DOWNLOADING_PREFETCH_RESOURCE	Found prefetch resource "%1" in HTML "%2"
-35162	LRW_MSG_SRV_NET_DOWNLOADING_PRERENDER_RESOURCE	Found prerender resource "%1" in HTML "%2"
-35161	LRW_MSG_SRV_NET_ACCUMULATED_RESPONSE_OVERSIZE	%4The accumulated response %2 from "%3" was completely truncated %1_Id-byte based on the "Max Response Log Size" Runtime setting (Preferences/Advanced Options/Log)
-35160	LRW_MSG_SRV_NET_RESPONSE_OVERSIZE	%5The response %3 from "%4" was truncated from %1_Id-byte to %2_Id-byte based on the "Max Response Log Size" Runtime setting (Preferences/Advanced Options/Log)
-35159	LRW_MSG_SRV_NET_RESPONSE_OVERSIZE2	%3The response data from "%2" exceeds the maximum response size of (%1_Id-byte) as defined in the Runtime Settings (Preferences > Logging) and cannot be fully displayed...
-35158	LRW_MSG_SRV_NET_FULL_RESPONSE_FILE	To view the full response, see "%1".
-35157	LRW_MSG_SRV_NET_DOWNLOADING_STREAM_RESOURCE	Stream "%1"
-35156	LRW_MSG_SRV_NET_STREAM_RETRYING	Attempting retry for stream "%1" with URL="%2" (% 3_Id tries out of % 4_Id).
-35155	LRW_MSG_SRV_NET_STREAM_RETRY_END	Open stream "%1" failed after % 2_Id retries.
-35154	LRW_MSG_SRV_NET_STREAM_ERREORDIRFORMAT	Dump\path directory format("%1") is set incorrectly, so file ("%2") cannot be saved.
-35153	LRW_MSG_SRV_NET_STREAM_DIRTIPMES	Dump-file("%1") has been saved.
-35152	LRW_MSG_SRV_NET_BYPASS_HTTP_STATUS_CODE	HTTP Status Code %1 is bypassed. Assuming "200 OK"
-35151	LRW_MSG_SRV_NET_PRAR_NOT_SAVED SINCE EMPTY SERVER TIME	Parameter %1 is not saved since server time was not obtained.
LrwSrvNet_res.h		
-26699	LRW_MSG_SRV_NET_TRANSFER_ENCODING	Unsupported "Transfer-Encoding" ignored. Additional information: Comment out or remove any preceding web_add_header and/or web_add_auto_header calls in the script specifying Accept?Encoding.
-26698	LRW_MSG_SRV_NET_CHUNKED_SIZE_MISSING	Chunk size missing or invalid ("Transfer-Encoding: chunked") for "%1" Additional information: Look in the script for web_add_header("Accept?Encoding", "chunked") and/or web_add_auto_header("Accept?Encoding", "chunked"), and comment out or remove these lines.

Error code	Handle	Message\Additional information
-26697	LRW_MSG_SRV_NET_CHUNKED_CRLF_MISSING	Missing CR/LF after body/trailer ("Transfer-Encoding: chunked") for "%1" Additional information: Look in the script for web_add_header("Accept?Encoding", "chunked") and/or web_add_auto_header("Accept?Encoding", "chunked"), and comment out or remove these lines.
-26696	LRW_MSG_SRV_NET_CONTENT_LEN_IGNORED	Content-Length ignored for non-identity Transfer-Encoding for "%1" Additional information: This is a warning message. The script most likely uses web_add_header and/or web_add_auto_header with Accept?Encoding. The server responded by sending a message with a response header Transfer?Encoding: and response body, is invalid. • Comment out or remove any lines in the script with web_add_header and/or web_add_auto_header with "Accept?Encoding".
-26695	LRW_MSG_SRV_NET_REDIR_MAX_DEPTH	Redirection depth (% 1 Id) exceeds max (% 2 Id) for "%3"
-26694	LRW_MSG_SRV_NET_REDIRECTING FROM	Redirecting "%1" (redirection depth is % 2 Id)
-26693	LRW_MSG_SRV_NET_REDIRECTING TO	To location "%1"
-26692	LRW_MSG_SRV_NET_PRT_REQ HDRS	%4% 1 Id-byte request headers for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26691	LRW_MSG_SRV_NET_PRT_REQ BODY	%4% 1 Id-byte request body for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26690	LRW_MSG_SRV_NET_PRT_RESP HDRS	%4% 1 Id-byte response headers for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26689	LRW_MSG_SRV_NET_PRT_RESP TRAIL HDRS	%4% 1 Id-byte response trailer headers for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26688	LRW_MSG_SRV_NET_PRT_RESP TRAIL HDRS IGN	%4% 1 Id-byte ignored response trailer headers for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26687	LRW_MSG_SRV_NET_PRT_RESP_OVERHEAD	%4% 1 Id-byte chunked response overhead for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26686	LRW_MSG_SRV_NET_PRT_RESP BODY	%4% 1 Id-byte response body for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26685	LRW_MSG_SRV_NET_PRT_RESP_BODY_CHUNK	%4% 1 Id-byte chunked response body for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26684	LRW_MSG_SRV_NET_PRT_RESP_REMAIN_CHUNK	%4% 1 Id-byte remaining chunked segment in error for "%2" (RelFrameId=%3, Internal ID=% 5 Id)
-26683	LRW_MSG_SRV_NET_SCAN_BUFFER_ERR	pe_scan_buffer failed (rc=% 1 Id) for "%2"
-26682	LRW_MSG_SRV_NET_SPACES_QUOTES	Embedded space(s) or misplaced quotes in value of "%1" response header for "%2" Additional information: The syntax of the response header is unrecognized by the Replay. If the syntax is invalid according to the HTTP specs, fix the server response. Otherwise, contact customer support.
-26681	LRW_MSG_SRV_NET_UNREF_FRAME ID	No buffer referring to Frame ID "%1" has been received. The %1/%2 request(s) specifying this Frame ID will be handled as "not found"
-26680	LRW_MSG_SRV_NET_RT_VIEWER EXCEP	Exception raised in Runtime Viewer in %1
-26679	LRW_MSG_SRV_NET_INTERNAL_ERROR	Internal Error - %1
-26678	LRW_MSG_SRV_NET_ATTEMPT_RETRY HTTP WITHOUT PHRASE	Attempting retry due to the above HTTP Status-Code of % 1 Id for "%2"
-26677	LRW_MSG_SRV_NET_HTTP_UNSUPP_REDIR WITH PHRASE	Unsupported HTTP redirection Status-Code=% 1 Id (%3) for "%2"
-26676	LRW_MSG_SRV_NET_HTTP_UNSUPP_REDIR WITHOUT PHRASE	Unsupported HTTP redirection Status-Code=% 1 Id ([status reason phrase unavailable]) for "%2"
-26675	LRW_MSG_SRV_NET_REDIR_WITHOUT_LOCATION_WITH PHRASE	Redirection HTTP Status-Code=% 1 Id (%3), but a "Location:" header is missing or empty for "%2" Additional information: The sever has returned an HTTP status code forf redirection but has not specified to which location. Try fixing the HTTP header on the server.
-26674	LRW_MSG_SRV_NET_REDIR_WITHOUT_LOCATION_WITHOUT PHRASE	Redirection HTTP Status-Code=% 1 Id ([status reason phrase unavailable]), but a "Location:" header is missing or empty for "%2" Additional information: Server has returned an HTTP status code of redirection but has not specified a status reason phrase. Try fixing the HTTP header on the server
-26673	LRW_MSG_SRV_NET_PENDING ADDED HEADERS END_INIT	Pending "%1" detected and reset at the end of the vuser_init section
-26672	LRW_MSG_SRV_NET_PENDING ADDED HEADERS END_VUSER	Pending "%1" detected and reset at the end of the Virtual User run
-26671	LRW_MSG_SRV_NET_PENDING ADDED HEADERS END_ITER	Pending "%1" detected and reset at the end of iteration number % 2 Id
-26670	LRW_MSG_SRV_NET_HEADER_NAME_EMPTY	Added header name is NULL or empty
-26669	LRW_MSG_SRV_NET_HEADER_NAME_ALL_SPACES_OR_COLONS	Header name invalid: NULL, empty, consists of white spaces only or contains embedded spaces or colons. Additional information: Header name invalid: NULL, empty, consists of white spaces only or contains embedded spaces or colons. Fix the argument in the of web_add_header or web_add_auto_header function.
-26668	LRW_MSG_SRV_NET_CONTROLLER_SYNC_FILE PROBLEM	Failed to open console sync file ("%1") for output. Internal error code (errno) was % 2 Id
-26667	LRW_MSG_SRV_NET_UPDATE_CORRELATION_INDEX_FILE FAILURE	Could not update correlation index file
-26666	LRW_MSG_SRV_NET_RESPONSE HTTP_UNEXPECTED_VER	Response does not start with "HTTP/1.1" or "HTTP/1.0" status line. Assuming "HTTP/1.1"
-26665	LRW_MSG_SRV_NET_MISSING_HTTP_STATUS_CODE	HTTP Status Code is missing or invalid. Assuming "200 OK"
-26664	LRW_MSG_SRV_NET_MISSING_COOKIE_NAME	Cookie without a name not added
-26663	LRW_MSG_SRV_NET_MISSING_CONTENT_LENGTH_VAL	Content-Length value is missing or invalid
-26662	LRW_MSG_SRV_NET_UNRECOGNIZED_CONNECTION_HEADER	Unrecognized "Connection:" header is ignored
-26661	LRW_MSG_SRV_NET_UNEXPECTED_END_OF_HTTP_HEADERS	Unexpected end of HTTP headers
-26660	LRW_MSG_SRV_NET_MISSING_HTTP_HEADERS	HTTP headers missing
-26659	LRW_MSG_SRV_NET_DOWNLOADING_RESOURCE	Found resource "%1" in HTML "%2"
-26658	LRW_MSG_SRV_NET_FTP_PROTOCOL_LIMITATION	FTP (ftp://) is supported in the "%1" function only

Error code	Handle	Message\Additional information
-26657	LRW_MSG_SRV_NET_RESPONSE_ADD_FAILED	Failed to process cookie "%1", probably due to invalid or unsupported syntax. Additional information: Failed to process cookie "cookie", probably due to invalid or unsupported syntax, Try fixing the cookie syntax.
-26656	LRW_MSG_SRV_NET_ADD_COOKIE_OR_REFERER	A Cookie or a Referer header is being added via web_add_header. This may not work
-26655	LRW_MSG_SRV_NET_RESOURCE_IN_CACHE	Resource "%1" is in the cache already and will not be downloaded again. Additional information: The most common reason for this error is invalid syntax, especially of the "expires" date format.
-26654	LRW_MSG_SRV_NET_HTTP_STATUS_304	Unexpected HTTP Status-Code=304 (%1) for "%2" (e.g., contents not in cache, no-cache indicated, etc.)%3
-26653	LRW_MSG_SRV_NET_PENDING_REG_MAY_FAIL	%1/%2/%3/%4 may produce incorrect results
-26652	LRW_MSG_SRV_NET_CONTENT_LEN_MISMATCH	Response body length (%1) does not match the expected length for "%3". Content-Length=%2 (Internal: expected difference=%4_id)
-26651	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_INVALID	HTTP Status-Code=%_1_id (%2) for "%3" An invalid status code was issued.
-26650	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_100	HTTP Status-Code=%_1_id (%2) for "%3"
-26649	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_101	HTTP Status-Code=%_1_id (%2) for "%3"
-26648	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_1XX	HTTP Status-Code=%_1_id (%2) for "%3"
-26647	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_200	HTTP Status-Code=%_1_id (%2) for "%3"
-26646	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_201	HTTP Status-Code=%_1_id (%2) for "%3"
-26645	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_202	HTTP Status-Code=%_1_id (%2) for "%3"
-26644	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_203	HTTP Status-Code=%_1_id (%2) for "%3"
-26643	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_204	HTTP Status-Code=%_1_id (%2) for "%3"
-26642	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_205	HTTP Status-Code=%_1_id (%2) for "%3"
-26641	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_206	HTTP Status-Code=%_1_id (%2) for "%3"
-26640	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_2XX	HTTP Status-Code=%_1_id (%2) for "%3"
-26639	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_300	HTTP Status-Code=%_1_id (%2) for "%3"
-26638	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_301	HTTP Status-Code=%_1_id (%2) for "%3"
-26637	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_302	HTTP Status-Code=%_1_id (%2) for "%3"
-26636	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_303	HTTP Status-Code=%_1_id (%2) for "%3"
-26635	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_304	HTTP Status-Code=%_1_id (%2) for "%3"
-26634	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_305	HTTP Status-Code=%_1_id (%2) for "%3"
-26633	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_307	HTTP Status-Code=%_1_id (%2) for "%3"
-26632	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_308	HTTP Status-Code=%_1_id (%2) for "%3"
-26631	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_3XX	HTTP Status-Code=%_1_id (%2) for "%3"
-26630	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_400	HTTP Status-Code=%_1_id (%2) for "%3"
-26629	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_401	HTTP Status-Code=%_1_id (%2) for "%3"
-26628	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_402	HTTP Status-Code=%_1_id (%2) for "%3"
-26627	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_403	HTTP Status-Code=%_1_id (%2) for "%3" Additional information: Try adding a client certificate with a web_set_certificate_ex function.
-26626	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_404	HTTP Status-Code=%_1_id (%2) for "%3"
-26625	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_405	HTTP Status-Code=%_1_id (%2) for "%3"
-26624	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_406	HTTP Status-Code=%_1_id (%2) for "%3"
-26623	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_407	HTTP Status-Code=%_1_id (%2) for "%3"
-26622	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_408	HTTP Status-Code=%_1_id (%2) for "%3"
-26621	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_409	HTTP Status-Code=%_1_id (%2) for "%3"
-26620	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_410	HTTP Status-Code=%_1_id (%2) for "%3"
-26619	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_411	HTTP Status-Code=%_1_id (%2) for "%3" Additional information: The server refuses to accept the request without a defined Content-Length1. The client MAY repeat the request if it adds a valid Content-Length header field containing the length of the message body in the request message.
-26618	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_412	HTTP Status-Code=%_1_id (%2) for "%3" Additional information: The Replay has sent a request header with an "If-*" that the server does not support. The server responded with the error "Precondition Failed" indicating that one or more of the conditions in the request has failed. The script most likely specifid a web_add_header and/or web_add_auto_header with "If-*". • Comment out or remove any preceding web_add_header and/or web_add_auto_header calls in the script specifying "If-*".

Error code	Handle	Message\Additional information
-26617	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_413	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The request is larger than the server is willing or able to process. Previously called "Request Entity Too Large". • Try to access the URL or the application being tested from a browser on the same machine.
-26616	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_414	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The server is refusing to service the request sent by the replay because the request URL is longer than the server is willing to interpret. The server responded with the error "Request-URI Too Long". • Try to access the URL or the application being tested from a browser on the same machine. • Try to replace the request to web_custom_request with POST method.
-26615	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_415	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The replay sent a request header with "Content-Encoding" that the server does not support. The server responded with the error "Unsupported Media Type". The script probably specifies web_add_header and/or web_add_auto_header with "Content-Encoding". • Try commenting out or removing any preceding web_add_header and/or web_add_auto_header calls in the script specifying "Content-Encoding".
-26614	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_416	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The replay sent a request header with "Range" that the server does not support. The server responded with the error "Requested Range Not Satisfiable". The script most likely specified web_add_header and/or web_add_auto_header with "Range". • Try commenting out or removing any preceding web_add_header and/or web_add_auto_header calls in the script specifying "Range".
-26613	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_417	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The replay sent a request header with "Expect" that the server does not support. The server responded with the error "EXPECTATION FAILED". The script probably specified web_add_header and/or web_add_auto_header with "Expect". • Try commenting out or removing any preceding web_add_header and/or web_add_auto_header calls in the script specifying "Expect".
-26612	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_4XX	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The server has returned an error code that the Replay does not support. • Try to access the URL or the application being tested from a browser on the same machine.
-26611	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_500	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The replay sent an unsupported request to the server. The server responded with the error "INTERNAL SERVER ERROR". Follow the same suggestions as in error 26611.
-26610	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_501	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The replay sent an unsupported request to the server. The server responded with the error "NOT IMPLEMENTED". • Try to access the URL or the application being tested from a browser on the same machine. • Comment out or remove any preceding web_add_header and/or web_add_auto_header calls in the script. • Check for values in the script that might need correlation.
-26609	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_502	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The server, acting as a gateway/proxy, informs that the upstream server has returned an invalid response. The gateway returned the error: "BAD GATEWAY". • Try to access the URL or the application being tested from a browser on the same machine. • If you are using a proxy server, try running the scenario without it.
-26608	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_503	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The server is currently unable to handle the request. The server returned the error: "SERVICE UNAVAILABLE". Try to access the URL or the application being tested from a browser on the same machine.

Error code	Handle	Message\Additional information
-26607	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_504	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The server, acting as a gateway/proxy, did not receive a timely response from an upstream server. The server returned the error: "GATEWAY TIMEOUT". • Try to access the URL or the application being tested from a browser on the same machine. • Rerun the failing scenario, and, concurrently, try to access the URL or the application being tested from a browser on another machine. If the response time is excessive, the server or the server application probably cannot sustain such loads. You should analyze the server for bottlenecks, and try to optimize server performance. • Run the scenario on Controller, and use the Analysis results to locate bottlenecks on the server, DNS, and/or network and try to optimize server performance. • If you are using a proxy server, try running the scenario without it.
-26606	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_505	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The replay is using an HTTP version that the server does not support. The server responded with the error "HTTP VERSION NOT SUPPORTED". • Try to access the URL or the application being tested from a browser on the same machine. • Try changing the HTTP version to "1.0" in Runtime Settings > Internet Protocol > Preferences > HTTP Version.
-26605	LRW_MSG_SRV_NET_HTTP_STATUS_CODE_5XX	HTTP Status-Code=%_1_Id (%2) for "%3" Additional information: The server has returned an error code that the Replay does not support. Try to access the URL or the application being tested from a browser on the same machine.
-26604	LRW_MSG_SRV_NET_THINK_TIME_RETRY_401	Think time of %1 seconds before retrying due to the above HTTP Status-Code of 401 for "%2"
-26603	LRW_MSG_SRV_NET_CONTENT_ENCODING	Unsupported "Content-Encoding" Additional information: Content coding values indicate an encoding transformation that has been or can be applied to an entity. The supported values are "gzip", "deflate" or "identity". "Compress" is not supported. This is only an issue if the response is encrypted and you expect to find specific values. • If the Vuser script contains a web_add_header or web_add_auto_header function specifying "Accept-Encoding" and an unsupported value, try to comment them out. • When adding a web_add_header or web_add_auto_header function specifying "Accept-Encoding", use a supported value (e.g., "gzip")
-26602	LRW_MSG_SRV_NET_NOT_DECOMPR_BUFFER_ALLOC	Not enough memory (%_1_Id bytes) for decompression buffer Additional information: Check the machine's memory resources, and close any unnecessary processes.
-26601	LRW_MSG_SRV_NET_DECOMPR_OPEN_FAILED	Decompression initialization function (wgzMemDecompressOpen) failed, return code=%_1_Id (%2), returned handle=%3 Additional information: Initializing the decompression module failed. A -4 return code indicates insufficient memory. A -7 return code means the decompression function is unsupported (i.e., it is not gzip, deflate, compress or identity). Other negative values indicate a system failure. The string explains the problem encountered by the function. • Try to address the problem described by the string. • If the return code is -4, check the machine's memory resources, and close any unnecessary processes. • If the return code is -7: ••If the Vuser script contains a web_add_header or web_add_auto_header function specifying "Accept-Encoding" and an unsupported value, try to comment them out. ••When adding a web_add_header or web_add_auto_header function with "Accept-Encoding", use a supported value (e.g., "gzip")
-26600	LRW_MSG_SRV_NET_DECOMPR_FAILED	Decompression function (wgzMemDecompressBuffer) failed, return code=%_1_Id (%2), inSize=%_3_Id, inUse=%_4_Id, outUse=%_5_Id Additional information: Failed to decompress a buffer. A negative return code denotes a system failure in the decompression module. A value of -4 indicates there is insufficient memory. The string explains the issue encountered by the function. The size of the input buffer in bytes ("inSize"), the number of input bytes processed ("inUse"), and the number of bytes written to the output buffer ("outUse") are all specified. Try to resolve the issue described by the string. If the return code is -4, check the machine's memory resources, and close all unnecessary processes.
-26599	LRW_MSG_SRV_NET_PRT_RESP_BODY_DECODED	%4%_1_Id-byte DECODED response body for "%2" (RelFrameld=%3, Internal ID=%_5_Id)
-26598	LRW_MSG_SRV_NET_PRT_RESP_BODY_ENCODED	%4%_1_Id-byte ENCODED response body received for "%2" (RelFrameld=%3, Internal ID=%_5_Id)
-26597	LRW_MSG_SRV_NET_NOT_ENOUGH_MEM	Not enough memory (%_1_Id bytes) for %2 Additional information: Check the machine's memory resources, and close any unnecessary processes.

Error code	Handle	Message\Additional information
-26596	LRW_MSG_SRV_NET_ADDED_HEADER_VALUE_SP	Added header value is NULL, empty or contains white spaces only. It is added anyway Additional information: Headers should contain at least one (non-space) value. • Add a non-space value to the header. • Generate headers using the web_remove_auto_header or web_revert_auto_header functions. • Remove the web_add_header or web_add_auto_header call.
-26595	LRW_MSG_SRV_NET_ADDED_HEADER_VALUE_NL	Added header value contains a newline character (\n) Additional information: Remove the newline character ('\n') from the script. To add additional headers, use a separate web_add_header or web_add_auto_header call for each header.
-26594	LRW_MSG_SRV_NET_ADDED_HEADER_UNRECOG	An unrecognized header ("%1") is being added Additional information: Possible causes: (i) Spelling error. (ii) The header is an application-defined header (iii) AN HTTP-defined header unrecognized by the Web Replay. For the latter two, ignore the message and contact support.
-26593	LRW_MSG_SRV_NET_ADDED_HEADER_RISKY_PRIMARY	The header being added may cause unpredictable results if applied to ALL the URLs generated on behalf of the next script function. It will apply to the primary URL only. Additional information: The same header. If the same header is applied to other requests, the results may be unpredictable. For example, when a request having a non-empty body is redirected to another URL, the redirection is always performed without specifying a body. Applying the same Content-Length header in the redirected request will cause the server to wait indefinitely for the body of the redirected request to arrive. Thus, the specified header will be applied only to the first ("primary") request and not to any derived requests. Similar considerations apply to the following headers: "Authorization", "Content-Encoding", "Content-Length", "Content-Location", "Content-MD5", "Content-Range", "Content-Type", "Host", "If-Match", "If-Modified-Since", "If-None-Match", "If-Range", "If-Unmodified-Since", "Proxy-Authorization", "Referer", "Transfer-Encoding". Check that you want to add this type of header. In the event that you want the specified header to apply to all requests, use web_add_auto_header (preferably with a corresponding web_revert_auto_header or web_remove_auto_header afterwards to deactivate adding this "risky" header).
-26592	LRW_MSG_SRV_NET_ADDED_HEADER_RISKY_ALL	The header being added may cause unpredictable results when applied to all ensuing URLs. It is added anyway Additional information: See error code 26593.
-26591	LRW_MSG_SRV_NET_ADDED_HEADER_ALREADY	A header of the same name has been added already. This header is added anyway. Additional information: Check that you intended for the same header type to appear more than once in the same request. If you did not, delete the unnecessary web_add_header.
-26590	LRW_MSG_SRV_NET_AUTO_HEADER_DISALLOWED	"%1" header not allowed in "%2" Additional information: Use another function instead. If the header that produces this message is "Cookie", use web_add_cookie.
-26589	LRW_MSG_SRV_NET_REMOVE_HEADER_NOP	%1 for "%2" had no effect Additional information: The web_remove_auto_header/web_revert_auto_header failed to stop Vusers from adding the specified header. Possible causes: • There was no preceding web_add_auto_header. • A previous web_remove_auto_header or web_revert_auto_header already had the effect requested by the current function call. • For implicitly generated headers, there was no previous web_add_auto_header, web_remove_auto_header or web_revert_auto_header that changed the implicit generation status.
-26588	LRW_MSG_SRV_NET_REMOVE_HEADER_IMP_CONT	Implicit generation of "%1" headers is continued
-26587	LRW_MSG_SRV_NET_REMOVE_HEADER_IMP_STOP	Implicit generation of "%1" headers is stopped
-26586	LRW_MSG_SRV_NET_REMOVE_HEADER_AUTO	Previous automatically added web header for "%1" removed
-26585	LRW_MSG_SRV_NET_REMOVE_HEADER_AUTO_IMP_CONT	Previous automatically added web header for "%1" removed, implicit generation is continued
-26584	LRW_MSG_SRV_NET_REMOVE_HEADER_AUTO_IMP_STOP	Previous automatically added web header for "%1" removed, implicit generation is stopped
-26583	LRW_MSG_SRV_NET_RES_NOT_DOWNLOADED_LIMIT	Resource "%1" will not be downloaded. Specified "ResourceByteLimit=% 2 _Id" exceeded already
-26582	LRW_MSG_SRV_NET_STAT_ERR	Could not obtain information about submitted/uploaded file "%1": %2 rc=%_3_Id, errno=%_4_Id, strerror="%5" Additional information: See error code -26581

Error code	Handle	Message\Additional information
-26581	LRW_MSG_SRV_NET_FOPEN_ERR	Could not open submitted/uploaded file "%1": errno=%_2_id, sterror="%3" Additional information: The most likely cause is "File not found". Possible reasons: • The file name is misspelled. • The files to be submitted aren't located directly under the Vuser directory. This may cause the script to fail when copying or moving to another machine or operating system (for example, a "\" for a directory name under Windows should be replaced with a "/" for Unix). • The file was deleted. • The drive letter may refer to different net locations on different machines. • Permissions problem. Troubleshooting: • Try to resolve the problem specified in the "error description". For example, if the file is not found, check that the file name is correct, the file has been copied with the script, and that the file exists on the recording and replay machine. • Copy the file to be submitted to the directory directly beneath the Vuser directory (not a subdirectory). Specify a simple name for the file (without drive/host/directory). • Check your file permissions. In a Windows operating system, an "errno" system variable of 13 means "Permission denied".
-26580	LRW_MSG_SRV_NET_FREAD_ERR	Error after reading %_1_id bytes from submitted/uploaded file "%2" Additional information: Try running the script again. Check that the file is not corrupted. Check that the file is accessible. If it is a network file, check the network connections.
-26579	LRW_MSG_SRV_NET_FILE_SIZE_MISMATCH	Number of bytes read (%_1_id) from submitted/uploaded file "%2" does not match the expected file size (%_3_id) Additional information: Try running the script again. Check that the file is not corrupted. Check that the file is accessible. If it is a network file, check the network connections.
-26578	LRW_MSG_SRV_NET_FRAME_HIER_DESTROYED	The HTML Frame Hierarchy now destroyed due to "Mode=%1" (non-HTML) downloading of a non-resource ("%2")
-26577	LRW_MSG_SRV_NET_PENDING_PE_NOT_FOUND	Pending %1/%2/%3/%4 request(s) are deleted and will be handled as "not found"
-26576	LRW_MSG_SRV_NET_DOWNLOADING_IN_FUNC_RES	Downloading resource "%1" (specified by argument number %_2_id)
-26575	LRW_MSG_SRV_NET_CACHE_OPERATION_FAILED	Cache operation ("%1") failed for "%2" Additional information: • Check the machine's memory resources, and close any unnecessary processes. • Deactivate caching. In the VuGen script, select Runtime Settings > Browser: Browser Emulation, and clear the Simulate browser cache option. Save and run the script again.
-26574	LRW_MSG_SRV_NET_RESOURCE_NOT_LOADED	Resource "%1" (detected in HTML) not downloaded. Resource downloading not requested
-26573	LRW_MSG_SRV_NET_DOWNLOADING_NON_RESOURCE	Detected non-resource "%1" in "%2"
-26572	LRW_MSG_SRV_NET_NOT_ENOUGH_MEM_FOR_HEADER	Not enough memory (%_1_id bytes) for the "%2" header value Additional information: Check the machine's memory resources, and close any unnecessary processes.
-26571	LRW_MSG_SRV_NET_UNSUPP_SCHEME_NON_RESOURCE	Non-resource "%1" (detected in HTML) not downloaded. Unsupported scheme Additional information: In most instances you can ignore this message. The URL of a non-resource (for example, an HTML frame) was detected in the response HTML. The "scheme" part of the URL (format "scheme://host/path") is not supported. Only "http:" and "https:" are supported. Note that in some cases (for example, when the scheme is "javascript:"), the recorder generates a separate script function to download the resulting URL. To record all requests and resources from the server: In VuGen, select Tools > Recording Options > Internet Protocol: Recording node, and select the URL-based script option.
-26570	LRW_MSG_SRV_NET_UNSUPP_SCHEME_RESOURCE	Resource "%1" (detected in HTML) not downloaded. Unsupported scheme
-26569	LRW_MSG_SRV_NET_AFT_END_OF_RESPONSE	Ignoring %_1_id byte(s) of data beyond the logical end of the response Additional information: • In Controller, check if all other users received the same warning at the same place. If other URLs from different servers didn't produce the same warning, this probably indicates normal server behavior. • If the problem is inconsistent, this may be a networking issue. If you are working through a proxy, try using a direct connection.
-26568	LRW_MSG_SRV_NET_RESPONSE_HTTP_09	No HTTP header found at beginning of server response, assuming this is a body with no header (as in HTTP/0.9)
-26567	LRW_MSG_SRV_NET_UNDETERMINED	%_1_id-byte undetermined data (before an HTTP Status Line has been identified) received for "%2", and will be handled and printed (or ignored) when determined

Error code	Handle	Message\Additional information
-26566	LRW_MSG_SRV_NET_NO_HTTP_STAT_UNDETERMINED	No HTTP Status Line detected. The undetermined data above and additional data received now will be handled as body without headers for "%1" Additional information: Possible causes: • An anti-virus server sent a special buffer before sending the actual HTTP header. • The server did not send an HTTP header. If the server did not send a header, the response's default HTTP properties are used. Check if the server can send the header.
-26565	LRW_MSG_SRV_NET_NO_HTTP_STAT	No HTTP Status Line detected. All data will be handled as body without headers for "%1" Additional information: If the server did not send a header, the response's default HTTP properties are used. Check if the server can send the header.
-26564	LRW_MSG_SRV_NET_HTTP_STAT_FOUND_UNDETERMINED	HTTP Status Line detected after some undetermined data, which will be ignored for "%1" Additional information: If the server did not send a header, the response's default HTTP properties are used. Check if the server can send the header.
-26563	LRW_MSG_SRV_NET_PRT_IGNORED	%4The ignored % 1 Id-byte undetermined data before the HTTP Status Line for "%2" (RelFrameld=%3, Internal ID=% 5 Id)
-26562	LRW_MSG_SRV_NET_204_WITH_BODY	Non-empty response body is invalid with HTTP Status Code 204 (No Content) for "%1" Additional information: Check your server HTTP settings for this URL. Check why there is body in the response.
-26561	LRW_MSG_SRV_NET_CONTENT_LEN_ADJUSTED	Content-Length (% 1 Id) adjusted to the length of the remainder of the segment after the end of the headers (% 2 Id) for "%3"
-26560	LRW_MSG_SRV_NET_HTTP_STATUS_304_SEARCH	%1%2/%3/%4 may produce incorrect results due to HTTP Status-Code=304 (%5) for "%6" Additional information: • Ensure that you want to emulate "every visit to the page" browser setting. To deactivate this setting, select Runtime Settings > Browser: Browser Emulation, and clear the Check for newer versions of stored pages every visit to the page option. Save and run the script again. • Put the web_reg_xxx function before the first request for this URL, since the first request will get the actual body.
-26559	LRW_MSG_SRV_NET_UNRECOGNIZED_PROXY_CONNECTION_HEADER	Unrecognized "Proxy-Connection:" header is ignored
-26558	LRW_MSG_SRV_NET_PRT_RESP_BODY_FROM_CACHE	%4% 1 Id-byte response body retrieved from cache for "%2" (RelFrameld=%3, Internal ID=% 5 Id)
-26557	LRW_MSG_SRV_NET_RETRIEVING_DATA_FROM_CACHE	Retrieving data from cache for "%1"
-26556	LRW_MSG_SRV_NET_UNRECOGNISED_DIGEST_FIELD	Unknown field "%1" in Digest Authenticate header for URL "%2"
-26555	LRW_MSG_SRV_NET_INCLUDE_FILTER_DISALLOWED	An "include" filter is not allowed when an "exclude" filter is active Additional information: Decide whether the URL should be included or excluded and cancel the opposite filter. Check for the relevant web_add_auto_filter, web_remove_auto_filter, or web_add_filter function.
-26554	LRW_MSG_SRV_NET_EXCLUDE_FILTER_DISALLOWED	An "exclude" filter is not allowed when an "include" filter is active Additional information: See error code -26555
-26553	LRW_MSG_SRV_NET_FILTERED	Not downloaded due to a filter, URL="%1" Additional information: If you want to download the URL, cancel the filter rule that applies to the URL before the step is committed. If the rule is web_add_auto_filter, use web_remove_auto_filter before the step and web_add_filter after it. If the opposite rule is web_add_filter, you should remove it.
-26552	LRW_MSG_SRV_NET_SETTING_FILTER_ID_IN_NON_AUTO	An ID is specified for a non-auto filter Additional information: Check that the ID in the web_remove_auto_filter matches the ID in the web_add_auto_filter that you want to cancel. Check that it was not applied more than once.
-26551	LRW_MSG_SRV_NET_SETTING_FILTER_ID_ALREADY_SET	A filter with "ID=%1" already exists. Use a different ID if you do not want the existing filter to be overwritten. Additional information: Use a different ID for the new filter if you don't want to overwrite the existing filter.
-26550	LRW_MSG_SRV_NET_FAILED_TO_DECODE_UTF8_BODY_FOR_URL	Failed to decode UTF8 content for URL %1 : %2 Additional information: Try to set a different locale or change to a machine with a compatible locale.
-26549	LRW_MSG_SRV_NET_PAST_CHUNKED_RESP	Ignoring % 1 Id bytes past the logical end of a "Transfer-Encoding: chunked" response for "%2"
-26548	LRW_MSG_SRV_NET_UNEXPECTEDLY_NOT_IN_CACHE	Contents unexpectedly not in cache. Check previous messages for URL="%1"

Error code	Handle	Message\Additional information
-26547	LRW_MSG_SRV_NET_NOT_PARSING	HTML parsing not performed for Content-Type "%1" ("ParseHtmlContentType" Runtime Setting is "%2"). URL="%3" Additional information: - Check the content-type of the URL to determine if parsing is required: "ParseHtmlContentType=HTML" indicates that HTML parsing should be performed only when Content-Type is "text/html", omitted or empty. "ParseHtmlContentType=TEXT" indicates that HTML parsing should be performed for all Content-Types starting with "text/", except "text/xml" and omitted/empty Content-Types. "ParseHtmlContentType=ANY" indicates that HTML parsing should be performed for all Content-Types, except "text/xml". - Parse the URL using one of the following: - Change the content-type header by adjusting the server settings. - Update the default.cfg file in the [web] section to "Add ParseHtmlContentType=ANY".
-26546	LRW_MSG_SRV_NET_NO_WEB_SET_USER	Authentication required, please use "%1", e.g. %2("%3user", "password", "host:port"); Additional information: Use the web_set_user function to set authorization.
-26545	LRW_MSG_SRV_NET_AUTO_TRANS_START	Starting Automatic Transaction "%1" failed (rc=% 2 _Id)
-26544	LRW_MSG_SRV_NET_AUTO_TRANS_PROP	Setting properties for Automatic Transaction "%1" failed (rc=% 2 _Id)
-26543	LRW_MSG_SRV_NET_NO_PROXY_USER	Proxy authentication required, please fill in the proxy user details in the Runtime Settings, Proxy tab, using the Authentication button. e.g. Username: %1user Password: password Additional information: - Specify a valid username and password in the Runtime Settings > Internet Protocol:Proxy > Authentication node. For NTLM, specify a domain and single backslash immediately preceding the username. - Add a web_set_user call before the function that failed, specifying a valid username and password (or change the previous web_set_user for the proxy's host/port). For NTLM, specify a domain and two backslashes immediately preceding the username.
-26542	LRW_MSG_SRV_NET_MISSING_EMPTY_CHUNK	Missing empty chunk or final newline at the end of "Transfer-Encoding: chunked" body for URL="%1" Additional information: Add a web_set_user call before the function that failed, specifying a valid username and password (or change the previous web_set_user for the proxy's host/port). For NTLM, specify a domain and two backslashes immediately preceding the username.
-26541	LRW_MSG_SRV_NET_INCOMPLETE_CHUNKED	Incomplete "Transfer-Encoding: chunked" body for URL="%1" (internal information: State=% 2 _Id=%3, _liChunkBodyRemainingLen=% 4 _Id)
-26540	LRW_MSG_SRV_SCRIPT_NOT_SUPPORTED	Unsupported language ("%1") or type ("%2") for a script. The script will not be evaluated
-26539	LRW_MSG_SRV_NET_SUPPRESSING_PARSING	Suppressing the HTML parsing of URL="%1" until script downloading is complete
-26538	LRW_MSG_SRV_NET_RESUMING_PARSING	Resuming HTML parsing of URL="%1"
-26537	LRW_MSG_SRV_NET_NOT_EVALUATED_ERRORS	Script not evaluated due to error(s) in downloading it (URL="%1")
-26536	LRW_MSG_SRV_NET_NOT_EVALUATED_EMPTY	Empty/unavailable script not evaluated (URL="%1")
-26535	LRW_MSG_SRV_NET_INTERNAL_ERROR_NOT_WAITING_SCRIPT_SRC	Internal Error - iAwaitingScriptSrcDownload==0 for mptTaskItemAwaitingThisScriptSrc=%1, URL="%2", from mptScriptSrcTaskItem=%3, URL="%4" in fvLrwSrvNetHandleTaskItemAwaitingScriptSrc. Aborting
-26534	LRW_MSG_SRV_NET_SCRIPT_SRC_NOT_DOWNLOADED	Parsing of "%1" incomplete - waiting for a script which has not been downloaded
-26533	LRW_MSG_SRV_NET_DOWNLOADING_SCRIPT	Downloading script "%1" (detected in HTML)
-26532	LRW_MSG_SRV_NET_UNSUPPORTED_BASE_URL_SCHEME	Unsupported scheme in URL "%1", specified in "BASE" element or document.location (not "http:", "https:", etc.)
-26531	LRW_MSG_SRV_NET_NO_SCRIPT_CLOSING_TAG	Missing closing of a "SCRIPT" tag in URL="%1"
-26530	LRW_MSG_SRV_NET_INTERNAL_ERROR_AWAITING_SRC_COUNT	Internal Error - iAwaitingScriptSrcDownloadCount=% 1 _Id in %2 for Task Item at %3, URL="%4". Aborting
-26529	LRW_MSG_SRV_NET_FAILED_ALLOC_ELEM	Failed to allocate a DOM element for representing "%1"
-26528	LRW_MSG_SRV_NET_DOWNLOADING_RESOURCE_WITHOUT_URL_OF_HTML	Downloading resource "%1" (detected in HTML)
-26527	LRW_MSG_SRV_NET_REFRESHING_WINDOW	META-Refresh to URL "%1"
-26526	LRW_MSG_SRV_NET_DOWNLOADING_BODY_BACKGROUND	Downloading BODY background="%1"
-26525	LRW_MSG_SRV_NET_DOWNLOADING_FRAME	Downloading frame, URL="%1"
-26524	LRW_MSG_SRV_NET_DOWNLOADING_INLINE_FRAME	Downloading inline frame, URL="%1"
-26523	LRW_MSG_SRV_NET_SCRIPT_FOR_NOT_SUPPORTED	Script binding to objects (<script for=>) not supported and ignored. The script will not be evaluated
-26522	LRW_MSG_SRV_NET_DOWNLOADING_OBJECT_CLASSID	Downloading <OBJECT classid="%1"> (detected in HTML)
-26521	LRW_MSG_SRV_NET_DOWNLOADING_OBJECT_DATA	Downloading <OBJECT data="%1"> (detected in HTML)
-26520	LRW_MSG_SRV_NET_RETRIEVING_POST_DATA_FROM_CACHE	Retrieving POST data from cache for History access to "%1"
-26519	LRW_MSG_SRV_NET_INCOMPLETE_CACHE_ENTRY	Attempting to use an incomplete cache entry for URL "%1"
-26518	LRW_MSG_SRV_NET_BAD_FILTERS_CFG	Invalid format for the following filters:\r\n%1\r\nView and modify the filters in the Runtime Settings > Internet Protocol > Filters view.
-26517	LRW_MSG_SRV_NET_BAD_FILTERS_SYNTAX_CFG	Error(s) generated while initializing the filter(s) defined in the Runtime Settings > Internet Protocol > Filters view. Open the Runtime settings to edit the filter.
-26516	LRW_MSG_SRV_NET_INVALID_HEADER	Note: "%1: %2" is invalid. Using "%1: %3"
-26515	LRW_MSG_SRV_NET_MAX_META_REFRESH	The limit (% 1 _Id) specified by "Maximum number of <META refresh> to the same page" exceeded for URL="%2". Refer to the Runtime Settings under "Internet Protocol" / "Preferences" / "Options..." (default is % 3 _Id)

Error code	Handle	Message\Additional information
-26514	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_EVALUATION_FAILED	Evaluation of the JavaScript code in URL="%1" failed
-26513	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_NOT_STR	JavaScript code in URL="%1" returned a non-string or an invalid value, which is ignored (internal returned type code was %_2_Id, length=%_3_Id)
-26512	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_VOID	JavaScript code in URL="%1" did not return a value
-26511	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_NAVIGATED	JavaScript code in URL="%1" has initiated a navigation to the target window
-26510	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_WINDOW_DELETED	The target window was deleted when evaluating URL="%1"
-26509	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_RESULT_WRITING	Evaluating URL="%1" returned "%2". Writing it to the target window
-26508	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_RESULT_IGNORED	Results of evaluating URL="%1" are ignored for a resource
-26507	LRW_MSG_SRV_NET_JAVASCRIPT_SCHEME_EMPTY	JavaScript code in URL="%1" returned an empty value
-26506	LRW_MSG_SRV_NET_ABORTING_TASK_WINDOW_DELETED	Aborting download of URL "%1" (RelFrameId=%2, Internal ID=%_3_Id) (e.g., due to the target document or object being deleted)
-26505	LRW_MSG_SRV_ADD_HEADER	"%1" header registered for adding to requests from the immediately following Action function
-26504	LRW_MSG_SRV_ADD_AUTO_HEADER	"%1" header registered for adding to requests from all following Action functions
-26503	LRW_MSG_SRV_ADD_AUTO_HEADER_REPL	"%1" header registered (superseding previous registration) for adding to requests from all following Action functions
-26502	LRW_MSG_SRV_NET_HEAD_WITH_BODY	Non-empty response body ignored for HTTP method "HEAD" (URL="%1")
-26501	LRW_MSG_SRV_NET_WINDOW_HTTP_STATUS_CODE	Window not downloaded due to HTTP Status-Code=%_1_Id (%2) for "%3"
LrwUtil_res.h		
-26499	LRW_MSG_UTIL_INTERNAL_ERROR	Internal Error - %1
-26498	LRW_MSG_UTIL_GET_PROXY_SETTING_ERROR	Obtaining the proxy settings from the default browser failed
-26497	LRW_MSG_UTIL_GET_PROXY_SETTING_WIN32_ERROR	Obtaining the proxy settings from the default browser is supported under WIN32 only
-26496	LRW_MSG_UTIL_ADD_AUTH_TO_PROXY_ERROR	Adding authorization entry for HTTP proxy failed
-26495	LRW_MSG_UTIL_UNEXPECTED_HTTP_VER_ERROR	Unexpected HTTP version Runtime Setting (HttpVer). Assuming HTTP/1.1 Additional information: The expected values are 1.0 and 1.1. In Runtime Settings > Preferences > Options, change the value of parameter "HTTP version" to 1.1 or 1.0.
-26494	LRW_MSG_UTIL_REGISTER_FRAME_ID_ERROR	At most %_1_Id Frame IDs can be registered
-26493	LRW_MSG_UTIL_DIFFERENT_RUN_TIME_SETTING_WARNING	Different Run Time Settings for timeout values (resolve=%_1_Id, connect=%_2_Id, receive=%_3_Id) may hinder performance for WinInet Replay
-26492	LRW_MSG_UTIL_X_NOT_FOLLOWED_BY_DIG	"\\x" not followed by 2 valid hex digits Additional information: A text buffer contains \\x or \\X that is not followed by two valid hexadecimal digits.\\x (or \\X) is a prefix for embedding binary data in text.
-26491	LRW_MSG_UTIL_INVALID_ESCAPE_SEQ	"\\ " not followed by x, X or \\ Additional information: Invalid escape sequence '\\ ' is not followed by any of x, X, \\, r, n, t. The combination of '\\ ' followed by one of the digits mentioned above represents control characters or a prefix of binary data.
-26490	LRW_MSG_UTIL_INVALID_SUBMIT_FILE_NAME	File name in a multipart submit is missing or empty. Using an empty file
-26489	LRW_MSG_UTIL_INVALID_SUBMIT_BOUNDARY	Invalid boundary in multipart submit data/file
-26488	LRW_MSG_UTIL_STAT_ERR	Could not obtain information about submitted file "%1": %2 rc=%_3_Id, errno=%_4_Id [%5]. Using an empty file
-26487	LRW_MSG_UTIL_OPENING_SUBMITTED_FILE_FAILED	Opening submitted file "%1" failed, errno=%_2_Id [%3]. Using an empty file
-26486	LRW_MSG_UTIL_READING_FILE_FAILURE	Error in reading file "%1" after having read %_2_Id bytes
-26485	LRW_MSG_UTIL_FILE_SIZE_MISMATCH	Number of bytes read (%_1_Id) from file "%2" does not match the expected file size (%_3_Id)
-26484	LRW_MSG_UTIL_NOT_ENOUGH_MEM	Not enough memory (%_1_Id bytes) for %2 Additional information: Try closing other applications on the machine, or running less virtual users.
-26483	LRW_MSG_UTIL_INVALID_ARGUMENT_VALUE	Value of the "%1" argument is invalid ("%2")
-26482	LRW_MSG_UTIL_FILED_TO_CREATE_UTF8_CONVERTER	Failed to create "%1" Unicode converter: %2 in %3 (error code %_4_Id)
-26481	LRW_MSG_UTIL_FAILED_TO_LOAD_UTF_LIBRARY	Failed to load the "%1" internationalization library. %2
-26480	LRW_MSG_UTIL_FAILED_TO_GET_ICCUC_FUN	Failed to find the "%1" internationalization function. %2
-26479	LRW_MSG_UTIL_UTF8_CONV_FAILED	Conversion of form submission data to the target charset failed: %1
-26478	LRW_MSG_UTIL_NTLM_NO_DOMAIN_AND_USER	domain and user are needed for NTLM authentication, note: two backslashes are needed, e.g. %1("Domain\\\\\\\\\\\\\\\\user", "password", "host:port");
-26477	LRW_MSG_UTIL_NTLM_NO_DOMAIN_OR_USER	both domain and user are needed for NTLM authentication, note: two backslashes are needed, e.g. %1("Domain\\\\\\\\\\\\\\\\user", "password", "host:port");
-26476	LRW_MSG_UTIL_FILE_LINE_INVALID	Cannot obtain script file/line for generating automatic transaction names. File name "%1" is invalid Additional information: The automatic transaction name is usually composed of the step name, file name, and line number. Replay will create an automatic transaction name in a different format.

Error code	Handle	Message\Additional information
-26475	LRW_MSG_UTIL_AUTO_TRANS_START	Starting Automatic Transaction "%1" failed (rc=% 2_Id)
-26474	LRW_MSG_UTIL_AUTO_TRANS_PROP	Setting properties for Automatic Transaction "%1" failed (rc=% 2_Id)
-26473	LRW_MSG_UTIL_AUTO_TRANS_END	Ending Automatic Transaction failed (rc=% 1_Id)
-26472	LRW_MSG_UTIL_USER_AGENT_NEWLINE	UserAgent argument value truncated at a new-line character ("\\n")
-26471	LRW_MSG_UTIL_FILE_NOT_MULTIPART	A "file" form field (name="%1" value="%2") defined when EncType is not "multipart/form-data". The file name, rather than its contents, will be sent Additional information: For a file upload to take place, the EncType attribute of the form element must be multipart/form-data.
-26470	LRW_MSG_UTIL_DISK_CACHE_FREAD_DATA_ERROR	An I/O error or an unexpected end of file when reading from disk cache file "%1". % 2_Id bytes requested, % 3_Id read, errno=% 4_Id, sterror="%5". URL number % 6_Id ("%7")
-26469	LRW_MSG_UTIL_DISK_CACHE_FWRITE_ERROR	Error writing to disk cache file "%1". % 2_Id bytes written instead of % 3_Id, errno=% 4_Id, sterror="%5"
-26468	LRW_MSG_UTIL_DISK_CACHE_CONTENT_SIZE_MISMATCH	Mismatch between length indicated by disk cache header (% 1_Id) and saved length (% 2_Id) for URL number % 3_Id in disk cache file "%4" (the line is "%5")
-26467	LRW_MSG_UTIL_DISK_CACHE_FILE_ALREADY_EXISTS_ERROR	Disk cache file "%1" exists already and "Replace=No" specified
-26466	LRW_MSG_UTIL_DISK_CACHE_FPRINTF_ERROR	Error writing to disk cache file "%1". errno=% 2_Id, sterror="%3" (possibly not of the LAST fprintf)
-26465	LRW_MSG_UTIL_DISK_CACHE_FOPEN_ERROR	Could not open disk cache file "%1": errno=% 2_Id, sterror="%3"
-26464	LRW_MSG_UTIL_DISK_CACHE_VERSION_NUMBERS_NOT_SUPPORTED	Version "% 1_Id.% 2_Id" of disk cache file "%3" is not supported
-26463	LRW_MSG_UTIL_DISK_CACHE_VERSION_STRING_NOT_SUPPORTED	Version "%1" of disk cache file "%2" is not supported
-26462	LRW_MSG_UTIL_DISK_CACHE_MISMATCH_READ_LITERAL	Line number % 1_Id does not start with "%2" in disk cache file "%3" (the line is "%4")
-26461	LRW_MSG_UTIL_DISK_CACHE_MISMATCH_ARGUMENT_READ	Argument number % 1_Id is invalid in line % 2_Id of disk cache file "%3" (the line is "%4")
-26460	LRW_MSG_UTIL_DISK_CACHE_MISMATCH_READ_DATA_LITERAL	"%1" not found in data of URL number % 2_Id in disk cache file "%3". Line read %4
-26459	LRW_MSG_UTIL_DISK_CACHE_MISMATCH_ARGUMENT_DATA_READ	Argument number % 1_Id is invalid in data of URL number % 2_Id of disk cache file "%3" (the line is "%4")
-26458	LRW_MSG_UTIL_DISK_CACHE_BAD_FILE_ERROR	File "%1" is not a disk cache file. First line is "%2" rather than starting with "%3"
-26457	LRW_MSG_UTIL_DISK_CACHE_REDUNDANT_TEXT_ERROR	Redundant text "%1" was found at the end of line number % 2_Id in disk cache file "%3"
-26456	LRW_MSG_UTIL_DISK_CACHE_REDUNDANT_TEXT_IN_DATA_ERROR	Redundant text "%1" was found at the end of data header number % 2_Id in disk cache file "%3"
-26455	LRW_MSG_UTIL_DISK_CACHE_INVALID_VALUE	Invalid value for "%1" in disk cache file "%2" line number % 3_Id (the line is "%4")
-26454	LRW_MSG_UTIL_NOT_ENOUGH_MEM_WITHOUT_BYTES	Not enough memory for %1
-26453	LRW_MSG_UTIL_DISK_CACHE_FGETS_EOF	Unexpected end of disk cache file "%1"
-26452	LRW_MSG_UTIL_DISK_CACHE_FGETS_TRUNCATED	Line too long (exceeds % 1_Id bytes) in disk cache file "%2"
-26451	LRW_MSG_UTIL_DISK_CACHE_FGETS_IO_ERROR	Error reading disk cache file "%1", errno=% 2_Id, sterror="%3"
-26450	LRW_MSG_UTIL_DISK_CACHE_FGETS_ERROR_LINE	The above disk cache file error occurred when reading line number % 1_Id
-26449	LRW_MSG_UTIL_DISK_CACHE_FGETS_ERROR_URL_NUMBER	The above disk cache file error occurred when reading the content of URL number % 1_Id
-26448	LRW_MSG_UTIL_NOT_FOUND_TEXT_VERIF	"Text=%1" not found for "%2"
-26447	LRW_MSG_UTIL_SUC_REQ_TEXT_VERIF	Registered "%1" successful for "Text=%2"
-26446	LRW_MSG_UTIL_FOUND_TEXT_VERIF	"Text=%1" found for "%2" (count=% 3_Id)
-26445	LRW_MSG_UTIL_SUC_TEXT_VERIF	Registered "%1" successful for "Text=%2" (count=% 3_Id)
-26444	LRW_MSG_UTIL_PARAM_STR_FAIL	Parameter SaveString failed (rc=% 1_Id) for "%2"
-26443	LRW_MSG_UTIL_TOPAZ_STEP_INFO	>>>> Debug info: hit info: URL: "%1"; RESOURCE: %2; HTTP response: % 3_Id; Downloaded bytes: % 4_Id; Uploaded bytes: % 5_Id;
-26442	LRW_MSG_UTIL_TOPAZ_STEP_TOTALS	>>>> Debug info: step info: Totals: Downloaded bytes: % 1_Id; Uploaded bytes: % 2_Id; Hits: % 3_Id; ID: %4;
-26441	LRW_MSG_UTIL_TOPAZ_TOTALS	>>>> Debug info: script info: Totals: Downloaded bytes: % 1_Id; Uploaded bytes: % 2_Id; Hits: % 3_Id; VUSER END STATUS: %4;
-26440	LRW_MSG_UTIL_REG_EXP_FAIL_TO_COMPILE	Failed to compile regular expression "%1". Return-code % 2_Id: %3
-26439	LRW_MSG_UTIL_MIC_REGEX_ERROR_NOMATCH	No match for regular expression "%1"
-26438	LRW_MSG_UTIL_MIC_REGEX_ERROR_BADPAT	Invalid syntax in regular expression "%1"
-26437	LRW_MSG_UTIL_MIC_REGEX_ERROR_ECOLLATE	Invalid collating element -- [= =] -- in regular expression "%1"
-26436	LRW_MSG_UTIL_MIC_REGEX_ERROR_ECTYPE	Invalid character class -- [: :] -- in regular expression "%1"
-26435	LRW_MSG_UTIL_MIC_REGEX_ERROR_EESCAPE	A backslash (\) is applied to an unescapable character in regular expression "%1"
-26434	LRW_MSG_UTIL_MIC_REGEX_ERROR_ESUBREG	Invalid back-reference number in regular expression "%1"
-26433	LRW_MSG_UTIL_MIC_REGEX_ERROR_EBRACK	Unbalanced brackets - [] - in regular expression "%1"
-26432	LRW_MSG_UTIL_MIC_REGEX_ERROR_EPAREN	Unbalanced parentheses - () - in regular expression "%1"
-26431	LRW_MSG_UTIL_MIC_REGEX_ERROR_EBRACE	Unbalanced braces - { } - in regular expression "%1"
-26430	LRW_MSG_UTIL_MIC_REGEX_ERROR_BADBR	Invalid repetition count(s) in { } within regular expression "%1"
-26429	LRW_MSG_UTIL_MIC_REGEX_ERROR_ERANGE	Invalid character range in [] within regular expression "%1"
-26428	LRW_MSG_UTIL_MIC_REGEX_ERROR_ESPACE	Not enough memory for processing regular expression "%1"
-26427	LRW_MSG_UTIL_MIC_REGEX_ERROR_BADRPT	Invalid use of a "repetition" operator ("*", "?" or "+") in regular expression "%1" (e.g., in "**A" there is no PRECEDING expression to be repeated)
-26426	LRW_MSG_UTIL_MIC_REGEX_ERROR_EMPTY	Empty (sub)expression in regular expression "%1"
-26425	LRW_MSG_UTIL_MIC_REGEX_ERROR_ASSERT	Unexpected error -- ASSERT -- when processing regular expression "%1"
-26424	LRW_MSG_UTIL_MIC_REGEX_ERROR_INVARG	Invalid argument for an internal function when processing regular expression "%1"

Error code	Handle	Message\Additional information
-26423	LRW_MSG_UTIL_MIC_REGEX_UNEXPECTED_RC	Unexpected internal return code (% 1_Id) when processing regular expression "%2"
-26422	LRW_MSG_UTIL_ERROR_IN_CREATE_UTF8_CONVERTER	Error during creation of "%1" Unicode converter: %2 in %3 (error code % 4_Id). Attempting to continue
-26421	LRW_MSG_UTIL_CANNOT_LOCATE_VUSER_FUNC	Failed to locate Vuser script function "%1", specified via the "%2" argument
-26420	LRW_MSG_UTIL_RECURSIVE_VUSER_FUNC	Ignoring an attempt to recursively call Vuser script function "%1", specified via the "%2" argument of "%3" in %4(% 5_Id)
-26419	LRW_MSG_UTIL_CALLING_VUSER_FUNC	Calling Vuser script function "%1", specified via the "%2" argument of "%3" in %4(% 5_Id)
-26418	LRW_MSG_UTIL_RETURNED_FROM_VUSER_FUNC	Returned (rc=% 1_Id) from Vuser script function "%2", specified via the "%3" argument of %4 in %5(% 6_Id)
-26417	LRW_MSG_UTIL_MIC_REGEX_ERROR_UNRECOGNIZED_RC	Unexpected error when processing regular expression "%1": unrecognized return-code (% 2_Id) from %3
-26416	LRW_NET_SOCKET_AUTOMATIC_PROXY_ASSOCIATE_WITH	Automatic Proxy Result Cache now associates %1:% 2_Id with proxy / direct connection %3:% 4_Id
-26415	LRW_NET_SOCKET_AUTOMATIC_PROXY_DISASSOCIATE_FROM	Automatic Proxy Result Cache now disassociates %1:% 2_Id from proxy / direct connection
-26414	LRW_NET_SOCKET_AUTOMATIC_PROXY_MARKED_PROXY_GOOD	Automatic Proxy Result Cache marked proxy %1:% 2_Id as "GOOD"
-26413	LRW_NET_SOCKET_AUTOMATIC_PROXY_MARKED_CONNECTION_GOOD	Automatic Proxy Result Cache marked direct connection %1:% 2_Id as "GOOD"
-26412	LRW_NET_SOCKET_AUTOMATIC_PROXY_MARKED_PROXY_BAD	Automatic Proxy Result Cache marked proxy %1:% 2_Id as "BAD" : %3
-26411	LRW_NET_SOCKET_AUTOMATIC_PROXY_MARKED_CLEAR	Automatic Proxy Result Cache cleared %1 mark from proxy %2:% 3_Id
LrwiAed_res.h		
-32599	LRWI_AED_MSG_INTERNAL_ERROR	Internal Error - %1
-32598	LRWI_AED_MSG_UNEXPECTED_ATTR_LOCATOR_KNOWN	Invalid/misplaced attribute ("%1", value "%2") in element "%3" (before line % 4_Id, column % 5_Id in file "%6") Additional information: See error code -32597 .
-32597	LRWI_AED_MSG_UNEXPECTED_ATTR_LOCATOR_UNKNOWN	Invalid/misplaced attribute ("%1", value "%2") in element "%3" (in file "%4") Additional information: An attribute in the ContentCheck XML file is either invalid or misplaced. Possible reasons: (i) The user manually edited the ContentCheck XML file. (ii) The XML file was created by a later version. Try to resolve the invalid/misplaced attribute in the specified file. Make a backup copy of the file before trying to edit or delete the offending attribute from the original file. Save any changes to the file, and run the script again.
-32596	LRWI_AED_MSG_PARSING_ERROR	%1 (in line % 2_Id, column % 3_Id in file "%4") Additional information: An error has been detected in the specified ContentCheck XML file. Possible reasons: (i) The user manually edited the ContentCheck XML file. (ii) The XML file was created by a later version. Try to resolve the error based upon the error description provided. Make a backup copy of the file before trying to troubleshoot the original file. Save any changes to the file, and run the script again.
-32595	LRWI_AED_MSG_GENERAL_OK	Operation successful
-32594	LRWI_AED_MSG_GENERAL_INVALID_PARAMETER	Invalid parameter to a ContentCheck function
-32593	LRWI_AED_MSG_GENERAL_INVALID_INTERNAL_PARAMETER	Invalid parameter to an INTERNAL ContentCheck function
-32592	LRWI_AED_MSG_GENERAL_DUPLICATE_ELEMENT	Duplicate Application or Rule name
-32591	LRWI_AED_MSG_GENERAL_INVALID_SORT_ORDER	Application or Rule name not in sort order
-32590	LRWI_AED_MSG_GENERAL_NO_MEM	Not enough memory Additional information: Check the machine's memory resources, and close any unnecessary processes running on the machine. If the problem remains, restart the computer and replay the script again.
-32589	LRWI_AED_MSG_GENERAL_INVALID_NAME	Invalid or empty Application/Rule name. Must consist of English letters, digits and/or " #@\$" only.
-32588	LRWI_AED_MSG_GENERAL_WRONG_LIST	Application/Rule element not in specified list
-32587	LRWI_AED_MSG_GENERAL_EMPTY_TEXT	Text is empty
-32586	LRWI_AED_MSG_GENERAL_EMPTY_PREFIX	Prefix is empty
-32585	LRWI_AED_MSG_GENERAL_EMPTY_SUFFIX	Suffix is empty
-32584	LRWI_AED_MSG_GENERAL_INVALID_RULE_LEVEL	Invalid Rule Level
-32583	LRWI_AED_MSG_GENERAL_CANCELED	Operation canceled
-32582	LRWI_AED_MSG_GENERAL_MERGE_CALLBACK_RESPONSE	Invalid response from the Merge callback
-32581	LRWI_AED_MSG_GENERAL_CONF_CALLBACK_RESPONSE	Invalid response from the Confirmation callback
-32580	LRWI_AED_MSG_GENERAL_MERGE_CALLBACK_NOT_SET	A merge callback has not been set (via xfeLrwiAedSetMergeCallback)
-32579	LRWI_AED_MSG_GENERAL_MERGE_CALLBACK_NEW_NAME	The Merge callback has not assigned the new Rule name
-32578	LRWI_AED_MSG_GENERAL_NON_SP_WSP_IN_VALUE	An unescaped white-space ('\\n', '\\r', '\\t', but not ' ') encountered
-32577	LRWI_AED_MSG_GENERAL_FILE_OPEN_FAILED	ContentCheck file open failed
-32576	LRWI_AED_MSG_GENERAL_UNAVAILABLE_FILE_INFO	File information (stat) could not be obtained
-32575	LRWI_AED_MSG_GENERAL_FILE_NOT_REG	ContentCheck file is not a regular file (e.g., it is a directory)
-32574	LRWI_AED_MSG_GENERAL_FILE_IS_EMPTY	ContentCheck file is empty
-32573	LRWI_AED_MSG_GENERAL_PARSING_ERROR	XML parsing error

Error code	Handle	Message\Additional information
-32572	LRWI_AED_MSG_GENERAL_INVALID_RC	Invalid return-code from a ContentCheck function Additional information: Disable ContentCheck: In VuGen, select Runtime Settings > Internet Protocol: ContentCheck, and clear the Enable ContentCheck during replay checkbox.
-32571	LRWI_AED_MSG_GENERAL_FILE_NOT_FOUND	A ContentCheck file does not exist
-32570	LRWI_AED_MSG_FUNC_FAILED_ERRNO	The "%1" function failed, rc=%_2_Id, errno=%_3_Id Additional information: Disable ContentCheck: In VuGen, select Runtime Settings > Internet Protocol: ContentCheck, and clear the Enable ContentCheck during replay checkbox.
-32569	LRWI_AED_MSG_FUNC_FAILED_LAST_ERROR	The "%1" function failed, GetLastError=%_2_Id
-32568	LRWI_AED_MSG_ADDING_APPL_FAILED	Adding Application "%1" failed Additional information: • Check if there is another application with the same name in the List of Applications and Rules (Runtime Settings > Internet Protocol: ContentCheck). If there is, delete or rename the application. • Undo any manual changes that you have made to the ContentCheck XML file. • Disable ContentCheck: In VuGen, select Runtime Settings > Internet Protocol: ContentCheck, and clear the Enable ContentCheck during replay checkbox.
-32567	LRWI_AED_MSG_ADDING_RULE_FAILED_LOCATOR_KNOWN	Adding Rule "%1" within Application "%2" failed (before line %_3_Id, column %_4_Id in file "%5") Additional information: See error code -32566.
-32566	LRWI_AED_MSG_ADDING_RULE_FAILED_LOCATOR_UNKNOWN	Adding Rule "%1" within Application "%2" failed Additional information: • Check if there is another rule with the same name in the List of Applications and Rules (Runtime Settings > Internet Protocol: ContentCheck). If there is, delete or rename the listed rule. • Undo any manual changes that you have made to the ContentCheck XML file. • Disable ContentCheck: In VuGen, select Runtime Settings > Internet Protocol: ContentCheck, and clear the Enable ContentCheck during replay checkbox.
-32565	LRWI_AED_MSG_GENERAL_LOAD_INST_FAILED	Loading the Installation ContentCheck File failed
-32564	LRWI_AED_MSG_GENERAL_LOAD_DFLT_FAILED	Loading the Defaults ContentCheck File failed
-32563	LRWI_AED_MSG_GENERAL_LOAD_SCRIPT_FAILED	Loading the Script ContentCheck File failed
-32562	LRWI_AED_MSG_GENERAL_LOAD_IMPORTED_FAILED	Loading of the imported ContentCheck File failed
-32561	LRWI_AED_MSG_GENERAL_CREATING_DFLT_AED_FAILED	Creating the Defaults ContentCheck File failed
-32560	LRWI_AED_MSG_GENERAL_CREATING_SCRIPT_AED_FAILED	Creating the Script ContentCheck File failed
-32559	LRWI_AED_MSG_GENERAL_MERGING_INST_DFLT_FAILED	Merging the Installation ContentCheck File into the Defaults ContentCheck File failed
-32558	LRWI_AED_MSG_GENERAL_MERGING_DFLT_SCRIPT_FAILED	Merging the Defaults ContentCheck File into the Script ContentCheck File failed
-32557	LRWI_AED_MSG_GENERAL_MERGING_IMP_SCRIPT_FAILED	Merging the Imported ContentCheck File into the Script ContentCheck File failed
-32556	LRWI_AED_MSG_GENERAL_SAVING_DFLT_AED_FAILED	Saving the Defaults ContentCheck File failed
-32555	LRWI_AED_MSG_GENERAL_SAVING_SCRIPT_AED_FAILED	Saving the Script ContentCheck File failed
-32554	LRWI_AED_MSG_GENERAL_UNAVAILABLE_HOST_NAME	Could not obtain the client Host Name
-32553	LRWI_AED_MSG_SAVE_OPEN_FOR_READING_FAILED	Could not open file "%1" for reading Additional information: Verify that the specified file exists. Check the file permissions for the operating system user under which the replay process runs.
-32552	LRWI_AED_MSG_SAVE_OPEN_FOR_WRITING_FAILED	Could not open file "%1" for writing Additional information: Check the file permissions for the operating system user under which the replay process runs.
-32551	LRWI_AED_MSG_GENERAL_INIT_NOT_CALLED_OR_FAILED	The Global (per-process) initialization function (xfeLrwiAedGlobalInit) not called or failed. No other ContentCheck function can be called
-32550	LRWI_AED_MSG_INVALID_MARK	Invalid Mark value (%_1_Id) for Application "%2"
-32549	LRWI_AED_MSG_REMOVE_FILE_FAILED	Removing a ContentCheck file ("%1") failed (os_remove_file rc=%_2_Id) Additional information: Make a backup copy of the specified file, and then try to manually delete the original file. If you are unable to delete the file, change the file permissions, or terminate the applications that are using it, and try again.
LrwiWebInfra_res.h		
-32999	LRWI_MSG_URL_INVALID_SCHEME	Invalid scheme (not "http:" / "https:" / "ws:" / "wss:") in "%1"
-32998	LRWI_MSG_URL_INVALID_HOST_NAME	Invalid host name in URL="%1"
-32997	LRWI_MSG_COMMON_INVALID_ARG	Invalid argument to "%1"
-32996	LRWI_MSG_COMMON_NO_MEM	Not enough memory (%1 bytes) for %2

Error code	Handle	Message\Additional information
-32995	LRWI_MSG_URL_SCHEMES_MISMATCH	The scheme (e.g., "http:") in the base and relative URLs do not match, and the relative URL does not specify a server
-32994	LRWI_MSG_URL_INVALID_PORT	Invalid port "%1" in URL "%2"
-32993	LRWI_MSG_INTERNAL_ERROR	Internal Error - %1
-32992	LRWI_MSG_MORE_THAN_ONE_RESERVED_CHAR	More than one "%1" in the same URL component of "%2"
-32991	LRWI_MSG_IPNG_FORMAT_ERROR	The IPv6 format of %1 is incorrect. Make sure you use the correct format: [...]
-32990	LRWI_MSG_UNIX_NTLM_INV_PARAMS	When not under Windows, the domain and user name must be specified for NTLM authentication
-32989	LRWI_MSG_NOT_ENOUGH_MEM	Not enough memory (%_1_id bytes) for %2
-32988	LRWI_MSG_FUNC_CALL_FAILED	%1 failed, rc=%_2_id
-32987	LRWI_MSG_AUTH_DIGEST_PARSE_FAILURE	Unrecognized field "%1" in HTTP Digest Authorization line
-32986	LRWI_MSG_SEARCH_REGISTRATION	Search registration for "%1" parameter is filtered by "%2"
MLdapReplayRes.h		
-205370	LRMLDAP_ADD_RESULT	Add attempt returned: %1 (rc = %_2_id)
-205369	LRMLDAP_ADD_SUCCESS	Add successful.
-205368	LRMLDAP_ASYNC_DELETE_ATTR_FAILED	Asynchronous delete attribute attempt returned -1
-205367	LRMLDAP_ASYNC_DELETE_ENTRY_FAILED	Asynchronous delete entry attempt returned -1
-205366	LRMLDAP_ASYNC_RENAME_FAILED	Asynchronous rename attempt returned -1
-205365	LRMLDAP_ATTR_VALUE_BY_NO	Attribute #%_1_id = %2
-205364	LRMLDAP_ATTR_VALUE_BY_NAME	Attribute %1 = %2
-205363	LRMLDAP_EMPTY_ATTR_NAME	AttrName cannot be an empty string.
-205362	LRMLDAP_DELETE_SUCCESS	Delete successful.
-205361	LRMLDAP_CURRENT_ENTRY	Current Entry:DN = %1
-205360	LRMLDAP_AUTH_FAILED1	Failed to authenticate user %1 to server, please check credentials. (Error Returned: %2)
-205359	LRMLDAP_AUTH_FAILED2	Failed to authenticate user %1 to server, please check credentials. (Return Code = -1)
-205358	LRMLDAP_SESSION_INIT_FAILED	Failed to initialize LDAP session for '%1':%_2_id
-205357	LRMLDAP_NO_COLON_BETWEEN_NAME_AND_PASSWORD	Invalid Syntax: No : found between username and password in LDAP address.
-205356	LRMLDAP_NO_SERVER_ADDRESS	Invalid Syntax: Server address not found.
-205355	LRMLDAP_NO_USERNAME	Invalid Syntax: Username not found.
-205354	LRMLDAP_LOGOFF_SUCCESS	Ldap Logoff successful.
-205353	LRMLDAP_LOGON_SUCCESS	Logon to Ldap service '%1':%_2_id successful.
-205352	LRMLDAP_ANON_LOGON_SUCCESS	Logon to Ldap service '%1':%_2_id successful. (Anonymous Logon)
-205351	LRMLDAP_MODIFY_FAILED	Modify attempt returned -1
-205350	LRMLDAP_MODIFY_RETURNED	Modify attempt returned: %1
-205349	LRMLDAP_MODIFY_SUCCESS	Modify successful.
-205348	LRMLDAP_NO_VALUE_EXISTS	No value exists for the specified offset.
-205347	LRMLDAP_NO_VALUES_EXISTS	No values exist for the specified index\\name.
-205346	LRMLDAP_RENAME_SUCCESS	Rename successful.
-205345	LRMLDAP_RESULT_RETURNED	Result attempt returned -1
-205344	LRMLDAP_SEARCH_FAILED	Search attempt returned -1
-205343	LRMLDAP_SEARCH_RETURNED	Search attempt returned: %1
-205342	LRMLDAP_SEARCH_RETURNED_ENTRIES	Search Returned %_1_id Entries
-205341	LRMLDAP_SEARCH_STARTED	Search started.
-205340	LRMLDAP_SET_TIMEOUT_FAILED	Set timeout error: %1 (Timeout Ignored)
-205339	LRMLDAP_SET_TIMEOUT_FAILED2	Set timeout error: %1
-205338	LRMLDAP_SYNC_DELETE_ATTR_RETURNED	Synchronous delete attribute attempt returned: %1
-205337	LRMLDAP_SYNC_DELETE_ENTRY_RETURNED	Synchronous delete entry attempt returned: %1
-205336	LRMLDAP_SYNC_RENAME_RETURNED	Synchronous rename attempt returned: %1
-205335	LRMLDAP_SESSION_CREATE_FAILED	Unable to create an LDAP user session object.
-205334	LRMLDAP_UNBIND_RETURNED	Unbind attempt returned: %1
-205333	LRMLDAP_INVALID_SERVER_TYPE	Invalid Server Type: Expected ldap or ldaps
-205332	LRMLDAP_INVALID_URL	Invalid ldap url entry (should be URL=ldap://username:password@server:port or URL=ldaps://username:password@server:port).
-205331	LRMLDAP_SSL_CERT_DIR_MISSING	The parameter SslCertDir is missing. Please add this parameter to mldap_logon(ex) call and have it equal the directory where a Cert8.db formatted file and a Key3.db file reside. If the Cert8.db formatted file has any name other than Cert8.db, then please include the name of the file along with the directory. Format: "SslCertDir=<CERT_DIR>\\<CERT_FILE>". Please place the paramter before "LAST".
-205330	LRMLDAP_INVALID_SSL_CERT_DIR	The parameter SslCertDir must equal equal the directory where a Cert8.db formatted file and a Key3.db file reside. If the Cert8.db formatted file has any name other than Cert8.db, then please include the name of the file along with the directory. Format: "SslCertDir=<CERT_DIR>\\<CERT_FILE>".

Error code	Handle	Message\Additional information
-205329	LRMLDAP_COMPARE_HELP	Please ensure that there is a DN, a ATTRIB, and a VALUE parameters. SAVERESULT parameter is optional. Ex. mldap_compare("LdapCompare","DN=Users","ATTRIB=State","VALUE=California","SAVERESULT=compRes",LAST);
-205328	LRMLDAP_COMPARE_FAILED	An error occurred while performing the compare: %1
-205327	LRMLDAP_COMPARE_RESULT	Part of the DN that matches an existing entry: %1
-205326	LRMLDAP_COMPARE_RETURNED	The compare returned: %1
-205325	LRMLDAP_SET_VERSION_FAILED	Set version error: %1
-205324	LRMLDAP_SET_OPTION_FAILED	Failed to set option %1 : %2
-205323	LRMLDAP_GET_OPTION_FAILED	Failed to get option %1 : %2
-205322	LRMLDAP_PARAM_REQUIRED	Parameter required : %1
-205321	LRMLDAP_SSL_FAILED	Failed to initialize client side SSL. LDAP library returned error : %1. Probably, Cert8.db file is missing or corrupted.
-205320	LRMLDAP_SSL_CERT_ENABLE_FAILED	Failed to enable SSL client certificate authentication : %1
-205319	LRMLDAP_ENABLE_TLS_FAILED	Failed to start TLS : %1
-205318	LRMLDAP_INVALID_SESSION	Invalid session : server was not specified.
-205317	LRMLDAP_TLS_ALREADY_ON	TLS is already ON. Second attempt will probably fail.
-205316	LRMLDAP_SSL_CHANGES_IGNORED	SSL certificates configuration can't be changed. Changes are ignored.
-205315	LRMLDAP_NO_ATTR_NO	Attribute # % 1 Id not found
-205314	LRMLDAP_SESSION_SSL_INIT_FAILED	Failed to initialize LDAP SSL session for "%1": % 2 Id. (Error Returned: %3)
-205313	LRMLDAP_SESSION_SSL_ENABLE_FAILED	Failed to enable SSL for LDAP session "%1": % 2 Id. (Error Returned: %3)
MicrosoftAzure.msgs.h		
-207299	LOCATION	Location
-207298	IMAGE	Image
-207297	STORAGE_ACCOUNT	Storage Account
-207296	USER	User
-207295	PASSWORD	Password
-207294	PORTS	Additional Ports
-207293	SIZE	Size
-207292	MEDIA_LINK	Media Link
-207291	STORAGE_ACCOUNT_DESC	All access to storage services takes place through the storage account. The storage account is the highest level of the namespace for accessing each of the fundamental services
-207290	IMAGE_DESC	The machine image contains the root file system for the image
-207289	SIZE_DESC	Virtual machines are now available in two tiers - basic or standard. Both types offer a choice of sizes.\n\nThe Standard tier of sizes now includes D-series VMs, designed to run applications that demand higher compute power and temporary disk performance.\n\nD-series VMs provide faster processors, a higher memory-to-core ratio, and a solid-state drive (SSD) for the temporary disk
-207288	RETYPE_PASSWORD	Retype password
-207287	LOCATION_DESC	Each location is a separate geographic area
-207286	USER_DESC	User name for logging into virtual machine
-207285	PASSWORD_DESC	Password for logging into virtual machine
-207284	PORTS_DESC	Additional ports to open in firewall
-207283	CERT_HELP	You can upload management certificates to the Azure certificate store for your subscription, using the Management Portal.
-207282	SUBSCRIPTION_HELP	A Microsoft Azure subscription is a unique user account in Azure. All resources available via the Service Management API are organized beneath the subscription. When you create an Azure subscription, it is uniquely identified by a subscription ID.
-207281	SUBSCRIPTION_ID	Subscription Id
-207280	PATH_TO_CERTIFICATE	Path to certificate
MqttReplayRes.h		
-222999	MQTT_MESSAGE_DESCRIPTION	Message from '% 1 s' with QoS=% 2 Id (% 3 s):
-222998	MQTT_MESSAGE_CONTENT	::: % 1_s ::: Additional information: This contains the payload of the message.
-222997	MQTT_INVALID_SETTING	Invalid '% 1 s' setting value, fall back to the default: % 2 s
-222996	MQTT_SETTING_VALUE	Read '% 1 s' setting: % 2_s
-222995	MQTT_AUTO_MESSAGE_LENGTH	Calculating payload length
-222994	MQTT_CREATE	Created new connection
-222993	MQTT_ASSIGN_CLIENT_ID	Assigned Client ID: % 1 s
-222992	MQTT_CONNECTING	Connecting to % 1 s
-222991	MQTT_CONNECTED	Connection successful

Error code	Handle	Message\Additional information
-222990	MQTT_DISCONNECTING	Disconnecting from server
-222989	MQTT_DISCONNECTED	Disconnection successful
-222988	MQTT_SUBSCRIBING	Subscribing to % 1 s
-222987	MQTT_SUBSCRIBED	Subscription successful
-222986	MQTT_UNSUBSCRIBING	Unsubscribing from % 1 s
-222985	MQTT_UNSUBSCRIBED	Unsubscription successful
-222984	MQTT_PUBLISHING	Publishing % 1 Id bytes to % 2 s
-222983	MQTT_PUBLISHED	Publishing successful
-222982	MQTT_SET_CLIENT_ID	Set Client ID to '% 1 s'
-222981	MQTT_FREE_MESSAGE	Dispose message with ID = % 1 Id
-222980	MQTT_GET_PAYLOAD	Retrieve payload of the message with ID = % 1 Id
-222979	MQTT_GET_PAYLOAD_LENGTH	Retrieve payload length of the message with ID = % 1 Id
-222978	MQTT_GET_TOPIC	Retrieve topic of the message with ID = % 1 Id
-222977	MQTT_SET_CREDENTIALS	Set credentials to % 1 s : % 2 s
-222976	MQTT_SET_TLS_PARAMETERS	Set TLS parameters to % 1 s : % 2 s
-222975	MQTT_SET_TLS_CERTIFICATE	Set TLS certificate parameters: certificate path '% 1 s', private key path '% 2 s', password % 3 s
-222974	MQTT_SET_LWT	Set Last Will and Testament message
-222973	MQTT_SET_DEFAULT_WAIT_TIMEOUT	Use default message wait timeout: % 1 Id msec
-222972	MQTT_AWAITING_MESSAGES	Wait for messages to arrive to the Inbox
-222971	MQTT_INBOX_SIZE	Inbox size: % 1 Id messages
-222970	MQTT_INBOX_CLEAR	Inbox cleared, deleted % 1 Id messages
-222969	MQTT_INBOX_READING	Reading message from Inbox
-222968	MQTT_INBOX_READ	Read Inbox successfully
-222967	MQTT_MESSAGE_SAVED	Message saved to cache, ID = % 1 Id
-222966	MQTT_EXCEPTION	% 1 s Additional information: This contains an explanatory message for the given exception.
-222965	MQTT_CLIENT_ERROR	MQTT Client failure (% 1 s)
-222964	MQTT_NOT_CONNECTED	Not connected to any server
-222963	MQTT_TIMED_OUT	The action '% 1 s' has timed out
-222962	MQTT_DUPLICATE_CLIENT_ID	Server closed the connection. Probably, another client with Client ID '% 1 s' has just connected, or the server doesn't support the passed parameters.
-222961	MQTT_CONNECTION_FAILED	Connection to % 1 s has failed (% 2 s)
-222960	MQTT_WRONG_PARAMETER	Wrong value of the parameter '% 1 s'
-222959	MQTT_TOO_MANY_CLIENTS	Unable to create more than % 1 Id clients
-222958	MQTT_INBOX_OVERFLOW	Inbox of the client with ID '% 1 s' has % 2 Id messages although it is not allowed to store more than % 3 Id messages
-222957	MQTT_RECONNECTING	Connection lost. Reconnecting in % 1 Id milliseconds...
-222956	MQTT_DATAPOINT_ERROR	Data point processing error: % 1 s
-222955	MQTT_PARAMETERIZATION_ERROR	Failed to substitute parameters in a string
-222954	MQTT_ALREADY_CONNECTED	The client is already connected to server
-222953	MQTT_UNFINISHED_REQUEST	% 1 s request has not been finished due to reconnect
-222952	MQTT_TOO_MANY_RECONNECTS	Number of reconnect attempts exceeded the maximum value (% 1 Id)
-222951	MQTT_CHANGE_SETTING_WHILE_CONNECTED	Changing setting while being connected will not affect current session
-222950	MQTT_WIZZ_ERR_NOT_BOOL	Entry % 1 s is not a boolean value.
-222949	MQTT_WIZZ_ERR_NOT_STRING	Entry % 1 s is not of type string.
-222948	MQTT_WIZZ_ERR_NOT_INT	Entry % 1 s is not of type int.
-222947	MQTT_WIZZ_ERR_NOT_FOUND	% 1 s not found.
-222946	MQTT_WIZZ_ERR_AUTH	Authentication needed.
-222945	MQTT_WIZZ_NO_AUTH	No authentication needed.
-222944	MQTT_WIZZ_ERR_PASS	Password is missing!
-222943	MQTT_WIZZ_USER	User name: % 1 s.
-222942	MQTT_WIZZ_ERR_USER	User name is missing!
-222941	MQTT_WIZZ_TEST	Have last will and testament.
-222940	MQTT_WIZZ_LWT	Last will and testament topic: % 1 s.
-222939	MQTT_WIZZ_ERR_LWT	Last Will and Testament topic is missing.
-222938	MQTT_WIZZ_LWT_PAYLOAD	Last Will and Testament payload: % 1 s.
-222937	MQTT_WIZZ_ERR_LWT_PAYLOAD	Last Will and Testament payload is missing!

Error code	Handle	Message\Additional information
-222936	MQTT_WIZZ_LW_RET_T	Is LW retained: true.
-222935	MQTT_WIZZ_LW_RET_F	Is LW retained: false.
-222934	MQTT_WIZZ_NO_LW	No last will and testament.
-222933	MQTT_WIZZ_ENCR	Encryption enabled.
-222932	MQTT_WIZZ_NO_ENCR	No encryption enabled.
-222931	MQTT_WIZZ_CERT	Certificate path: % 1 s.
-222930	MQTT_WIZZ_ERR_CERT	Certificate path is missing!
-222929	MQTT_WIZZ_PRIVATE_KEY_PATH	Private key path: % 1 s.
-222928	MQTT_WIZZ_ERR_PRIVATE_KEY_PATH	Private key file path is missing!
-222927	MQTT_WIZZ_COMM_SSL	\\t/* SSL settings */
-222926	MQTT_WIZZ_TLS	TLS Settings enabled.
-222925	MQTT_WIZZ_NO_TLS	No TLS settings enabled.
-222924	MQTT_WIZZ_COMM_TLS	\\t/* TLS settings */
-222923	MQTT_WIZZ_BROKER_URL	Broker URL: % 1 s.
-222922	MQTT_WIZZ_COMM_CONN	\\t/* Connect to an MQTT broker */
-222921	MQTT_WIZZ_ERR_BROKER_URL	Connection URL is missing!
-222920	MQTT_WIZZ_COMM_DISC	\\t/* Disconnect % 1 s */
-222919	MQTT_WIZZ_SUBS	We have subscriber.
-222918	MQTT_WIZZ_NO_SUBS	No subscriber enabled.
-222917	MQTT_WIZZ_TOPIC_SUBS	Topic to subscribe: % 1 s.
-222916	MQTT_WIZZ_ERR_TOPIC_SUBS	Subscriber topic is missing!
-222915	MQTT_WIZZ_COMM_SUBS	\\t/* Subscribe to topic: % 1 s */
-222914	MQTT_WIZZ_COMM_UNSUBS	\\t/* Unsubscribe from topic: % 1 s */
-222913	MQTT_WIZZ_UNSUB	Unsubscribe, end of script.
-222912	MQTT_WIZZ_ERR_PUB_TOPIC	Publisher topic is missing!
-222911	MQTT_WIZZ_ERR_PUB_PAYLOAD	Publisher payload is missing!
-222910	MQTT_WIZZ_COMM_DECLAIED	\\t/* Declared in % 1 s" */
-222909	MQTT_WIZZ_COMM_OPTIONAL_CONN	\\t/* Optional connection settings */
-222908	MQTT_WIZZ_PUB	Publisher enabled.
-222907	MQTT_WIZZ_TOPIC_PUB	Topic to publish: % 1 s.
-222906	MQTT_WIZZ_PAYLOAD	Payload: % 1 s.
-222905	MQTT_WIZZ_QA	Quality of service: % 1 s.
-222904	MQTT_WIZZ_RET_T	Retain: true.
-222903	MQTT_WIZZ_RET_F	Retain: false.
-222902	MQTT_WIZZ_XML	XML file load result: % 1 s.
-222901	MQTT_WIZZ_ERR_XML	Failed to read XML!
-222900	MQTT_WIZZ_ERR_XML_PATH	XML path is missing!
-222899	MQTT_WIZZ_ERR_TEMP_PATH	Temp directory path is missing!
-222898	MQTT_WIZZ_COMM_GEN	\\n***SCRIPT GENERATION***\\n
-222897	MQTT_WIZZ_ERROR	Script generation failed!
-222896	MQTT_WIZZ_ERR_OPEN	Failed to open % 1 s file!
-222895	MQTT_WIZZ_ERR_SCRIPT	Script folder path is missing!
-222894	MQTT_WIZZ_INFO	Added to % 1 s.
-222893	MQTT_WIZZ_ERR	Error
Pop3ReplayRes.h		
-205720	LRPOP3_USER_NAME_FAILED	User name failed.
-205719	LRPOP3_COMMAND	Command: % 1 s
-205718	LRPOP3_LOGON_FAILED	Logon Failed (Socket ID = 0)
-205717	LRPOP3_COMMAND_SEND_FAILED	Error sending % 1 s command to server.
-205716	LRPOP3_RECV_FAILED	Error after recving % 1 ld bytes from socket (socket error = % 2 ld).
-205715	LRPOP3_RECV_EMAIL_FAILED	Error recieving email from server.
-205714	LRPOP3_RECV_DELE_FAILED	Error received from server after sending DELE % 1 ld command.
-205713	LRPOP3_RECV_LIST_FAILED	Error received from server after sending LIST command.
-205712	LRPOP3_RECV_RETR_FAILED	Error received from server after sending RETR command.
-205711	LRPOP3_RECV_STAT_FAILED	Error received from server after sending STAT command.
-205710	LRPOP3_SEND_DELE_FAILED	Error sending DELE % 1 ld command to server.

Error code	Handle	Message\Additional information
-205709	LRPOP3_SEND_LIST_FAILED	Error sending LIST command to server.
-205708	LRPOP3_SEND_RETR_FAILED	Error sending RETR command to server.
-205707	LRPOP3_SEND_STAT_FAILED	Error sending STAT command to server.
-205706	LRPOP3_SEND_LOGON_FAILED	Error sending user name and password.
-205705	LRPOP3_CONNECT_FAILED	Failed to connect: Check server address and port number.
-205704	LRPOP3_ID_RECV_FAILED	Failed to receive POP3 server identification.
-205703	LRPOP3_SHOW_MAIL	if (showMail) % 1 s
-205702	LRPOP3_SHOW_MAIL_END_BODY	if (showMail) ***** End of Mail Body *****\r\n
-205701	LRPOP3_INVALID_SYNTAX1	Invalid Server Type: Expected pop3://user:pass@server[:port] or pop3s://user:pass@server[:port], Received: % 1 s
-205700	LRPOP3_INVALID_SYNTAX2	Invalid Syntax: No : found between password and username in URL.
-205699	LRPOP3_INVALID_SYNTAX3	Invalid Syntax: No @ found between password and server name.
-205698	LRPOP3_INVALID_SYNTAX4	Invalid Syntax: Server address not found
-205697	LRPOP3_INVALID_SYNTAX5	Invalid Syntax: Username not found.
-205696	LRPOP3_LIST_SUCCESS	List completed successfully.\r\n
-205695	LRPOP3_LIST_ALL	Listing all available messages\r\n
-205694	LRPOP3_QUIT_RECV_FAILED	Error received from server after sending QUIT command.
-205693	LRPOP3_QUIT_SEND_FAILED	Error sending QUIT command to server.
-205692	LRPOP3_MAIL_DELETED	Mail% 1 Id deleted.
-205691	LRPOP3_MESSAGE_BYTES	Message #% 1 Id - % 2 Id bytes\r\n
-205690	LRPOP3_LIST_NOTICE	List notice : 'Message' must be a positive integer. The parameter was ignored.
-205689	LRPOP3_DELETE_NO_MAIL	No mail on server to delete.
-205688	LRPOP3_LIST_NO_MAIL	No mail on server to list.
-205687	LRPOP3_RETRIEVE_NO_MAIL	No mail on server to retrieve.
-205686	LRPOP3_PASSWORD_FAILED	Password failed.
-205685	LRPOP3_SECURE_CONN_FAILED	Failed to establish a secure POP3 session.
-205684	LRPOP3_LOGON_SUCCESS	Pop3 Logon successful.
-205683	LRPOP3_SESSION_CLOSED	Pop3 session closed.
-205682	LRPOP3_SESSION_NOT_EXIST	Pop3 session does not exist, nothing to free.
-205681	LRPOP3_SESSION_FREED	Pop3 session freed.
-205680	LRPOP3_RECEIVED_BYTES	Received % 1 Id bytes (requested % 2 Id bytes)
-205679	LRPOP3_RECEIVED_EMAIL	Receiving Email #% 1 Id\r\n
-205678	LRPOP3_RECEIVED_WARNING	Retrieve Warning: No messages to retrieve (Expecting: RetrieveList=# argument).
-205677	LRPOP3_RETRIEVED_WARNING	Server Reply: % 1 s\r\n
-205676	LRPOP3_SERVER_RETURNED	Server returned: -ER% 1 s
-205675	LRPOP3_MESSAGE_OUT_OF_RANGE	The specified message is out of range. 'Message' must be within total messages (% 1 Id).
-205674	LRPOP3_LIST_TIMEOUT	Time out error receiving list from server.
-205673	LRPOP3_TOTAL_MESSAGES	Total Messages : % 1 Id messages (% 2 Id Bytes)
-205672	LRPOP3_SESSION_CREATION_FAILED	Unable to create a POP3 user session object.
-205671	LRPOP3_SESSION_ESTABLISHED	Establish new POP3 Session to % 1 s: % 2 Id as % 3 s
-205670	LRPOP3_END_OF_BODY	***** End of Mail Body *****\r\n
-205669	LRPOP3_LOGON_FAILED2	Command Error: Cannot Send Command: Logon Failed (Socket ID = 0)
-205668	LRPOP3_LOGON_FAILED3	Cannot Send Logoff Request: Logon Failed (Socket ID = 0)
SFTP_res.h		
-1000100	SFTP_NULL_ARG	Argument "%1" is NULL.
-1000099	SFTP_INVALID_ARG_VALUE	Argument "%1" has invalid value.
-1000098	SFTP_WRONG_QUIT_REPLY	Wrong QUIT reply code % 1 Id.
-1000097	SFTP_RECEIVED_DATA	Received data from server.
-1000096	SFTP_QUIT_EARLY_DISCONNECT	Server disconnected us without an answer.
-1000095	SFTP_LIST_DIR	Listing directory...
-1000094	SFTP_LIST_FAILED	Directory listing failed. %1.
-1000093	SFTP_LOG_OFF	Logging off...
-1000092	SFTP_LOGOFF_FAILED	Failed to log off. %1.
-1000091	SFTP_LOGON_FAILED	Failed to log on. %1.
-1000090	SFTP_LOG_ON	Logging on to "%1".
-1000089	SFTP_CWD	Changing directory to "%1"...
-1000088	SFTP_CWD_FAILED	Directory change failed. %1.

Error code	Handle	Message\Additional information
-1000087	SFTP_SEND_COMMAND	Send command "%1".
-1000086	SFTP_SERVER_REPLY	Server reply:\n%1
-1000085	SFTP_WELCOME_MESSAGE_ERROR	Failed to load Welcome Message file "%1".
-1000084	SFTP_WELCOMES_EQUAL	Welcome message is the same as while recording.
-1000083	SFTP_WELCOMES_NOT_EQUAL	Welcome messages are different\nExpected:\n%1\nGot:\n%2
-1000082	SFTP_SESSION_TIME	Session time: %_1_ld msec.
SapMediator_res.h		
-107399	SAP_MED_DONE	SAP Mediator done
-107398	SAP_DLL_VERSION	SAP Mediator version %1
-107397	SAP_ERR_FAILED_TO_INITIALIZE_LOG_OR_INI	Could not read INI files or setting output message logging failed
-107396	SAP_ERR_FAILED_TO_SEND_SAMPLES	Failed to send data
-107395	SAP_ERR_FAILED_TO_LOCATE_TRANS_SERVER	No valid connection to transaction server
-107394	SAP_ERR_MONITOR_DCOM_OBJECT_PROGID_IS_MISSING	Monitor failed to initialize DCOM object: ProgID is empty
-107393	SAP_ERR_MONITOR_FAILED_TO_CREATE_DCOM_OBJECT	Monitor failed to create instance of DCOM object
-107392	SAP_ERR_COCREATEINSTANCE_FAILED	Failed to create instance of object "%1": %2
-107391	SAP_ERR_FAILED_TO_CREATE_COM_OBJECT	Failed to create COM object
-107390	SAP_ERR_UNEXPECTED_RFC_DESTINATION_FORMAT	Unexpected format of RFC Destination name
-107389	SAP_ERR_FAILED_TO_INIT_LOGON_INFO	Failed to initialize logon info in DCOM object
-107388	SAP_ERR_FAILED_TO_CREATE_RFC_DESTINATION	Failed to define destination for RFC connection
-107387	SAP_ERR_FAILED_TO_SET_MONITOR_CONNECTION	Monitor failed to initialize conenction to SAP server
-107386	SAP_ERR_BAD_FUNCTION_PARAMETERS	Wrong parameters passed to the function
-107385	SAP_ERR_MISSING_DATA_TO_INVOKE_FUNCTION	Missing data to invoke RFC function
-107384	SAP_NOTIFY_CLIENT_NOT_INITIALIZED	Monitor client is not initilaized
-107383	SAP_ERR_FAILED_TO_INVOKE_FUNCTION	Failed to invoke RFC function "%1": %2
-107382	SAP_ERR_CANT_SELECT_FUNCTION	Mediator failed to select function
-107381	SAP_ERR_GETIDSOFNAMES_FAILED	Failed to find function "%1" in object "%2": %3
-107380	SAP_ERR_PUT_PROPERTY_FAILED	Failed to change property "%1": %2
-107379	SAP_ERR_FAILED_TO_RETRIEVE_SYSTEM_INFO	Failed to retrieve system info: %1
-107378	SAP_ERR_FAILED_TO_CREATE_SYSTEM_INFO_OBJECT	Failed to create instance of DCOM object for retrieving system info
-107377	SAP_ERR_COULD_NOT_GET_FIELDS_COLLECTION	Failed to get "Fields" collection from recordset: %1
-107376	SAP_ERR_COULD_NOT_FIND_FIELD_IN_RECORDSET	Failed to find field "%1" in recordset: %2
-107375	SAP_ERR_COULD_NOT_GET_VALUE_FROM_RECORDSET	Failed to get value of field "%1": %2
-107374	SAP_ERR_FAILED_TO_READ_TABLE_FIELDS	Failed to read table fields
-107373	SAP_ERR_NO_NUM_OF_FIELDS_MATCH	The number of fields do not match
-107372	SAP_NOTIFY_FAILED_TO_START_MONITOR	Failed to initialize one of the monitors
-107371	SAP_ERR_FAILED_TO_ADD_SERVER_MONITOR	One or more monitors could not be added to process
-107370	SAP_ERR_FAILED_TO_RELEASE_MONITOR	Failed to release monitor
-107369	SAP_ERR_FAILED_TO_ALLOCATE_MEMORY_FOR_MONITOR	Failed to create new servers monitor
-107368	SAP_ERR_FAILED_TO_RELEASE_SOME_MONITORS	Some of the monitors could not be released
-107367	SAP_ERR_FAILED_TO_GET_SRV_TOPOLOGY	Failed to get servers topology through the designated server
-107366	SAP_ERR_FAILED_TO_CREATE_SERVER_OBJ	Failed to create new "%1" server object, memory error
-107365	SAP_ERR_FAILED_TO_ACCESS_SERVER	Server "%1" is unreachable
-107364	SAP_ERR_FAILED_TO_CREATE_SERVER_COLLECTOR	Failed to create monitor for "%1" server
-107363	SAP_ERR_FAILED_TO_GET_SERVER_INFO	One or more servers data could not be retrieved
-107362	SAP_ERR_FAILED_TO_RELEASE_TOPOLOGY_EXPLORER	Failed to release Topology explorer
-107361	SAP_ERR_FAILED_TO_CREATE_TOPOLOGY	Failed to create server topology
-107360	SAP_ERR_FAILED_TO_RELEASE_TOPOLOGY	Failed to terminate server topology
-107359	SAP_ERR_EXPLORE_FAILED	Failed to get SAP topology from designated server
-107358	SAP_ERR_EXPLORE_FAILED_MSG	Failed to get SAP topology from designated server: %1
-107357	SAP_ERR_GET_LOCAL_SERVERS_FAILED	Failed to get list of SAP servers: %1
-107356	SAP_ERR_FAILED_TO_CREATE_COLLECTOR	One or more monitors do not work
-107355	SAP_ERR_EXPLORE_NO_BD_DATA_WILL_BE_AVAILABLE	No SAP diagnostics data will be collected
-107354	SAP_ERR_SRMON_FAILED_TO_CREATE	Failed to create SR monitor for SAP server "%1"
-107353	SAP_ERR_SRMON_FAILED_TO_INITIALIZE	Failed to initialize SR monitor for SAP server "%1"
-107352	SAP_ERR_SRMON_FAILED_TO_FETCH_DATA	Failed to retrieve SR data for SAP server "%1": %2
-107351	SAP_ERR_SRMON_NO_DATA_FOR_INTERVAL	No SR data was collected for SAP server "%1" %2

Error code	Handle	Message\Additional information
-107350	SAP ERR SRMON FAILED TO READ SERVER TIME	Failed to read time on SAP server %1
-107349	SAP ERR FAILED TO READ DATA FROM SR	Failed to read data from SR monitor
-107348	SAP ERR WPMON FAILED TO CREATE	Failed to create work processes monitor for SAP server "%1"
-107347	SAP ERR WPMON FAILED TO INITIALIZE	Failed to initialize work processes monitor for SAP server "%1"
-107346	SAP ERR WPMON FAILED TO FETCH DATA	Failed to retrieve status of work processes on SAP server "%1": %2
-107345	SAP ERR WPMON NO DATA FOR INTERVAL	No work processes data was collected for SAP server "%1" %2
-107344	SAP ERR FAILED TO READ DATA FROM WP	Failed to read data from Work Process monitor
-107343	SAP ERR OSMON FAILED TO CREATE	Failed to create OS monitor for SAP server "%1"
-107342	SAP ERR OSMON FAILED TO INITIALIZE	Failed to initialize OS monitor for SAP server "%1"
-107341	SAP ERR OSMON FAILED TO FETCH DATA	Failed to retrieve OS monitor data on SAP server "%1": %2
-107340	SAP ERR OSMON NO DATA FOR INTERVAL	No OS monitor data was collected for SAP server "%1" %2
-107339	SAP ERR FAILED TO READ DATA FROM OS	Failed to read data from Operating System monitor
-107338	SAP ERR VICOL FAILED TO CREATE	Failed to create Version Info collector for SAP server "%1"
-107337	SAP ERR VICOL FAILED TO INITIALIZE	Failed to initialize Version Info collector for SAP server "%1"
-107336	SAP ERR VICOL FAILED TO FETCH DATA	Failed to retrieve version information for SAP server "%1": %2
-107335	SAP SCENARIO TIME TEMPLATE	from %1 to %2
-107334	SAP SCENARIO TIME WHOLE	for whole scenario time
ScriptApi_res.h		
-238999	MSG SCRIPT API INTERNAL ERROR	Internal Error (call Customer Service): %1
-238998	MSG SCRIPT API ARG SPECIFIED ALREADY	The "%1" argument (#% 2 _ld) was specified more than once.
-238997	MSG SCRIPT API ARG MISSING EMPTY	The "%1" argument is missing or empty
-238996	MSG SCRIPT API ARG UNRECOG	The "%1" argument (#% 2 _ld) is invalid or not recognized at this position in the function call
-238995	MSG SCRIPT API ARG ONE OF 2 MUST BE SPECIFIED	One of the arguments "%1"/"%2" must be specified
-238994	MSG SCRIPT API ARG ONE OF 3 MUST BE SPECIFIED	One of the arguments "%1"/"%2"/"%3" must be specified
-238993	MSG SCRIPT API ARG NOT BOOLEAN	The "%1" argument (#% 2 _ld) does not specify a valid Boolean value (e.g. "true", "false", "on", "off", "yes", "no", "1", "0")
-238992	MSG SCRIPT API BOTH ARGS	Either both or none of the "%1" and "%2" arguments should be specified
-238991	MSG SCRIPT API ARG MISSING	Required argument ("%1") is missing or not recognized at this position in the function call
-238990	MSG SCRIPT API 2 ARGS EXCL	The arguments "%1"/"%2" are mutually exclusive
-238989	MSG SCRIPT API 3 ARGS EXCL	The arguments "%1"/"%2"/"%3" are mutually exclusive
-238988	MSG SCRIPT API ARG ONE OF 4 MUST BE SPECIFIED	One of the arguments "%1"/"%2"/"%3"/"%4" must be specified
-238987	MSG SCRIPT API 4 ARGS EXCL	The arguments "%1"/"%2"/"%3"/"%4" are mutually exclusive
-238986	MSG SCRIPT API ARG REGEXP NOT SUPPORTED	Regular expressions (/RE) are not supported for the "%1" argument (#% 2 _ld)
-238985	MSG SCRIPT API 2 ARGS INCL	At least one of the arguments "%1"/"%2" must be specified
-238984	MSG SCRIPT API ARG SET MISSING	Required "%1" argument collection is missing.
-238983	MSG SCRIPT API ARG SET MISSING END KW	Invalid "%1"(% 2 _ld) arguments - end marker ("%3") is missing
-238982	MSG SCRIPT API ARG SET MISSING END KW NO INDEX	Invalid "%1" arguments - end marker ("%2") is missing
-238981	MSG SCRIPT API ARG FILE NOT FOUND	File not found "%1"
-238980	MSG SCRIPT API GENERIC ERROR	"%1"
-238979	MSG SCRIPT API INVALID VALUE	"Invalid value for the "%1" argument (number % 2 _ld)"
-238978	MSG SCRIPT API ARG OPTION INVALID EXPLAINED	Problem with %1 for the "%2" argument, (number % 3 _ld). Using %4 in argument of type %5 is illegal/unsupported
-238977	MSG SCRIPT API ERROR PREFIX	"Error: "
-238976	MSG SCRIPT API WARNING PREFIX	"Warning: "
SiebelMediator_res.h		
-107199	MSR MED DONE	Siebel ARM Mediator done.
-107198	MSR DLL VERSION	Siebel ARM Mediator version %1
-107197	MSR OUT OF MEM	Out of memory for %1
-107196	MSR OUT OF MEM WITH SIZE	Out of memory for %1 (size % 2 _ld)
-107195	MSR REGISTER SERVER	Registering server "%1" "%2" "%3" "%4" ID=% 5 _ld
-107194	MSR INVALID SERVER TYPE	Invalid server type (%1)
-107193	MSR MAX SERVERS MSG	Maximum number of servers is limited to % 1 _ld
-107192	MSR NO WEB SERVERS	No Web servers in topology
-107191	MSR NO APP SERVERS	No App servers in topology
-107190	MSR FILE COPY REQ	Requesting copy of file "%1" from server "%2"
-107189	MSR PROCESSING FILE	Processing file "%1"
-107188	MSR SERVER NAME	Server name "%1"

Error code	Handle	Message\Additional information
-107187	MSR_GETTIMEOFDAY_FAILED	Function "gettimeofday" failed
-107186	MSR_SYSTEM_FUNC_FAILED	System function %1 failed (System Error % 2_Id)
-107185	MSR_CREATE_ANALYZER_FAILED	Failed to create SarmAnalyzer process (System Error %_1_Id). Check that you copied the required dll files from the Siebel application server to the mediator machine. For more information, refer to the Help Center.
-107184	MSR_PROCESSING_FILE_DONE	Processed file of %_1_Id bytes. Time taken: %2 seconds
-107183	MSR_NO_TRANS	No transactions found
-107182	MSR_TOTAL_TRANS	Total number of transactions found is %_1_Id
-107181	MSR_NO_FILES_FOUND	No files found for server "%1" in directory "%2"
-107180	MSR_FAIL_TO_OPEN_FILE	Fail to open file "%1" for reading
-107179	MSR_SIEBEL_753_FORMAT	Siebel7.53 CSV format detected
-107178	MSR_SIEBEL_77_FORMAT	Siebel7.7 CSV format detected
-107177	MSR_ILLEGAL_HEADER_TOK	Illegal token "%1" at the header of the CSV file
-107176	MSR_INVALID_CSV_FORMAT	Invalid input file. (level = %_1_Id, i = %_2_Id, rc = %_3_Id)"
-107175	MSR_INVALID_AREA	Invalid Area (%_1_Id)
-107174	MSR_INVALID_AREA_SUB	Invalid Area/SubArea (%_1_Id/%_2_Id)
-107173	MSR_WRONG_WEB_AREA	Incorrect configuration setting. Area %1 is found in Web server %2. Please change Server Type setting to App.
-107172	MSR_WRONG_APP_AREA	Incorrect configuration setting. Area %1 is found in App server %2. Please change Server Type setting to Web.
-107171	MSR_UNKNOWN_AREA	Unknown Area Symbol (%1)
-107170	MSR_UNKNOWN_SUB_AREA	Unknown Sub Area Symbol (%1)
-107169	MSR_PERFORMANCE_PROBLEM_DELETED_FILE	Some files were deleted from directory %1 before being copied to the mediator machine. Check that the number of files parameter (SARMMMaxFiles/SIEBEL_SARMMMaxFiles) or the file size parameter (SARMMMaxFileSize/SIEBEL_SARMMMaxFileSize) on Siebel server machine %2 is not too small. Otherwise check that mediator machine has sufficient resources.
-107168	MSR_DIR_OPERATION_FAILED	Dir operation on server "%1" directory "%2" failed with code %_3_Id
-107167	MSR_FILE_COPY_ERR	Error copying file "%1" (code=%_2_Id)
-107166	MSR_DUP_CLICKID	%_1_Id duplicated ClickID(s) found. The results may be inaccurate. Delete all Siebel ARM logs and run the scenario again.
-107165	MSR_TIMER_SET	Timer interval set to %_1_Id seconds
-107164	MSR_INTERNAL_ERROR	Internal Error: Please contact HP Customer Support (Err Msg: "%1", Function: "%2", Code: "%_3_Id")
-107163	MSR_FAIL_TO_LOAD_RESOURCE	Fail to load resource file "%1"
-107162	MSR_AREA_NOT_FOUND	Area ID %_1_Id not found in resource file "%2"
-107161	MSR_SUB_AREA_NOT_FOUND	Sub Area ID %_1_Id in Area ID %_2_Id not found in resource file "%3"
-107160	MSR_AREA_SYMBOL_NOT_FOUND	Area symbol %1 not found in resource file "%2"
-107159	MSR_SUB_AREA_SYMBOL_NOT_FOUND	Sub Area symbol %1 in Area ID %_2_Id not found in resource file "%3"
-107158	MSR_DB_ERROR	Database error in function "%1" table "%2". Database error string "%3"
-107157	MSR_WRONG_DB_VERSION	Wrong Database version %_1_Id
-107156	MSR_DB_VERSION_MSG	Database version %_1_Id
-107155	MSR_WRONG_SIEBEL_VERSION	Wrong Siebel version %_1_Id
-107154	MSR_SIEBEL_VERSION_MSG	Siebel version %_1_Id
-107153	MSR_EMPTY_SVR_NAME_TABLE	Empty Database server names table
-107152	MSR_START_OFFLINE	Starting offline processing.
-107151	MSR_OFFLINE_DONE	Offline processing complete. Time taken: %1 seconds
-107150	MSR_VUSER_ID_ERROR	Vuser ID "%_1_Id" out of range (1 - 100) for ClickID %_2_Id
-107149	MSR_CSV_READING_ERROR	Error code %_1_Id when reading CSV file
-107148	MSR_INVALID_SESSION	Invalid session "%1" at SARM ID %_2_Id
-107147	MSR_SESSION_NOT_FOUND	Session string property not found for SARM ID %d
-107146	MSR_NO_NEW_TREES	No new trees found
-107145	MSR_READ_PROP_FILE	Reading properties file "%1"
-107144	MSR_GET_TMP_DIR_FAIL	Failed to locate the Mediator machine's temporary directory
-107143	MSR_DB_FILE_IS	Database file location: "%1"
SilverLT_res.h		
-202805	SAMPLE_PROTOCOL_INVALID_ORDINAL_ARG	argument "%1" ("%2") is invalid - should be one of "ALL", "1", "2" and so on.
SmtplayRes.h		
-205820	LRSMTMP_SESSION_NOT_EXIST	Smt session does not exist, nothing to free.
-205819	LRSMTMP_INVALID_URL	Invalid Smt url entry (should be URL=smt://emailid:password@emailserver or URL=smtps://emailid@emailserver).
-205818	LRSMTMP_CONNECTION_FAILED	Failed to connect to %_1_s: %_2_Id
-205817	LRSMTMP_SECURE_CONNECTION_FAILED	Failed to establish a secure SMTP session.

Error code	Handle	Message\Additional information
-205816	LRSMTMP_NO_WELCOME	Did not receive SMTP welcome message. Disconnecting (rc = %_1_id).
-205815	LRSMTMP_AUTH_FAILED	Authentication failed for %_1_s:%_2_s
-205814	LRSMTMP_LOGON_FAILED	Logon Session failed! %_1_s %_2_s
-205813	LRSMTMP_CC	Smtp send mail Cc: %_1_s
-205812	LRSMTMP_NOT_LOGGED_ON	Not logged on!
-205811	LRSMTMP_NO_SESSION_OBJECT	Unable to obtain SMTP user session object.
-205810	LRSMTMP_NOT_CONNECTED	Not connected to SMTP server.
-205809	LRSMTMP_NO_DATA	Mail request does not contain data. Skipping.
-205808	LRSMTMP_MAIL_FROM_FAILED	MAIL FROM request failed (rc = %_1_id).
-205807	LRSMTMP_SEND_START_FAILED	Failed to start sending Message segment (rc = %_1_id).
-205806	LRSMTMP_SERVER_RESPONSE	Server responded w/ %_1_s
-205805	LRSMTMP_NO_MEMORY	MEMORY OVERFLOW!
-205804	LRSMTMP_MAIL_ABORTED	Smtp session aborted last mail.
-205803	LRSMTMP_ABORT_MAIL	Aborting mail... %_1_s
-205802	LRSMTMP_SESSION_CREATION_FAILED	Unable to create an SMTP user session object.
-205801	LRSMTMP_ABORT_MAIL_FAILED	Abort mail failed. (See below for details)\r\n
-205800	LRSMTMP_CONTENTS	: %_1_s
-205799	LRSMTMP_READ_FILE_FAILED	Unable to access/read file : %_1_s
-205798	LRSMTMP_DIR_INCLUSION_FAILED	Unable to include directory : %_1_s
-205797	LRSMTMP_SEND_REQUEST_FAILED	Error sending request to SMTP server (rc = %_1_id)
-205796	LRSMTMP_RECV_RESPONSE_FAILED	Error receiving response from SMTP server (rc = %_1_id)
-205795	LRSMTMP_SESSION_FREED	Smtp session freed.
-205794	LRSMTMP_LOGON	Smtp Logon to %_1_s
-205793	LRSMTMP_LOGON_SUCCESS	Smtp Logon successful.
-205792	LRSMTMP_SESSION_CLOSED	Smtp Session closed.
-205791	LRSMTMP_NOTICE	Smtp Notice: %_1_s : %_2_s
-205790	LRSMTMP_TO	Smtp send mail To: %_1_s
-205789	LRSMTMP_BCC	Smtp send mail Bcc: %_1_s
-205788	LRSMTMP_MULTIADDR_FROM_WARN	Cannot use CommonName when multiple addresses are specified in the From field. Left unmodified.
-205787	LRSMTMP_SENT	\r\n>>>\r\n%1\r\n
-205786	LRSMTMP_RECEIVED	\r\n<<<\r\n%1\r\n
-205785	LRSMTMP_BAD_ADDRESS	Bad address '%1': %2
-205784	LRSMTMP_INTERNAL_ERROR	Internal error
TWEB.h		
-242999	TWEB_NO_URL	No URL provided!
-242998	TWEB_OPEN_SESSION_FAILED	Session opening failed. Last error %_1_id.
-242997	TWEB_CONNECTION_FAILED	Failed to create HTTP GET request. Last error %_1_id.
-242996	TWEB_REQUEST_SENDING_FAILED	Failed to send HTTP GET request. Last error %_1_id.
-242995	TWEB_GET_FAILED	Failed to execute HTTP GET request. Last error "%1".
-242994	TWEB_NO_HEADER_NAME	No header name provided!
-242993	TWEB_NO_HEADER_VALUE	No header value provided!
-242992	TWEB_DELAY_DURATION	Delay duration %_1_id msec.
-242991	TWEB_ADD_HEADER	Header "%1: %2" added.
-242990	TWEB_FILE_OPEN_FAILED	Failed to save response to "%1".. Last error %_2_id.
-242989	TWEB_INVALID_URL	Invalid URL provided. Last error %_1_id.
-242988	TWEB_ONLY_HTTP_SUPPORTED	Only HTTP scheme is supported.
-242987	TWEB_NO_HOSTNAME	No hostname in the URL!
-242986	TWEB_GET_URL	HTTP GET %1
-242985	TWEB_TIMER	Timer alarm!
-242984	TWEB_REQUEST_CREATION_FAILED	Failed to create HTTP GET request. Last error %_1_id.
VnpLog_res.h		
VnpUtils_res.h		

Error code	Handle	Message\Additional information
WebConvertFromFormattedFilterImpl_res.h		
-210999	DFE_WARNING_ILLEGAL_DATA	Failed to create web_convert_from_formatted step. Decoded data is empty or has invalid tags.
WebConvertFromFormattedPostFilterImpl_res.h		
-220999	DFE_WARNING_ILLEGAL_DATA	Failed to create web_convert_from_formatted step. Decoded data is empty or has invalid tags.
WebDataFormatsCodeGen_res.h		
-209999	GWT_CONTENT_IDENT	GWT content has been identified. Consider using GWT DFE. See documentation for more information.
al_res.h		
-66999	ALAB_MSG_GENERIC	1.00%
-66998	ALAB_MSG_FAILED_LAUCH_ON_REMOTE	Failed launch autolab server process on remote machine %1.
-66997	ALAB_MSG_LAUCH_ON_REMOTE_READY	Launch On remote ready.
-66996	ALAB_MSG_FAILED_REGISTER_ON_SERVICES	Failed register on %1 service.
-66995	ALAB_MSG_ENCODE_MSG_FAILED	Failed to encode the message.
-66994	ALAB_MSG_FAILED_DECODE_XDR	Failed decode message for %1.
-66993	ALAB_MSG_FAILED_OPEN_PROCESS_TOKEN	OpenProcessToken() failed with % 1 _ld.
-66992	ALAB_MSG_FAILED_LOOKUP_PRIV_VAL	LookupPrivilegeValue() failed with % 1 _ld.
-66991	ALAB_MSG_FAILED_ADJUST_TOKEN_PRIV	AdjustTokenPrivileges() failed with % 1 _ld.
-66990	ALAB_MSG_FAILED_EXIT_WIN	ExitWindowsEx() failed with % 1 _ld.
-66989	ALAB_MSG_FAILED_REBOOT	Failed Perform Reboot.
-66988	ALAB_MSG_FAILED_OPEN_REG_KEY	Failed to open registry key.
-66987	ALAB_MSG_FAILED_SET_KEY_VALUE	Failed to set the key value %1. Reason is % 2 _ld.
-66986	ALAB_MSG_KILLED_LAUCH_ON_REMOTE	Abnormal termination of process.
-66985	ALAB_MSG_FAILED_STORE_LOGON_CONFIG	Failed to store auto logon configuration before reboot.
-66984	ALAB_MSG_FAILED_REMOVE_KEY_VALUE	Failed to remove key value %1.
-66983	ALAB_MSG_NO_REBOOT_PROGRESS_CB	No reboot progress callback.
-66982	ALAB_MSG_FAILED_POST_LOGON_CONFIG	Failed to post logon configuration message.
-66981	ALAB_MSG_FAILED_ENABLE ALOGON	Failed to enable auto logon.
-66980	ALAB_MSG_FAILED_POST_REBOOT_STATUS	Failed to post reboot status message.
-66979	ALAB_MSG_NO_REBOOT_ACK_SERVICE_NAME	There is no reboot acknowledgement service name in the command line.
-66978	ALAB_MSG_NO_INSTALL_ACK_SERVICE_NAME	There is no install acknowledgement service name in the command line.
-66977	ALAB_MSG_NO_INSTALL_PROGRESS_CB	No install progress callback supplied.
-66976	ALAB_MSG_NO_INSTALL_CMD_LINE	There is no install command line supplied.
-66975	ALAB_MSG_FAILED_PARSE_INSTALL_CMD_LINE	Failed to parse install command line.
-66974	ALAB_MSG_INVALID_COPY_PATCH_CMDLINE	Invalid copy patch command line.
-66973	ALAB_MSG_FAILED_GET_STAT	Failed to copy path. Reason - os_stat function failed.
-66972	ALAB_MSG_FAILED_TO_CREATE_MFT_OPERATION	Failed to create mft operation. rc = % 1 _ld
-66971	ALAB_MSG_UNKNOWN_MFT_OPERATION	Unknown mft operation %1.
-66970	ALAB_MSG_MFT_OPERATION_FAILED	Mft operation failed. rc = % 1 _ld
-66969	ALAB_MSG_FAILED_GET_PRODUCT_PATH_BY_ID	Failed to get product path by %s key.
-66968	ALAB_MSG_FAILED_POST_INSTALL_STATUS	Failed to post install status message.
-66967	ALAB_MSG_INVALID_PATH	Invalid path of the patch destination.
-66966	ALAB_MSG_FAILED_EXTRACT_PATCH_FILE_NAME	Failed to extract patch file name.
-66965	ALAB_MSG_FAILED_GET_TEMP_DIR	Failed to get temporary directory on remote machine %1.
-66964	ALAB_MSG_FAILED_POST_COPY_PATCH_CMD	Failed to post 'Copy Patch' protocol message to the AL Server side on %1.
-66963	ALAB_MSG_FAILED_POST_MSG	Failed to post message.
-66962	ALAB_MSG_FAILED_INITIALIZE	Failed to initialize Auto Lab.
-66961	ALAB_MSG_FAILED_ADD_MACHINE	Failed to add machine %1 to Auto Lab.
-66960	ALAB_MSG_FAILED_REMOVE_BUSY_MACHINE	Failed to remove %1 machine from Auto Lab. Machine is occupied by task.
-66959	ALAB_MSG_FAILED_POST_ADD_MACHINE_NOTIFICATION	Failed to post 'Add Machine' notification to the AL UI Center.
-66958	ALAB_MSG_UNKNOWN_UI_REQUEST	Unknown request type from Auto Lab UI arrived.
-66957	ALAB_MSG_UNKNOWN_ALMANAGER_RESPONSE	Unknown response type from Auto Lab Manager arrived.
-66956	ALAB_MSG_FAILED_READ_ALMAP_CFG	Failed read auto lab configuration file %1. The file is corrupted.
-66955	ALAB_MSG_UNKNOWN_PLATFORM	Unknown platform type for %1 machine in the auto lab configuration file %2. The file is corrupted.
-66954	ALAB_MSG_INVALID_UI_MONIKER	Cannot create CUIShadow object: invalid Auto Lab UI sender moniker.

Error code	Handle	Message\Additional information
-66953	ALAB_MSG_FAILED_POST_NOTIFY	Failed to post status message to the Auto Lab UI from Auto Lab Manager.
-66952	ALAB_MSG_FAILED_POST_CONNECT_INFO	Failed to post Auto Lab Configuration Information to the Auto Lab UI side.
-66951	ALAB_MSG_NO_MACHINE_HANDLE	The machine %1 is not part of the Auto Lab configuration.
-66950	ALAB_MSG_FAILED_GET_ALMANAGER	Failed to get the Auto Lab Manager object from TLS entry.
-66949	ALAB_MSG_REBOOT_REQUEST_FAILED	The request to reboot machine %1 failed.
-66948	ALAB_MSG_INVALID_NEW_MACHINE_INFO	Failed to add new machine to the Auto Lab: invalid machine properties.
-66947	ALAB_MSG_CP_PATCH_REQUEST_FAILED	The request 'Copy Patch' is failed on %1 machine.
-66946	ALAB_MSG_FAILED_ATTACH_UI	Attach Auto Lab UI as Son to the al_manager process is failed.
-66945	ALAB_MSG_FAILED_ATTACH_ON_REMOTE	Failed attach to al manager process on the %1 machine.
-66944	ALAB_MSG_KILLED_ATTACH_ON_REMOTE	Abnormal termination of the al manager process on %1 machine.
-66943	ALAB_MSG_NO_USER_CALLBACK	There is no user callback supplied fro %1.
-66942	ALAB_MSG_FAILED_LOAD_ALMAP_CFG	Failed to load %1 configuration file.
-66941	ALAB_MSG_FAILED_CREATE_REQUESTS_LIST	Failed to create requests list.
-66940	ALAB_MSG_CANNOT_ERASE_REQUEST	Failed to erase request from requests list: no such request.
-66939	ALAB_MSG_INVALID_PARAMETERS_FOR_CP_PATCH	Failed to perform 'Copy Patch' request on %1. Invalid parameters.
-66938	ALAB_MSG_FAILED_GET_UIM_NAME	Failed to get the machine name on which Auto Lab UI is running.
-66937	ALAB_MSG_FAILED_POST_DISCONNECT_MSG	Failed to post disconnect request from Auto Lab UI side to AL Manager.
-66936	ALAB_MSG_FAILED_POST_REQUEST_TO_ALM	Failed to post %1 Request message to the AL Manager.
-66935	ALAB_MSG_ALUI_CANNOT_FIND_REQUEST	Report Progress Status arrived for %1 machine for unknown request in AL UI.
-66934	ALAB_MSG_NO_REQUEST_ID	Report Progress Status arrived for %1 machine with unknown request identifier.
-66933	ALAB_MSG_MACHINE_ALREADY_EXISTS	Failed to add %1 machine to AL: machine already exists in the AL configuration.
-66932	ALAB_MSG_FAILED_UI_INITIALIZE	Failed to initialize Auto Lab UI Manager.
-66931	ALAB_MSG_UI_ALREADY_ATTACHED_TO_ALM	Connection to AL Manager failed: AL UI from %1 is already attached to the AL Manager on %2.
-66930	ALAB_MSG_FAILED_DISCONNECT_NO_CONNECTION	Cannot disconnect from AL Manager: AL UI from %1 wasn't connected.
-66929	ALAB_MSG_UI_IS_NOT_CONNECTING	Auto Lab UI is not connecting to the Auto Lab Manager.
-66928	ALAB_MSG_ALM_NOT_RESPONDING	Auto Lab Manager on %1 is not responding.
-66927	ALAB_MSG_MACHINE_NOT_EXISTS	The machine %1 is not part of the AL Configuration.
-66926	ALAB_MSG_UPLOAD_FILES_REQUEST_FAILED	Failed to perform 'Upload Files' request.
-66925	ALAB_MSG_FAILED_CANCEL_MFT	Failed to cancel mercury file transfer process (ID = %1_Id).
-66924	ALAB_MSG_FAILED_CREATE_UNIQUE_DIR	Failed to create unique directory name for the uploaded files.
-66923	ALAB_MSG_FAILED_COMPOSE_TMP_LOCATION	Failed to compose temporary location for uploaded files.
-66922	ALAB_MSG_FAILED_UPLOAD_FILES	Failed to upload the files from the AL UI side to the AL Manager.
-66921	ALAB_MSG_FAILED_REMOVE_ALM_FILES	Failed to remove %1 from the AL Manager machine.
-66920	ALAB_MSG_FAILED_CLEAN_TMP_PATCH_DST	Failed to remove Patch from its temporary location %1.
-66919	ALAB_MSG_FAILED_GET_ALUIMANAGER	Failed to get the Auto Lab UI Manager object from TLS entry.
-66918	ALAB_MSG_INSTALL_AGENT_REQUEST_FAILED	The request to install AL Agent on the %1 machine failed.
-66917	ALAB_MSG_WNET_ADD_CONNECTION_FAILED	Failed to create connection with remote machine %1 (system error = % 2_Id).
-66916	ALAB_MSG_WNET_CANCEL_CONNECTION_FAILED	Failed to cancel the remote connection with %1 (system error = % 2_Id).
-66915	ALAB_MSG_CREATE_SHARE_FAILED	Failed to create share '%1' on drive %2 on machine %3 (system error - % 4_Id).
-66914	ALAB_MSG_DESTROY_SHARE_FAILED	Failed to destroy share '%1' on machine %2 (system error - % 3_Id).
-66913	ALAB_MSG_FAILED_GET_SHARE_INFO	Failed to get share information on %1 machine (system error - % 2_Id).
-66912	ALAB_MSG_INSTALL_SERVICE_FAILED	Failed to install %1 service on the %2 (system error - % 3_Id).
-66911	ALAB_MSG_FAILED_OPEN_SCM	Failed to open Service Control Manager on %1 (system error - % 2_Id).
-66910	ALAB_MSG_FAILED_STOP_SERVICE	Failed to stop service %1 on %2 (system error - % 3_Id).
-66909	ALAB_MSG_FAILED_REMOVE_SERVICE	Failed to remove service %1 on %2 (system error - % 3_Id).
-66908	ALAB_MSG_FAILED_OPEN_SERVICE	Failed to open service %1 on %2 (system error - % 3_Id).
-66907	ALAB_MSG_FAILED_START_SERVICE	Failed to start service %1 on %2 (system error - % 3_Id).
-66906	ALAB_MSG_FAILED_DOWNLOAD_SETUP_DIR	Failed to download Setup Directory for ALSetupService from %1 to %2.
-66905	ALAB_MSG_FAILED_REMOVE_SETUP_DIR	Failed to remove AutoLab Setup Service Directory from %1 on %2 machine.
-66904	ALAB_MSG_FAILED_GET_RUNTIME_ENV	Failed to get runtime environment of the AutoLab Manager.
-66903	ALAB_MSG_FAILED_REBOOT_AFTER_INSTALL_AGENT	The installation of the AL Agent on %1 do not completed. To complete it, please perform reboot of the machine manually.
-66902	ALAB_MSG_INSTALL_LOG_NOT_EXISTS	The installation process of the AL Agent on %1 failed. The Log file of installation was not created.
-66901	ALAB_MSG_MACHINE_FAILED_DOWN	The remote machine %1 failed to down after installation/uninstalling process.
-66900	ALAB_MSG_MACHINE_FAILED_UP	The remote machine %1 failed to restart after reboot.
-66899	ALAB_MSG_FAILED_RESTORE_SETTINGS	Failed to restore LogOn machine configuration settings on %1 after reboot.
-66898	ALAB_MSG_FAILED_CREATE_TRIGGER	Failed to create trigger.
-66897	ALAB_MSG_FAILED_CREATE_WT	Failed to create worker thread for copy Setup Directory.

Error code	Handle	Message\Additional information
-66896	ALAB MSG FAILED CREATE WT FOR CONNECT	Failed to create workerthread for checking connection with remote machine.
-66895	ALAB MSG UNINSTALL ALAGENT REQUEST FAILED	The request to perform the Uninstall of the AL Agent on the %1 machine failed.
-66894	ALAB MSG NO UNINSTALL PROGRESS CB	No Uninstall progress callback supplied.
-66893	ALAB MSG UNINSTALL LOG NOT EXISTS	The Uninstall process of the AL Agent on %1 failed. The Log file of Uninstall was not created.
-66892	ALAB MSG LAUNCH CHECK FAILED	Launch Checker failed to perform Launch.
-66891	ALAB MSG CHECK CONNECTION FAILED	Connection Checker failed to connect to the remote machine.
-66890	ALAB MSG FAILED CREATE REQUEST IMPLEMENTOR	Failed to create the 'request implementor' for %1 request type.
-66889	ALAB MSG SERVER FAILED POST MESSAGE	Auto Lab Server failed to post protocol message for %1 request type.
-66888	ALAB MSG FAILED TRANSFER DATA TO REQUEST IMPLEMENTOR	Failed to transfer the data to the request implementor for %1 request type.
-66887	ALAB MSG NO BASE SERVICE NAME	No service name in the command line for communication between AL Server and Generic Request at AL Manager side.
-66886	ALAB MSG NO BUS WS NAME	No Web Server name was provided to AL Agent running under BUS mode. AL Agent can't initiate communication channels to AL Manager.
-66885	ALAB MSG FAILED CREATE GENERIC SLAVE	Failed to create Generic Slave for request type %1 (error is % 2 Id).
-66884	ALAB MSG NO REQUEST IMPLEMENTOR	No Requests Implementor IFS for request type %1.
-66883	ALAB MSG CLEAN INSTALL REQUEST FAILED	The request to install %1 on the %2 machine failed.
-66882	ALAB MSG NO PRODUCT NAME	The product name for install/uninstall is not specified.
-66881	ALAB MSG NO SETUP LOCATION	The setup.exe location of the %1 is not specified.
-66880	ALAB MSG FAILED REBOOT AFTER CLEAN INSTALL	The installation of the %1 on %2 do not completed. To complete it, please perform reboot of the machine manually.
-66879	ALAB MSG FAILED REBOOT AFTER CLEAN UNINSTALL	Failed to reboot machine %1 after Uninstall process of the %2.
-66878	ALAB MSG CLEAN UNINSTALL REQUEST FAILED	The request to uninstall %1 from %2 machine failed.
-66877	ALAB MSG CLEAN INSTALL LOG NOT EXISTS	The installation process of the %1 on %2 failed. The Log file of installation was not created.
-66876	ALAB MSG CLEAN UNINSTALL LOG NOT EXISTS	The Uninstall process of the %1 on %2 failed. The Log file of Uninstall was not created.
-66875	ALAB MSG FAILED POST MSG TO WT	Failed to post the message to the Worker Thread.
-66874	ALAB MSG DOWN TIMEOUT	Failed to identify that machine is down (TIMEOUT).
-66873	ALAB MSG FAILED GET CONNECT INFO	Failed to get connect information.
-66872	ALAB MSG FAILED CREATE UISESSION	Failed to create UI Session object for Auto Lab UI with %1 identifier.
-66871	ALAB MSG UISESSION ALREADY CONNECTED	The Auto Lab UI Center on %1 (center identifier %2) is already connected to the Auto Lab Manager.
-66870	ALAB MSG FAILED POST TO UICENTER	Failed to post the message to UI Center.
-66869	ALAB MSG REQUEST FROM UNKNOWN SESSION	The request arrived from unknown Session Center.
-66868	ALAB MSG DISCONNECT FROM UNKNOWN UISESSION	Disconnect request arrived to unknown Session Center.
-66867	ALAB MSG FAILED ATTACH TASK	Failed to attach task ID = % 1 Id - no such task in the Task Center.
-66866	ALAB MSG FAILED DETACH TASK	Failed to detach task ID = % 1 Id - task not found in the Task Center.
-66865	ALAB MSG FAILED RUN TASK	Failed to run task ID = % 1 Id - the task not found in Task Center.
-66864	ALAB MSG FAILED DESTROY TASK NOT FOUND	Failed to destroy task ID = % 1 Id - task not found in Task Center.
-66863	ALAB MSG FAILED CANCEL TASK NOT FOUND	Failed to cancel task ID = % 1 Id - task not found in Task Center.
-66862	ALAB MSG FAILED ERASE TASK FROM SESSION	Failed to erase the task % 1 Id from session task list - task not found.
-66861	ALAB MSG FAILED RUN TASK MACHINE_BUSY	Failed to run %1 task on %2 machine. Machine is busy.
-66860	ALAB MSG FAILED LOAD ALM_CFG	Failed to load Auto Lab Manager configuration.
-66859	ALAB MSG FAILED POST CREATE TASK TO AL_SERVER	Failed to post 'Create Task' message to the AL Server side.
-66858	ALAB MSG FAILED DESTROY LOADER TASK	Failed to perform loader request to destroy the task with ID=% 1 Id - task not found.
-66857	ALAB MSG FAILED CREATE LOADER_TASK	Failed to perform loader request to create a task with type %1.
-66856	ALAB MSG FAILED CREATE TASK	Failed to create the %1 task.
-66855	ALAB MSG FAILED REGISTER ON TIMER	Failed to register on %1 timer.
-66854	ALAB MSG FAILED REGISTER ON BHB TIMER	Failed to register on BHB timer.
-66853	ALAB MSG FAILED CREATE REBOOT SLAVE	Failed to create Reboot slave. No task specification.
-66852	ALAB MSG FAILED CREATE INSTALL SLAVE	Failed to create Install slave. No task specification.
-66851	ALAB MSG FAILED POST PROTOCOL MSG TO SLAVE	Failed to post task protocol message to Slave.
-66850	ALAB MSG FAILED SEND REMOTE LOGON INFO	AL Server: Failed to send LogOn Machine Configuration.
-66849	ALAB MSG INVALID REBOOT MSG	Invalid reboot protocol message: not all parameters arrived.
-66848	ALAB MSG NO UPLOAD_LOCATION	Upload Files Request: no location specified.
-66847	ALAB MSG INVALID_COPY_PATCH_PARAM	Invalid parameters for "Copy Patch" request.
-66846	ALAB MSG FAILED COPY_PATCH	Failed copy patch.
-66845	ALAB MSG SLAVE NOT FOUND	The slave with ID=% 1 Id is not found.
-66844	ALAB MSG FAILED DECODE XDR_ALM_REQUEST	Failed to decode AL Manager request
-66843	ALAB MSG FAILED TO_CONNECT_BUS	Failed to connect to Bus with the following arguments - %1, %2, %3, %4
-66842	ALAB MSG FAILED TO_CREATE_PUBLISHER	Failed to created Bus Publisher with subject name - %1
-66841	ALAB MSG FAILED TO_CREATE_SUBSCRIBER	Failed to created Bus Subscriber with subject name - %1
-66840	ALAB MSG SENDING MSG WHILE BUS IS_DISCONNECTED	Attempt to send guarantee message while BUS is Disconnected.

Error code	Handle	Message\Additional information
-66839	ALAB_MSG_NO_CONFIG_FILE_PATH	No config file name was provided for AL Agent communication to BUS.
-66838	ALAB_MSG_BUS_NOTIFICATION_ARRIVED	BUS %1 notification arrived
-66837	ALAB_MSG_FAILED_SEND_BHB_REQUEST	Failed to send BUS HeartBeat request.
-66836	ALAB_MSG_FAILED_SEND_BHB_RESPOND	Failed to send BUS HeartBeat respond.
-66835	ALAB_MSG_FAILED_WEB_SERVICE_INITIALIZE	Failed to initialize AL Web Service.
-66834	ALAB_MSG_FAILED_CREATE_WT_FOR_WS	Failed to create worker thread for AL Web Service.
-66833	ALAB_MSG_FAILED_GET_MT_CONTEXT	Failed to get Main Thread context for %s.
-66832	ALAB_MSG_WS_FAILED_TO_BIND_PORT	Auto Lab Web Service: Failed to bind to port % 1 Id.
-66831	ALAB_MSG_FAILED_CREATE_FIFO	Auto Lab Web Service: Failed to create fifo for soap environments.
-66830	ALAB_MSG_WS_FAILED_TO_ACCEPT_NEW_CONNECTION	Auto Lab Web Service: Failed to accept a new connection. SOAP error % 1 Id: %2.
-66829	ALAB_MSG_FAILED_RETRIVE_SOAP_SERVER	Auto Lab Web Service: Failed to retrieve Soap Server from Soap Environment.
-66828	ALAB_MSG_WRONG_INPUT	Wrong Input in %1 API.
-66827	ALAB_MSG_NO_MACHINE_SPEC	NULL passed instead of %1 in machine specification.
-66826	ALAB_MSG_WS_CONVERT_TYPES_ERROR	1.00%
-66825	ALAB_MSG_FAILED_POST_MSG_TO_MAIN_THREAD	Failed post %1 request to ALM.
-66824	ALAB_MSG_FAILED_POST_MSG_TO_WORKER_THREAD	Failed post %1 message to SOAP Server (on worker thread).
-66823	ALAB_MSG_ERROR_WEB_SERVICE_COMMUNICATION_TIMEOUT	Auto Lab Web Service: Communication timeout error.
-66822	ALAB_MSG_ERROR_AL_SERVER	from %1: %2.
-66821	ALAB_MSG_NOTIFY_CREATE_TASK	AL Task created: machine = %1 type = %2 id = % 3 Id.
-66820	ALAB_MSG_NOTIFY_TASK_SPEC	%1 - %2.
-66819	ALAB_MSG_FAILED_GET_KEY_VALUE	Failed to get the key value %1. Reason is % 2 Id.
-66818	ALAB_MSG_FAILED_LOGON_USER	Failed to logon user %1 after reboot.
-66817	ALAB_MSG_FAILED_RESTORE_CONFIG	Failed to restore LogOn machine configuration.
-66816	ALAB_MSG_FAILED_TO_RUN_TASK	Failed to run task % 1 Id (error is % 2 Id).
-66815	ALAB_MSG_FAILED_TO_CANCEL_TASK	Failed to cancel task % 1 Id (error is % 2 Id).
-66814	ALAB_MSG_INVALID_USER_DETAILS	Unknown user name or bad password.
alra_res.h		
-66499	ALAB_MSG_FAILED_GET_RUNTIME_ENV	Failed to get runtime environment of the AutoLab Manager.
-66498	ALAB_MSG_FAILED_DOWNLOAD_SETUP_DIR	Failed to download Setup Directory for ALSetupService from %1 to %2.
-66497	ALAB_MSG_FAILED_REMOVE_SETUP_DIR	Failed to remove AutoLab Setup Service Directory from %1 on %2 machine.
-66496	ALAB_MSG_CLEAN_INSTALL_LOG_NOT_EXISTS	The installation process of the %1 on %2 failed. The Log file of installation was not created.
-66495	ALAB_MSG_CLEAN_UNINSTALL_LOG_NOT_EXISTS	The Uninstall process of the %1 on %2 failed. The Log file of Uninstall was not created.
-66494	ALAB_MSG_DOWN_TIMEOUT	Failed to identify that machine is down (TIMEOUT).
-66493	ALAB_MSG_MACHINE_FAILED_DOWN	The remote machine %1 failed to down after installation/uninstalling process.
-66492	ALAB_MSG_FAILED_RESTORE_SETTINGS	Failed to restore LogOn machine configuration settings on %1 after reboot.
-66491	ALAB_MSG_MACHINE_FAILED_UP	The remote machine %1 failed to restart after reboot.
-66490	ALAB_MSG_FAILED_REBOOT_AFTER_CLEAN_INSTALL	The installation of the %1 on %2 do not completed. To complete it, please perform reboot of the machine manually.
-66489	ALAB_MSG_FAILED_REBOOT_AFTER_CLEAN_UNINSTALL	Failed to reboot machine %1 after Uninstall process of the %2.
-66488	ALAB_MSG_WNET_CANCEL_CONNECTION_FAILED	Failed to cancel the remote connection with %1 (system error = % 2 Id).
-66487	ALAB_MSG_DESTROY_SHARE_FAILED	Failed to destroy share '%1' on machine %2 (system error - % 3 Id).
-66486	ALAB_MSG_FAILED_GET_SHARE_INFO	Failed to get share information on %1 machine (system error - % 2 Id).
-66485	ALAB_MSG_INSTALL_SERVICE_FAILED	Failed to install %1 service on the %2 (system error - % 3 Id).
-66484	ALAB_MSG_FAILED_OPEN_SCM	Failed to open Service Control Manager on %1 (system error - % 2 Id).
-66483	ALAB_MSG_FAILED_STOP_SERVICE	Failed to stop service %1 on %2 (system error - % 3 Id).
-66482	ALAB_MSG_FAILED_REMOVE_SERVICE	Failed to remove service %1 on %2 (system error - % 3 Id).
-66481	ALAB_MSG_FAILED_OPEN_SERVICE	Failed to open service %1 on %2 (system error - % 3 Id).
-66480	ALAB_MSG_FAILED_START_SERVICE	Failed to start service %1 on %2 (system error - % 3 Id).
-66479	ALAB_MSG_FAILED_CREATE_WT_FOR_CONNECT	Failed to create workerthread for checking connection with remote machine.
-66478	ALAB_MSG_FAILED_POST_MSG_TO_WT	Failed to post the message to the Worker Thread.
-66477	ALAB_MSG_FAILED_DECODE_XDR	Failed decode message for %1.
-66476	ALAB_MSG_FAILED_CREATE_WT	Failed to create workerthread for copy Setup Directory.
-66475	ALAB_MSG_WNET_ADD_CONNECTION_FAILED	Failed to create connection with remote machine %1 . Please check the username and the password. (system error = % 2 Id).
-66474	ALAB_MSG_CREATE_SHARE_FAILED	Failed to create share '%1' on drive %2 on machine %3 (system error - % 4 Id).
-66473	ALAB_MSG_CLEAN_INSTALL_REQUEST_FAILED	The request to install %1 on the %2 machine failed.
-66472	ALAB_MSG_FAILED_COPY_SERVICE_SETUP_DIR	Failed to copy Service Setup directory to %1 (error = % 2 Id).
-66471	ALAB_MSG_FAILED_REMOVE_SERVICE_SETUP_DIR	Failed to remove Service Retup directory %1 (error = % 2 Id).

Error code	Handle	Message\Additional information
-66470	ALAB_MSG_FAILED_CREATE_NETDIR	Failed to create netdir %1 (error = % 2 _ld).
-66469	ALAB_MSG_FAILED_REMOVE_NETDIR	Failed to remove netdir %1 (error = % 2 _ld).
-66468	ALAB_MSG_FAILED_COPY_FILE	Failed to copy file: src - %1 dest - %2.
-66467	ALAB_MSG_ILLEGAL_ARGUMENTS	Illegal arguments to function %1.
-66466	ALAB_MSG_FAILED_TO_LAUNCH_PROCESS	Failed to launch process with command line '%1'.
-66465	ALAB_MSG_WAIT_ON_PROCESS_TIMED_OUT	Wait for process termination timed out after % 1 _ld seconds. (process - %2).
-66464	ALAB_MSG_FAILED_TO_CREATE_PROCESS	Failed to create process with command line - %1.
-66463	ALAB_MSG_FAILED_DEL_FILE	Failed to delete file %1.
-66462	ALAB_MSG_FAILED_LIST_DIR	Failed to list directory %1.
-66461	ALAB_MSG_FAILED_TO_GET_USER_HOME_DIR	Failed to get user's home dir on remote unix machine.
-66460	ALAB_MSG_SRC_NOT_VALID	Validation of source %1 failed.
-66459	ALAB_MSG_DST_NOT_VALID	Validation of destination %1 failed.
-66458	ALAB_MSG_GENERIC_ERROR_BUFFER	***** START OF GENERIC ERROR BUFFER *****\n%1\n***** END OF GENERIC ERROR BUFFER *****
-66457	ALAB_MSG_INTERPROC_MUTEX_FAILED	Failed to create interprocess mutex in %1 (reason - %2).
-66456	ALAB_MSG_FAILED_TO_OPEN_CONSOLE_INPUT	Failed to create handle for the console input buffer. Cannot use the ssh passphrase. (System error: % 1 _ld)
-66455	ALAB_MSG_FAILED_TO_WRITE_CONSOLE_INPUT	Failed to write the ssh passphrase into the console input buffer. (System error: % 1 _ld)
-66454	ALAB_MSG_FAILED_TO_OPEN_CONSOLE_OUTPUT	Failed to create handle for the console output buffer. (System error: % 1 _ld)
-66453	ALAB_MSG_FAILED_TO_READ_CONSOLE_OUTPUT	Failed to read the data from the console output buffer. (System error: % 1 _ld)
-66452	ALAB_MSG_CONSOLE_OUTPUT_BUFFER	***** START OF CONSOLE OUTPUT BUFFER *****\n%1\n***** END OF CONSOLE OUTPUT BUFFER *****
-66451	ALAB_MSG_ADD_SHARE_FAILED_CRED_CONFLICT	Failed to add share to drive %1 on machine %2 . Please refer to the troubleshooting guide with the following system error. (system error - % 3 _ld).
-66450	ALAB_MSG_ADD_SHARE_FAILED_OTHER	Failed to add share to drive %1 on machine %2 . Please verify that the supplied username has administrator privileges on the server. (system error - % 3 _ld).
amf_res.h		
-200999	AMF_MSG_HTTP_TRANSPORT_PROVIDER_FAILED	HTTP Transport Provider function %1 failed: rc=% 2 _ld
-200998	AMF_MSG_HTTP_INVALID_PARAMETER	%1: invalid parameter %2
-200997	AMF_INTERNAL_ERROR	Internal Error (call customer services): %1
-200996	AMF_HEADER_SET_ALREADY_DEFINED	AMF header set "%1" is already defined. Overriding the existing definitions.
-200995	AMF_ENVELOPE_HEADER_SET_ALREADY_DEFINED	AMF envelope header set "%1" is already defined. Overriding the existing definitions.
-200994	AMF_HEADER_SET_UNDEFINED	Undefined AMF header set "%1"
-200993	AMF_ENVELOPE_HEADER_SET_UNDEFINED	Undefined AMF envelope header set "%1"
-200992	AMF_ENCODING_ERROR	Encoding of AMF message failed. Error is : %1
-200991	AMF_REQUEST_HTTP_STATUS_CODE	HTTP status code % 1 _ld was returned by the server
-200990	AMF_REQUEST_XML	Sending AMF request message. The following XML describes the message content:
-200989	AMF_DECODING_ERROR	Decoding of AMF message failed. Error is : %1
-200988	AMF_RESPONSE_XML	AMF response message received. The following XML describes the message content:
-200987	AMF_BODY_STATUS	Server returned %1 for message # % 2 _ld : %3
-200986	AMF_STEP_WITH_STEP_NAME_STARTED	%1 ("%2") started
-200985	AMF_STEP_STARTED	%1 started
-200984	AMF_STEP_SUCCESSFULLY_ENDED	%1 was successful
-200983	AMF_STEP_WITH_STEP_NAME_SUCCESS	%1 ("%2") was successful
-200982	AMF_STEP_END_STATUS	There was %1 while %2
-200981	AMF_STEP_WITH_STEP_NAME_END_STATUS	There was %1 during the %2 ("%3")
-200980	AMF_FAILED_TO_INITIALIZE_AMF_ENCODER	Failed to initialize AMF infrastructure : %1
-200979	AMF_EMPTY_RESPONSE	Invalid AMF response - empty response body
-200978	AMF_REQUEST_MESSAGE_NOT_ACKNOWLEDGED	Invalid AMF response - message # % 1 _ld was not acknowledged by the server response. Information on error can be found in XML in the extended log.
-200977	AMF_REPORT_MSG_STEP_FAILED	<CENTER>Step failed</CENTER>
-200976	AMF_REPORT_MSG_FAILED_ON_HTTP	<CENTER>Step failed on HTTP request</CENTER>
-200975	AMF_REPORT_MSG_FAILED_ON_AMF	<CENTER>Step failed on AMF request</CENTER>
-200974	AMF_REPORT_MSG_FAILED_ON_PARSING_PARAMS	<CENTER>Step failed while parsing step parameters</CENTER>
-200973	AMF_REPORT_MSG_STEP_WARNING_HTTP	<CENTER>Step passed with warning on HTTP request</CENTER>
-200972	AMF_REPORT_MSG_STEP_WARNING_PARSING_PARAMS	<CENTER>Step passed with warning while parsing step parameters</CENTER>
-200971	AMF_REPORT_MSG_STEP_WARNING_AMF	<CENTER>Step passed with warning on AMF request</CENTER>
-200970	AMF_REPORT_SET_VERSION_DETAILS	<CENTER>Set AMF Version to % 1 _ld</CENTER>

Error code	Handle	Message\Additional information
-200969	AMF REPORT DEFINE AMF HEADER SET DETAILS	<CENTER>Defined AMF header set "%1"</CENTER>
-200968	AMF REPORT DEFINE AMF ENVELOPE HEADER SET DETAILS	<CENTER>Defined AMF envelope header set "%1"</CENTER>
-200967	AMF REPORT STEP SUCCEEDED DETAILS	<CENTER>%1 was successful</CENTER>
-200966	AMF REPORT DEFINE FLEX AMF HEADER SET DETAILS	<CENTER>Defined Flex AMF header set "%1"</CENTER>
-200965	AMF REPORT DEFINE FLEX AMF ENVELOPE HEADER SET DETAILS	<CENTER>Defined Flex AMF envelope header set "%1"</CENTER>
-200964	AMF FLEX HEADER SET ALREADY DEFINED	Flex AMF header set "%1" is already defined. Overriding the existing definitions.
-200963	AMF FLEX ENVELOPE HEADER SET ALREADY DEFINED	Flex AMF envelope header set "%1" is already defined. Overriding the existing definitions.
-200962	AMF ERROR	1%
-200961	AMF REPLAY UTILS HTTP STATUS CODE INVALID	HTTP Status-Code=% 1 Id (%2) for "%3"
-200960	AMF REPLAY UTILS HTTP STATUS CODE 100	HTTP Status-Code=% 1 Id (%2) for "%3"
-200959	AMF REPLAY UTILS HTTP STATUS CODE 101	HTTP Status-Code=% 1 Id (%2) for "%3"
-200958	AMF REPLAY UTILS HTTP STATUS CODE 1XX	HTTP Status-Code=% 1 Id (%2) for "%3"
-200957	AMF REPLAY UTILS HTTP STATUS CODE 200	HTTP Status-Code=% 1 Id (%2) for "%3"
-200956	AMF REPLAY UTILS HTTP STATUS CODE 201	HTTP Status-Code=% 1 Id (%2) for "%3"
-200955	AMF REPLAY UTILS HTTP STATUS CODE 202	HTTP Status-Code=% 1 Id (%2) for "%3"
-200954	AMF REPLAY UTILS HTTP STATUS CODE 203	HTTP Status-Code=% 1 Id (%2) for "%3"
-200953	AMF REPLAY UTILS HTTP STATUS CODE 204	HTTP Status-Code=% 1 Id (%2) for "%3"
-200952	AMF REPLAY UTILS HTTP STATUS CODE 205	HTTP Status-Code=% 1 Id (%2) for "%3"
-200951	AMF REPLAY UTILS HTTP STATUS CODE 206	HTTP Status-Code=% 1 Id (%2) for "%3"
-200950	AMF REPLAY UTILS HTTP STATUS CODE 251	HTTP Status-Code=% 1 Id (%2) for "%3"
-200949	AMF REPLAY UTILS HTTP STATUS CODE 252	HTTP Status-Code=% 1 Id (%2) for "%3"
-200948	AMF REPLAY UTILS HTTP STATUS CODE 255	HTTP Status-Code=% 1 Id (%2) for "%3"
-200947	AMF REPLAY UTILS HTTP STATUS CODE 2XX	HTTP Status-Code=% 1 Id (%2) for "%3"
-200946	AMF REPLAY UTILS HTTP STATUS CODE 300	HTTP Status-Code=% 1 Id (%2) for "%3"
-200945	AMF REPLAY UTILS HTTP STATUS CODE 301	HTTP Status-Code=% 1 Id (%2) for "%3"
-200944	AMF REPLAY UTILS HTTP STATUS CODE 302	HTTP Status-Code=% 1 Id (%2) for "%3"
-200943	AMF REPLAY UTILS HTTP STATUS CODE 303	HTTP Status-Code=% 1 Id (%2) for "%3"
-200942	AMF REPLAY UTILS HTTP STATUS CODE 304	HTTP Status-Code=% 1 Id (%2) for "%3"
-200941	AMF REPLAY UTILS HTTP STATUS CODE 305	HTTP Status-Code=% 1 Id (%2) for "%3"
-200940	AMF REPLAY UTILS HTTP STATUS CODE 307	HTTP Status-Code=% 1 Id (%2) for "%3"
-200939	AMF REPLAY UTILS HTTP STATUS CODE 3XX	HTTP Status-Code=% 1 Id (%2) for "%3"
-200938	AMF REPLAY UTILS HTTP STATUS CODE 400	HTTP Status-Code=% 1 Id (%2) for "%3"
-200937	AMF REPLAY UTILS HTTP STATUS CODE 401	HTTP Status-Code=% 1 Id (%2) for "%3"
-200936	AMF REPLAY UTILS HTTP STATUS CODE 402	HTTP Status-Code=% 1 Id (%2) for "%3"
-200935	AMF REPLAY UTILS HTTP STATUS CODE 403	HTTP Status-Code=% 1 Id (%2) for "%3"
-200934	AMF REPLAY UTILS HTTP STATUS CODE 404	HTTP Status-Code=% 1 Id (%2) for "%3"
-200933	AMF REPLAY UTILS HTTP STATUS CODE 405	HTTP Status-Code=% 1 Id (%2) for "%3"
-200932	AMF REPLAY UTILS HTTP STATUS CODE 406	HTTP Status-Code=% 1 Id (%2) for "%3"
-200931	AMF REPLAY UTILS HTTP STATUS CODE 407	HTTP Status-Code=% 1 Id (%2) for "%3"
-200930	AMF REPLAY UTILS HTTP STATUS CODE 408	HTTP Status-Code=% 1 Id (%2) for "%3"
-200929	AMF REPLAY UTILS HTTP STATUS CODE 409	HTTP Status-Code=% 1 Id (%2) for "%3"
-200928	AMF REPLAY UTILS HTTP STATUS CODE 410	HTTP Status-Code=% 1 Id (%2) for "%3"
-200927	AMF REPLAY UTILS HTTP STATUS CODE 411	HTTP Status-Code=% 1 Id (%2) for "%3"
-200926	AMF REPLAY UTILS HTTP STATUS CODE 412	HTTP Status-Code=% 1 Id (%2) for "%3"
-200925	AMF REPLAY UTILS HTTP STATUS CODE 413	HTTP Status-Code=% 1 Id (%2) for "%3"
-200924	AMF REPLAY UTILS HTTP STATUS CODE 414	HTTP Status-Code=% 1 Id (%2) for "%3"
-200923	AMF REPLAY UTILS HTTP STATUS CODE 415	HTTP Status-Code=% 1 Id (%2) for "%3"
-200922	AMF REPLAY UTILS HTTP STATUS CODE 416	HTTP Status-Code=% 1 Id (%2) for "%3"
-200921	AMF REPLAY UTILS HTTP STATUS CODE 417	HTTP Status-Code=% 1 Id (%2) for "%3"
-200920	AMF REPLAY UTILS HTTP STATUS CODE 451	HTTP Status-Code=% 1 Id (%2) for "%3"
-200919	AMF REPLAY UTILS HTTP STATUS CODE 4XX	HTTP Status-Code=% 1 Id (%2) for "%3"
-200918	AMF REPLAY UTILS HTTP STATUS CODE 500	HTTP Status-Code=% 1 Id (%2) for "%3"
-200917	AMF REPLAY UTILS HTTP STATUS CODE 501	HTTP Status-Code=% 1 Id (%2) for "%3"
-200916	AMF REPLAY UTILS HTTP STATUS CODE 502	HTTP Status-Code=% 1 Id (%2) for "%3"
-200915	AMF REPLAY UTILS HTTP STATUS CODE 503	HTTP Status-Code=% 1 Id (%2) for "%3"
-200914	AMF REPLAY UTILS HTTP STATUS CODE 504	HTTP Status-Code=% 1 Id (%2) for "%3"
-200913	AMF REPLAY UTILS HTTP STATUS CODE 505	HTTP Status-Code=% 1 Id (%2) for "%3"

Error code	Handle	Message\Additional information
-200912	AMF_REPLAY_UTILS_HTTP_STATUS_CODE_552	HTTP Status-Code=% 1 Id (%2) for "%3"
-200911	AMF_REPLAY_UTILS_HTTP_STATUS_CODE_553	HTTP Status-Code=% 1 Id (%2) for "%3"
-200910	AMF_REPLAY_UTILS_HTTP_STATUS_CODE_554	HTTP Status-Code=% 1 Id (%2) for "%3"
-200909	AMF_REPLAY_UTILS_HTTP_STATUS_CODE_561	HTTP Status-Code=% 1 Id (%2) for "%3"
-200908	AMF_REPLAY_UTILS_HTTP_STATUS_CODE_5XX	HTTP Status-Code=% 1 Id (%2) for "%3"
-200907	AMF_FLEX_STEP_IS_ASYNC	step "%1" is an asynchronous step
-200906	AMF_FLEX_ASYNC_INTERNAL_WARNING	AMF asynchronous step Internal Warning: "%1"
-200905	AMF_FLEX_ASYNC_STEP_FAILED_TO_GET_REQ_ID	step "%1" (AMFStepCall::HandleAsyncRequest) failed to get request Id
aws_api_res.h		
-17199	AWS_MSG_EMPTY_ACCESSKEY	%1: Access key is empty.
-17198	AWS_MSG_EMPTY_SECRETKEY	%1: Secret key is empty.
-17197	AWS_MSG_EMPTY_SECRETID	%1: SecretId is empty.
-17196	AWS_MSG_FAILED_TO_CONNECT	%1: Failed to connect to the AWS server, please verify the ServerURL value and try again(error code %2).
-17195	AWS_MSG_AWS_ERROR	%1: error message from AWS is "%2".
-17194	AWS_MSG_AWS_NO_TOKEN	%1: http request success, but no token in response.
-17193	AWS_MSG_FAILED_TO_SET_PARAM	%1: save parameter failed, check the ResultParamName parameter.
aws_res.h		
-24400	AWS_SENT_MESSAGES	Sent messages: % 1 s.
-24399	AWS_SENT_BYTES	Sent bytes: % 1 s.
-24398	AWS_SENT_DURATION	Send duration: % 1 s.
-24397	AWS_REC_MESSAGES	Received messages: % 1 s.
-24396	AWS_REC_BYTES	Received bytes: % 1 s.
-24395	AWS_FAILED_PROP	Failed to get property: % 1 s.
-24394	AWS_NULL_POINTER	Nullpointer in conn[threadID] with threadID: % 1 s.
-24393	AWS_ACTION_ERROR	Error in exec_action: % 1 s.
-24392	AWS_LONG_PATH	Path is too long.
-24391	AWS_DESCRIPTION	Description
-24390	AWS_ERROR	Error: % 1 s
-24389	AWS_WARNING	Warning: % 1 s
-24388	AWS_NOTIFY	Notify: % 1 s
-24387	AWS_COMMAND	Executing command: % 1 s
-24386	AWS_GEN_C_JAVA	Found Java path: % 1 s.
-24385	AWS_GEN_C_NO_JAVA	JAVA was not found.
-24384	AWS_GEN_C_FAILED_LAUNCH	Failed to launch java application.
-24383	AWS_GEN_RETCODE_OK	Java application ended with code 0.
-24382	AWS_GEN_RETCODE_ERROR	Java application ended with code % 1 Id. Check CodeGenerationJava.txt for more logs.
-24381	AWS_GEN_JSON_NOT_FOUND	File ScriptGenItems.json does not exist in script folder.
-24380	AWS_GEN_EMPTY_JSON_FILE	File ScriptGenItems.json is empty. Nothing to generate.
azure_api_res.h		
-155000	AZURE_API_MSG_GENERIC_MESSAGE	1%
-154999	AZURE_API_MSG_FAILED_TO_CONNECT_SERVICE	Failed to connect the Azure api service.
-154998	AZURE_API_MSG_SEVER_RETURNED_ERROR	Get the error from azure server : %1.
binext_res.h		
-18900	BINVU_ACTION_NOT_FOUND	Vuser action %1 is not found. System error: %2.
-18899	BINVU_ACTION_ISCALLED	Calling Vuser action %1.
-18898	BINVU_ACTION_EXCEPT	Exception was raised when calling Vuser action %1: %2.
-18800	BINDRV_CANNOT_LOAD_UDLL	Cannot load Vuser library %1. System error: %2.
-18799	BINDRV_CANNOT_FREE_DLL	Cannot free Vuser library. System error: %2.
-18798	BINDRV_LOADLIB_EXCEPTION	Exception was raised while trying to load %1: %2.
-18797	BINDRV_UNLOADLIB_EXCEPTION	Exception was raised while unloading dynamic library: %1.
-18796	BINDRV_CONFIG_MISSING_ATTRIB_ERROR	The attribute %1 is missing.
-18795	BINDRV_EXEC_ACTION2	Error: cannot execute action %1. Handle is NULL.

Error code	Handle	Message\Additional information
-18794	BINDRV_TOO_MANY_PARAMETERS	Too many parameters to action %1 (% 2 ld > % 3 ld)
bridge_res.h		
-21999	BRIDGE_MSG_ERROR_TEMP_DIR_NOT_FOUND	Bridge: Temporary directory was not found.
-21998	BRIDGE_MSG_ERROR_ENCODE_DATA	Bridge: Failed to encode bridge message data.
-21997	BRIDGE_MSG_ERROR_CRITICAL_SECTION	Bridge: CriticalSection - %1.
-21996	BRIDGE_MSG_ERROR_CREATE_RESULTS_DIRECTORY	Bridge: Cannot create results directory "%1".
-21995	BRIDGE_MSG_ERROR_CONVERT_TO_NETDIR_PATH	Bridge: Cannot create network path (local path: "%1", netpath: "%2").
-21994	BRIDGE_MSG_ERROR_DECODE_START_SCENARIO_MSG	Bridge: Failed to decode start scenario data.
-21993	BRIDGE_MSG_WARNING_CREATE_WINDOW	Bridge: Failed to create bridge UI window.
-21992	BRIDGE_MSG_WARNING_LISTEN_SERVICE	Bridge: Unable to listen to service "%1".
-21991	BRIDGE_MSG_ERROR_CONNECTION_NOT_ALLOWED	Bridge: Connection is not allowed from host %1.
-21990	BRIDGE_MSG_WARNING_NO_CONTROLLERHOST	Bridge: 'controllerhost' is not found in command line.
-21989	BRIDGE_MSG_ERROR_FILE_PATH_TOO_LONG	Bridge: Failed to open directory since the path's string length exceeds the maximum allowed size of 247 characters, %1.
-21988	BRIDGE_MSG_ERROR_NETDIR	Bridge: Failed to get netdir.
-21987	BRIDGE_MSG_ERROR_WEB_CONNECTOR_INVALID_INFO	Bridge: Invalid information received for web connector transfer.
-21986	BRIDGE_MSG_ERROR_WEB_CONNECTOR_CREATE	Bridge: Failed to create web connector.
-21985	BRIDGE_MSG_ERROR_WEB_CONNECTOR_SEND_CLIENT_FAILED	Bridge: Failed to send data when web connector transfer finished.
-21984	BRIDGE_MSG_ERROR_WEB_CONNECTOR_TIMER_STOP	Bridge: Failed to stop web connector timer.
-21983	BRIDGE_MSG_ERROR_WEB_CONNECTOR_TIMER_START	Bridge: Failed to start web connector timer.
-21982	BRIDGE_MSG_ERROR_WEB_CONNECTOR_CONFIG_INIT_FAIL	Bridge: Failed to initialize attrib manager.
cciext_res.h		
-19900	CCIVUSER_INIT_CONTEXT	Vuser failed to create CCI context.
-19899	CCIVUSER_INIT_LOAD_ALLEXTDLL	Vuser failed to load DLLs for CCI context.
-19898	CCIVUSER_NO_EXT_DLL	Extension Dll name was not found; there may be unresolved symbols.
-19897	CCIVUSER_LOAD_EXT	CCI cannot load extension %1.
-19896	CCIVUSER_LOAD_UDLL	CCI cannot load user defined library %1.
-19895	CCIVUSER_INIT_LOAD_CODEFILE	CCI cannot load code file %1.
-19894	CCIVUSER_EXIT_UNLOAD_USERDLL	Obsolete
-19893	CCIVUSER_EXIT_UNLOAD_EXTDLL	Obsolete
-19892	CCIVUSER_EXEC_FUNCBYNAME	Obsolete
-19891	CCIVUSER_CCI_PRINT_MSG	CCI trace: %1.
-19890	CCIVUSER_CCI_ERROR_MSG	C interpreter run time error: %1.
-19889	CCIVUSER_LOAD_EXT_OK	CCI loaded extension %1 OK.
-19888	CCIVUSER_LOAD_UDLL_OK	CCI loaded user Dll %1 OK.
-19887	CCIVUSER_EXEC_FUNCBYNAME_OK	Obsolete
-19886	CCIVUSER_CCI_SECURITY_ERROR_MSG	CCI security error:You are running under secure mode and the function %1 is not allowed in this mode.
-19885	CCISecurity_CONFIG_CONTAINER_ERROR	CCI security error:Unable to create security configuration container.
-19884	CCISecurity_ADD_INI_FILE_ERROR	CCI security error:Unable to add security file of %1 to the security configuration container.
-19883	CCISERVER_MEM_ALLOC	Error in %1: Memory allocation failed.
-19882	CCISERVER_NO_VUSER	%1 cannot be called under server mode.
-19881	CCISERVER_EXEC_ACTION2	Error: cannot execute action %1. Handle is NULL.
-19880	CCISERVER_FUNC_FAIL	A call to %1 from %2 failed. Message id [% 3 ld].
-19879	CCI_CONFIG_MISSING_ATTRIB_ERROR	The attribute %1 is missing.
-19878	CCI_GENERAL_MSG	Obsolete
-19877	CCI_REACHED_MAX_EXT	Reached maximum extension dlls allowed (% 1 ld).
-19876	CCI_ARGUMENT_IS_NULL	On call to function %1 the argument %2 is NULL.
-19875	CCI_TOO_MANY_PARAMETERS	Too many parameters to action %1 (% 2 ld > % 3 ld)
-19800	CCIDRV_COMPILATION_FAILED	Vuser compilation failed.
-19799	CCIDRV_COMPILATION_ERROR	CCI compilation error -%1.
-19798	CCIDRV_CANNOT_OPEN_LOG_FILE	Cannot open CCI logfile %1. Unable to report the compilation errors.
-19797	CCIDRV_DEBUG_COMPILATION_FAILED	Vuser compilation failed. Please set CCIDebug to Off in CCI section of mdrv.dat file.
ce_client_msg_res.h		
-70499	CE_MSG_ERROR_FAILED_TO_CONSTRUCT	CE: Failed to construct %1; reason %2.
-70498	CE_MSG_ERROR_PT_MANAGER_NULL	CE: Per-thread manager not valid in %1.

Error code	Handle	Message\Additional information
-70497	CE MSG ERROR INVALID HANDLE	CE: Invalid handle in %1 call.
-70496	CE MSG ERROR OPERATION WHILE GROUP NOT READY	CE: Perform operation on not ready group.
-70495	CE MSG ERROR FAILED TO CREATE SERVICE HANDLE	CE: Failed to create %1 for service %2.
-70494	CE MSG ERROR XDR FAILED ENCODE	CE: Failure in xdr encoding : %1.
-70493	CE MSG ERROR XDR FAILED DECODE	CE: Failure in xdr decoding : %1.
-70492	CE MSG ERROR FAILED TO POST MESSAGE	CE: Failed to post message %1 to %2.
-70491	CE MSG ERROR FAILED CREATE GROUP	CE: Failure in creation group. Reason is %1.
-70490	CE MSG ERROR UNKNOWN TYPE VALUE	CE: Unknown value % 1 Id for type %2.
-70489	CE MSG ERROR NOT FOUND HANDLE	CE: Not found handle %1 during %2.
-70488	CE MSG ERROR FAILED TO ALLOCATE MEMORY	CE: Failed to allocate memory for %1 required size = % 2 Id bytes.
-70487	CE MSG ERROR VUREF ERROR	CE: Vuser reference (%1): Failed in function %2. Reason - %3.
-70299	CE MSG DBG GENERIC1	CE Client Debug: %1
-70298	CE MSG DBG GROUP COMMAND SENT	CE Client Debug: Group % 1 Id, Command sent type = % 2 Id.
-70297	CE MSG DBG GROUP MESSAGE SENT	CE Client Debug: Group % 1 Id, Message sent service = %2.
ce_server_msg_res.h		
-70999	CE MSG ERROR FAILED TO CONSTRUCT	CE Server: Failed to construct %1; reason: %2.
-70998	CE MSG ERROR FAILED TO CREATE SERVICE HANDLE	CE Server: Failed to create %1 for service %2.
-70997	CE MSG ERROR XDR FAILED ENCODE	CE Server: Failure in xdr encoding : %1.
-70996	CE MSG ERROR XDR FAILED DECODE	CE Server: Failure in xdr decoding : %1.
-70995	CE MSG ERROR FAILED TO POST MESSAGE	CE Server: Failed to post message %1 to %2.
-70994	CE MSG ERROR UNKNOWN TYPE VALUE	CE Server: Unknown value % 1 Id for type %2.
-70993	CE MSG ERROR FAILED LAUNCH API	CE Server: Failed to %1 rc = % 2 Id.
-70992	CE MSG ERROR GROUP NOT FOUND	CE Server: Group % 1 Id not found during %2
-70991	CE MSG ERROR REPORT NOT FOUND	CE Server: Report % 1 Id not found during %2
-70990	CE MSG ERROR VUSER NOT FOUND	CE Server: Vuser not found in %1.
-70989	CE MSG ERROR MDRV FAILED	CE Server: Abnormal mdrv termination. Mdrv process got failed status.
-70988	CE MSG ERROR MDRV KILLED	CE Server: Abnormal mdrv termination. Mdrv process got killed status.
-70987	CE MSG ERROR VUSER FAILED	CE Server: Vuser process/thread failed.
-70986	CE MSG ERROR FAILED TO HANDLE COMMAND	CE Server: Failed to handle command; reason = %1.
-70985	CE MSG ERROR FAILED TO HANDLE CONTROL REQUEST	CE Server: Failed to handle %1 control request; reason = %2.
-70984	CE MSG ERROR MDRV NOT ALLOCATED TO THREAD	CE Server: Vuser thread failed to allocate mdrv for running.
-70983	CE MSG ERROR NOT READY VUSER GOT KILLED	CE Server: Vuser got to killed status without being in ready or exiting.
-70982	CE MSG ERROR FAILED VUID FORMATTING REPLACE	CE Server: Failed to format command line by vuid replacement. VuidFormat = %1.
-70981	CE MSG ERROR FAILED TO ALLOCATE REND DETAILS HASH	CE Server: Failed to allocate rendezvous hash table.
-70980	CE MSG ERROR FAILED TO ALLOCATE VUSERS REND_HASH	CE Server: Failed to allocate Vusers hash table.
-70979	CE MSG ERROR UNKNOWN RENDEZVOUS NAME	CE Server: Failed to release % 1 Id vusers from unknown rendezvous %2.
-70978	CE MSG ERROR ILLEGAL RENDEZVOUS_CONTROL_COMMAND	CE Server: Received %1 command while rendezvous report is not active.
-70699	CE MSG DBG GENERIC1	CES Debug: %1
-70698	CE MSG DBG VUSER STATUS	CES Debug: Vuser % 1 Id: %2
-70697	CE MSG DBG MDRV STATUS	CES Debug: Mdrv (serial % 1 Id): %2
-70696	CE MSG DBG VUSER MESSAGE RECIEVED	CES Debug: Vuser % 1 Id: received message on service %2
-70695	CE MSG DBG GROUP CREATE STATUS	CES Debug: Group created. Vusers: % 1 Id, Mdrv Name: %2, Mdrv CmdLine: %3, Thread CmdLine: %4, Vuid Format CmdLine: %5.
-70694	CE MSG DBG GROUP COMMAND ARRIVED	CES Debug: Group % 1 Id, Command arrived type = % 2 Id.
-70693	CE MSG DBG GROUP MESSAGE ARRIVED	CES Debug: Group % 1 Id, Message arrived service = %2.
-70692	CE MSG DBG GROUP SUMMARY	CES Debug: Group % 1 Id, Summary = %2.
-70691	CE MSG DBG QUOTA MANAGER INVOKE START	CES Debug: Quota manager invocation started.
-70690	CE MSG DBG QUOTA MANAGER INVOKE END	CES Debug: Quota manager invocation ended (% 1 Id invoked).
-70549	CE MSG WARNING TOO MANY TO REALEASE	CE Server: Release amount exceeds actual number of vusers in rendezvous %1. Requested - % 2 Id, Released - % 3 Id.
citrix_res.h		
-91999	CITRIX MSG E NOT DISPLAYED	%1The window does not exist.%2
-91998	CITRIX MSG E DISPLAYED	%1The window exists.%2
-91997	CITRIX MSG E ILLEGAL PARAMETER	%1An illegal parameter was passed to this function.%2
-91996	CITRIX MSG E GENERAL ERROR	%1A general error occurred.%2
-91995	CITRIX MSG E DISCONNECTED	%1An unexpected disconnection occurred.%2
-91994	CITRIX MSG E WRONG ICAFILE	%1An ICA file is corrupted or the path is not valid.%2

Error code	Handle	Message\Additional information
-91993	CITRIX_MSG_E_NOT_ACTIVE	%1The window is not active.%2
-91992	CITRIX_MSG_E_INCORRECT_CLIENT_VER	0.01 Additional information: Incorrect client version.
-91991	CITRIX_MSG_E_NFUSE_FAIL	ctx_nfuse_connect(%1) failed. Internal Error: %2
-91990	CITRIX_MSG_E_OUT_OF_TIME	%1Operation exceeded timeout. %2
-91989	CITRIX_MSG_E_INTERNAL	Internal Error : %1
-91988	CITRIX_MSG_E_SYNC_ATTRIB	%1Sync on the attribute failed on the agent side. %2
-91987	CITRIX_MSG_E_QUERY_SESSION	0.01 Additional information: WFQuerySessionInformation() failed
-91986	CITRIX_MSG_E_NEEDS_SESSION	0.01 Additional information: This program must be run from within an ICA session.
-91985	CITRIX_MSG_E_CHANNEL_OPEN	0.01 Additional information: Failed to open the channel - error <number>.
-91984	CITRIX_MSG_E_TEXT_TRAP_INIT	1%
-91983	CITRIX_MSG_E_TEXT_TRAP_CONFIGURE	1%
-91982	CITRIX_MSG_E_WRITE_CHANNEL	1%
-91981	CITRIX_MSG_E_READ_CHANNEL	1%
-91980	CITRIX_MSG_E_WRONG_ARGUMENTS	%1 %2 Additional information: Wrong arguments passed to the function <function_name>.
-91979	CITRIX_MSG_E_CLICKS_NUMBER	%1 %2 Additional information: Cannot get the number of clicks.
-91978	CITRIX_MSG_E_LIST_ITEM	%1 %2 Additional information: The list item <item_name> is not found.
-91977	CITRIX_MSG_E_UNKNOWN_CLASS_NAME	%1 %2 Additional information: Unknown classname.
-91976	CITRIX_MSG_E_WRONG_MENU_HANDLE	%1 %2 Additional information: Wrong menu handle.
-91975	CITRIX_MSG_E_INVALID_MENU	%1 %2 Additional information: Number of menu items is 0 - probably invalid menu.
-91974	CITRIX_MSG_E_MENU_ITEM	%1 %2 Additional information: The menu item <item_name> doesn't exist.
-91973	CITRIX_MSG_E_CREATE_WINDOW	0.01 Additional information: Could not create window.
-91972	CITRIX_MSG_E_CREATE_HOOK	0.01 Additional information: Cannot create the focus hook.
-91971	CITRIX_MSG_E_CLIENT_NOT_FOUND	0.01 Additional information: Client not found.
-91970	CITRIX_MSG_E_TOO_LONG_DIR_NAME	Results directory path is too long . Please try to set the path with less characters .
-91969	CITRIX_MSG_E_SYNC_TEXT	%1Sync on the text failed on the agent side. %2
-91968	CITRIX_MSG_E_CREATE_SNAPSHOT	Unable to create screen snapshot : %1
-91967	CITRIX_MSG_E_DRIVER_INIT	%1Agent driver is absent.%2
-91966	CITRIX_MSG_INFNO IMAGE_SYNC_PASSED_NORMAL	Image synchronization succeeded, %1 percent match, Tolerance = %2.

Error code	Handle	Message\Additional information
-91965	CITRIX_MSG_INFNOR_IMAGE_SYNC_FAILED_NORMAL	Image synchronization failed, %1 percent match, Tolerance = %2.
-91964	CITRIX_MSG_INFEXT_IMAGE_SYNC_PASSED_EXTENDED	Image synchronization succeeded, %1 percent match, Tolerance = %2. Detected score is %3, image entropy is %4, match at (%5, %6).
-91963	CITRIX_MSG_INFEXT_IMAGE_SYNC_FAILED_EXTENDED	Image synchronization failed, %1 percent match, Tolerance = %2. Detected score is %3, image entropy is %4, match at (%5, %6).
-91962	CITRIX_MSG_ERRNOR_RSIP_DYNAMIC_LOADER_WAS_NOT_INIT	RSIP component's dynamic loader was not properly initialized. Error %1.
-91961	CITRIX_MSG_WAREXT_UNABLE_TO_OPEN_FILE	Unable to open %1 file.
-91960	CITRIX_MSG_ERRNOR_UNABLE_TO_OBTAIN_REPLAY_SNAPSHOT_DIR	Unable to obtain replay snapshot's directory for bitmap comparison.
-91959	CITRIX_MSG_ERRNOR_UNABLE_TO_OBTAIN_RECORD_SNAPSHOT_DIR	Unable to obtain record snapshot's directory for bitmap comparison.
-91958	CITRIX_MSG_WAREXT_UNABLE_TO_DELETE_FILE	Unable to delete file %1 with error: %2.
-91957	CITRIX_MSG_ERRNOR_INTERNAL_RSIP_ERROR	Internal RSIP component error.
-91956	CITRIX_MSG_ERRNOR_IMAGE_DETECTOR_IS_NOT_INIT	ImageDetector is not initialized.
-91955	CITRIX_MSG_E_WINDOW_SIZE_FORMAT	Failed to get window size, wrong format.
-91954	CITRIX_MSG_REGISTRY_PATCH_INSTALLATION_PASSED_SUCCESS	The Citrix registry patch installed successfully.
-91953	CITRIX_MSG_E_REGISTRY_PATCH_INSTALLATION_FAILED	The Citrix registry patch failed to install. Reason: %1 You need to install the following registry patch manually: <Opentext Performance Engineering installation folder>\\dat\\Enable_Citrix_API.reg. Double-click the file to install the registry patch.
-91952	CITRIX_MSG_E_REGISTRY_PATCH_INSTALLATION_INFO_RECORD	The Citrix registry patch was not installed and Opentext Performance Engineering could not record on this version of the Citrix client. The following registry patch must be installed: <Opentext Performance Engineering installation folder>\\dat\\Enable_Citrix_API.reg.
-91951	CITRIX_MSG_E_REGISTRY_PATCH_INSTALLATION_INFO_REPLAY	The Citrix registry patch was not installed and Opentext Performance Engineering could not replay on this version of the Citrix client. The following registry patch must be installed manually: <Opentext Performance Engineering installation folder>\\dat\\Enable_Citrix_API.reg.
-91950	CITRIX_MSG_E_WRONG_WINSTATE_ARG	Wrong [window state] argument was passed. Expected value is %1 or %2
comext_res.h		
-20900	COMVU_COINIT_FAILED	Obsolete
-20899	COMVU_CI_FAILED	Failed to create COM object (CoCreateInstance). Please check if the component is registered. System error: %1
-20898	COMVU_CANNOT_GET_ACTION_ID	Failed to get ID of action %1. System error: %2
-20897	COMVU_DISPINVOKE_FAILED	Dispatch-invoke failed on Vuser action id for %1. System error: %2
-20896	COMVU_DISPINVOKE_EXCEPTION_HR	Dispatch-invoke raised an exception in Vuser action %1. System error: %2
-20895	COMVU_DISPINVOKE_EXCEPTION_DESC	Dispatch-invoke raised exception in Vuser action: %1, exception file: %2, description: %3
-20894	COMVU_DISPINVOKE_EXCEPTION_RAISED	Dispatch-invoke raised exception in Vuser action %1.
-20893	COMVU_SUCESS_GETIDSOFNAMES	Successfully retrieved action id for: %1.
-20892	COMVU_COINIT_TYPE	Obsolete
-20891	COMVU_COUNINIT_TYPE	Obsolete
-20800	COMDRV_NO_IID	Component IID not specified (check your .USR file), trying to use IID_IDispatch instead.
-20799	COMDRV_CANNOT_READ_IID	Cannot read component id %1 - please check for syntax error . System error: %2.
-20798	COMDRV_NO_COMID	Component ProgId and CLSID are not specified - one of them is required.
-20797	COMDRV_CANNOT_READ_CLSID	Cannot read component CLSID %1 - check for syntax error. System error: %2.
-20796	COMDRV_CANNOT_READ_PROGID	Cannot read component ProgID %1 - verify that the component is registered. System error: %2.
-20795	COMDRV_CANNOT_CREATE_MREG	Failed to create COM registration utility. System error: %1.
-20794	COMDRV_CANNOT_REGISTER_COMP	Failed to register component %1. System error: %2
-20793	COMDRV_REGISTRATION_ERROR	Failed to register component %1. Server reported error: %2.
-20792	COMDRV_UNREGISTRATION_ERROR	Failed to unregister component %1. Server reported error: %2.
-20791	COMDRV_CANNOT_UNREGISTER_COMP	Cannot unregister component %1. System error: %2
-20790	COMDRV_COINIT_TYPE	Obsolete
-20789	COMDRV_COUNINIT_TYPE	Obsolete
-20788	COMDRV_REGISTER_COMPONENT_OK	Registration of %1 completed successfully.
-20787	COMDRV_UNREGISTER_COMPONENT_OK	UN-registration of %1 completed successfully.
comm_res.h		
-50999	COMM_MSG_GENERAL_MESSAGE	1%
-50998	COMM_MSG_WRITING_MESSAGE_FAILED	Communication Extension - Failed to write message %1 to fd %2 errno=%3
-50997	COMM_MSG_FAILED_TO_TRANSLATE_HOST	Communication Extension - Failed to reach host: %1
-50996	COMM_MSG_FAILED_TO_OPEN_SOCKET	Communication Extension - Failed to open socket, errno=%1
-50995	COMM_MSG_FAILED_TO_CONNECT_SOCKET	Communication Extension - Failed to connect to socket, errno=%1
-50994	COMM_MSG_RUN_HANDLER_NULL_CONTEXT	Communication Extension - No valid context received with Run signal
-50993	COMM_MSG_PAUSE_HANDLER_NULL_CONTEXT	Communication Extension - No valid context received with Pause signal
-50992	COMM_MSG_ERROR_IN_RPC_START_CONNECTION	Communication Extension - Error while starting RPC communication: \n%1
-50991	COMM_MSG_ERROR_IN_CREATE_CLIENT	Communication Extension - Error while creating RPC CLIENT: \n%1
-50990	COMM_MSG_ERROR_IN_CREATE_SERVER	Communication Extension - Error while creating RPC SERVER: \n%1

Error code	Handle	Message\Additional information
-50989	COMM_MSG_ERROR_IN_RPC_CLIENT_CALL	Communication Extension - %1
devweb_ext_msg.h		
	DEVWEB_EXT_GENERIC_MSG	1%
-227998	DEVWEB_EXT_ERROR_DEVWEB_HOME_NOT_CONFIGURED	The DEVWEB_PATH environment variable is not configured.
-227997	DEVWEB_EXT_ERROR_DEVWEB_EXECUTABLE_NOT_EXISTS	The DevWeb executable is not placed in the specified location '%1'.
-227996	DEVWEB_EXT_INFO_DEVWEB_HOME_LOCATION	Using the following DEVWEB_PATH environment variable: '%1'
-227995	DEVWEB_EXT_ERROR_DEVWEB_PROCESS_NOT_READY	The DevWeb engine is not ready
-227994	DEVWEB_EXT_ERROR_DEVWEB_PROCESS_FAIL_TO_START	The DevWeb engine failed to start with exit code %1
-227993	DEVWEB_EXT_ERROR_UNABLE_TO_BIND_PORT	Unable to bind to free port in range 1024 to 65535
-227992	DEVWEB_EXT_USER_ABORTED	The user aborted the execution, message: %1
-227991	DEVWEB_EXT_ERROR_DEVWEB_VALIDATION	The script validation failed: %1
-227990	DEVWEB_EXT_MSG_9	0.01 Additional information: Placeholder messages for the mdrv process.
-227989	DEVWEB_EXT_MSG_10	1%
-227988	DEVWEB_EXT_MSG_11	1%
-227987	DEVWEB_EXT_MSG_12	1%
-227986	DEVWEB_EXT_MSG_13	1%
-227985	DEVWEB_EXT_MSG_14	1%
-227984	DEVWEB_EXT_MSG_15	1%
-227983	DEVWEB_EXT_MSG_16	1%
-227982	DEVWEB_EXT_MSG_17	1%
-227981	DEVWEB_EXT_MSG_18	1%
-227980	DEVWEB_EXT_MSG_19	1%
-227979	DEVWEB_EXT_MSG_20	1%
-227978	DEVWEB_EXT_MSG_21	1%
-227977	DEVWEB_EXT_MSG_22	1%
-227976	DEVWEB_EXT_MSG_24	1%
-227975	DEVWEB_EXT_MSG_25	1%
-227974	DEVWEB_EXT_MSG_26	1%
-227973	DEVWEB_EXT_MSG_27	1%
-227972	DEVWEB_EXT_MSG_28	1%
-227971	DEVWEB_EXT_MSG_29	1%
-227970	DEVWEB_EXT_MSG_30	1%
-227969	DEVWEB_EXT_MSG_31	1%
-227968	DEVWEB_EXT_MSG_32	1%
-227967	DEVWEB_EXT_MSG_33	1%
-227966	DEVWEB_EXT_MSG_34	1%
-227965	DEVWEB_EXT_MSG_35	1%
-227964	DEVWEB_EXT_MSG_36	1%
-227963	DEVWEB_EXT_MSG_37	1%
-227962	DEVWEB_EXT_MSG_38	1%
-227961	DEVWEB_EXT_MSG_39	1%
-227960	DEVWEB_EXT_MSG_40	1%
-227959	DEVWEB_EXT_MSG_41	1%
-227958	DEVWEB_EXT_MSG_42	1%
-227957	DEVWEB_EXT_MSG_43	1%
-227956	DEVWEB_EXT_MSG_44	1%
-227955	DEVWEB_EXT_MSG_45	1%
-227954	DEVWEB_EXT_MSG_46	1%
-227953	DEVWEB_EXT_MSG_47	1%
-227952	DEVWEB_EXT_MSG_48	1%
-227951	DEVWEB_EXT_MSG_49	1%
-227950	DEVWEB_EXT_MSG_50	1%

Error code	Handle	Message\Additional information
-227949	DEVWEB_ENGINE_MSG_1	0.01 Additional information: Placeholder messages for the DevWeb engine.
-227948	DEVWEB_ENGINE_MSG_2	1%
-227947	DEVWEB_ENGINE_MSG_3	1%
-227946	DEVWEB_ENGINE_MSG_4	1%
-227945	DEVWEB_ENGINE_MSG_5	1%
-227944	DEVWEB_ENGINE_MSG_6	1%
-227943	DEVWEB_ENGINE_MSG_7	1%
-227942	DEVWEB_ENGINE_MSG_8	1%
-227941	DEVWEB_ENGINE_MSG_9	1%
-227940	DEVWEB_ENGINE_MSG_10	1%
-227939	DEVWEB_ENGINE_MSG_11	1%
-227938	DEVWEB_ENGINE_MSG_12	1%
-227937	DEVWEB_ENGINE_MSG_13	1%
-227936	DEVWEB_ENGINE_MSG_14	1%
-227935	DEVWEB_ENGINE_MSG_15	1%
-227934	DEVWEB_ENGINE_MSG_16	1%
-227933	DEVWEB_ENGINE_MSG_17	1%
-227932	DEVWEB_ENGINE_MSG_18	1%
-227931	DEVWEB_ENGINE_MSG_19	1%
-227930	DEVWEB_ENGINE_MSG_20	1%
-227929	DEVWEB_ENGINE_MSG_21	1%
-227928	DEVWEB_ENGINE_MSG_22	1%
-227927	DEVWEB_ENGINE_MSG_24	1%
-227926	DEVWEB_ENGINE_MSG_25	1%
-227925	DEVWEB_ENGINE_MSG_26	1%
-227924	DEVWEB_ENGINE_MSG_27	1%
-227923	DEVWEB_ENGINE_MSG_28	1%
-227922	DEVWEB_ENGINE_MSG_29	1%
-227921	DEVWEB_ENGINE_MSG_30	1%
-227920	DEVWEB_ENGINE_MSG_31	1%
-227919	DEVWEB_ENGINE_MSG_32	1%
-227918	DEVWEB_ENGINE_MSG_33	1%
-227917	DEVWEB_ENGINE_MSG_34	1%
-227916	DEVWEB_ENGINE_MSG_35	1%
-227915	DEVWEB_ENGINE_MSG_36	1%
-227914	DEVWEB_ENGINE_MSG_37	1%
-227913	DEVWEB_ENGINE_MSG_38	1%
-227912	DEVWEB_ENGINE_MSG_39	1%
-227911	DEVWEB_ENGINE_MSG_40	1%
-227910	DEVWEB_ENGINE_MSG_41	1%
-227909	DEVWEB_ENGINE_MSG_42	1%
-227908	DEVWEB_ENGINE_MSG_43	1%
-227907	DEVWEB_ENGINE_MSG_44	1%
-227906	DEVWEB_ENGINE_MSG_45	1%
-227905	DEVWEB_ENGINE_MSG_46	1%
-227904	DEVWEB_ENGINE_MSG_47	1%
-227903	DEVWEB_ENGINE_MSG_48	1%
-227902	DEVWEB_ENGINE_MSG_49	1%
-227901	DEVWEB_ENGINE_MSG_50	1%
-227900	DEVWEB_ENGINE_MSG_51	1%
-227899	DEVWEB_ENGINE_MSG_52	1%
-227898	DEVWEB_ENGINE_MSG_53	1%
-227897	DEVWEB_ENGINE_MSG_54	1%
-227896	DEVWEB_ENGINE_MSG_55	1%
-227895	DEVWEB_ENGINE_MSG_56	1%

Error code	Handle	Message\Additional information
-227894	DEVWEB_ENGINE_MSG_57	1%
-227893	DEVWEB_ENGINE_MSG_58	1%
-227892	DEVWEB_ENGINE_MSG_59	1%
-227891	DEVWEB_ENGINE_MSG_60	1%
-227890	DEVWEB_ENGINE_MSG_61	1%
-227889	DEVWEB_ENGINE_MSG_62	1%
-227888	DEVWEB_ENGINE_MSG_63	1%
-227887	DEVWEB_ENGINE_MSG_64	1%
-227886	DEVWEB_ENGINE_MSG_65	1%
-227885	DEVWEB_ENGINE_MSG_66	1%
-227884	DEVWEB_ENGINE_MSG_67	1%
-227883	DEVWEB_ENGINE_MSG_68	1%
-227882	DEVWEB_ENGINE_MSG_69	1%
-227881	DEVWEB_ENGINE_MSG_70	1%
-227880	DEVWEB_ENGINE_MSG_71	1%
-227879	DEVWEB_ENGINE_MSG_72	1%
-227878	DEVWEB_ENGINE_MSG_73	1%
-227877	DEVWEB_ENGINE_MSG_74	1%
-227876	DEVWEB_ENGINE_MSG_75	1%
-227875	DEVWEB_ENGINE_MSG_76	1%
-227874	DEVWEB_ENGINE_MSG_77	1%
-227873	DEVWEB_ENGINE_MSG_78	1%
-227872	DEVWEB_ENGINE_MSG_79	1%
-227871	DEVWEB_ENGINE_MSG_80	1%
-227870	DEVWEB_ENGINE_MSG_81	1%
-227869	DEVWEB_ENGINE_MSG_82	1%
-227868	DEVWEB_ENGINE_MSG_83	1%
-227867	DEVWEB_ENGINE_MSG_84	1%
-227866	DEVWEB_ENGINE_MSG_85	1%
-227865	DEVWEB_ENGINE_MSG_86	1%
-227864	DEVWEB_ENGINE_MSG_87	1%
-227863	DEVWEB_ENGINE_MSG_88	1%
-227862	DEVWEB_ENGINE_MSG_89	1%
-227861	DEVWEB_ENGINE_MSG_90	1%
-227860	DEVWEB_ENGINE_MSG_91	1%
-227859	DEVWEB_ENGINE_MSG_92	1%
-227858	DEVWEB_ENGINE_MSG_93	1%
-227857	DEVWEB_ENGINE_MSG_94	1%
-227856	DEVWEB_ENGINE_MSG_95	1%
-227855	DEVWEB_ENGINE_MSG_96	1%
-227854	DEVWEB_ENGINE_MSG_97	1%
-227853	DEVWEB_ENGINE_MSG_98	1%
-227852	DEVWEB_ENGINE_MSG_99	1%
-227851	DEVWEB_ENGINE_MSG_100	1%
-227850	DEVWEB_RUNNER_MSG_1	0.01 Additional information: Placeholder messages for the Node.js runner.
-227849	DEVWEB_RUNNER_MSG_2	1%
-227848	DEVWEB_RUNNER_MSG_3	1%
-227847	DEVWEB_RUNNER_MSG_4	1%
-227846	DEVWEB_RUNNER_MSG_5	1%
-227845	DEVWEB_RUNNER_MSG_6	1%
-227844	DEVWEB_RUNNER_MSG_7	1%
-227843	DEVWEB_RUNNER_MSG_8	1%
-227842	DEVWEB_RUNNER_MSG_9	1%
-227841	DEVWEB_RUNNER_MSG_10	1%
-227840	DEVWEB_RUNNER_MSG_11	1%

Error code	Handle	Message\Additional information
-227839	DEVWEB_RUNNER_MSG_12	1%
-227838	DEVWEB_RUNNER_MSG_13	1%
-227837	DEVWEB_RUNNER_MSG_14	1%
-227836	DEVWEB_RUNNER_MSG_15	1%
-227835	DEVWEB_RUNNER_MSG_16	1%
-227834	DEVWEB_RUNNER_MSG_17	1%
-227833	DEVWEB_RUNNER_MSG_18	1%
-227832	DEVWEB_RUNNER_MSG_19	1%
-227831	DEVWEB_RUNNER_MSG_20	1%
-227830	DEVWEB_RUNNER_MSG_21	1%
-227829	DEVWEB_RUNNER_MSG_22	1%
-227828	DEVWEB_RUNNER_MSG_24	1%
-227827	DEVWEB_RUNNER_MSG_25	1%
-227826	DEVWEB_RUNNER_MSG_26	1%
-227825	DEVWEB_RUNNER_MSG_27	1%
-227824	DEVWEB_RUNNER_MSG_28	1%
-227823	DEVWEB_RUNNER_MSG_29	1%
-227822	DEVWEB_RUNNER_MSG_30	1%
dotnet6_res.h		
-228999	DOTNET6_MISSING_LIBRARIES	Could not add required dotnet libraries to path %_1_s.
-228998	DOTNET6_SDK_BITNESS_MISMATCH	SDK bitness and replay mode must match.
-228997	DOTNET6_BITNESS_NOT_FOUND	Cannot get bitness for SDK.
-228996	DOTNET6_MAXIMUM_ERRORS	Exceeded maximum number of compilation errors.
-228995	DOTNET6_NO_SDK_SET	SDK not found.
-228994	DOTNET6_DIRECTORY_DOESNT_EXIST	Given directory does not exist: %_1_s.
-228993	DOTNET6_EXECUTABLE_NOT_FOUND	Dotnet executable was not found at given path: %_1_s.
-228992	DOTNET6_EXECUTABLE_NOT_FOUND_VERSION	Could not find compatible SDKs (supported versions are 6 and 8).
-228991	DOTNET6_CANNOT_DELETE	Could not delete all output files before compilation.
-228990	DOTNET6_DIRECTORY_NOT_WRITABLE	Cannot compile script because Vuser directory is not writable.
-228989	DOTNET6_COMPILATION_ERROR	Error during script compilation.
-228988	DOTNET6_MUTEX_ERROR	Could not acquire mutex.
-228987	DOTNET6_SHARED_DLL_ERROR	Could not get DotNetSharedDLLs.
-228986	DOTNET6_METHOD_NOT_EXIST	Virtual user method %_1_s does not exist.
-228985	DOTNET6_METHOD_RETURNED_VALUE	Virtual user method %_1_s does not return an integer.
-228984	DOTNET6_INNER_EXCEPTION	Inner exception: %_1_s
-228983	DOTNET6_MANAGER_IS_NULL	Execution exception: Replay manager is null.
-228982	DOTNET6_PT_ERROR	Error in PerThreadInit. Cannot create ReplayManager.
-228981	DOTNET6_SDK_SEARCH_REG	Searching sdk in Windows registries.
-228980	DOTNET6_SDK_SEARCH_PATH	Searching sdk in PATH environment variable
-228979	DOTNET6_SDK_FOUND	Found valid path for .NET sdk: %_1_s.
-228978	DOTNET6_SDK_SEARCH_REG_PATH	Searching sdk in registry path: %_1_s.
-228977	DOTNET6_CANNOT_LOAD_LIBRARY	Cannot load library "nethost.dll".
-228976	DOTNET6_CANNOT_LOAD_RUNTIME	Could not load SDK runtime libraries. Please check runtime settings - SDK version.
-228975	DOTNET6_SDK_FORMAT	SDK version format is wrong. Expected format major version without build number.
-228974	DOTNET6_UNSUPPORTED	You are using unsupported SDK !
-228973	DOTNET6_SUPPORTED	SDK version is not supported. Supported versions are 6 and 8.
-228972	DOTNET6_CURRENT_VERSION	SDK version is %_1_ld!
-228971	DOTNET6_NO_VERSION	No SDK version is set.
-228970	DOTNET6_USING_DEFAULT	Using .NET 6 as default value.
drvcomm_res.h		
-42999	COMM_MSG_XDR_FAILED_ENCODING	Communication extension - XDR failed while encoding %1.
extansion_res.h		
-46999	EXTANSION_MSGS_PER_THREAD_FUNCTION_FAILED	Failed to initialize transaction server.
-46998	EXTANSION_MSGS_ERROR_MSG_FROM_CHANNEL	Channel error message : %1(error nuber: %2)

Error code	Handle	Message\Additional information
-46997	EXTANSION_MSGS_FAILED_TO_INITIALIZE_CLIENT_PARAM	Failed to initialize trans client param - %1 or %2.
-46996	EXTANSION_MSGS_FAILED_TO_OPEN_CHANEL_TRANS_SERVER	Failed to open transaction server channel.
-46995	EXTANSION_MSGS_FAILED_TO_OPEN_CHANEL_TRANS_CLIENT	Failed to open transaction client channel.
-46994	EXTANSION_MSGS_FAILED_TO_CREATE_BR_TR_OBJECT	Failed to create Br_Tr object.
-46993	EXTANSION_MSGS_FAILED_TO_CREATE_LISTENER_SERVICE_FOR_ERRORS	Failed to create listener service for errors
-46992	EXTANSION_MSGS_FAILED_TO_DECODE_ERROR_DATA	Failed to decode error data
-46991	EXTANSION_MSGS_FAILED_TO_CREATE_TIMER_OBJECT	Faild to create timer object.
-46990	EXTANSION_MSGS_FAILED_TO_OPEN_CHANEL_BRIDGE_SERVER	Failed to open bridge server channel
-46989	EXTANSION_MSGS_FAILED_TO_OPEN_CHANEL_BRIDGE_CLIENT	Failed to open bridge client channel.
-46988	EXTANSION_MSGS_FAILES_TO_SET_INTERNAL_ATTRIB	Failed to set transaction server attribute.
-46987	EXTANSION_MSGS_BRTR_QUIT_FROM_BRIDGE	Quit message from bridge arived.
-46986	EXTANSION_MSGS_END_SCENARIO_FROM_BRIDGE	end scenario message from bridge arived.
-46985	EXTANSION_MSGS_TR_SETTINGS_FROM_BRIDGE	config setting message from bridge arived ---> %1.
-46984	EXTANSION_MSGS_SENDING_VUSER_CMD_LINE	sendin command line through bridge ---> %1
-46983	EXTANSION_DEBUG_MESSAGE	Debug info from lr_bridge ---> %1
-46982	EXTENSION_NO_LIC_MON	There is no license for monitor '%1' used by the Monitors over FireWall component.
-46981	EXTENSION_CANT_INIT_LIC_DLL	The Monitors over FireWall component cannot initialize the license dll.
-46980	EXTENSION_STREAMING_BUFFERING_OPEN_TIME	Time to start(Can play)
-46979	EXTENSION_STREAMING_BUFFERING_LAG_TIME	Buffering pause time
-46978	EXTENSION_STREAMING_BUFFERING_SEEK_TIME	Buffering seek time
-46977	EXTENSION_STREAMING_PLAYING_TIME	Playing time
-46976	EXTENSION_STREAMING_VIDEO_QUALITY	Video Quality(Bandwidth)
-46975	EXTENSION_STREAMING_BANDWIDTH	Bandwidth
-46974	EXTENSION_STREAMING_DOWNLOAD_SPEED	Download speed
-46973	EXTENSION_STREAMING_NUMBER_OF_PLAY_EVENTS	Number of play events
-46972	EXTENSION_STREAMING_NUMBER_OF_SEEK_EVENTS	Number of seek events
-46971	EXTENSION_STREAMING_NUMBER_OF_PAUSE_EVENTS	Number of pause events
-46970	EXTENSION_STREAMING_NUMBER_OF_DOWNLOAD_RETRIES	Number of download retries
-46969	EXTENSION_STREAMING_NUMBER_OF_BUFFERING_VIDEO	Number of buffering video
-46968	EXTENSION_STREAMING_NUMBER_OF_LAGGING_VIDEO	Number of lagging video
-46967	EXTENSION_STREAMING_NUMBER_OF_PLAYING_VIDEO	Number of playing video
flex_res.h		
-202999	FLEX_MSG_INTERNAL_ERROR	Internal Error - %1
-202998	FLEX_MSG_FLEX_STEP_WITH_STEP_NAME_START	%1("%2") started
-202997	FLEX_MSG_FLEX_STEP_WITH_STEP_NAME_SUCCESS	%1("%2") was successful
-202996	FLEX_MSG_FLEX_STEP_WITH_STEP_NAME_END_STATUS	%1("%2") ended with "%3" status
-202995	FLEX_MSG_FLEX_STEP_START	%1 started
-202994	FLEX_MSG_FLEX_STEP_SUCCESS	%1 was successful
-202993	FLEX_MSG_FLEX_STEP_END_STATUS	There was %1 during %2
-202992	FLEX_MSG_FLEX_GENERAL_MESSAGE	1%
-202991	FLEX_MSG_DATAPOINT_FAILED	Reporting user data point "%1" failed (Transaction_UserDataPoint rc=%_2_id)
-202990	FLEX_RTMP_NET_ERROR_MESSAGE_CONNECT_SAME_RTMP_CONNECTION_ID	Requesting two connections with the same rtmpConnectionId
-202989	FLEX_RTMP_NET_ERROR_MESSAGE_WRONG_HOST_FORMAT	Wrong format of host parameter
-202988	FLEX_RTMP_NET_ERROR_MESSAGE_NO_ADDRESS_FOUND	No address found for establishing connection
-202987	FLEX_RTMP_NET_ERROR_MESSAGE_HOST_NOT_FOUND	Host not found for establishing connection
-202986	FLEX_RTMP_NET_ERROR_MESSAGE_TIMEOUT_EXPIRED	Connection failed due to timeout
-202985	FLEX_RTMP_NET_ERROR_MESSAGE_UNKNOWN	RTMP communication level(Connect/Send/Receive): Unknown exception
-202984	FLEX_RTMP_NET_ERROR_MESSAGE_HANDSHAKE_FAILED	Handshake failed while establishing an RTMP connection
-202983	FLEX_RTMP_NET_ERROR_MESSAGE_SEND_FAILED	RTMP send failed
-202982	FLEX_RTMP_NET_ERROR_MESSAGE_RECV_FAILED	RTMP receive failed
-202981	FLEX_RTMP_NET_ERROR_MESSAGE_NO_CONNECTION_ID	RTMP communication level(Send/Receive/Disconnect): RTMP connection ID does not exist
-202980	FLEX_RTMP_NET_TIMEOUT_MESSAGE	Timeout expired
-202979	FLEX_RTMP_NET_ERROR_MESSAGE_NO_DEFAULT_VERSION	RTMP handshake: Server did not respond with the default RTMP version "%_1_id"

Error code	Handle	Message\Additional information
-202978	FLEX_RTMP_NET_ERROR_MESSAGE_NO_APPLICABLE_ADDRESS_FOUND	No applicable address found for establishing connection
-202977	FLEX_RTMP_NET_ERROR_MESSAGE_SSL_CONNECTION_CLOSED_UNEXPECTEDLY	SSL connection closed unexpectedly
-202976	FLEX_RTMP_MSG_HANDLER_CONNECT_TWO_IDENTICAL_CID	RTMP connection id already exists.
-202975	FLEX_RTMP_MSG_HANDLER_DISCONNECT_CID_NOT_EXIST	Invalid RTMP connectionId. Disconnect failed.
-202974	FLEX_RTMP_MSG_HANDLER_RECEIVE_CID_NOT_EXIST	Invalid RTMP connectionId. Receive failed.
-202973	FLEX_RTMP_MSG_HANDLER_UNABLE_TO_DECODE	Error occurred while decoding RTMP binary message.
-202972	FLEX_RTMP_MSG_HANDLER_SCRIPT_API_NOT_SUPPORTED	ScriptApi: "%1" not supported in function: "%2"
-202971	FLEX_RTMP_MSG_HANDLER_CONNECT_TWO_IDENTICAL_SID	RTMP session id already exists.
-202970	FLEX_RTMP_SCENARIO_MNGR_SERVER_ERROR	Error returned from the server: "%1".
-202969	FLEX_RTMP_SCENARIO_MNGR_SERVER_ERROR_NO_DESCRIPTION	Error returned from the server. See extended log for full details.
-202968	FLEX_RTMP_SCENARIO_MNGR_NO_CONNECTION_ID	Internal Error (Scenario Manager): Connection/Session ID does not exist.
-202967	FLEX_RTMP_SCENARIO_MNGR_SENDING_AUTO_ACK	Sending automatic acknowledge message. Bytes read so far: % 1 _Id.
-202966	FLEX_RTMP_SCENARIO_MNGR_SENDING_AUTO_PING_RESPONSE	Sending automatic ping response message. Timestamp to be sent: % 1 _Id.
-202965	FLEX_RTMP_SCENARIO_MNGR_AUTO_ACK_FINISH	Finished sending acknowledgment message.
-202964	FLEX_RTMP_SCENARIO_MNGR_AUTO_PING_RESPONSE_FINISH	Finished sending ping response message.
-202963	FLEX_RTMP_EXTENDED_START_OF_RTMP_PACKETS_TO_SEND_LIST	The following RTMP messages will be sent:
-202962	FLEX_RTMP_EXTENDED_RTMP_MESSAGE	RTMP header: ChunkStreamID:% 1 _Id MessageStreamID:% 2 _Id DataType:%3 , RTMP message: %4
-202961	FLEX_RTMP_EXTENDED_RTMP_MESSAGE_NO_BINARY	RTMP header: ChunkStreamID:% 1 _Id MessageStreamID:% 2 _Id DataType:%3 , Binary body length: % 4 _Id
-202960	FLEX_RTMP_EXTENDED_END_OF_RTMP_PACKETS_TO_SEND_LIST	End of list of RTMP messages to be sent.
-202959	FLEX_RTMP_EXTENDED_START_OF_RECEIVED_RTMP_PACKETS_LIST	The following RTMP messages have been received:
-202958	FLEX_RTMP_EXTENDED_END_OF_RECEIVED_RTMP_PACKETS_LIST	End of list of received RTMP messages.
-202957	FLEX_RTMP_EXTENDED_STARTED_PACKET_HANDLING	Started handling RTMP %1 message
-202956	FLEX_RTMP_EXTENDED_FINISHED_PACKET_HANDLING	Finished handling RTMP %1 message
-202955	FLEX_RTMP_EXTENDED_DATA_MESSAGE_EXTRACTED_FROM_FLV	Data message extracted from FLV tag: %1
-202954	FLEX_RTMP_EXTENDED_STREAM_ENDED_WITH_SUMMARY_TIMEOUT	%1 summary: Timeout exceeded
-202953	FLEX_RTMP_EXTENDED_STREAM_ENDED_WITH_SUMMARY_STOP_SUCCESS	%1 summary: Stream successfully received. NetStream.Play.Stop message received from server
-202952	FLEX_RTMP_EXTENDED_STREAM_ENDED_WITH_SUMMARY_TIMESTAMP	%1 summary: Stream received until minimum play duration (% 2 _Id millisec)
-202951	FLEX_RTMP_EXTENDED_STREAM_ENDED_WITH_SUMMARY_UNKNOWN	f%1 summary: Stream ended for unknown reason
-202950	FLEX_RTMP_EXTENDED_LAST_RECEIVED_TIMESTAMP	Last received media timestamp: % 1 _Id millisec
-202949	RTMP_REPORT_MSG_STEP_FAILED	<CENTER>Step failed</CENTER>
-202948	RTMP_REPORT_MSG_FAILED_ON_RTMP	<CENTER>Step failed on RTMP request</CENTER>
-202947	RTMP_REPORT_MSG_FAILED_ON_PARSING_PARAMS	<CENTER>Step failed while parsing step parameters</CENTER>
-202946	RTMP_REPORT_MSG_STEP_WARNING_PARSING_PARAMS	<CENTER>Step passed with warning while parsing step parameters</CENTER>
-202945	RTMP_REPORT_MSG_STEP_WARNING_RTMP	<CENTER>Step passed with warning on RTMP request</CENTER>
-202944	RTMP_REPORT_STEP_SUCCEEDED_DETAILS	<CENTER>%1 was successful</CENTER>
-202943	RTMP_TUNNELED_REPORT_MSG_FAILED_ON_HTTP	<CENTER>Step failed on HTTP request</CENTER>
-202942	FLEX_RTMP_NET_MESSAGE_START_CONNECTING	Establishing connection with %1
-202941	FLEX_RTMP_NET_MESSAGE_FINISHED_CONNECTING	Connection with %1 has been established
-202940	FLEX_RTMP_NET_MESSAGE_STARTING_HANDSHAKE	Starting an RTMP handshake with host %1 on port %2
-202939	FLEX_RTMP_NET_MESSAGE_FINISHED_HANDSHAKE	Successfully finished RTMP handshake with host %1 on port %2
-202938	FLEX_RTMP_NET_MESSAGE_SENDING_STARTED	Sending the following bytes to %1:\n%2
-202937	FLEX_RTMP_NET_MESSAGE_SENDING_FINISHED	Successfully finished sending bytes to %1
-202936	FLEX_RTMP_NET_MESSAGE_RECEIVING_STARTED	Starting to receive bytes from %1
-202935	FLEX_RTMP_NET_MESSAGE_RECEIVING_FINISHED	Received the following bytes from %1:\n%2
-202934	FLEX_RTMP_NET_MESSAGE_RECEIVING_FINISHED_EX	Received a total of % 1 _Id bytes from %2
-202933	FLEX_RTMP_NET_MESSAGE_DISCONNECTING	Disconnecting from %1
-202932	FLEX_RTMP_NET_INIT_HANDSHAKE	RTMP handshake: initiating RTMP handshake
-202931	FLEX_RTMP_NET_HANDSHAKE_SENDING_C0_C1	RTMP handshake: Sending C0 and C1
-202930	FLEX_RTMP_NET_HANDSHAKE_RECEIVING_S0_S1	RTMP handshake: Receiving S0 and S1
-202929	FLEX_RTMP_NET_HANDSHAKE_SENDING_C2	RTMP handshake: Sending C2
-202928	FLEX_RTMP_NET_HANDSHAKE_RECEIVING_S2	RTMP handshake: Receiving S2
-202927	FLEX_RTMP_NET_ERROR_ILLEGAL_C0_C1_CHUNK_SIZE	Illegal C0,C1 chunk size
-202926	FLEX_RTMP_TUNNELED_STEP_WITH_STEP_NAME_END_STATUS	There was %1 during Flex RTMP Tunneled step ("%2")

Error code	Handle	Message\Additional information
-202925	FLEX_RTMP_TUNNELED_STEP_NAME_SUCCESS	Flex RTMP Tunneled step ("%1") was successful
-202924	FLEX_RTMP_TUNNELED_FAILEDTO_WRITE_TO_SNAPSHOT	Flex RTMP Tunneled step Failed to write to snapshot, Task id is undefined
-202923	FLEX_RTMP_TUNNELED_MESSAGE_DISCONNECTING	Disconnecting from %1
-202922	FLEX_RTMP_TUNNELED_EMPTY_MESSAGE_BUFFER	Failed to Send automatic message due to empty buffer
-202921	FLEX_ERROR	0.01 Additional information: Generic error.
-202920	FLEX_RTMP_REG_SAVE_PARAM_NO_MATCHES_FOUND	No matches were found for the specified query: "%1"
-202919	FLEX_RTMP_REG_SAVE_PARAM_RESERVE1	
-202918	FLEX_RTMP_REG_SAVE_PARAM_RESERVE2	
-202917	FLEX_RTMP_REG_SAVE_PARAM_RESERVE3	
-202916	FLEX_RTMP_REG_SAVE_PARAM_RESERVE4	
-202915	FLEX_RTMP_MSG_HANDLER_CONNECT_TWO_IDENTICAL_CID_WITH_SUGGESTION	RTMP connection id already exists. Turn on "Close all open RTMP connections after each iteration" at "Runtime Settings->Flex->RTMP"
gatling_ext_msg.h		
-229999	GATLING_EXT_GENERIC_MSG	1%
-229998	GATLING_EXT_ERROR_3RD_PARTY_MSG	Gatling internal error: %1
-229997	GATLING_ERROR_GATLING_HOME_NOT_CONFIGURED	The GATLING_HOME environment variable is not configured.
-229996	GATLING_EXT_ERROR_GATLING_MEASUREMENT_FAILURE	Failed to initialize Gatling measurements server.
-229995	GATLING_EXT_ERROR_GATLING_PROCESS_FAIL_TO_START	The Gatling engine failed to start with exit code %1
-229994	GATLING_EXT_ERROR_GATLING_EXECUTABLE_NOT_EXISTS	Failed to find the Gatling executable.
-229993	GATLING_EXT_ERROR_GATLING_INVALID_CONFIG	Failed to find the Gatling script or class
-229992	GATLING_EXT_ERROR_GATLING_PROCESS_NOT_READY	The Gatling engine is not ready
-229991	GATLING_EXT_ERROR_UNABLE_TO_BIND_PORT	Unable to bind to free port in range 1024 to 65535
-229990	GATLING_EXT_ERROR_ABORTED	The user aborted the execution, message: %1
-229989	GATLING_EXT_WARN_DATA_LOSS	There could be data loss because of truncation
-229988	GATLING_EXT_WARN_JAVA_HOME	Gatling requires 64bit JDK 11 or JDK 17. Check the Java settings in the runtime settings or the JAVA_HOME environment variable.
-229987	GATLING_EXT_ERROR_FAILED_TO_CREATE_PIPE	Failed to create pipes for Gatling.
-229986	GATLING_EXT_ERROR_PROCESS_UNEXPECTEDLY_QUIT	The Gatling engine quited unexpectedly. exit code "%1".
-229985	GATLING_EXT_ERROR_NOT_FOUND	The Gatling execution engine was not Found. To continue working with it, please install it with the installation guide.
general_categories.h		
33553433	GENERAL_MSG_CAT_INTERNAL_ERROR	Internal error
33553434	GENERAL_MSG_CAT_NETWORK_ERROR	Network error
33553435	GENERAL_MSG_CAT_FILE_ACCESS	File access error
33553436	GENERAL_MSG_CAT_INVALID_ARGUMENT	Invalid argument error
33553437	GENERAL_MSG_CAT_SSL_ERROR	SSL error
33553438	GENERAL_MSG_CAT_AUTH_ERROR	Authentication error
33553439	GENERAL_MSG_CAT_SYSTEM_ERROR	System call error
33553440	GENERAL_MSG_CAT_FTP_ERROR	FTP error
33553441	GENERAL_MSG_CAT_HTTP_ERROR	HTTP error
33553442	GENERAL_MSG_CAT_OUT_OF_MEMORY_ERROR	Out of memory
har_ext_msg.h		
-230999	HAREXT_ERROR_VUSER_RUN_RESULT_NOT_FOUND	Could not find vuser run result file '%1'.
-230998	HAREXT_ERROR_HAR_GENERATOR_NOT_FOUND	HARGenerator.exe is not found from '%1'.
-230997	HAREXT_ERROR_FAILED_GENERATE_HAR_WITH_EXCEPTION	Exception thrown when calling HARGenerator.exe.
-230996	HAREXT_WARN_NO_HAR_GENEARTED	HAR file is not generated. Vuser run result may not contain any HTTP transactions.
-230995	HAREXT_NOTIFY_HAR_GEN_EXIT	HARGenerator.exe exits with '%1'.
-230994	HAREXT_DEBUG_PRINT_HARGEN_CMD	Command line used to generate HAR file: '%1'.
interp_manager_res.h		
-64900	IM_NO_SUCH_INTERP_CLIENT	Can't load interpreter loader client named %1.
-64899	IM_FAILED_TO_LOAD_DLL	Obsolete
-64898	IM_FAILED_TO_LOAD_FUNC	Obsolete

Error code	Handle	Message\Additional information
-64897	IM_NULL_ARG	Argument %2 was passed to function %1 as NULL.
-64896	IM_MEM_ALLOC	Error in %1: Memory allocation failed.
-64895	IM_NULL_ARGUMENT	Obsolete
-64894	IM_FUNC_IS_NULL	Function %1 of interpreter client %2 is NULL.
-64893	IM_INTERPRETER_ACTION_FAILED	Failed to %1 by interpreter %2.
-64892	IM_FUNC_CALL_NOT_ALLOWED	Calling function %1 of interpreter client %2 is not allowed due to incorrect working mode.
is_m.h		
4000	STORM_EXT_OK	Ok
4001	STORM_EXT_SERVER_GENERAL_ERR	Index Server general error
4002	STORM_EXT_IS_INIT_FAILED	Index Server initialization failed
4003	STORM_EXT_IS_INSUFFICIENT_MEMORY	Index Server: insufficient memory
4004	STORM_EXT_INVALID_PARAMETERS	Invalid function parameters
4005	STORM_EXT_INSUFFICIENT_RECORDS	Insufficient records for parameter '%1' in table to provide the Vuser with unique data
4006	STORM_EXT_IS_ALREADY_CLOSED	Index Server is already closed
4007	STORM_EXT_CANNOT_OPEN_ANY_DT	Cannot open any data table
4008	STORM_EXT_CANNOT_OPEN_DT	Cannot open one or more data tables
4009	STORM_EXT_CANNOT_RETRIEVE_TEST_INFO	Error in retrieving test information
4010	STORM_EXT_IS_ALREADY_INIT	Index Server is already init
4011	STORM_EXT_IS_INIT_FAILED	Index Server initialization failed
4012	STORM_EXT_ERROR_CODE_OUT_OF_RANGE	Error Code is out of range
4013	STORM_EXT_UNIQUE_PARAM_ERR_DURATION	You cannot run a test using the "unique" parameter type in a scenario scheduled to run continuously (Duration option). Either change the parameter type, or run the scenario without this scheduling mode.
4014	STORM_EXT_UNIQUE_PARAM_ERR_GOAL	You cannot run a test using the "unique" parameter type in a Goal Oriented Scenario. Either change the parameter type, or run the Manual Scenario.
iso_res.h		
-231999	ISO_SENT_MESSAGES	Sent messages: % 1 s.
-231998	ISO_SENT_BYTES	Sent bytes: % 1 s.
-231997	ISO_REC_DURATION	Receive duration: % 1 s.
-231996	ISO_REC_MESSAGES	Received messages: % 1 s.
-231995	ISO_REC_BYTES	Received bytes: % 1 s.
-231994	ISO_FAILED_PROP	Failed to get property: % 1 s.
-231993	ISO_NULL_POINTER	Nullpointer in conn[threadID] with threadID: % 1 s.
-231992	ISO_ACTION_ERROR	Error in exec action: % 1 s.
-231991	ISO_LONG_PATH	Path is too long.
-231990	ISO_DESCRIPTION	Description
-231989	ISO_ERROR	Error: % 1 s
-231988	ISO_WARNING	Warning: % 1 s
-231987	ISO_NOTIFY	Notify: % 1 s
-231986	ISO_COMMAND	Executing command: % 1 s
javaInteraction_res.h		
-22999	JAVA_INTERACTION_INVALID_HOST	Invalid host or port number. Probably Java wasn't spawned.
-22998	JAVA_INTERACTION_LOST_CONN_PAR	Lost connection to Java Server: % 1 s.
-22997	JAVA_INTERACTION_LOST_CONN	Lost connection to Java Server.
-22996	JAVA_INTERACTION_INCORRECT_MESSAGE	Incorrect message.
-22995	JAVA_INTERACTION_INTER_CONN	Java connection interrupted: % 1 s.
-22994	JAVA_INTERACTION_UNRECOGNIZED_API	Unrecognized function call: % 1 s. Handler is not activated, probably it is not supported for this protocol.
-22993	JAVA_INTERACTION_CLASSPATH_MISSING	Missing java classpath: % 1 s.
-22992	JAVA_INTERACTION_INVALID_JAVA_PATH	Invalid java exe path: % 1 s.
-22991	JAVA_INTERACTION_PATH_TOO_LONG	Script path too long!
-22990	JAVA_INTERACTION_FAILED_CONN	Failed to connect to java process.
-22989	JAVA_INTERACTION_JAVA_INIT_FAILED	Java process initialization failed: % 1 s.
-22988	JAVA_INTERACTION_WRONG_PARAM	Wrong number of parameter in function call: % 1 s.
-22987	JAVA_INTERACTION_INVALID_CLASSPATH	Invalid classpath entry: % 1 s.
-22986	JAVA_INTERACTION_QUOTES	Quoted string is not properly terminated: % 1 s.

Error code	Handle	Message\Additional information
-22985	JAVA_INTERACTION_ENVIRONMENT_VAR_SUBS	Environment: % 1 s substituted with: % 2 s.
-22984	JAVA_INTERACTION_JAVA9	"\\"Use -Xbootclasspath parameters\\" option is not available from Java 9 and above. Using regular classpath."
-22983	JAVA_INTERACTION_SED	Failed to launch sed.exe.Check that your PATH environment variable contains path to sed executable.
-22982	JAVA_INTERACTION_FAILED_PROP	Failed to get property % 1 s.
-22981	JAVA_INTERACTION_FILE_NOT_FOUND	File is not found: % 1 s.
-22980	JAVA_INTERACTION_FILE_NOT_CREATED	Failed to create file: % 1 s.
-22979	JAVA_COMPILATION_ERROR	Failed to compile the Actions.java file. Please add the <JDK>\\bin to the path and try again.
-22978	JAVA_GENERAL_MESSAGE	% 1 s
java_search_res.h		
-236999	JAVA_SEARCH_EMPTY	1%
-236998	JAVA_SEARCH_VALIDATING	validating JDK: %1
-236997	JAVA_SEARCH_JDK_NOT_FOUND	JDK not found
-236996	JAVA_SEARCH_IN_REG_OLD	search current JDK in Windows registry at(SOFTWARE\\JavaSoft\\Java Development Kit)
-236995	JAVA_SEARCH_IN_REG_NEW	search current JDK in Windows registry at (SOFTWARE\\JavaSoft\\JDK)
-236994	JAVA_SEARCH_IN_REG_LOCATION	search current JDK in Windows registry at (%1)
-236993	JAVA_SEARCH_IN_REG_SysWOW64	search current JDK in Windows registry at (SOFTWARE\\Wow6432Node\\JavaSoft\\Java Development Kit)
-236992	JAVA_SEARCH_IN_VAR	search in %1
-236991	JAVA_SEARCH_JAVAC_NOT_FOUND	JDK found at %1, but javac is not found. Is it JRE(not JDK) directory?
-236990	JAVA_SEARCH_JVM_NOT_FOUND	JDK found at %1, but jvm.dll(jvm.so) is not found
-236989	JAVA_SEARCH_JDK_FOUND_AT	JDK found at %1
-236988	JAVA_SEARCH_JVM_CAN_NOT_LOAD	JDK found at %1, but can not load jvm.dll(jvm.so) from %2.
-236987	JAVA_SEARCH_EXPECT_BIT	Expect %1-bit JVM. To enable %2-bit JVM, please specify the JDK path in the "Runtime Settings"->"Java VM" and select the check-box: "Miscellaneous"->"Replay script with 64-bit" accordingly.
-236986	JAVA_SEARCH_FAILED_TO_EXECUTE	Failed to execute %1
-236985	JAVA_SEARCH_UNSUPPORTED	Unsupported java version found at %1. version: %2 architecture: %3
-236984	JAVA_SEARCH_FULL_OUTPUT	Full java output %1
javaext_msg.h		
-100499	JAVAEXT_ERROR_FAILED_TO_START_JVM	Failed to start Java virtual machine (return code = % 1 ld)
-100498	JAVAEXT_ERROR_FAILED_TO_LOAD_CLASS_LOADER_CLASS	Failed to load class loader class
-100497	JAVAEXT_ERROR_FAILED_TO_CREATE_GLOBAL_REF	Failed to add a global reference to an object of class %1
-100496	JAVAEXT_ERROR_FAILED_TO_ATTACH_THREAD	Failed to attach current thread to the Java virtual machine (return code = % 1 ld)
-100495	JAVAEXT_ERROR_NO_CLASS_NAME_SPECIFIED	No class name specified in parameter '%1'
-100494	JAVAEXT_ERROR_INVALID_HANDLE	An invalid handle was passed to function %1
-100493	JAVAEXT_ERROR_NO_METHOD_SIGNATURE_SPECIFIED	No method signature was specified in parameter %1 to javaext_exec_func2
-100492	JAVAEXT_ERROR_FAILED_TO_FETCH_METHOD_ID	Failed to fetch method ID for method %1 (signature : %2) of class %3
-100491	JAVAEXT_ERROR_FAILED_TO_CREATE_OBJECT	Failed to create an object of class %1 (signature : %2)
-100490	JAVAEXT_ERROR_FAILED_TO_CREATE_STRING	Failed to create Java string for string %1
-100489	JAVAEXT_ERROR_FAILED_TO_CREATE_ARRAY	Failed to create an array of type %1
-100488	JAVAEXT_ERROR_FAILED_TO_CALL_METHOD	Failed to call method %1 of class %2
-100487	JAVAEXT_ERROR_OBJECT_NOT_CREATED	Client tried to call a method on a null object of class %1
-100486	JAVAEXT_ERROR_OBJECT_ALREADY_CREATED	Client tried to call a constructor for an existing object of class %1
-100485	JAVAEXT_ERROR_ILLEGAL_METHOD_SIGNATURE_FORMAT	Method %1 of class %2 was called with an illegal signature (%3)
-100484	JAVAEXT_ERROR_UNSUPPORTED_METHOD_RETURN_TYPE	An unsupported return type was specified in signature %1 (only integer types up to 32 bit and void are allowed)
-100483	JAVAEXT_ERROR_JAVA_EXCEPTION_THROWN	Java virtual machine has thrown the following exception : %1
-100482	JAVAEXT_ERROR_FAILED_TO_CREATE_CLASS_CONTEXT	Failed to create a context for class %1
-100481	JAVAEXT_ERROR_FAILED_TO_CREATE_OBJECT_CONTEXT	Failed to create object context for object of class %1
-100480	JAVAEXT_ERROR_JAR_FILE_DOES_NOT_EXIST	Jar file %1 does not exist
-100479	JAVAEXT_ERROR_FAILED_TO_UPDATE_DYNAMIC_LIBRARY_PATH	Failed to update dyncall library path with %1
-100478	JAVAEXT_ERROR_FAILED_TO_LOAD_JVM	Failed to load Java virtual machine. Reason : %1
-100477	JAVAEXT_WARNING_INCORRECT_DEBUGGING_PARAMETERS	Debugging params are incorrect (%1), remote debugging is disabled
-100476	JAVAEXT_ERROR_FAILED_TO_CONVERT_JAVA_STRING	Failed to convert a Java string to C string
-100475	JAVAEXT_ERROR_OUTPUT_BUFFER_IS_TOO_SMALL	Buffer supplied when calling method %1 is too small (supplied size : % 2 ld, required size : % 3 ld)
-100474	JAVAEXT_ERROR_FAILED_TO_EXTRACT_ARRAY	Failed to extract an array of type %1
-100473	JAVAEXT_ERROR_FAILED_TO_SET_ARRAY_ELEMENT	Failed to set an array element of type %1. Index : % 2 ld, array size : % 3 ld
-100472	JAVAEXT_ERROR_FAILED_TO_SET_ARRAY_REGION	Failed to set an array region of type %1. Indices : % 2 ld to % 3 ld

Error code	Handle	Message\Additional information
-100471	JAVAEXT_ERROR_JVM_EXITED	Java virtual machine exited, exit status = % 1 ld
-100470	JAVAEXT_ERROR_JVM_ABORTED	Java virtual machine terminated abnormally
-100469	JAVAEXT_ERROR_SCRIPT_EXCEPTION	A system exception was thrown in method %1 of class %2. Description : %3
jmxext_msg.h		
-232999	JMXEXT_GENERIC_MSG	'%1'
-232998	JMXEXT_ERROR_3RD_PARTY_MSG	JMeter internal error: %1
-232997	JMETER_ERROR_JMX_FILE_NOT_CONFIGURED	The JMX file is not configured.
-232996	JMXEXT_ERROR_FAILED_TO_GET_JAVA	Jmeter Required JRE 8+. Check the Java settings in the runtime settings or the JAVA_HOME environment variable.
-232995	JMXEXT_ERROR_FAILED_TO_CREATE_PIPE	Failed to create pipes for Jmeter.
-232994	JMETER_ERROR_PROCESS_UNEXPECTEDLY_QUIT	The JMeter Process quitted unexpectedly, exit code '%1'.
-232993	JMETER_ERROR_NOT_FOUND	The JMeter engine was not Found. To continue working with it, please install it with the installation guide.
jsext_msg.h		
-100999	JSEXT_ERROR_FAILED_TO_OPEN_FILE	Failed to open javascript file '%1'.
-100998	JSEXT_ERROR_FAILED_TO_GET_FILE_PATH	Failed to get javascript file path '%1'.
-100997	JSEXT_ERROR_FAILED_TO_FIND_SCRIPT	Failed to find script in compiled map '%1'.
-100996	JSEXT_ERROR_V8_EXCEPTION	Script error. Exception string is '%1'.
-100995	JSEXT_ERROR_V8_EXCEPTION_WITH_INFO	'%1'.\n\t\tSource line: '%2'.
-100994	JSEXT_NOTIFY_RUN_SCRIPT_RESULT	The script running result of '%1' is '%2'.
-100993	JSEXT_ERROR_RUN_SCRIPT_ERROR	Run script '%1' error.
-100992	JSEXT_NOTIFY_CALL_FUNCTION_RESULT	The function call result of '%1' in '%2' is '%3'.
-100991	JSEXT_ERROR_CALL_FUNCTION_ERROR	Call function '%1' in script '%2' error.
-100990	JSEXT_WARN_NO_ADDON_IN_SECTION	Addon name was not found in section '%1'.
-100989	JSEXT_WARN_FAILED_TO_LOAD_ADDON	Failed to load addon %1.
-100988	JSEXT_DEBUG_LOAD_ADDON_OK	JsExt loaded extension %1 OK.
-100987	JSEXT_WARN_FAILED_TO_GET_V8_FUNC	Failed to get function '%1' from '%2'.
-100986	JSEXT_WARN_INIT_LOAD_CODEFILE	JsExt cannot load code file %1.
-100985	JSEXT_ERROR_FAILED_TO_PARSE_DEBUG_MESSAGE	Parse debug message failed, might be invalid json. '%1'.
-100984	JSEXT_WARN_BREAKPOINT_NOT_EXIST	Failed to delete breakpoint. The breakpoint doesn't exist.
-100983	JSEXT_WARN_FAILED_TO_GET_CALL_STACK	Failed to get call stack.
-100982	JSEXT_WARN_FAILED_TO_SET_BREAKPOINT	Failed to set breakpoint.
-100981	JSEXT_WARN_FAILED_TO_DELETE_BREAKPOINT	Failed to delete breakpoint.
-100980	JSEXT_GENERIC_MSG	'%1'
kafka_res.h		
-233999	KAFKA_SENT_BYTES	Sent bytes: % 1 ld.
-233998	KAFKA_RECEIVED_BYTES	Received bytes: % 1 ld.
-233997	KAFKA_SEND_DURATION	Send duration(ms): % 1 ld.
-233996	KAFKA_SENT_MESSAGES_1	Sent message: 1.
-233995	KAFKA_RECEIVED_MESSAGES	Received messages: % 1 ld.
-233994	KAFKA_WRONG_PARAMETERS	Wrong number of parameter in function call: % 1 s.
-233993	KAFKA_PATH	Path is too long.
-233992	KAFKA_ERROR_DESCRIPTION	Exception description: % 1 s.
-233991	KAFKA_NULL_POINTER	Nullpointer in conn[threadID] with threadID = % 1 ld.
-233990	KAFKA_MAXUSERS	Failed to get property MaxVusersPerJava.
-233989	KAFKA_ERROR	Error: % 1 s.
-233988	KAFKA_WARNING	Warning: % 1 s.
-233987	KAFKA_REC_STARTED	Recording started.
-233986	KAFKA_REC_JAVA_STARTED	Launching recording application.
-233985	KAFKA_REC_CONNECTED	Connected to KafkaListener.
-233984	KAFKA_REC_EVENT	Kafka event recorded.
-233983	KAFKA_REC_EVENT_SENT	Event % 1 s sent.
-233982	KAFKA_REC_EVENT_SUCCESS	Event % 1 s sent and executed successfully.
-233981	KAFKA_REC_EVENT_ERROR	Event % 1 s sent and executed with error.
-233980	KAFKA_REC_EVENT_UNEXP	Event % 1 s received an unexpected response.
-233979	KAFKA_REC_RESPONSE	Response for function % 1 s.

Error code	Handle	Message\Additional information
-233978	KAFKA_REC_EVENT_COUNTER	Event counter started.
-233977	KAFKA_REC_FAILED_COPY	Failed to copy consumer properties file to script directory.
-233976	KAFKA_REC_FAILED	Failed to start Java application for recording. Check JDK/JRE path and classpath.
-233975	KAFKA_REC_FAILED2	Failed to launch recording process.
-233974	KAFKA_REC_FAILED3	Failed to launch application: % 1 s.
-233973	KAFKA_REC_ENV	Please check/correct your PATH environment variable.
-233972	KAFKA_REC_ERROR	Recording has thrown an error. CodeGeneration process will not start!
-233971	KAFKA_REC_RTS	Resetting classpath RTS.
-233970	KAFKA_REC_CODEGEN	Launching code generation process.
-233969	KAFKA_REC_CODEGEN_ERROR	Could not start code generation.
-233968	KAFKA_REC_EVENTS_EXIST	Found recorded events.
-233967	KAFKA_REC_EVENTS_DEFAULT	Just default event recorded.
-233966	KAFKA_REC_JAVA	Found Java: % 1 s.
-233965	KAFKA_REC_JAVA_PARAM	Found Java parameters: % 1 s.
-233964	KAFKA_REC_RO	Failed to update script configuration file to match recording options.
-233963	KAFKA_REC_PROPS	Cannot get Vugen root folder.
-233962	KAFKA_REC_COPY_ERROR	Error occurred while copying kafka_ro.ini to script folder: % 1 s.
-233961	KAFKA_REC_COPY_ERROR2	Error occurred while copying kafka configuration file to script folder: % 1 s.
-233960	KAFKA_REC_DIR	Cannot create "props" folder.
-233959	KAFKA_REC_COMMENT	Inserting Comment: % 1 s.
-233958	KAFKA_REC_RENDEZVOUS	Inserting rendezvous: % 1 s.
-233957	KAFKA_REC_TRAN_S	Starting transaction: % 1 s.
-233956	KAFKA_REC_TRAN_E	Ending transaction: % 1 s.
-233955	KAFKA_REC_COM	Error when communicating with java process.
launcher_msg.h		
-29999	LNCH_ERR_FLAGS	Launching process (%1) failed. The flag "LNCH_FLG_GET_READY_STATUS" cannot be used without the "LNCH_FLG_MDRV_BASED" flag.
-29998	LNCH_ERR_THREAD_FLAGS	Launching thread failed. The flag "LNCH_FLG_GET_READY_STATUS" cannot be used without the "LNCH_FLG_MDRV_BASED" flag.
-29997	LNCH_ERR_KILL_NOTFOUND	Cannot kill process or thread with moniker "%1". The specified process or thread was not found.
-29996	LNCH_ERR_PROCESS_FAILED	Process "%1" was not created. Reason: %2.
-29995	LNCH_ERR_PROCESS_ATTACH_FAILED	Process with attachable label "%1" was not attached. Reason: %2.
-29994	LNCH_ERR_THREAD_FAILED	One thread was not created. Reason: %1.
-29993	LNCH_ERR_APPNAME	Missing app_name parameter. A process was not created.
-29992	LNCH_ERR_REMOTE_HOST_NOT_RESP	Client %1 is not responding.
-29991	LNCH_ERR_HOST1	Process "%1" failed. No remote host name was given.
-29990	LNCH_ERR_HOST2	Process "%1" failed. You cannot work remotely on the local host. Use the "lnch_on_process()" function instead.
-29989	LNCH_ERR_HOST_ATTACH	Failed to attach to process with attach label "%1". No remote host name was given.
-29988	LNCH_ERR_LNCH_SERVICE	"m_agent_process" was not loaded on remote machine "%1". Reason: %2.
-29987	LNCH_ERR_PROCESS_REMOTE	Process "%1" was not created on remote host "%2". Reason: %3.
-29986	LNCH_ERR_PROCESS_REMOTE_ATTACH	Process with attachable label "%1" on remote host "%2" was not attached. Reason: %3.
-29985	LNCH_ERR_THREAD_REMOTE	Thread was not created on remote host "%1". Reason: %2.
-29984	LNCH_ERR_KILL_REMOTE	Process "%1" on remote host "%2" was not killed because it didn't reach READY status yet.
-29983	LNCH_ERR_MONIKER	Process "%1" failed. The moniker size that was passed is not big enough.
-29982	LNCH_ERR_THRD_MONIKER	Thread failed. The moniker size that was passed is not big enough.
-29981	LNCH_ERR_PARAMETER_NOT_INIT	One or more variables were not initialized (check if the pt_init and pp_init functions of the Launcher were called).
-29980	LNCH_ERR_PROCESS_KILL	Failed to kill process "%1" on remote host "%2". The moniker was not returned yet.
-29979	LNCH_ERR_THREAD_KILL	Failed to kill thread on remote host "%1". The moniker was not returned yet.
-29978	LNCH_ERR_SERVER_USR	Usr file "br_lrch_server usr" was not found.
-29977	LNCH_ERR_FAIL_KILL_PROCESS	Failed to kill process "%1". Reason: %2.
-29976	LNCH_ERR_FAIL_KILL_THREAD	Failed to kill thread. Reason: %1.
-29975	LNCH_ERR_FAIL_CREATE_QUOTA_OBJ	Failed to create quota manager object from pp_init of Launcher.
-29974	LNCH_ERR_SERVER_CREATE_ERROR	Failed to create "%1" server.
-29973	LNCH_ERR_RESET_STAUS_CB	Failed to reset launcher status call back function. Reason: %1.
-29972	LNCH_ERR_PROCESS_THREAD_ABNORMAL_EXIT	Process or thread has exited abnormally. Reason: %1.
-29971	LNCH_ERR_PARSING_CMDLN	Failed in parsing command line "%1".
-29970	LNCH_ERR_FAILED_LOAD_REG	Installation of additional environments required. Failed to read registry key: "%1".

Error code	Handle	Message\Additional information
-29969	LNCH_ERR_FAILED_LOAD_REG_ETXRA	Installation of additional environments required. Failed to read registry keys:"%1" and "%2".
-29968	LNCH_ERR_FAILED_FIND_APP_EXTRA	Failed to find application %1 in paths: "%2", "%2%4bin"\n, "%3" and "%3%4bin".
-29967	LNCH_ERR_FAILED_FIND_APP	Failed to find application %1 in paths: "%2" and "%2%3bin".
-29966	LNCH_ERR_WRITE_CMDLN	Failed to write command line into file. Reason: %1.
-29965	LNCH_ERR_FAILED_CREATE_PUBLISH_SUBSCRIBE_OBJ	Failed to create publish subscribe object from pt_init of Launcher.
-29964	LNCH_ERR_SECURITY_FILE_ERROR	Security Error: Security Processes file not found.
-29963	LNCH_ERR_PROCESS_NOT_RESP	Process "%1" is not responding.
-29962	LNCH_ERR_FAILED_ATTACH_COMM	Failed to attach to process with label "%1". Reason: Communication error.
-29961	LNCH_ERR_ATTACH_TEMPDIR	Failed to attach to process with label "%1". Error in creating temp directory.
-29960	LNCH_ERR_ATTACH_PARSECMDLN	Failed to attach to process with label "%1". Error in parsing command line into file.
-29959	LNCH_ERR_ATTACH_CREATE_NETDIR	Failed to attach to process with label "%1". Error in creating netdir directory,or global_dir directory.
-29958	LNCH_ERR_ATTACH_AS_SON_ALREADY_HAS_PARENT	Failed to attach to process with label "%1". Process already has parent.
-29957	LNCH_ERR_ATTACH_ALREADY_HAS_PARENT	Failed to attach to process. Process already has parent.
-29956	LNCH_ERR_ATTACH_LABEL	Missing attach label parameter. A process was not attached.
-29955	LNCH_ERR_ATTACH_NO_CONFIRMATION_FROM_PARENT	Failed to attach to parent process. No attach confirmation received from parent.
-29954	LNCH_ERR_MONIKER_ATTACH	Failed to attach to Process with label "%1". The moniker size passed was not big enough.
-29953	LNCH_ERR_DETACH_NOTFOUND	Cannot detach process or thread with moniker "%1". Process was not found.
-29952	LNCH_ERR_FAILED_DETACH_COMM	Failed to detach from process with label "%1". Reason: Communication error.
-29951	LNCH_ERR_DETACH_NO_PARENT	Failed to detach from parent. Reason: This process has no parent.
-29950	LNCH_ERR_FAILED_DETACH_PARENT_COMM	Failed to detach from parent process. Reason: Communication error.
-29949	LNCH_ERR_GET_ATTACH_LABEL_OUT_BUF_SIZE	Failed to return label. The label out size passed was not big enough.
-29948	LNCH_ERR_GET_ATTACH_LABEL_NO_OUT_BUF	Failed to return label. The label out buffer is NULL.
-29947	LNCH_ERR_ATTACH_FAILED_GET_HOST_NAME	Failed to attach to process with label "%1". Reason: Failed to get current host name.
-29946	LNCH_ERR_ATTACH_FAILED_GET_HOST_BY_NAME	Failed to attach to process with label "%1". Reason: Failed to get current host info by the name "%2".
-29945	LNCH_ERR_ATTACH_FAILED_READ_COMMANDS	Failed to attach to process with label "%1". Reason: Failed to read commands.
-29944	LNCH_ERR_DETACH_FAILED_READ_COMMANDS	Failed to detach process with moniker "%1". Reason: Failed to read commands.
-29943	LNCH_ERR_PREVIOUS_DETACH_IN_PROCESS	Failed to detach from parent. Previous detach already in process.
-29942	LNCH_ERR_CONFLICTING_CMDLINE_FLAGS	Command line has conflicting flags: -%1 and -%2.
-29941	LNCH_ERR_ATTACH_READCMDLN	Failed to attach to process with label "%1". Error in reading command line.
-29940	LNCH_ERR_UNSECURE_PROCESS_IN_SECURITYMODE	Process "%1" was not created. You are running under secure mode and this process is not allowed in this mode.
-29939	LNCH_ERR_CREATE_DAEMON_FAILED	Failed to fork while creating daemon. Reason: %1.
-29938	LNCH_ERR_DETACH_FAILED	Failed to detach process with moniker "%1". Reason: %2.
-29937	LNCH_ERR_KILL_FAILED	Failed to kill process or thread with moniker %1. Reason: %2.
-29936	LNCH_ERR_FAILED_CONNECT_TO_PARENT	Failed to connect to parent, reason - %1.
-29935	LNCH_ERR_NO_ROUTER_AVAILABLE	Failed to connect to router. Router port not available (Hint: check the merc_agent.cfg file in the dat directory of your installation).
-29934	LNCH_ERR_FAILED_TO_FIND_GD_NAME	Failed to find guarantee delivery name in the command line (-lnch_gd_name option).
-29933	LNCH_ERR_WEB_SERVER_ATTACH	Failed to attach over firewall to process with attach label "%1" on remote host "%2", no web server name was given.
-29932	LNCH_ERR_NO_FAMILY_JUST_FOR_PROCESS	Launching with no family flag is just for process.
-29931	LNCH_ERR_MATCHER_THREAD_INIT_FAILED	The matchers thread initialization failed.
-29930	LNCH_ERR_MATCHER_PROCESS_INIT_FAILED	The matchers process initialization failed.
-29929	LNCH_ERR_ATTACH_FAILED_READ_COMMANDS_IN_SON	Failed to read commands sent in attach request.
-29928	LNCH_ERR_FAILED_LAUNCH_ATTACH_WITH_SAME_GDNAME	Failed to launch/attach process, process with gd name %1 already exists.
-29927	LNCH_ERR_FAILED_CALL_USER_CALLBACK	Failed to call one or more user callbacks in process uses guaranty delivery communication.
-29926	LNCH_ERR_USER_CALLBACK_EXCEPTION	Exception was raised when calling user callback in process uses guarantee delivery communication.
-29925	LNCH_ERR_ATTACH_FW_NO_SECTION_OR_ACCEPTOR_NAME	Failed to attach over firewall to process with label "%1", reason - no http section name or acceptor name was passed.
-29924	LNCH_ERR_NO_MI_LISTENER_NAME	Failed to start connection over firewall. No "MI Listener Name" was given.
-29923	LNCH_ERR_NO_LOCAL_MACHINE_KEY	Failed to start connection over firewall. No "Local Machine Key" was given.
-29922	LNCH_ERR_NO_HOST_NAME_IN_TIMEOUT_CONNECTION	Failed to register connection request from "%1". No host name was given.
-29921	LNCH_ERR_FAILED_ARCHIVE_SAVE_OPERATION	Failed to save launcher operation into archive.
-29920	LNCH_ERR_FAILED_RESTORE_ARCHIVE	Failed to restore launcher archive.
-29919	LNCH_ERR_HOST_NOT_FOUND_IN_ROUTER_TABLE	Failed to add request to router table. Reason - could not find host "%1" in router table.
-29918	LNCH_ERR_POST_NOT_RESPONDING_MSG	Failed to post a message to host "%1", that host "%2" is not responding.
-29917	LNCH_ERR_CREATE_DAEMON_EXIT_SERVER	Failed to create a shared memory custom channel server "%1", for aborting the daemon.
-29916	LNCH_ERR_FAILED_GET_HOST_NAME	Failed to get current host name.
-29915	LNCH_ERR_FAILED_ATTACH_CLUSTER	Failed to attach to cluster. Reason - %1.
-29914	LNCH_ERR_FAILED_LAUNCH_ATTACH_GUARANTEE	Failed to launch/attach using flag LNCH_FLG_GUARANTY, current process should have attachable label (-lnch_attachable option).
-29913	LNCH_ERR_FAILED_GET_CLUSTER_NAME	Failed to get ClusterName from file: %1.

Error code	Handle	Message\Additional information
-29912	LNCH_ERR_GD_ERROR	Guaranty delivery error: %1 (GD name: %2), %3.
-29911	LNCH_FAILED_READ_GD_ATTRIBS	Failed to read GD attributes from command line: %1.
-29910	LNCH_FAILED_INIT_GD	Failed to initialize GD object with name: %1, reason - %2.
-29909	LNCH_ERR_PROCESS_NOT_ATTACHABLE	Process failed to be attachable on label "%1". Reason: Communication error .
-29908	LNCH_FAILED_READ_PERSISTENT_BUFFER	Failed to read from persistent buffer.
-29907	LNCH_FAILED_WRITE_PERSISTENT_BUFFER	Failed to write to persistent buffer.
-29906	LNCH_FAILED_GET_MONIKER_FROM_CMDLINE	Failed to get moniker from command line.
-29905	LNCH_ERR_USR_TOKEN	Missing lnch_user_token parameter.A process was not created.
-29904	LNCH_ERR_REMOTE_PROCESS_FAILED	Process "%1" on machine "%2" was not created. Reason: - %3.
-29903	LNCH_ERR_FAILED_REMOVE_ARCHIVE	Failed to remove corrupted archive from the disk.
-29902	LNCH_ERR_PVC_DECODE	protocol version compatibility decode error.
-29901	LNCH_ERR_PVC_INTERNAL	protocol version compatibility internal error.
-29900	LNCH_ERR_PVC_VERSION_MISMATCH	version mismatch, remote end doesn't support our version.
-29899	LNCH_ERR_NO_WEB_SERVER_NAME	Failed to create http connection string, web_server name is not found.
-29898	LNCH_ERR_XDR_FAILED_DECODE	XDR failed to decode launcher message.
-29897	LNCH_ERR_LG_STATUS_MEM_ALLOC	Cannot send the LG STATUS response. Memory allocation failed.
-29896	LNCH_ERR_LG_STATUS_MAX_SIZE	Cannot send the LG STATUS response. Data buffer exceeds max size.
-29895	LNCH_ERR_LG_STATUS_BUF_ENCODING	Cannot send the LG STATUS response. Data buffer encoding failed.
-29894	LNCH_ERR_FAILED_TO_SIGNAL_CLOUD_AGENT	Failed to signal cloud provisioning agent.
-29799	LNCH_WARN_PROCESS_NOT_ATTACHABLE	Obsolete.
-29798	LNCH_WARN_DETACH_NO_CONFIRMATION_FROM_PARENT	Failed to receive confirmation from parent after detach. Parent is probably down.
-29797	LNCH_WARN_GET_LABEL_FROM_WORKER_THREAD	Failed to get attached label from worker thread, reason - attached label doesn't exist.
-29796	LNCH_WARN_RECEIVED_UNEXPECTED_ATTACH_REQUEST	Received an unexpected attach request from parent.
-29795	LNCH_WARN_ATTACH_WRONG_VALUE	Read wrong value for attribute "%1" in file "%2". Expected "%3" or "%4" and read "%5".
-29794	LNCH_WARN_INIT_USER_TOKEN_FAILED	Failed init user token for user %1 , system error: %2.
-29793	LNCH_WARN_IMPERSONATE_USER_FAILED	Failed impersonate user token , system error: %2.
-29792	LNCH_WARN_ATTACH_FROM_CLUSTER_WITHOUT_CLUSTER	Flag LNCH_FLG_ATTACH_FROM_CLUSTER is used and cluster was not initialized. Flag LNCH_FLG_STUBBORN will be used instead.
-29791	LNCH_WARN_CLUSTER_NAME_NOT_EXIST	Cluster name was not supplied, attachable label will be used as unique name for the cluster.
-29790	LNCH_WARN_FAILED_GET_HOST_FROM_DB	Failed to update host name from database (trying to use old host - %1).
-29789	LNCH_WARN_FAILED_GET_HOST_FROM_DB_NOT_SET	Failed to get host name from database, reason - host name is not set yet.
-29788	LNCH_WARN_CONNECTION_EXPIRED	Guarantee delivery connection %1 has expired (last connection open time % 2 Id, time now % 3 Id, connection timeout % 4 Id).
-29787	LNCH_WARN_COMMIT_FALSE	GD message was not committed.
-29786	LNCH_WARN_ARCHIVE_CORRUPTED	Archive is corrupted. Delete corrupted archive from the disk, some data may be lost.
-29785	LNCH_WARN_CREATE_BUS_TOPOLOGY_MNGR_ERROR	Failed to create bus topology manager.
-29749	LNCH_ERR_SERVICE_PARAM	Cannot set service %1 - some parameters were not found.
-29748	LNCH_ERR_CLIENT_PARAM	Cannot use service client - service name was not passed .
-29747	LNCH_ERR_SERVICE_ALREADY_SET	Service %1 "%2" is already active .
-29746	LNCH_ERR_SERVICE_NOT_FOUND	Cannot unset service %1 with id= % 2 Id ,the service was not set .
-29745	LNCH_ERR_SERVICE_NOT_FOUND_NAME	Cannot unset service %1 "%2",the service was not set .
-29744	LNCH_ERR_SERVICE_NO_MONIKER	Cannot use client service "%1" ,no process/thread with moniker "%2" was found .
-29743	LNCH_ERR_SERVICE_NOT_MDRV	Cannot use client service "%1" ,process/thread with the moniker "%2" is not mdrv based.
-29742	LNCH_ERR_SERVICE_NO_PARENT	Cannot use client service "%1" ,this process/thread is not mdrv based or you are in the root process.
-29741	LNCH_ERR_SERVICE_MSG_FAIL	Message sent by service with id=% 1 Id failed. No service provider was set at the target point.
-29740	LNCH_ERR_SERVICE_MSG_FAIL_NAME	Message sent by service "%1" failed. No service provider was set at the target point.
-29739	LNCH_ERR_SERVICE_POST_MSG_FAILED	Service client with id=% 1 Id failed to post a message ,reason - %2.
-29738	LNCH_ERR_SERVICE_POST_MSG_FAILED_NAME	Service client "%1" failed to post a message ,reason - %2.
-29737	LNCH_ERR_FAILED_SET_LISTENER	Failed to set service listener "%1".
-29736	LNCH_ERR_MONIKER_NULL	NULL moniker was passed.
-29735	LNCH_ERR_SERVICE_NO_FAMILY	Cannot use client service "%1" ,this process/thread has not family flag.
-29734	LNCH_ERR_SERVICE_CB_FAILED	Message sent by service "%1" failed, reason - %2.
-29733	LNCH_ERR_PROVIDE_SERVICE	Cannot provide service "%1", reason - %2.
-29732	LNCH_ERR_UNPROVIDE_SERVICE	Cannot unprovide service "%1", reason - %2.
-29731	LNCH_ERR_LISTEN_TO_SERVICE	Cannot set listener for service "%1", reason - %2.
-29730	LNCH_ERR_UNLISTEN_TO_SERVICE	Cannot unset listener for service "%1", reason - %2.
-29729	LNCH_ERR_CALL_USER_CB	Message sent by service "%1" failed, reason - %2.
-29728	LNCH_ERR_THREAD_POOL	Thread Pool internal Error, reason - %1.
-29727	LNCH_ERR_FAILED_LAUNCH_NANNY	Failed to launch nanny process.

Error code	Handle	Message\Additional information
-29726	LNCH_ERR_FAILED_OPEN_CONNECTOR_TO_NANNY	Failed to open connector to nanny (nanny process) with command line : %1.
-29725	LNCH_ERR_FAILED_GET_POST_HANDLE_FROM_CONNECTOR_TO_NANNY	Failed to get post handle from connector to nanny.
-29724	LNCH_ERR_SERVICE_FAILED_PARENT_SON	Failed to deliver a p2p message from parent to child process, reason - %1.
-29723	LNCH_ERR_SERVICE_FAILED_SON_PARENT	Failed to deliver a p2p message from son to parent process, reason - %1.
-29722	LNCH_ERR_HOST_MAY_CRASH	The remote host's status is 'Failed'. Check the remote host machine [and verify that it has not crashed].
-29599	LNCH_WARN_INI_FILE_NOT_FOUND	File "service_provider.dat" was not found.
-29549	LNCH_DBG_PROCESS_ON_OK	Process (%1) was launched.
-29548	LNCH_DBG_PROCESS_ATTACH_OK	Process (%1) was attached.
-29547	LNCH_DBG_THRD_ON_OK	Thread (data="%1") was launched.
-29546	LNCH_DBG_PROCESS_ON_FAILED	Process (%1) failed to launch.
-29545	LNCH_DBG_PROCESS_ATTACH_FAILED	Process (%1) failed to be attached.
-29544	LNCH_DBG_THRD_ON_FAILED	Thread (data="%1") failed to launch.
-29543	LNCH_DBG_PP_INIT	Launcher pp_init function started.
-29542	LNCH_DBG_PP_END	Launcher pp_end function started.
-29541	LNCH_DBG_PT_INIT	Launcher pt_init function started.
-29540	LNCH_DBG_PT_END	Launcher pt_end function started.
-29539	LNCH_DBG_LOCATION	Entered to message callback "%1", the message type is "% 2 c" .
-29538	LNCH_DBG_LOCATION_SERVICE	Entered to message callback "%1", the message type is "% 2 c" (service ID = % 3 ld).
-29537	LNCH_DBG_LOCATION_SERVICE_FROM_TO	Entered to message callback "%1", the message type is "% 2 c" (service ID = % 3 ld) from %4 to %5.
-29536	LNCH_DBG_LOCATION_SERVICE_NAME	Entered to message callback "%1", the message type is "% 2 c" (service "%3").
-29535	LNCH_DBG_FAILED_POST_END_MSGS	Failed to post messages from the communication file "%1" .
-29534	LNCH_DBG_LNCH_MSG_FAILED	Message of type "% 1 c", Failed because could not find launcher object with moniker "%2".
-29533	LNCH_DBG_HEART_BEAT	Heartbeat timeout is % 1 ld msec ,and the limit is % 2 ld times.
-29532	LNCH_DBG_SOFT_KILL	Process/thread with moniker "%1" was exited in %2 way, reason - %3.
-29531	LNCH_DBG_FORK_FOR_CREATING_DAEMON	Fork for creating daemon succeeded.
-29530	LNCH_DBG_RECEIVED_ATTACH_AS_SON_REQUEST	Received an "attach as son" request.
-29529	LNCH_DBG_START_ATTACH_AS_PARENT	Starting to attach as parent.
-29528	LNCH_DBG_POSTED_ATTACH_MESSAGE_TO_SON	Posted "attach as parent" message to son.
-29527	LNCH_DBG_GENERAL	1.00%
-29526	LNCH_DBG_FW_POST_DISCONNECT_MSG	Failed to post "FireWall disconnect request" to agent with host symbol "%1".
-29525	LNCH_DBG_PVC_DISREGARD	Recieved protocol version compatibility internal message, disregarding message.
-29524	LNCH_DBG_PVC_ERROR_SEND	Revievd message with higher version, sending protocol version compatibility reply.
-29523	LNCH_DBG_FW_ADD_REQUEST_NO_PRIOR_ENTRY	RouterTable debug: In AddRequest, hostName: %1, other side: %1 - no prior other_ptr entry.
-29522	LNCH_DBG_FW_ADD_REQUEST_OTHER_SIDE_POST_HANDLE_EXISTS	RouterTable debug: In AddRequest, hostName: %1, other side: %2 - other_ptr has post handle.
-29521	LNCH_DBG_FW_ADD_REQUEST_OTHER_SIDE_NO_POST_HANDLE	RouterTable debug: In AddRequest, hostName: %1, other side: %2 - other_ptr doesn't have post handle.
-29520	LNCH_DBG_FW_ADD_POST_HANDLE_NO_PRIOR_ENTRY	RouterTable debug: In AddPostHandle, hostName: %1 - no prior entry.
-29519	LNCH_DBG_FW_ADD_POST_HANDLE_POST_HANDLE_EXISTS	RouterTable debug: In AddPostHandle, hostName: %1 - has post handle.
-29518	LNCH_DBG_FW_ADD_POST_HANDLE_NO_POST_HANDLE	RouterTable debug: In AddPostHandle, hostName: %1 - doesn't have post handle.
-29517	LNCH_DBG_FW_DELETE_REQUEST	RouterTable debug: In DeleteRequest, hostName: %1, other side: %2.
-29516	LNCH_DBG_FW_DELETE_ALL_REQUESTS	RouterTable debug: In DeleteAllRequests, hostName: %1, force = % 2 ld, post_not_resp = % 3 ld.
-29449	LNCH_DBG_SERVICE_CLIENT_NOTSET	Service client "%1" was not set.
-29448	LNCH_DBG_SERVICE_SET_OK	Service %1 "%2" was set.
-29447	LNCH_DBG_SERVICE_UNSET_OK	Service %1 with id=% 2 ld was unset.
-29446	LNCH_DBG_SERVICE_UNSET_OK_NAME	Service %1 "%2" was unset.
-29445	LNCH_DBG_CLIENT_SET_OK	Service client "%1" was set.
-29444	LNCH_DBG_CLIENT_UNSET_OK	Service client "% 1 ld" was unset.
-29443	LNCH_DBG_CLIENT_UNSET_OK_NAME	Service client "%1" was unset.
-29442	LNCH_DBG_SERVICE_MSG_FAILED	Service client with id=% 1 ld failed to post a message.
-29349	LNCH_PS_ERR_SERVICE_PROVIDER_NOT_SET	Could not set provider for service %1.
-29348	LNCH_PS_ERR_SERVICE_USE_FAILED	Use client for service %1 failed.
-29347	LNCH_PS_ERR_NO_PUBLISHER_WITH_NAME	No publisher was found for service %1.
-29346	LNCH_PS_ERR_SERVICE_NAME_POST_MSG_FAILED	Post %1 for publish-subscribe service %2 failed.
-29345	LNCH_PS_ERR_SERVICE_NAME_PUBLISH_FAILED	Publish for service %1 failed.
-29344	LNCH_PS_ERR_SERVICE_NAME_SUBSCRIBE_FAILED	Subscribe for service %1 failed.
-29343	LNCH_PS_ERR_NAME_WRONG_PUBLISHER_PROPAGATE_STATUS	Attempted to publish for publish-subscribe service with %1 using wrong propagating status.
-29342	LNCH_PS_ERR_SERVICE_NAME_UNPUBLISH_FAILED	Could not unpublish service %1. An appropriate publisher for this service was not found.

Error code	Handle	Message\Additional information
-29341	LNCH PS ERR SERVICE_NAME_UNSUBSCRIBE_FAILED	Could not unsubscribe service %1. A subscriber for this service was not found.
-29340	LNCH PS ERR ML_INIT_FAILED	matchers handle initialization failed.
-29339	LNCH PS ERR ML_REGISTER_FAIL	registration of criteria failed.
-29338	LNCH PS ERR ML_FIND_MATCH_FAIL	can't find match for subject %1 failed.
-29337	LNCH PS ERR CREATE_TRIGGER_FAIL	Fail to create trigger.
-29336	LNCH PS ERR REGISTER_TRIGGER_FAIL	Fail to register trigger.
-29335	LNCH PS ERR FAILED_PUBLISH_SERVICE	Failed to publish service "%1", reason - %2.
-29334	LNCH PS ERR FAILED_UNPUBLISH_SERVICE	Failed to unpublish service "%1", reason - %2.
-29333	LNCH PS ERR FAILED_POST_PUBLISHED_SERVICE	Failed to post published service "%1", reason - %2.
-29332	LNCH PS ERR FAILED_SUBSCRIBE	Cannot set subscriber "%1", reason - %2.
-29331	LNCH PS ERR FAILED_UNSUBSCRIBE	Cannot unset subscriber "%1", reason - %2.
-29330	LNCH PS ERR ML_DESERIALIZED_SUBJECT	Fail to deserialize the message subject.
-29329	LNCH PS ERR ML_SERIALIZED_SUBJECT	Fail to serialize the message subject.
-29328	LNCH PS ERR ML_NO_SUBJECT	Publisher with no subject.
-29327	LNCH PS ERR ML_NO_MATCHER_EXT	Matcher %1 is not found, in function %2.
-29326	LNCH PS ERR ML_MATCHER_IS_NULL	The matcher name parameter is NULL.
-29274	LNCH TC ERR CREATE_TC_FAILED	Cannot create thread context for %1 thread, reason - %2.
-29273	LNCH TC ERR XDR_FAILED_DECODE	XDR failed to decode thread context message.
-29272	LNCH TC ERR CREATE_CLIENT_FAILED	Failed to create custom channel client on main thread(connection string: %1).
-29271	LNCH TC ERR LAUNCH_ON_NOTIFY_FAILED	Failed to notify worker thread, reason - %1.
-29270	LNCH TC ERR SEND_MONIKER_FAILED	Failed to send moniker to the worker thread, reason - %1.
-29199	LNCH PS DBG_SERVICE_PROVIDER_SET_OK	Successfully set provider for service %1.
-29198	LNCH PS DBG_SERVICE_PROVIDER_NOT_SET	Set provider for service %1 failed in function %2.
-29197	LNCH PS DBG_SERVICE_CLIENT_USE_OK	Use client for service %1.
-29196	LNCH PS DBG_SERVICE_USE_FAILED	Use client for service %1 failed in function %2.
-29195	LNCH PS DBG_PUBLISHER_FOUND_WITH_NAME	Publisher for service %1 found.
-29194	LNCH PS DBG_NO_PUBLISHER_WITH_NAME	No publisher was found for service with %1 in function %2.
-29193	LNCH PS DBG_SERVICE_NAME_POSTED_OK	Posted %1 for publish-subscribe service %2.
-29192	LNCH PS DBG_PUBLISHED_SERVICE_NAME_POSTED_OK	Posted published service %1.
-29191	LNCH PS DBG_SERVICE_NAME_POST_MSG_FAILED	Post %1 for publish-subscribe service %2 failed in function %3.
-29190	LNCH PS DBG_SERVICE_NAME_PUBLISH_FAILED	Publish for service %1 failed in function %2.
-29189	LNCH PS DBG_NAME_PUBLISHER_PROPAGATE_STATUS_OK	Added publisher for publish-subscribe service with %1 has same propagating status as existing publisher.
-29188	LNCH PS DBG_HANDLE_EXISTS_AT_END	Handle %1 still exists after deleting %2.
-29187	LNCH PS DBG_ML_FIND_MATCH_FAIL	Find matching criteria for %1 failed on function %2.
-29186	LNCH PS DBG_CREATE_TRIGGER_FAIL	Fail to create trigger in %1.
-29185	LNCH PS DBG_REGISTER_TRIGGER_FAIL	Fail to register trigger in %1.
-29184	LNCH PS DBG_WRONG_PLACE	You are in a safety cleanup section, which you shouldn't have reached.
-29099	LNCH PS WARN_ML_UNREGISTER_FAIL	Failed to unregister %1.
-29049	LNCH NTF_REQUEST_ATTACH_AS_PARENT	Received request for attaching to process with label "%1" as parent from machine "%2".
-29048	LNCH NTF_REQUEST_ATTACH_AS_SON	Received request for attaching to process with label "%1" as son from machine "%2".
-29040	LNCH RM ERR_FAILED_OPEN_P2P_SERVER	Failed to open %1 p2p server.
-29039	LNCH RM ERR_FAILED_OPEN_P2P_CLIENT	Failed to open %1 p2p client.
-29038	LNCH RM ERR_XDR_FAILED_ENCODE	XDR failed to encode registration data
-29037	LNCH RM ERR_FAILED_CREATE_CONNECTOR_TO_AGENT	Failed to create connector to agent.
-29036	LNCH RM ERR_XDR_FAILED_DECODE	XDR failed to decode registration data
-29030	LNCH RM DBG_REGISTER_REQ	Register Manager : register REQ for % 1 Id offsprings.
-29029	LNCH RM DBG_UNREGISTER_REQ	Register Manager : unregister REQ for % 1 Id offsprings.
-29020	LNCH NMM ERR_XDR_FAILED_DECODE	XDR failed to decode nmm data.
-29019	LNCH NMM ERR_XDR_FAILED_ENCODE	XDR failed to encode nmm data.
-29018	LNCH NMM ERR_DATA_MISSING	Non Mdrv Message - Data Missing in message.
-29017	LNCH NMM ERR_DATA_MISSING_NO_SUBJECT	Non Mdrv Message - No subject in message.
-29016	LNCH NMM ERR_FAILED_CREATE_ACC	Non Mdrv Message - Failed to create acceptor.
-29015	LNCH NMM ERR_FAIL_TO_PUBLISH	Non Mdrv Message - Fail to publish on subject %1.
-29014	LNCH NMM ERR_FAIL_TO_SEND_REQUEST	Non Mdrv Message - Fail to send request on subject %1.
-29010	LNCH RR ERR_FAILED_CREATE_PUBLISHER	RR Failed to create publisher with subject %1.
-29009	LNCH RR ERR_FAILED_CREATE_SUBSCRIBER	RR Failed to create subscriber with subject %1.
-29008	LNCH RR ERR_XDR_FAILED_DECODE	XDR failed to decode rr data.

Error code	Handle	Message\Additional information
-29007	LNCH_RR_ERR_XDR_FAILED_ENCODE	XDR failed to encode rr data.
-29006	LNCH_RR_ERR_CANT_CREATE_TIMER	RR Failed to create timer.
-29005	LNCH_RR_ERR_PS_INTRF_NOT_SUPPLIED	Publish Subscribe interface is NULL or not passed to RR.
le_msg.h		
-76999	LE_FAILED_CREATE_CUSTOM_CHANNEL_SERVER	Failed to create custom channel server.
-76998	LE_FAILED_CREATE_CUSTOM_CHANNEL_CLIENT	Failed to create custom channel client.
-76997	LE_FAILED_CREATE_WORKER_THREAD	Failed to create worker thread.
-76996	LE_COMMANDS_NULL	Argument commands is NULL (must have at least -le_cfg_file option).
-76995	LE_FAILED_FIND_CFG_FILE	Failed to find cfg file (-le_cfg_file option).
-76994	LE_FAILED_LOAD_CONFIG_FILE	Failed to load configuration file: %1.
-76993	LE_FAILED_PARSING_COMMANDS	Failed to parsing commands: %1.
-76992	LE_FAILED_FIND_PARTICIPANTS_RECORD	Failed to find participants record into configuration file: %1.
-76991	LE_FAILED_FIND_PORT	Failed to find port number for host name: %1.
-76990	LE_FAILED_OPEN_SERVER	Failed to open server with port % 1 _ld.
-76989	LE_FAILED_FIND_CURRENT_MACHINE_NAME	Failed to find ip or name of the current machine in the configuration file.
-76988	LE_FAILED_GET_HOST_NAME	Failed to get current host name (gethostname() failed).
-76987	LE_FAILED_GET_HOST_INFO	Failed to get information about current host (os_gethostbyname() failed).
-76986	LE_FAILED_NOTIFY_MAIN_THREAD	Failed to notify main thread about change status.
-76985	LE_WORKER_THREAD_DOWN	Worker thread has gone down, abort the process.
-76984	LE_HOST_NAME_AMBIGUOUS	Host name or port number is ambiguous (check configuration file and -le_port_number option).
-76983	LE_FAILED_CREATE_LOCK_DIR	Failed to create directory for error detector %1.
-76982	LE_EXCEPTION_IN_USER_CB	Exception was raised in leader notify callback.
-76799	LE_MESSAGE_ARRIVED_IN_WRONG_STATE	Message %1 arrived and state is not %2.
-76798	LE_FAILED_OBTAIN_LOCK	Failed to obtain lock, reason: %1.
-76797	LE_FAILED_FREE_LOCK	Failed to free lock, reason: %1.
-76796	LE_ERROR_DETECTION_LOCK_NOT_IN_USE	This process doesn't use error detection lock.
-76795	LE_CANNOT_DELAY_NONACTIVE_NOTIFICATION	Cannot delay non-active notification, reason - %1.
-76699	LE_CALL_USER_CALLBACK	Call user callback with flags % 1 _ld.
-76698	LE_START_ELECTION	Start election.
-76697	LE_START_REORGANIZATION	Start reorganization.
-76696	LE_SEND_MESSAGE	Send %1 message to id % 2 _ld.
-76695	LE_NEW_LEADER	There is new leader with id % 1 _ld.
-76694	LE_START_MONITORING	Start monitoring process with id % 1 _ld.
-76693	LE_IM_LEADER	I'm a new leader.
-76692	LE_LEADER_DOWN	Leader has gone down.
-76691	LE_MESSAGE_ARRIVED	Message %1 arrived from process with id % 2 _ld.
-76690	LE_DELAY_NONACTIVE_NOTIFICATION	Delay non-active notification.
-76689	LE_READY_AFTER_NONACTIVE_NOTIFICATION	Ready after delay non-active notification.
-76499	LE_OPEN_CONNECTION	Open connection to the process with id %1.
-76498	LE_CLOSE_CONNECTION	Close connection to the process with id %1.
-76497	LE_POST_MESSAGE	Post message % 1 _ld to client %2.
-76496	LE_FAILED_POST_MESSAGE	Failed to post message, reconnect.
-76495	LE_CONNECTION_READY	Connection is ready with id %1.
Inch_icon_res.h		
-57800	LNCH_ICON_GUI_COPYRIGHT	Copyright © 1994-2002 Mercury Interactive
log_res.h		
-44999	VUSERLOG_ERROR_OPEN_FILE	Log extension: Cannot open Vuser log file %1
-44998	VUSERLOG_ERROR_WRITE_MSG	Log extension: Failed to write to the log file the message :"%1".
-44997	VUSERLOG_ERROR_CRITICAL_SECTION	Log extension: CriticalSection - %1.
-44996	VUSERLOG_ERROR_CREATE_RESULTS_DIRECTORY	Log extension: Cannot create results directory "%1".
-44995	VUSERLOG_ERROR_NO_LOG_FILE_NAME	Log extension: Cannot set Vuser log file (-vuser_log option was not passed in command line).
-44994	VUSERLOG_ERROR_FAILED_XDR_MSG	Log extension: Failed to encode the message :"%1".
-44993	VUSERLOG_NOTIFY_VUSER_STATUS	Log extension: Vuser: Status=%1 Iterations: Total=%2 Passed=%3

Error code	Handle	Message\Additional information
lr_host_balancer_msgs.h		
-205840	RED_LINE_ERROR	Error: %1 % 2 Id%%
-205839	RED_LINE_RESOURCE	Resource "%1": % 2 Id%% of time is above % 3 Id
-205838	YELLOW_LINE_WARNING	Warning: %1 % 2 Id%%
-205837	YELLOW_LINE_RESOURCE	Resource "%1": % 2 Id%% of time is above % 3 Id
lr_mon_http_msgs.h		
-47500	INTERNAL_ERROR	Internal error. Details: %1 (entry point: %2).
-47499	CANT_INIT_CONNECTION	Cannot initialize connection. Measurement: %1, machine: %2 (entry point: %3).
-47498	ERROR_NO_SERVER_OBJECT	Internal error. Cannot find internal object for machine: %1. Measurement: %2. Hint: Delete this machine and add it again (Use the Add Machine dialog box for this operation) (entry point: %3).
-47497	CAN_NOT_INIT_WININET	Cannot initialize Wininet.dll on local machine (part of initialization of machine %1). Details: %2 (entry point: %3).
-47496	CAN_NOT_CONNECT_TO_SERVER	Cannot connect to server: %1, port: %2, login: %3. Details: %4 (entry point: %5).
-47495	CAN_NOT_OPEN_REQUEST	Cannot open request. Machine: %1, URL: %2, Port: % 3 Id. Details: %4 (entry point: %5).
-47494	FAILED_TO_SEND_REQUEST_TO_SERVER	Failed to send a request to server: %1. URL: http://%2:<password>@%3:% 4 Id%5. Details: %6. Hint: Check this URL in the Internet Browser (entry point: %7).
-47493	ERROR_RETURN_CODE_FROM_SERVER	HTTP response error code: (% 1 Id) from server %2, URL %3 (entry point: %4).
-47492	QUERY_DATA_AVAILABLE_FAILED	No available data returned from server %1. Details: %2 (entry point: %3).
-47491	READING_FILE_ERROR	Failed to read data returned from server %1. Details: %2 (entry point: %3).
-47490	HTML_PARSING_ERROR	Parsing error. Cannot find token: %1 in the data returned from the server. Measurement: %2 Server: %3. URL: http://%4:<password>@%5:% 6 Id%7 Hint: the Netscape statistics html page might be different from the supported one. Check this URL in the Internet Browser. Check that such a token exists on the Netscape statistics html page returned from the server. (entry point: %8).
-47489	CANT_CREATE_MEASUREMENT	Cannot create measurement %1 on machine %2. Details: %3. Hint: Check that there is such a measurement on this machine. Check that you selected the right platform for the monitored machine in the Add Machine dialog box. Note: When you monitor a Windows machine some counters may not be available. Try to delete this measurement and add it again (use the Add Resources dialog box) (entry point: %4).
-47488	CANT_GET_MEASUREMENT_DATA	Cannot access data for measurement %1 on machine %2. Details: %3. Hint: Check that there is such a measurement on the machine (use the Add Machine dialog box) (entry point: %4).
-47487	CANT_GET_MEASUREMENT_DATA_NO_DETAILS	Cannot access data for measurement %1 on machine %2. Hint: Check that there is such a measurement on the machine (use the Add Machine dialog box) (entry point: %3).
-47486	ERROR_NO_MEASUREMENT	The internal object for the measurement %1 was not found on the machine %2. Hint: Delete this measurement and try adding it again (entry point: %3).
-47485	CANT_CREATE_INTERNAL_MEASUREMENT_OBJECT	A fatal error occurred in initializing an internal object for the measurement %1 machine %2. Hint: Close the monitoring application and reopen it (entry point: %3).
-47484	HTTP_REQUEST_ERROR_CODE	HTTP error code % 1 Id: %2. Hint: Check the following URL in the Internet Browser: http://%3%4:% 5 Id%6 (entry point: %7).
-47483	NO_NETSCAPE_SITE	Site exists, but does not return a Netscape statistics html page. Machine: %1. URL: http://%2:<password>@%3:% 4 Id%5. Hint: Check this URL in the Internet Browser. If you do not get a Netscape statistics html page, delete this machine in the Add Machine dialog box (entry point: %6).
-47482	PARSING_ERROR	Parsing error, cannot find token: %1. Measurement: %2. Hint: Such a measurement does not exist, or the html page may be different from the supported one (entry point: %3).
-47481	FAILED_TO_SEND_REQUEST_TO_SERVER_NO_USERNAME	Failed to send a request to server %1, URL: http://%2:% 3 Id%4. Details: %5. Hint: Check this URL in the Internet Browser (entry point: %6).
-47480	MEMORY_ALLOCATION_ERROR	Failed to allocate memory for server: %1. Details: %2 (entry point: %3).
-47479	APACHE_PARSING_ERROR	Parsing error, cannot find token: %1. Measurement: %2. Hints: 1) Such a measurement does not exist, or the html page may be different from the supported one. 2) Try to replace the Apache.cfg with appropriate Apache_<version>.cfg file in <Installation>\dat\monitors and rerun the application (entry point: %3).
lr_mon_netd_msgs.h		
-47400	INTERNAL_ERROR	Internal error. Details: %1 (entry point: %2).
-47399	NETMON_NOT_SUPPORTED_PLATFORM	Cannot activate %1 measurement on source host: %2. Details: UNIX platforms not supported on this monitor (entry point: %3).
lr_mon_pdh_msgs.h		
-47300	INTERNAL_ERROR	Internal error.\r\nDetails: %1 (entry point: %2).
-47299	ERROR_NO_MACHINE	Cannot connect to machine %1.\r\nReason: %2\r\nHints:\r\nCheck that your login user name appears as administrator on this machine.\r\nCheck that remote registry is available on this machine.\r\nCheck that you have entered the correct machine name.\r\nCheck that the machine exists and that it is online (use the ping utility for this operation).\r\nDelete the machine and add it again. (entry point: %3).
-47298	MON_EXCEPTION	Exception occurred.\r\nMachine: %1, measurement: %2 (entry point: %3).

Error code	Handle	Message\Additional information
-47297	PDH_INTERNAL_ERROR	Internal error (MS PDH interface).\r\nMachine: %1.\r\nDetails: %2\r\nHint:\r\nEnsure that the machine does not have memory problems.\r\nClose the application and reopen it (entry point: %3).
-47296	CANT_CREATE_MEASUREMENT	Cannot create measurement %1 on machine %2.\r\nDetails: %3\r\nHint:\r\nCheck that there is such a measurement on this machine.\r\nCheck that you selected the right platform for the monitored machine in the Add Machine dialog box.\r\nNote: When you monitor a Windows machine some counters may not be available.\r\nTry to delete this measurement and add it again (use the Add Resources dialog box) (entry point: %4).
-47295	CANT_GET_MEASUREMENT_DATA	Cannot access data for measurement %1 on machine %2.\r\nDetails: %3\r\nHint:\r\nCheck that there is such a measurement on the machine (use the Add Machine dialog box) (entry point: %4).
-47294	MON_EXCEPTION_NO_NAME	Exception occurred.\r\nMachine: %1 (entry point:%2).
-47293	ERROR_NO_MEASUREMENT	The internal object for the measurement %1 was not found on the machine %2.\r\nHint:\r\nDelete this measurement and try adding it again (entry point: %3).
-47292	ERROR_PDH_NO_DATA	Cannot collect data on the machine %1.\r\nDetails: The query does not currently have any counters.\r\nHint:\r\nClose the application and reopen it later (it seems to be a temporary problem) (entry point: %2).
-47291	INVALID_QUERY	The query object for machine %1 is invalid (initialization error).\r\nHint:\r\nDelete this machine and add it again (Use the Add Machine dialog box for this operation) (entry point: %2).
-47290	ERROR_NO_MACHINE_OBJECT	The internal object for machine %1 is invalid (initialization error).\r\nHint:\r\nDelete this machine and add it again (use the Add Machine dialog box for this operation) (entry point: %2).
-47289	ERROR_INVALID_MACHINE_OR_OFFLINE	Cannot connect to machine %1.\r\nThe machine name may be invalid, or the machine may be offline.\r\nHint:\r\nCheck that you have entered the correct machine name in the Add Machine dialog box.\r\nCheck that the machine exists and that it is online (use the ping utility for this operation).\r\nDelete the machine name in the Add Machine dialog box, and add it again (entry point: %2).
-47288	ERROR_INVALID_MACHINE_OR_OFFLINE_DETAILS	Cannot connect to machine %1.\r\nThe machine name may be invalid, or the machine may be offline.\r\nDetails: %2\r\nHint:\r\nCheck that you have entered the correct machine name in the Add Machine dialog box.\r\nCheck that the machine exists and that it is online (use the ping utility for this operation).\r\nIf problems persist, delete the machine name in the Add Machine dialog box, and add it again.\r\nIf this does not work, close the monitoring application, reopen it, and add this machine again (entry point: %3).
-47287	NTMON_ERROR_MACHINE_AFTER_REBOOT	Some of the requested measurements of this machine could not be measured due to invalid timestamp (The machine could be in a restart progress).
-47286	PDH_VERSION_ERROR	Cannot find some functions (%1) in %2. (platform: %3).\r\nHint:\r\nThe DLL has a different version than the supported one (entry point: InitPdhDll).
-47285	PDH_VERSION_ERROR_SYSTEM	Cannot find some functions (%1) in %2 (platform: %3).\r\nHint:\r\nThe DLL has a different version from the supported one.\r\nRename this dll.\r\nClose the monitoring application and run it again (entry point: InitPdhDll).
-47284	NTMON_CANNOT_LOAD_LIBRARY	Cannot load %1 (platform: %2).\r\nHint:\r\nCheck that such a file exists (entry point: %3).
-47283	ERROR_ON_HOST	Error on machine %1: %2 (entry point: %3).
-47282	ERROR_TEST_MACHINE_FAILED_TO_FIND_DEF_OBJECT	Connection successful.\r\nNote: Object '%1' was not found on %2 (entry point: %3).
-47281	ERROR_TEST_MACHINE_FAILED_TO_REMOTE_REGISTRY	Cannot access %1 key on host %2 with error\r\n%3(entry point: %4).
lr_mon_rstat_msgs.h		
-47200	INTERNAL_ERROR	Internal error. Details: %1 (entry point: %2).
-47199	ERROR_NO_SERVER_OBJECT	Internal error. Cannot find internal object for machine: %1. Measurement: %2. Hint: Delete this machine and add it again (Use the Add Machine dialog box for this operation) (entry point: %3).
-47198	CAN_NOT_ADD_MEASUREMENT	Cannot add measurement: %1 (Fatal initialization error) machine: %2. Hint: Delete this measurement from the machine and add it again (use Add Resources dialog box for this operation) (entry point: %3).
-47197	INTERNAL_RPC_ERROR	Internal rpc error (error code:%_1_id). Machine: %2. Hint: Check that RPC on this machine is up and running. Check that rstat daemon on this machine is up and running (use rpcinfo utility for this verification). Details: %3 (entry point: %4).
-47196	MON_EXCEPTION	Exception occurred. Machine: %1, measurement: %2 (entry point:%3).
-47195	CANT_GET_MEASUREMENT_DATA_NO_DETAILS	Cannot access data for measurement %1 on machine %2. Hint: Check that there is such a measurement on the machine (use the Add Machine dialog box) (entry point: %3).
-47194	CANT_GET_MEASUREMENT_BY_ID	Cannot access data for measurementId %_1_id on machine %2. There are just %_2_id measurements on this machine. Hint: Check that there is such a measurement on the machine (use the Add Machine dialog box) (entry point: %3).
-47193	MON_EXCEPTION_NO_NAME	Exception occurred. Machine: %1 (entry point:%2).
-47192	ERROR_NO_MEASUREMENT	The internal object for the measurement %1 was not found on the machine %2. Hint: Delete this measurement and try adding it again (entry point: %3).
-47191	CANT_INIT_RPC	Cannot initialize RPC on the machine %1. Hint: Check that the RPC is up and running on %2 (use rpcinfo utility for this verification). Details: %3 (entry point:%4).
-47190	CANT_INIT_RPC_HOST_CLIENT	Cannot initialize the monitoring on %1. Error while creating the RPC client. Ensure that the machine can be connected and that it runs the rstat daemon (use rpcinfo utility for this verification). Detailed error: %2 (entry point: %3).
-47189	CANT_GET_SSH_DATA	Cannot access data for measurement %1 on machine %2. Hint: Check that there is such a measurement on the machine (entry point: %3).
-47188	ERROR_MACHINE_CONNECTION	Cannot connect to %1. Hint: make sure it exists and it is visible from your network (entry point: %2).

Error code	Handle	Message\Additional information
-47187	ERROR_BAD_CREDENTIALS	Cannot authenticate to %1. Hint: make sure that the credentials you entered are valid (entry point: %2).
-47186	ERROR_SSH_TRY_RPC	Cannot connect to %1. Starting initialize RPC on the machine %1. Hint: make sure that machine exists and the credentials you entered are valid (entry point: %2).
lr_mon_sitescopes_msgs.h		
-47700	INTERNAL_ERROR	Internal error.\r\nDetails: %1 (entry point: %2).
-47699	XML_MONITOR_HTTP_REQUEST_ERROR_CODE	HTTP error code % 1 Id: %2.\r\nHint:\r\nCheck the following URL in the Internet Browser: http://%3%4:% 5 Id%6 (entry point: %7).
-47698	XML_MONITOR_INT_FILE_MISSING	The required file for monitor initialization does not exist (<Installation Root>\dat\monitors\XMLMonitorShared.ini).\r\nPlease consult installation instructions regarding this file (entry point: %1).
-47697	XML_MONITOR_INIT_FAILURE	Failed to initialize monitor.\r\nDetails: %1 (entry point: %2).
-47696	XML_MONITOR_GENERAL_EXCEPTION	General error. Exception was raised.\r\nDetails: %1.
-47695	XML_MONITOR_CONNECTION_FAILURE	Failed to connect to server %1, port % 2 Id.\r\nDetails: %3\r\nHint:\r\nCheck that Web Server is up and running (entry point: %4).
-47694	XML_MONITOR_TRANSPORT_INIT	Cannot initialize "TransportProviderUUID" COM object for monitor %1.\r\nCheck its registration.\r\nHint:\r\nUse UUID specified in "<Installation Root>\dat\monitors\XMLMonitorShared.ini" (entry point: %2).
-47693	XML_MONITOR_ERROR_NO_MACHINE_OBJECT	The internal object for machine %1 is invalid (initialization error).\r\nHint:\r\nDelete this machine and add it again (use the Add Machine dialog box for this operation) (entry point: %2).
-47692	XML_MONITOR_CANNOT_LOAD_LIBRARY	Cannot load %1.\r\nHint:\r\nCheck that such a file exists (entry point: %2).
-47691	XML_MONITOR_INIT_INTERNET_FAILURE	Cannot initialize Internet connection component.\r\nDetails: %1 (entry point: %2).
-47690	XML_MONITOR_NO_FILE	Required file %1 does not exist (entry point: %2).
-47689	XML_MONITOR_FILE_LOADING	Loading of file %1 failed.\r\nDetails: %2 (entry point: %3).
-47688	XML_MONITOR_NO_PARSER	MSXML parser is not available on %1.
-47687	XML_MONITOR_PARSING_ERROR	Parsing error.\r\nDetails: host %1, port % 2 Id, line: % 3 Id.\r\nReason: %4.\r\nContents: %5
-47686	XML_PARSING_ERROR	Parsing error.\r\nDetails: host %1, line: % 2 Id.\r\nReason: %3.
-47685	XML_SS_ERR_PARSE_OBJECT_DATA_FAILED	Failed to add measurement '%1' on host '%2'.
-47684	XML_FAILED_TO_FIND_SITESCOPE_DATA	Internal error: Failed to find SiteScope server information (entry point: %1).
-47683	XML_GET_UI_PROPERTIES_BAD_PARAM	Internal error: Failed to get configuration properties (entry point: %1).
-47682	SS_VALIDATE_PROPERTIES_FAILED	Properties were not initialized.
-47681	SS_GET_MONITOR_PROPERTIES_FAILED	'%1' monitor failed to retrieve measurements.\r\nPlease verify that you entered the correct monitor properties,\r\nand that you have the right permissions.
-47680	SS_HOST_PROPERTY_IS_EMPTY	Property Host was not initialized.
-47679	SS_MONITOR_VALIDATION_FAILED	'%1' monitor properties validation failed
-47678	SS_CONFIGURING_UNIX_MACHINE	Configuring Unix Remote Machine
-47677	SS_MONITOR_FAILED	Monitor failed to retrieve measurements.\r\nPlease verify that you have the right access permissions
-47676	SS_MONITOR_FAILED_TO_RETRIVE_DATA	Monitor failed to retrieve measurements data.\r\nMonitor status: '%1'
-47675	SS_FAILED_TO_START_PROCESS	Failed to start process: '%1'.
-47674	SS_JVM_VERSION_MISMATCH	Java Virtual Machine Version mismatch: Required version: %1 %2.
-47673	XML_FAILED_TO_CONNECT_XML_SOURCE	Failed to connect to XML source on % 1 Id.
-47672	SS_NOT_AVAILABLE	SiteScope service on machine '%1' is not available.
-47671	SS_FAILED_TO_RETRIEVE_PROPERTIES	Failed to retrieve configuration properties for host %1 (SiteScope Server on machine %2).
-47670	SS_FAILED_TO_CREATE_MONITOR	Failed to create monitor on host %s (SiteScope Server on machine %s).
-47669	SS_TEST_REMOTE_MACHINE_FAILED	Testing connection to machine %s failed (SiteScope error: %s).\r\nPlease verify that you entered the correct monitor properties, and that you have the right permissions.
-47668	SS_MONITOR_ERROR	Monitor name :%s. %s
lr_mon_snmp_msgs.h		
-47100	INTERNAL_ERROR	Internal error. Details: %1 (entry point: %2).
-47099	MON_EXCEPTION	Exception occurred. Machine: %1, measurement: %2 (entry point:%3).
-47098	SNMP_TIME_OUT	Machine: %1. Details: %2. Hint: Check that the SNMP agent is up and running. Check 'SNMP_community_name' entry in <installation>\dat\monitors\snmp.cfg (entry point: %3)
-47097	MAX_NUM_OF_MEASUREMENTS	Cannot add more than % 1 Id measurements to one machine. Machine: %2, measurement: %3 (entry point:%4).
-47096	SNMP_NO_AGENT	Cannot access data from %1 agent on machine %2. Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (Use the ping utility for this operation). Check that %3 agent on the machine is up and running. Check 'SNMP_community_name' entry in <installation>\dat\monitors\snmp.cfg (entry point: %4).
-47095	SNMP_NO_COUNTER	Cannot access data from %1 agent for measurement %2 on machine %3. Details: %4. This measurement will be deleted from the query (entry point: %5). Hint: Check that such a measurement exists on this machine. If the measurement exists, delete it and add it again.
-47094	SNMP_CANT_CREATE_OBJECT	A fatal error occurred in initializing an internal SNMP object for the machine %1. Details: %2 (entry point:%3). Hint: Close the monitoring application and reopen it.

Error code	Handle	Message\Additional information
-47093	SNMP_INTERNAL_ERROR	Internal SNMP error. Cannot access data on the machine: %1. Details: %2 (entry point: %3). Hint: Close the monitoring application and reopen it later.
-47092	MON_EXCEPTION_NO_NAME	Exception occurred. Machine: %1 (entry point:%2).
-47091	NO_IP_ADDRESS	Cannot resolve machine's IP address for machine %1 (entry point: %2). Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (use the ping utility for this operation). If you continue to receive an error message, delete the machine name in the Add Machine dialog box, and enter the machine's IP address instead.
-47090	LOADING_ERROR	Cannot load %1 dll to access the UI. Machine: %2 (entry point: %3). Hint: Check that the dll exists in <application root>\bin directory.
-47089	CANT_CREATE_INTERNAL_HOST_OBJECT	A fatal error occurred in initializing an internal object for the machine %1 (entry point: %2). Hint: Close the monitoring application and reopen it.
-47088	ERROR_NO_SERVER_OBJECT	Internal error. Cannot find internal object for machine: %1. Measurement: %2 (entry point: %3). Hint: Delete this machine and add it again (Use the Add Machine dialog box for this operation).
-47087	ERROR_INVALID_MACHINE_OR_OFFLINE	Cannot connect to machine %1. The machine name may be invalid, or the machine may be offline (entry point: %2). Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (use the ping utility for this operation). Delete the machine name in the Add Machine dialog box, and add it again.
-47086	CAN_NOT_ADD_MEASUREMENT	Cannot add measurement: %1 (Fatal initialization error). machine: %2 (entry point: %3). Hints: 1. You cannot add the same measurement both with and without a "name modifier", delete this measurement. 2.Delete this measurement from the machine and add it again. (Use Add Resources dialog box for this operation).
-47085	INSTANCE_NAME_DIFFERS	Cannot add measurement: %1, machine %2. Reason: the associated name was changed from %3 to %4. Hint: delete this measurement and select an appropriate one (entry point: %5)
-47084	CANT_VERIFY_INSTANCE_NAME	Cannot add measurement: %1, machine %2. Reason: cannot retrieve current associated name for verification. Expected associated name is %3. Hint: delete this measurement and select an appropriate one (entry point: %4)
lr_mon_vmon_msgs.h		
-95100	COUNTER_IS_NEGATIVE	Counter value is less than zero!
-95099	ORACLE_MONITOR	Oracle monitor
-95098	LOOK_IN_ORACLE_DOCS	Look it up in the Oracle documentation.
-95097	RATE_SUFFIX	%1 (rate)
-95096	ABS_SUFFIX	%1 (absolute)
-95095	INSTANCE_ID	INSTANCE
-95094	ERROR_IN_POSITION	Error in position %3\ %4\ (Counter name: %1\ \nQuery: %2)
-95093	QUERY_IS_NOT_SELECT	Query is not a SELECT statement.\ \n(Counter name: %1\ \nQuery: %2)
-95092	ONLY_ONE_ITEM_ALLOWED	Only one item allowed in select list.\ \n(Counter name: %1\ \nQuery: %2)
-95091	RESULT_MUST_BE_NUMBER	Result of query must be a NUMBER instead of data type %3.\ \n(Counter name: %1\ \nQuery: %2)
-95090	QUERY_RETURNED_NO_ROWS	Query returned no rows.\ \n(Counter name: %1\ \nQuery: %2)
-95089	QUERY_RETURNED_MORE_THAN_ONE_ROW	Query returned more than one row.\ \n(Counter name: %1\ \nQuery: %2\ \n)
-95088	COULD_NOT_FIND	Could not find%1.\ \nCheck their access permissions.
-95087	COULD_NOT_LOGIN	Could not login to database server.\ \n%1.
-95086	QUERY_RETURNED_NULL	NULL value returned.
-95085	COULD_NOT_CREATE_THREAD	Could not create custom monitor thread.
-95084	COULD_NOT_CONNECT	Could not connect to server to activate measurement.\ \n%1.
-95083	MEASUREMENT_NOT_FOUND	Measurement to be deactivated was not found.
-95082	ORACLE_KEY_NOT_EXIST	Oracle registry key HKEY_LOCAL_MACHINE\ \SOFTWARE\ \ORACLE does not exist.\ \nPlease check registry to see that Oracle is properly installed.
-95081	ORACLE_DLL_NOT_LOADED	Could not load Oracle DLL.\ \nMake sure it is in the search path.\ \n%1.
-95080	FAILED_GET_PROGRAM_NAME	Failed to get program name for TestMachine process.
-95079	PROCESS_NOT_CREATED	Unable to create extra process for TestMachine.
-95078	PROCESS_NOT_TERMINATED	TestMachine process did not terminate.
-95077	UNKNOWN_TEST_MACHINE_ERROR	Unknown TestMachine error.
-95076	UNDEFINED_OBJECT_TYPE	Undefined object type.
lr_mon_xml_msgs.h		
-47600	INTERNAL_ERROR	Internal error.\ \nDetails: %1 (entry point: %2).
-47599	XML_MONITOR_HTTP_REQUEST_ERROR_CODE	HTTP error code % 1 Id: %2.\ \nHint:\ \nCheck the following URL in the Internet Browser: http://%3%4:% 5 Id%6 (entry point: %7).
-47598	XML_MONITOR_INT_FILE_MISSING	The required file for monitor initialization does not exist (<Installation Root>\dat\monitors\XMLMonitorShared.ini).\ \nPlease consult installation instructions regarding this file (entry point: %1).
-47597	XML_MONITOR_INIT_FAILURE	Failed to initialize monitor.\ \nDetails: %1 (entry point: %2).
-47596	XML_MONITOR_GENERAL_EXCEPTION	General error. Exception was raised.\ \nDetails: %1.
-47595	XML_MONITOR_CONNECTION_FAILURE	Failed to connect to server %1, port % 2 Id.\ \nDetails: %3\ \nHint:\ \nCheck that Web Server is up and running (entry point: %4).

Error code	Handle	Message\Additional information
-47594	XML_MONITOR_TRANSPORT_INIT	Cannot initialize "TransportProviderUUID" COM object for monitor %1.\r\nCheck its registration.\r\nHint:\r\nUse UUID specified in "<Installation Root>\dat\monitors\XMLMonitorShared.ini" (entry point: %2).
-47593	XML_MONITOR_ERROR_NO_MACHINE_OBJECT	The internal object for machine %1 is invalid (initialization error).\r\nHint:\r\nDelete this machine and add it again (use the Add Machine dialog box for this operation) (entry point: %2).
-47592	XML_MONITOR_CANNOT_LOAD_LIBRARY	Cannot load %1.\r\nHint:\r\nCheck that such a file exists (entry point: %2).
-47591	XML_MONITOR_INIT_INTERNET_FAILURE	Cannot initialize Internet connection component.\r\nDetails: %1 (entry point: %2).
-47590	XML_MONITOR_NO_FILE	Required file %1 does not exist (entry point: %2).
-47589	XML_MONITOR_FILE_LOADING	Loading of file %1 failed.\r\nDetails: %2 (entry point: %3).
-47588	XML_MONITOR_NO_PARSER	MSXML parser is not available on %1.
-47587	XML_MONITOR_PARSING_ERROR	Parsing error.\r\nDetails: host %1, port % 2 Id, line: % 3 Id.\r\nReason: %4.\r\nContents: %5
-47586	XML_PARSING_ERROR	Parsing error.\r\nDetails: host %1, line: % 2 Id.\r\nReason: %3.
-47585	GENERAL_ERROR	%1 (entry point: %2).
-47584	XML_MONITOR_BAD_LOGIN	\r\nBad login info".
-47583	XML_MONITOR_ERROR_CREATE_HOST	\r\nCannot create host data.
-47582	XML_MONITOR_DIFFERENT_CREDS	\r\nDifferent credentials for the same host.\r\nThere are active counters, so can't terminate host.
-47581	XML_MONITOR_CANT_INIT_HOST	\r\nCannot init host data: %1\r\n
-47580	XML_MONITOR_SIS_SERVER_ERROR	Server %1, port % 2 Id internal error: %3\r\n
lr_sapgui_mon_res.h		
-47999	INTERNAL_ERROR	Internal error. Details: %1 (entry point: %2).
-47998	ERROR_NO_MACHINE	Cannot connect to machine %1. Details: %2 (entry point: %3). Hint: Check that your login user name appears as administrator on this machine.
-47997	CANT_INIT_CONNECTION	Cannot initialize connection. Measurement: %1, machine: %2 (entry point: %3).
-47996	ERROR_NO_SERVER_OBJECT	Internal error. Cannot find internal object for machine: %1. Measurement: %2 (entry point: %3). Hint: Delete this machine and add it again (Use the Add Machine dialog box for this operation).
-47995	CAN_NOT_INIT_WININET	Cannot initialize Wininet.dll on local machine (part of initialization of machine %1). Details: %2 (entry point: %3).
-47994	CAN_NOT_CONNECT_TO_SERVER	Cannot connect to server: %1, port: %2, login: %3. Details: %4 (entry point: %5).
-47993	CAN_NOT_OPEN_REQUEST	Cannot open request. Machine: %1, URL: %2, Port: % 3 Id. Details: %4 (entry point: %5).
-47992	FAILED_TO_SEND_REQUEST_TO_SERVER	Failed to send a request to server: %1. URL: http://%2:<password>@%3:% 4 Id%5. Details: %6 (entry point: %7). Hint: Check this URL in the Internet Browser.
-47991	ERROR_RETURN_CODE_FROM_SERVER	HTTP response error code: (% 1 Id) from server %2, URL %3 (entry point: %4).
-47990	QUERY_DATA_AVAILABLE_FAILED	No available data returned from server %1. Details: %2 (entry point: %3).
-47989	READING_FILE_ERROR	Failed to read data returned from server %1. Details: %2 (entry point: %3).
-47988	STATUS_DENIED	Access denied, the login or password might be incorrect. Machine: %1, login: %2 (entry point: %3).
-47987	HTML_PARSING_ERROR	Parsing error. Cannot find token: %1 in the data returned from the server. Measurement: %2 Server: %3. URL: http://%4:<password>@%5:% 6 Id%7 Hint: the Netscape statistics html page might be different from the supported one. Check this URL in the Internet Browser. Check that such a token exists on the Netscape statistics html page returned from the server. (entry point: %8).
-47986	CAN_NOT_ADD_MEASUREMENT	Cannot add measurement: %1 (Fatal initialization error). machine: %2 (entry point: %3). Hint: Delete this measurement from the machine and add it again. (Use Add Resources dialog box for this operation).
-47985	INTERNAL_RPC_ERROR	Internal rpc error (error code: %1 Id). Machine: %2 (entry point: %3). Hint: Check that RPC on this machine is up and running. Check that rstat daemon on this machine is up and running. (Use rpcinfo utility for this verification). Details: %4.
-47984	MON_EXCEPTION	Exception occurred. Machine: %1, measurement: %2 (entry point: %3).
-47983	SNMP_TIME_OUT	Machine: %1. Details: %2. Hint: Check that the SNMP agent is up and running. (entry point: %3)
-47982	MAX_NUM_OF_MEASUREMENTS	Cannot add more than % 1 Id measurements to one machine. Machine: %2, measurement: %3 (entry point: %4).
-47981	SNMP_NO_AGENT	Cannot access data from %1 agent on machine %2. Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (Use the ping utility for this operation). Check that %3 agent on the machine is up and running (entry point: %4).
-47980	SNMP_NO_COUNTER	Cannot access data from %1 agent for measurement %2 on machine %3. Details: %4. This measurement will be deleted from the query (entry point: %5). Hint: Check that such a measurement exists on this machine. If the measurement exists, delete it and add it again.
-47979	SNMP_CANT_CREATE_OBJECT	A fatal error occurred in initializing an internal SNMP object for the machine %1. Details: %2 (entry point: %3). Hint: Close the monitoring application and reopen it.
-47978	SNMP_INTERNAL_ERROR	Internal SNMP error. Cannot access data on the machine: %1. Details: %2 (entry point: %3). Hint: Close the monitoring application and reopen it later.
-47977	PDH_INTERNAL_ERROR	Internal error (MS PDH interface). Machine: %1. Details: %2 (entry point: %3). Hint: Ensure that the machine does not have memory problems. Close the application and reopen it.
-47976	CANT_CREATE_MEASUREMENT	Cannot create measurement %1 on machine %2. Details: %3 (entry point: %4). Hint: Check that there is such a measurement on this machine. Check that you selected the right platform for the monitored machine in the Add Machine dialog box. Note: Not all the counters are available on any Windows machine. Delete this measurement and add it again. (Use the Add Resources dialog box).

Error code	Handle	Message\Additional information
-47975	CANT_GET_MEASUREMENT_DATA	Cannot access data for measurement %1 on machine %2. Details: %3 (entry point: %4). Hint: Check that there is such a measurement on the machine (Use the Add Machine dialog box).
-47974	CANT_GET_MEASUREMENT_DATA_NO_DETAILS	Cannot access data for measurement %1 on machine %2 (entry point: %3). Hint: Check that there is such a measurement on the machine (Use the Add Machine dialog box).
-47973	CANT_GET_MEASUREMENT_BY_ID	Cannot access data for measurementId %_1_Id on machine %2. There are just %_2_Id measurements on this machine (entry point: %3). Hint: Check that there is such a measurement on the machine (Use the Add Machine dialog box).
-47972	MON_EXCEPTION_NO_NAME	Exception occurred. Machine: %1 (entry point:%2).
-47971	ERROR_NO_MEASUREMENT	The internal object for the measurement %1 was not found on the machine %2 (entry point: %3). Hint: Delete this measurement and try adding it again.
-47970	ERROR_PDH_NO_DATA	Cannot collect data on the machine %1. Details: The query does not currently have any counters (entry point: %2). Hint: Close the application and reopen it later (it seems to be a temporary problem).
-47969	INVALID_QUERY	The query object for machine %1 is invalid (initialization error) (entry point: %2). Hint: Delete this machine and add it again (Use the Add Machine dialog box for this operation).
-47968	ERROR_NO_MACHINE_OBJECT	The internal object for machine %1 is invalid (initialization error) (entry point: %2). Hint: Delete this machine and add it again (Use the Add Machine dialog box for this operation).
-47967	ERROR_INVALID_MACHINE_OR_OFFLINE	Cannot connect to machine %1. The machine name may be invalid, or the machine may be offline (entry point: %2). Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (use the ping utility for this operation). Delete the machine name in the Add Machine dialog box, and add it again.
-47966	ERROR_INVALID_MACHINE_OR_OFFLINE_DETAILS	Cannot connect to machine %1. The machine name may be invalid, or the machine may be offline. Details: %2 (entry point: %3). Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online. (Use the ping utility for this operation). If problems persist, delete the machine name in the Add Machine dialog box, and add it again. If this does not work, close the monitoring application, reopen it, and add this machine again.
-47965	ERROR_INVALID_MACHINE_OR_OFFLINE_DETAILS_TMP	Cannot connect to machine %1. The machine name may be invalid, or the machine may be offline. Details: The network path was not found. (entry point: %2). Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (use the ping utility for this operation). If problems persist, delete the machine name in the Add Machine dialog box, and add it again. If this does not work, close the monitoring application, reopen it, and add this machine again.
-47964	NO_IP_ADDRESS	Cannot resolve machine's IP address for machine %1 (entry point: %2). Hint: Check that you have entered the correct machine name in the Add Machine dialog box. Check that the machine exists and that it is online (use the ping utility for this operation). If you continue to receive an error message, delete the machine name in the Add Machine dialog box, and enter the machine's IP address instead.
-47963	LOADING_ERROR	Cannot load %1 dll to access the UI. Machine: %2 (entry point: %3). Hint: Check that the dll exists in <application root>\bin directory.
-47962	CANT_CREATE_INTERNAL_HOST_OBJECT	A fatal error occurred in initializing an internal object for the machine %1 (entry point: %2). Hint: Close the monitoring application and reopen it.
-47961	CANT_CREATE_INTERNAL_MEASUREMENT_OBJECT	A fatal error occurred in initializing an internal object for the measurement %1 machine %2 (entry point: %3). Hint: Close the monitoring application and reopen it.
-47960	CANT_INIT_RPC	Cannot initialize RPC on the machine %1 (entry point:%2). Hint: Check that the RPC is up and running on %3 (use rpcinfo utility for this verification). Details: %4.
-47959	CANT_INIT_RPC_HOST_CLIENT	Cannot initialize the monitoring on %1. Error while creating the RPC client. Ensure that the machine can be connected and that it runs the rstat daemon (use rpcinfo utility for this verification) (entry point: %2). Detailed error: %3.
-47958	RPC_NOT_CONNECTED	Internal RPC error, or invalid client object on machine %1, see previous error (entry point: %2). Details: %3. Hint: Ensure that the machine can be connected and that it runs the rstat daemon (use rpcinfo utility for this verification).
-47957	HTTP_REQUEST_ERROR_CODE	HTTP error code %_1_Id: %2. Hint: Check the following URL in the Internet Browser: http://%3%4:%_5_Id%6 (entry point: %7).
-47956	NO_NETSCAPE_SITE	Site exists, but does not return a Netscape statistics html page. Machine: %1. URL: http://%2:<password>@%3:%_4_Id%5 (entry point:%6). Hint: Check this URL in the Internet Browser. If you do not get a Netscape statistics html page, delete this machine in the Add Machine dialog box.
-47955	PARSING_ERROR	Parsing error, cannot find token: %1. Measurement: %2. Hint: Such a measurement does not exist, or the html page may be different from the supported one (entry point: %3).
-47954	FAILED_TO_SEND_REQUEST_TO_SERVER_NO_USERNAME	Failed to send a request to server %1, URL: http://%2:%_3_Id%4. Details: %5 (entry point:%6). Hint: Check this URL in the Internet Browser.
-47953	XML_MONITOR_INT_FILE_MISSING	The required file for monitor initialization does not exist (<Installation Root>\\data\\monitors\\XMLMonitorShared.ini). Please consult installation instructions regarding this file.
-47952	XML_MONITOR_INIT_FAILURE	Failed to initialize monitor. Details: %1.
-47951	XML_MONITOR_GENERAL_EXCEPTION	General error. Exception was raised. Details: %1.
-47950	XML_MONITOR_CONNECTION_FAILURE	Failed to connect to server. Details: %1. Hint: Check that Web Server is up and running.
-47949	MEMORY_ALLOCATION_ERROR	Failed to allocate memory for server.%1.\nDetails: %2 (entry point: %3).
-47948	NTMON_ERROR_MACHINE_AFTER_REBOOT	It appears that machine %1 was rebooted and is now online. Note that it could take some time to refresh all measurements selected for this machine. Hint: If you do not receive measurement data, check the connection to the machine (entry point: %2)
lr_socks_res.h		
-56999	LR SOCKS MSG_GET_ATTRIB	Required configuration parameter "%1" is invalid or missing.

Error code	Handle	Message\Additional information
-56998	LR SOCKS MSG OUT_OF_MEMORY	Out of memory. Detected in call to %1
-56997	LR SOCKS MSG TLS_ALLOC_FAILED	Failed to allocate thread local storage in %1. Error code % 2 _ld.
-56996	LR SOCKS MSG HOOK_REGISTER_FAILED	Failed to register "%1". Error code % 2 _ld.
-56995	LR SOCKS MSG HOOK_UNREGISTER_FAILED	Failed to unregister "%1". Error code % 2 _ld.
-56994	LR SOCKS MSG TLS_SET_FAILED	Failed to set up thread local storage.
-56993	LR SOCKS MSG FUNC_FAILED	Failed to call %1 function from %2. The system returned error code % 3 _ld.
-56992	LR SOCKS MSG_SOCKET_NOT_FOUND	Socket descriptor not found. Hint: the problem may be solved applying the following: (1) Update Run-Time Settings to Run Vuser as a process. (2) Add the following line into mdrv.dat, [lr_socks] section: 'ExtCmdLineConc=-UsingWinNet Yes'.
-56991	LR SOCKS MSG_GET_INV_ATTRIB	Configuration parameter "%1" is invalid. (Value given is %2)
-56990	LR SOCKS MSG_GET_ATTRIB_NONE	All configuration parameters are missing.
-56989	LR SOCKS MSG_OVERLAPPED	Overlapped socket operation is not supported in call to %1
-56988	LR SOCKS MSG_MULTIPLE_BUFFERS	Multiple buffers in sockets I/O are not supported in call to %1
-56987	LR SOCKS MSG_GET_VUVERS	Failed to obtain Vuser variables.
-56986	LR SOCKS MSG_UNEXPECT_NOTIFY	Unexpected call of notify function.
-56985	LR SOCKS MSG_ATTRIB_CHANGED_PARAMS	Invalid parameter(s) passed to OnLocalAttribChanged callback.
-56984	LR SOCKS MSG_ANY_ENGLISH_MESSAGE	1%
-56983	LR SOCKS MSG_WININET_AND_THREAD_MODE_CONFLICT	Modem emulation and IP spoofing are unavailable in WinNet mode. To use these features, disable WinNet mode, or enable "Run Vuser as a process" in the run-time settings.
-56982	LR SOCKS MSG_FAILED_TO_RETRIEVE_HOOKED_FUNCTION	Failed to retrieve hooked function %1
-56981	LR SOCKS MSG_FAILED_TO_SET_INTERNAL_BUF_SIZE	Failed to set internal %1 buffer size in %2. The system returned error code % 3 _ld.
-56980	LR SOCKS MSG_DEBUG_MESSAGE	lr_socks debug message: %1
-56979	LR SOCKS MSG_FAILED_TO_HOOK_CREATE_PROCESS	Failed to setup process injection methods. Error: %1
-56978	LR SOCKS MSG_FAILED_TO_CREATE_INJECTED_PROCESS	Failed to create injected process. Error: %1
-56977	LR SOCKS MSG_FAILED_TO_FREE_DRV_INJECTED_PROCESS	Failed to free driver from injected process. Error: %1
-56976	LR SOCKS MSG_NO_VALID_IPS_FOUND_ON_MACHINE	IP Spoofing failed: There are no IP addresses for spoofing.
-56975	LR SOCKS MSG_RANDOM_MODEM_SPEED	Download : % 1 _ld bps, Upload : % 2 _ld bps network bandwidth.
-56974	LR SOCKS MSG_MODEM_MIN_MAX_MISSING	Configuration parameter "%1" is missing a minimum or maximum value. The value entered is "%2".
-56973	LR SOCKS MSG_MODEM_MIN_MAX_INVALID	Configuration parameter "%1" minimum value is greater than the maximum value. Modem speed minimum value = "% 2 _ld" and maximum value = "% 3 _ld"
-56972	LR SOCKS MSG_MODEM_CANNOT_FIND_USR	Failed to get usr file. Cannot detect protocol type.
-56971	LR SOCKS MSG_MODEM_PARAMETER_IS_EMPTY	Configuration parameter "%1" is missing, value set to '%2' as Configuration parameter "%3".
-56970	LR SOCKS MSG_MODEM_ALL_PARAMETER_ARE_EMPTY	Configuration parameters "%1" and "%2" are missing.
-56969	LR SOCKS MSG_NETWORK_VIRTUALIZATION_NO_LOCATION_ID	Failed to get Network Virtualization Location ID. Network Virtualization disabled.
-56968	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_INIT_COMAPI	Failed to initialize Network Virtualization Emulation COM API (%1). Network Virtualization disabled.
-56967	LR SOCKS MSG_NETWORK_VIRTUALIZATION_CREATE_SHUNRA_COMAPI	A Network Virtualization Emulation instance has been created.
-56966	LR SOCKS MSG_NETWORK_VIRTUALIZATION_DISABLED_MODEM_SPEED	Network Virtualization is enabled. As a result Modem Speed settings are disabled.
-56965	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_WSPCONNECT	Network Virtualization not added , TrapWSPConnect Failed error code % 1 _ld.
-56964	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_CONNECT	Could not connect to Network Virtualization - onConnect function failed resulting in error=%1. Scenario will run without Network Virtualization.
-56963	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_DISCONNECT	Could not disconnect from Network Virtualization - onDisconnect function failed resulting in error=%1. Scenario will continue to run with Network Virtualization.
-56962	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_GET_VUSER_ID	Network Virtualization failed to get Vuser ID.
-56961	LR SOCKS MSG_NETWORK_VIRTUALIZATION_ON_CONNECT_DISCONNECT_FAILED_TOO_MUCH	Network Virtualization has failed. The Network Virtualization service may have been restarted. Check the service and start the scenario again.
-56960	LR SOCKS MSG_GET_FAILED_TO_LOAD_HOOK_LIBRARY	Failed to load hook library.
-56959	LR SOCKS MSG_VUSER_WININET	Virtual user running with WinNet
-56958	LR SOCKS MSG_VUSER_IP	Virtual user assigned IP is %1
-56957	LR SOCKS MSG_VUSER_IP6	Virtual user assigned IP6 is [%1]
-56956	LR SOCKS MSG_VUSER_MAX_BANDWIDTH	Virtual user uses maximum network bandwidth
-56955	LR SOCKS MSG_VUSER_UPLOAD	Virtual user uses Upload: % 1 _ld bps, Download % 2 _ld bps network bandwidth
-56954	LR SOCKS MSG_NETWORK_VIRTUALIZATION_NO_SHUNRA_VERSION	Failed to get Network Virtualization version. Network Virtualization disabled.
-56953	LR SOCKS MSG_NETWORK_VIRTUALIZATION_NO_VIRTUAL_GROUP_ID	Failed to get Network Virtualization Virtual Group ID. Network Virtualization disabled.
-56952	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_LOAD_LIBRARY	Failed to load library '%1'. Network virtualization disabled.
-56951	LR SOCKS MSG_NETWORK_VIRTUALIZATION_FAILED_TO_GETPROCADDRESS	Failed to get process address from '%2'.

Error code	Handle	Message\Additional information
-56950	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_FAILED_TO_INIT_DYNAMIC_FILTER	Failed to initialize Network Virtualization Emulation Dynamic Filter API (%_1_Id). Network Virtualization disabled.
-56949	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_INIT_DYNAMIC_FILTER	Initialized Dynamic Filter API for Network Virtualization emulation.
-56948	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_FAILED_TO_ADD_DYNAMIC_FILTER	Could not add the dynamic filter to Network Virtualization, causing the error %_1_Id. The scenario will run without Network Virtualization.
-56947	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_FAILED_TO_DEL_DYNAMIC_FILTER	Could not remove the dynamic filter to Network Virtualization, causing the error %_1_Id. The scenario will continue to run with Network Virtualization.
-56946	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_FAILED_TO_CLOSE_DYNAMIC_FILTER	Failed to close Network Virtualization Emulation Dynamic Filter API (%_1_Id).
-56945	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_CLOSE_DYNAMIC_FILTER	The Network Virtualization Emulation Dynamic Filter API was closed.
-56944	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_WRONG_VERSION_FORMAT	Incorrect version number format for Network Virtualization, %1.
-56943	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_FAILED_TO_ENABLE_DYNAMIC_FILTER	Failed to enable the Dynamic Filter API due to an incorrect version number, %1.
-56942	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_ENABLE_DYNAMIC_FILTER	Dynamic Filter API version '%1' was enabled.
-56941	LR_SOCKS_MSG_NETWORK_VIRTUALIZATION_NO_SHUNRA_ON_WIN64	Network Virtualization 9.x is not supported on Windows x64 platform
lr_tcpbdown_res.h		
-202599	LR_TCPBREAKDOWN_MSG_GET_ATTRIB	Required configuration parameter "%1" is invalid or missing
-202598	LR_TCPBREAKDOWN_MSG_OUT_OF_MEMORY	Out of memory. Detected in call to %1
-202597	LR_TCPBREAKDOWN_MSG_TLS_ALLOC_FAILED	Failed to allocate thread local storage in %1. Error code %_2_Id
-202596	LR_TCPBREAKDOWN_MSG_HOOK_REGISTER_FAILED	Failed to register "%1".
-202595	LR_TCPBREAKDOWN_MSG_HOOK_UNREGISTER_FAILED	Failed to unregister "%1". Error code %_2_Id
-202594	LR_TCPBREAKDOWN_MSG_FAILED_TO_LOAD_LIBRARY	Failed to load library "%1": error code %_2_Id
-202593	LR_TCPBREAKDOWN_MSG_SERVICE_PROVIDER_NAME	Library "%1" is default sockets Service Provider
-202592	LR_TCPBREAKDOWN_MSG_COULD_NOT_FIND_FUNCTION	Failed to find address of function "%1" in library "%2": error code %_3_Id
-202591	LR_TCPBREAKDOWN_MSG_HOOK_REPLACE_API_FAILED	Failed to install hook on "%1" (HRESULT: %_2_Id)
-202590	LR_TCPBREAKDOWN_MSG_TLS_SET_FAILED	Failed to set up thread local storage
-202589	LR_TCPBREAKDOWN_MSG_FUNC_FAILED	Failed to call %1 function from %2. The system returned error code %_3_Id
-202588	LR_TCPBREAKDOWN_MSG_SOCKET_NOT_FOUND	Socket descriptor not found. Hint: the problem might be solved applying the following: (1) Update Run-Time Settings to Run Vuser as a process. (2) Add the following line into mdrv.dat, [lr_socks] section: 'ExtCmdLineConc=-UsingWinInet Yes'.
-202587	LR_TCPBREAKDOWN_MSG_GET_INV_ATTRIB	Configuration parameter "%1" is invalid (the value given is %2)
-202586	LR_TCPBREAKDOWN_MSG_GET_ATTRIB_NONE	All configuration parameters are missing
-202585	LR_TCPBREAKDOWN_MSG_OVERLAPPED	Overlapped socket operation is not supported in call to %1
-202584	LR_TCPBREAKDOWN_MSG_MULTIPLE_BUFFERS	Multiple buffers in sockets I/O are not supported in call to %1
-202583	LR_TCPBREAKDOWN_MSG_GET_VUVARs	Failed to obtain Virtual user variables
-202582	LR_TCPBREAKDOWN_MSG_UNEXPECT_NOTIFY	Unexpected call of notify function
-202581	LR_TCPBREAKDOWN_MSG_ATTRIB_CHANGED_PARAMS	Invalid parameter(s) passed to OnLocalAttribChanged callback
-202580	LR_TCPBREAKDOWN_MSG_ANY_ENGLISH_MESSAGE	1%
-202579	LR_TCPBREAKDOWN_MSG_WININET_AND_THREAD_MODE_CONFLICT	Modem emulation and IP spoofing are unavailable in WinInet mode. To use these features, disable WinInet mode, or enable "Run Vuser as a process" in the run-time settings.
-202578	LR_TCPBREAKDOWN_MSG_FAILED_TO_RETRIEVE_HOOKED_FUNCTION	Failed to retrieve hooked function %1
-202577	LR_TCPBREAKDOWN_MSG_FAILED_TO_SET_INTERNAL_BUF_SIZE	Failed to set internal %1 buffer size in %2. The system returned error code %_3_Id
-202576	LR_TCPBREAKDOWN_MSG_DEBUG_MESSAGE	lr_tcpbreakdown debug message: %1
-202575	LR_TCPBREAKDOWN_MSG_FAILED_TO_HOOK_CREATE_PROCESS	Failed to setup process injection methods. Error: %1
-202574	LR_TCPBREAKDOWN_MSG_FAILED_TO_CREATE_INJECTED_PROCESS	Failed to create injected process. Error: %1
-202573	LR_TCPBREAKDOWN_MSG_FAILED_TO_FREE_DRV_INJECTED_PROCESS	Failed to free driver from injected process. Error: %1
-202572	LR_TCPBREAKDOWN_MSG_NO_VALID_IPS_FOUND_ON_MACHINE	IP Spoofing failed: There are no IP addresses for spoofing.
-202571	LR_TCPBREAKDOWN_MSG_TIMEDIFF_FROM_FIRST_MEASUREMENT	Time diff from first measurement in milisec : %_1_Id
-202570	LR_TCPBREAKDOWN_MSG_TRANSACTION_DURATION	Transaction duration in milisec : %_1_Id
-202569	LR_TCPBREAKDOWN_MSG_DNS_TIME	DNS time in milisec : %_1_Id
-202568	LR_TCPBREAKDOWN_MSG_CONNECTION_ESTABLISHMENT	Connection establishment time in milisec : %_1_Id
-202567	LR_TCPBREAKDOWN_MSG_NETWORK_TIME_TO_FIRST_BUFFER	Network time to first buffer in milisec : %_1_Id
-202566	LR_TCPBREAKDOWN_MSG_SERVER_TIME_TO_FIRST_BUFFER	Server time to first buffer in milisec : %_1_Id
-202565	LR_TCPBREAKDOWN_MSG_TOTAL_TIME_TO_FIRST_BUFFER	Total time to first buffer in milisec : %_1_Id
-202564	LR_TCPBREAKDOWN_MSG_TIME_TO_DOWNLOAD_TIME	Download time in milisec : %_1_Id

Error code	Handle	Message\Additional information
-202563	LR_TCPBREAKDOWN_MSG_TCP_ACTIVITIES_TIME	TCP Activities time in milisec : % 1 _ld
-202562	LR_TCPBREAKDOWN_MSG_DOWNLOAD_SIZE	Total download size : % 1 _ld
-202561	LR_TCPBREAKDOWN_MSG_DESTINATION_ADDRESS	Destination IP address : % 1 _ld.% 2 _ld.% 3 _ld.% 4 _ld
-202560	LR_TCPBREAKDOWN_MSG_TRANSACTION_MEASUREMENTS_START	***** TCP breakdown statistics for transaction %1 - start *****
-202559	LR_TCPBREAKDOWN_MSG_TRANSACTION_MEASUREMENTS_END	***** TCP breakdown statistics for transaction %1 - end *****
-202558	LR_TCPBREAKDOWN_MSG_TRANSACTION_CONNECTION	----->Connection PID=% 1 _ld SOCKET=% 2 _ld<-----
-202557	LR_TCPBREAKDOWN_MSG_TRANSACTION_CONNECTION_Ex	----->Connection From (%1:% 2 _ld) to (%3:% 4 _ld)<-----
-202556	LR_TCPBREAKDOWN_MSG_TRANSACTION_REQUEST	---->Request number =% 1 _ld<---
-202555	LR_TCPBREAKDOWN_MSG_BLANK_RAW	
-202554	LR_TCPBREAKDOWN_MSG_SINGLE_USER_MODE	Single Vuser mode activated
-202553	LR_TCPBREAKDOWN_MSG_DEBUG_REQUEST_START	{{{{{ REQUEST START
-202552	LR_TCPBREAKDOWN_MSG_DEBUG_REQUEST_END	REQUEST END }}}}
-202551	LR_TCPBREAKDOWN_MSG_ASYNC_SOCKET_CREATED	Socket % 1 _ld was created with "Overlapped" flag
-202550	LR_TCPBREAKDOWN_MSG_ASYNC_FUNCTION_CALLED	Unsupported overlapped operation was initiated by "%1" function
-202549	LR_TCPBREAKDOWN_MSG_SOCKET_PROPERTY_CHANGED	Property "%1" for socket % 2 _ld was changed to "%3"
-202548	LR_TCPBREAKDOWN_MSG_LAST_ERROR	Last error is %1 in function id % 2 _ld.
-202547	LR_TCPBREAKDOWN_MSG_FAILED_TO_GET_INTERPRETER_LOCATION	Failed to get current position of interpreter in the script
lrd_m.h		
-61999	LRD_MSG_SENTENCE_SEPARATOR	". "
-61998	LRD_MSG_STAT_OK	OK
-61997	LRD_MSG_STAT_OK_INFO	OK (informational return-code=%1)
-61996	LRD_MSG_STAT_WARNING	Warning, return-code=%1
-61995	LRD_MSG_STAT_ERROR	ERROR, return-code=%1
-61994	LRD_MSG_STAT_CONTINUED_ERROR	Warning: continuing after error, return-code=%1
-61993	LRD_MSG_ADDINFO_NEXT_SET_AVAIL	(next result set available)
-61992	LRD_MSG_ADDINFO_NO_MORE_DATA	(no more data)
-61991	LRD_MSG_ADDINFO_NULL_DATA	(null data)
-61990	LRD_MSG_ADDINFO_EXP_DB_OP_FAIL	(an expected failure of a database operation)
-61989	LRD_MSG_ADDINFO_NO_FETCH_DATA	(no fetchable data)
-61988	LRD_MSG_ADDINFO_NO_FETCH_SET	(no fetchable result is set active; operation ignored, as requested)
-61987	LRD_MSG_ADDINFO_NO_MORE_SETS	(no more result sets)
-61986	LRD_MSG_FINAL_ACTIONS	%1: %2%3%4 %5
-61985	LRD_MSG_PARAM_NOT_SET_NO_FETCH	Parameter "%1" not set via a previous lrd_save_col (column %2) for this cursor. No rows fetched
-61984	LRD_MSG_PARAM_FROM_ANOTHER_ROW	Parameter "%1" value taken from row %2 (lrd_save_col for column %3 requested row %4, which was not fetched)
-61983	LRD_MSG_CONNECTION_INFO	User="%1", Server="%2"
-61982	LRD_MSG_PARAM_NOT_SET_BIND_DATA	Param "%1" not set. Previous lrd_save_col specified column %2, for which no lrd_bind_col/lrd_col_data has been issued successfully
-61981	LRD_MSG_ROWS_FETCHED	%1 row(s) fetched
-61980	LRD_MSG_COL	Column=%1
-61979	LRD_MSG_PLACEHOLDER	Placeholder "%1"
-61978	LRD_MSG_ROWS_PROCESSED	%1 row(s) processed
-61977	LRD_MSG_COL_ROW_PARAM	Column=%1, Row=%2, Param="%3"
-61976	LRD_MSG_PARAM	Param="%1"
-61975	LRD_MSG_SAVE_RESTRICT_DATATYPE	Note: Param "%1" cannot be used in lrd_stmt (restricted datatype)
-61974	LRD_MSG_SAVE_TO_PRINTABLE_ERR	lrdfncl_to_printable failed (return-code=%1). Marking param "%2" as invalid
-61973	LRD_MSG_SAVE_NULL_DATA	Note: Param "%1" cannot be used in lrd_stmt (NULL data)
-61972	LRD_MSG_SAVE_INVALID_DATA	Invalid data%1. Marking param "%2" as invalid
-61971	LRD_MSG_UNINIT_PARAM_FAILED	Uninitialization of param "%1" failed (lrd_save_value rc=%2). Continuing normally, but invalid references to the parameter may not be identified as such
-61970	LRD_MSG_LR_SAVE_PARAM_FAILED	Saving of param "%1" failed (lrd_save_value rc=%2)
-61969	LRD_MSG_SERVER_ATTACH_SERVER_ID	ServerHandle=%1, ServerID=%2%3%4
-61968	LRD_MSG_ATTR_SET	TargetHandle=%1, %2=%3%4%5
-61967	LRD_MSG_SESSION_BEGIN	SvcCtxHandle=%1, SessionHandle=%2
-61966	LRD_MSG_SEND_DATA	Request="%1"
-61965	LRD_MSG_ORA8_BIND_COL	StmtHandle=%1, Column=%2
-61964	LRD_MSG_ORA8_BIND_PLACEHOLDER	StmtHandle=%1, Placeholder "%2"
-61963	LRD_MSG_ORA8_EXEC	StmtHandle=%1, SvcCtxHandle=%2, %3 row(s) processed

Error code	Handle	Message\Additional information
-61962	LRD MSG_ORA8_FETCH	StmtHandle=%1, %2 row(s) fetched
-61961	LRD MSG_ORA8_SAVE_COL	StmtHandle=%1, Column=%2, Row=%3, Param="%4"
-61960	LRD MSG_ORA8_STMT	StmtHandle=%1, Text=%2%3%4
-61959	LRD MSG_LOGON	EnvHandle=%1, SvcCtxHandle=%2, User=%3%4%5, ServerID=%6%7%8
-61958	LRD MSG_ATTR_GET	TargetHandle=%1, %2, ValuePtr=%3
-61957	LRD MSG_SESSION_END	SvcCtxHandle=%1, SessionHandle=%2
-61956	LRD MSG_LOGOFF	SvcCtxHandle=%1
-61955	LRD MSG_SERVER_DETACH	ServerHandle=%1
-61954	LRD MSG_ORA8_COMMIT	SvcCtxHandle=%1
-61953	LRD MSG_ORA8_ROLLBACK	SvcCtxHandle=%1
-61952	LRD MSG_ORA8_LOB_READ	SvcCtxHandle=%1, LobDescriptor=%2, bytes read = %3
lrt_m.h		
-28999	LRT MSG_SENTENCE_SEPARATOR	". "
-28998	LRT MSG_STAT_OK	OK
-28997	LRT MSG_STAT_ERROR_0	ERROR
-28996	LRT MSG_STAT_ERROR_1	ERROR: %1
-28995	LRT MSG_STAT_ERROR_2	ERROR: %1: %2
-28994	LRT MSG_STAT_WARNING_1	Warning: %1
-28993	LRT MSG_UNKNOWN_ERROR	Unknown error
-28992	LRT MSG_INIT_FAILED	Failed to initialize TUXEDO replay
-28991	LRT MSG_TPINIT_NO_ALLOC	Failed to allocate TPINIT buffer
-28990	LRT MSG_TUXDIR_UNDEFINED	Make sure TUXDIR environment variable is defined
-28989	LRT MSG_TUXDIR_NO_CAT	Make sure TUXEDO message catalog is found under locale directory of TUXDIR
-28988	LRT MSG_LOAD_LRT_MSG_FAILED	Failed to load Opentext Performance Engineering TUXEDO runtime library
-28987	LRT MSG_LOAD_TUX_FAILED	Failed to load TUXEDO library
-28986	LRT MSG_CHECK_PATH	Check the search path
-28985	LRT_MSG_BAD_PATH	TUXEDO library %1 was not found in search path.\\nlf replay is on same machine as recording, find libwsc.dll in recording log,\\n\\rand make sure the directory containing it is in the search path
-28984	LRT MSG_FREE_TUX_FAILED	Failed to free TUXEDO library
-28983	LRT MSG_TUX_LIB_DIR	Cannot open TUXEDO library directory %1
-28982	LRT MSG_TUX_LIB_NOT_FOUND	The TUXEDO libraries were not found in directory %1
-28981	LRT MSG_USE_TUXEDO63	Maybe should use TUXEDO63 replay instead of TUXEDO
-28980	LRT MSG_NOT_SUPPORTED_4	Function not supported in TUXEDO 4.x
-28979	LRT MSG_NOT_SUPPORTED_5	Function not supported in TUXEDO 4.x or TUXEDO 5.x
-28978	LRT MSG_BEFORE	Before %1
-28977	LRT MSG_AFTER	After %1
-28976	LRT MSG_PARM_SAVE_FAIL	Failed to save parameter
-28975	LRT MSG_PARM_SUBST_FAIL	Parameter substitution failed
-28974	LRT MSG_MALLOC_FAIL	Memory allocation failed
-28973	LRT MSG_FML_NO_FIELD	No field id corresponds to field
-28972	LRT MSG_FML_NO_TYPE	Illegal field type
-28971	LRT MSG_FML_MISSING_ID	No field name or id present
-28970	LRT MSG_FML_GET_FAIL	Failed to get value of field
-28969	LRT MSG_FML_SAVE_FAIL	Failed to save value of field
-28968	LRT MSG_MEMCPY_SIZE_DIFFER	Sizes differ - The size argument of lrt_memcpy should be equal to the size after parameterization
-28967	LRT MSG_MEMCPY_SIZE_ARG	The size argument of lrt_memcpy is %1
-28966	LRT MSG_MEMCPY_SIZE_BEFORE	The size before parameterization is %1
-28965	LRT MSG_MEMCPY_SIZE_AFTER	The size after parameterization is %1
-28964	LRT MSG_SAVE_STRING_NEGATIVE_SIZE	Buffer size must be positive
-28963	LRT MSG_SAVE_STRING_BUFFER_SMALL	Buffer size must be at least as large as search string
-28962	LRT MSG_SAVE_STRING_EMPTY	Search string can't be empty
-28961	LRT MSG_SAVE_STRING_NOT_FOUND	String not found in buffer
-28960	LRT MSG_SAVE_STRING_END_OUT	End of search string must be inside buffer
-28959	LRT MSG_SAVE_STRING_START_OUT	Start of search string must be inside buffer
-28958	LRT MSG_PUTENV_NOT_DONE	%1 was not performed
-28957	LRT MSG_AEWPUTENV_NOT_DONE	lrt_AEWputenv is performed only on Win16

Error code	Handle	Message\Additional information
-28956	LRT MSG SENT DATA	Request buffer sent
-28955	LRT MSG SENT_NODATA	No data is sent
-28954	LRT MSG RECV_DATA	Reply buffer received
-28953	LRT MSG RECV_NODATA	No data is returned
-28952	LRT MSG BUF_TYPE	%1 buffer
-28951	LRT MSG BUF_TYPE_LEN	%1 buffer has length %2
-28950	LRT MSG BUF_TYPE_SUBTYPE_LEN	%1 buffer of subtype %2 has length %3
-28949	LRT MSG IN_TRAN	Transaction is in progress
-28948	LRT MSG NOTIN_TRAN	No transaction is in progress
-28947	LRT MSG TRACE_REPLAY	A trace of TUXEDO replay is stored in %1
-28946	LRT MSG TRACE_COMPARE	It can be compared with a trace in %1 for differences
-28945	LRT MSG OPEN_FAIL	Failed to open file %1
-28944	LRT MSG WDIFF	Use %1 to compare recording trace file %2 with replay trace file %3
-28943	LRT MSG COMPARE_NOW	To compare now, double click here. LaunchApplication: wdiff %1 %2
-28942	LRT MSG PS_ERROR	PeopleSoft error in replay buffer %1
-28941	LRT MSG SIZE_ERROR	The actual length of buffer %1, %2, does not match the expected length, %3
-28940	LRT MSG RECV_BYTES	
-28939	LRT MSG NORECV_BYTES	
-28938	LRT MSG SEND_BYTES	
-28937	LRT MSG NOSENT_BYTES	
-28936	LRT MSG BAD_PATTERN_FORMAT	Bad search pattern format
-28935	LRT MSG BAD_PASSWORD	Incorrect password was used during login
-28934	LRT MSG BAD_AUTHENTICATION	Incorrect password or other authentication data was used during login
lrun_api_res.h		
-17999	LRUN MSG 2_GENERIC_MESSAGE	1%
-17998	LRUN MSG FAILED_TO_GET_TLS_ENTRY	Failed to get %1 thread TLS entry.
-17997	LRUN MSG SET_DEBUG_MSG	lrun: lr_set_debug_message can only be set for %1 or %2
-17996	LRUN MSG THINKTIME_1	lr think time: %1 seconds
-17995	LRUN MSG THINKTIME_2	lr think time: %1 seconds (recorded think time was %2 seconds)
-17994	LRUN MSG INVALID_PARAMETERS	Invalid arguments for %1 function
-17993	LRUN MSG SAVE_SEARCH_STRING_FAILED	Failed to find %1 occurrences of search string - %2.
-17992	LRUN MSG USING_LIMIT_THINK_TIME	Think time - Waiting %1 seconds (according to limit).
-17991	LRUN MSG FAILED_TO_ADD_ITEM_TO_MFIFO	Failed to add item to mfifo data structure.
-17990	LRUN MSG CANNOT_FREE_MFIFO_SINCE_THERE_IS_NO_STRUCTURE	Cannot free the mfifo structure. It does not exist.
-17989	LRUN MSG CANNOT_FREE_MFIFO_SINCE_THERE_IS_NO_ITEM	Cannot free an mfifo item. It does not exist.
-17988	LRUN MSG TRIMMED	[Trimmed Message]
-17987	LRUN MSG RENDEZVOUS	Rendezvous %1
-17986	VUSER COMM MSG_XDR_FAILED_ENCODING	Communication - XDR failed while encoding %1.
-17985	LRUN MSG IP_SPOOFING_LOAD_LIB	IP Spoofing: Unable to load library %1
-17984	LRUN MSG IP_SPOOFING_STATS	IP Spoofing: Unable to retrieve IP statistics from %1: %2
-17983	LRUN MSG IP_SPOOFING_REGISTER_HOOKS	IP Spoofing: Unable to register bind hook %1
-17982	LRUN MSG IP_SPOOFING_NO_POOL	IP Spoofing: No IP Pool. Cannot activate spoofing.
-17981	LRUN MSG IP_SPOOF_ERR_NEXT_HOOK	IP Spoofing: NextWSPHook failed.
-17980	LRUN MSG IP_SPOOFING_NO_UNIQUE_STR	IP Spoofing: unique attribute incorrect or missing.
-17979	LRUN MSG IP_SPOOF_ERR_CONVERT_TO_DOTTED_FORMAT	IP Spoofing: Failed to set IP %_1_id for Vuser.
-17978	LRUN MSG_NO_RENDZ	Rendezvous is not allowed in Vuser initialization or termination.
-17977	LRUN MSG IP_SPOOFING_NO_MDRV_INDEX	IP Spoofing: Distribute IP attribute incorrect or missing.
-17976	LRUN MSG_ERROR_ITERATION_NUM	Failed to calculate number of iterations for action %1.
-17975	LRUN MSG_ERROR_FAILED_SET_PARAM_CONTEXT	Failed set context of parameters for '%1'.
-17974	LRUN MSG_ERROR_FAILED_UNSET_PARAM_CONTEXT	Failed unset context of parameters for '%1'.
-17973	LRUN MSG_IP_SPOOFING_ENABLE_ERROR	You cannot enable or disable IP spoofing from the command line.
-17972	LRUN MSG_FORCE_THINK_TIME	%1: %_2_2f seconds.
-17971	LRUN MSG_ERROR_ACTION_NAME	Invalid action name.
-17970	LRUN_MSG_SAVE_SEARCH_STRING_FAILED_SAVE	Failed to save searched string to the parameter. There are not %_1_id characters with offset %_2_id relative to the end of occurrence number %3 of search string - %4.
-17969	LRUN MSG_WARNING_REPLACED_THINK_TIME	The actual think time is bigger than LR_MAX_THINK_TIME (%_1_id seconds) and therefore is replaced by LR_MAX_THINK_TIME.

Error code	Handle	Message\Additional information
-17968	LRUN MSG LR CONVERT STRING ENCODING FAILED	Conversion of string encoding failed (internal error % 1 Id).
-17967	LRUN MSG ERROR ARG UNRECOG CHANGE TO	The "%1" argument is unrecognized. Change the argument to %2.
-17966	LRUN MSG ERROR CANNOT COMPRESS PARAM	Cannot compress the value in Parameter "%1", (internal error % 2 Id).
-17965	LRUN MSG ERROR CANNOT COMPRESS PARAM MEM_ERROR	Cannot compress the value in Parameter "%1". Not enough memory.
-17964	LRUN MSG ERROR CANNOT DECOMPRESS PARAM	Cannot decompress the value in Parameter "%1", (internal error % 2 Id).
-17963	LRUN MSG ERROR CANNOT DECOMPRESS PARAM CORRUPT	Cannot decompress the value in Parameter "%1". Compressed data corrupted.
-17962	LRUN MSG ERROR CANNOT DECOMPRESS PARAM MEM_ERROR	Cannot decompress the value in Parameter "%1". Not enough memory.
-17961	LRUN_MSG_ERROR_PARAM_NOT_EXIST	Parameter "%1" does not exist. Check spelling or the steps creating the parameter. If "%1" is a dynamic parameter created by searching a buffer, check if the search string exists in the buffer.
-17960	LRUN MSG ERROR SCRIPT API ARG UNRECOG	The argument "%1" is unrecognized or misplaced.
-17959	LRUN MSG ERROR SCRIPT API UNSUPPORTED_VALUE	Invalid DIGITS value ("%1").
-17958	LRUN MSG ERROR GETTIME FAILED	Failed to get time from operating system.
-17957	LRUN_MSG_WARNING_TOO_MANY_DIGITS	Invalid value for DIGITS (% 1 Id). If no valid DIGITS argument is passed, the default (% 2 Id) is used. Valid values for the DIGITS argument are integers between 1-% 3 Id.
-17956	LRUN MSG ERROR SCRIPT API ARG MISSING	Argument %1 is missing or misplaced.
-17955	LRUN MSG ERROR SCRIPT API INVALID_NEGATIVE_ARG	Argument %1 cannot be negative.
-17954	RUN MSG ERROR SCRIPT API ACTION FAILED DETAILS	Action failed: %1. Error code: (% 2 Id). Error message: %3.
-17953	RUN MSG ERROR SCRIPT API ALLOC FAILED	Failed allocating memory of size (% 1 Id) for %2.
-17952	RUN MSG ERROR SCRIPT API REGEX NOT ONE GROUP	The regular expression %1 does not contain exactly one capture group.
-17951	LRUN MSG ERROR SCRIPT API ARG UNRECOG FLAG	Invalid flag found: (% 1 Id).
-17950	RUN MSG ERROR SCRIPT API REGEX_COMPILE_FAILED	Regular Expression compilation failed at offset (% 1 Id): %2.
-17949	RUN MSG REGEX PARSED ARGS	Received Regular Expression [%1], ordinal [% 2 Id], case-sensitive [%3], parameter [%4], size of buffer to scan: [% 5 Id].
-17948	LRUN MSG ERROR FILENAME NULL	Filename must not be NULL.
-17947	LRUN MSG ERROR OPEN FILE	Can not open file.
-17946	LRUN MSG ERROR ALLOCATE MEMO FILE	Can not allocate memory for file.
-17945	LRUN MSG ERROR ALLOCATE MEMO New PARAMETER	Can not allocate memory for new parameter.
-17944	LRDB MSG DBManagement ColInitialize PR	DB Management execution failed (ColInitialize problem)
-17943	LRDB MSG DBCONNECTION STEP STARTED	DB Connection "%1" started ... Wait
-17942	LRDB MSG DBCONNECTION STEP SUCCESS	DB connection was successful
-17941	LRDB MSG DBCONNECTION STEP ERROR	There was an error during DB Connection
-17940	LRDB MSG DBCONNECTION STEP FAILURE	DB Connection execution failed
-17939	LRDB MSG DBCONNECTION ERROR	DB Connection failed ("%1")
-17938	LRDB REP DB CALL CONNECTION STEP FAILED	<CENTER>Connection failed</CENTER>
-17937	LRDB REP DB CALL CONNECTION STEP SUCCESS	<CENTER>Connection was successful</CENTER>
-17936	LRDB MSG DBDISCONNECTION STEP STARTED	DB disconnect "%1" started
-17935	LRDB MSG DBDISCONNECTION STEP SUCCESS	DB disconnect was successful
-17934	LRDB MSG DBDISCONNECTION STEP FAILURE	DB disconnect execution failed
-17933	LRDB MSG DBDISCONNECTION ERROR	DB disconnect failed ("%1")
-17932	LRDB MSG DBDISCONNECTION STEP ERROR	DB disconnect failed
-17931	LRDB REP DB CALL DISCONNECTION STEP FAILED	<CENTER>Disconnection failed</CENTER>
-17930	LRDB REP DB CALL DISCONNECTION STEP SUCCESS	<CENTER>Disconnection was successful</CENTER>
-17929	LRDB MSG REPORT FORMATTER FAILED	Error while formatting the report
-17928	LRDB MSG STEP FAILURE	Action execution failed
-17927	LRDB MSG STEP NAME ERROR	Step name must be the first argument of the function
-17926	LRDB MSG DB EXEC QUERY STEP STARTED	SQL Statement execution "%1" started
-17925	LRDB MSG DB EXEC QUERY STEP SUCCESS	SQL Statement execution was successful
-17924	LRDB MSG DB EXEC QUERY STEP ERROR	There was an error during SQL Statement execution
-17923	LRDB MSG DB EXEC QUERY FAILURE	SQL Statement execution failed
-17922	LRDB MSG DB EXEC QUERY ERROR	SQL Statement failed ("%1")
-17921	LRDB REP DB CALL EXEC QUERY STEP FAILED	<CENTER>SQL Statement execution failed</CENTER>
-17920	LRDB REP DB CALL EXEC QUERY STEP SUCCESS	<CENTER>SQL Statement execution was successful</CENTER>
-17919	LRDB MSG DB GET VALUE STEP STARTED	Get db value "%1" started
-17918	LRDB MSG DB GET VALUE STEP SUCCESS	Get db value was successful
-17917	LRDB MSG DB GET VALUE STEP ERROR	There was an error during getting db value
-17916	LRDB MSG DB GET VALUE FAILURE	Getting db value failed
-17915	LRDB MSG DB GET VALUE ERROR	Getting db failed ("%1")
-17914	LRDB REP DB CALL GET VALUE STEP FAILED	<CENTER>Get db value failed</CENTER>

Error code	Handle	Message\Additional information
-17913	LRDB REP DB CALL GET VALUE STEP SUCCESS	<CENTER>Get db value was successful</CENTER>
-17912	LRDB MSG ASSERT STEP STARTED	Checkpoint validation "%1" started
-17911	LRDB MSG ASSERT STEP SUCCESS	Checkpoint validation was successful
-17910	LRDB MSG ASSERT STEP ERROR	There was an error during Checkpoint validation
-17909	LRDB MSG ASSERT FAILURE	Checkpoint validation failed
-17908	LRDB MSG ASSERT EMPTY PARAMETER	Parameter is empty
-17907	LRDB MSG ASSERT INVALID PARAMETER	Invalid Parameter
-17906	LRDB MSG ASSERT ERROR	Checkpoint validation failed {"%1"}
-17905	LRDB REP DB CALL ASSERT STEP FAILED	<CENTER>Checkpoint validation failed</CENTER>
-17904	LRDB REP DB CALL ASSERT STEP SUCCESS	<CENTER>Checkpoint validation was successful</CENTER>
-17903	LRDB MSG DS ACTION STEP STARTED	Dataset action "%1" started
-17902	LRDB MSG DS ACTION STEP SUCCESS	Dataset action was successful
-17901	LRDB MSG DS ACTION STEP ERROR	There was an error during dataset action
-17900	LRDB MSG DS ACTION FAILURE	Dataset action action failed
-17899	LRDB MSG DS ACTION ERROR	Dataset action failed {"%1"}
-17898	LRDB MSG PRINT ONE ARGUMENT	"%1"
-17897	LRDB REP DB CALL DS ACTION STEP FAILED	<CENTER>Dataset action failed</CENTER>
-17896	LRDB REP DB CALL DS ACTION STEP SUCCESS	<CENTER>Dataset action was successful</CENTER>
-17895	LRDB MSG QT REPLAY ENGINE COM ERROR	Com error. %1. % 2 Id.
-17894	MSG_INVALID_API_CALL	Invalid API Call
-17893	MSG_LOAD_LIB_FAIL	Cannot load library
-17892	MSG_UNKNOWN_SCRIPT_LANGUAGE	Unknown script language
-17891	LRUN MSG WEEK COUNT BASE	The week count starts from % 1 Id.
-17890	LRUN MSG GET AES KEY FAILED	Failed to get the key. Please verify if the key exists in the attributes, environment variables, or the specified key location.
-17889	LRUN MSG AES KEY INVALID	Invalid key. Please ensure the key consists of 64 hexadecimal characters. For more details, please refer to the documentation.
-17888	LRUN MSG DECRYPT FAILED	Decryption failed. Please check the key and ciphertext.
-17887	LRUN MSG ENCRYPT FAILED	Encryption failed.
magent_config_res.h		
-93800	MAGENT_CONFIG_ERR_CANT_WRITE_TO_FILE	Could not write to file %1. System error: %2To use a different path, set the environment variable %3 to the new file path, and run again.
-93799	MAGENT_CONFIG_AGENT_CONFIG_TITLE	Agent Configuration
-93798	MAGENT_CONFIG_FAILED_TO_SHUTDOWN_AGENT	Failed to shut down running Agent (sys error - %1)
-93797	MAGENT_CONFIG_FAILED_TO_RESTART_AGENT	Failed to restart Agent (sys error - %1)
mchan_msgs.h		
-59999	MCHAN_USER_CALLBACK_INITIALIZE_ERROR	Server didn't get user wakeup call back function.
-59998	MCHAN_SERVER_RESPONSIVE_HANDLE_INITIALIZE_ERROR	Server didn't get responsive select handle (user's call backs can't be called) , mchan_pp_init API must be called first.
-59997	MCHAN_CLIENT_RESPONSIVE_HANDLE_INITIALIZE_ERROR	Client didn't get responsive select handle (can't be asynchronous client).
-59996	MCHAN_EXTRA_KEY_INITIALIZE_ERROR	Failed to send extra key to the server.
-59995	MCHAN_LL_SERVER_NAME_INITIALIZE_ERROR	Linked List client failed to initialize server pointer.
-59994	MCHAN_LL_CLIENT_INITIALIZE_ERROR	Failed to initialize Linked List client - Server not responding.
-59993	MCHAN_CREATE_DYNAMIC_ARRAY_INITIALIZE_ERROR	Failed to create dynamic array.
-59992	MCHAN_CREATE_SOCKET_ASSOCIATOR_ERROR	Failed to create socket associator object.
-59991	MCHAN_GET_SOCKET_HASHTABLE_ERROR	Error occurred while trying to get connected socket global hash table.
-59990	MCHAN_GET_SOCKET_FROM_HASH_ERROR	Error occurred while trying to get connected socket from hash table.
-59989	MCHAN_GET_SOCKET_ASSOCIATOR_FROM_HASH_ERROR	There is no open TCP connection to %1.
-59988	MCHAN_CREATE_STL_LLIST_ERROR	Failed to create STL linked list object.
-59987	MCHAN_NOT_VALID_SERVER_NAME_ERROR	The server name is not valid.
-59986	MCHAN_CREATE_SOCKET_ERROR	Failed to create socket while calling socket function.
-59985	MCHAN_NO_AVAILABLE_SOCKETS_ERROR	Failed to create socket. There are no more available socket descriptors.
-59984	MCHAN_NO_SPACE_FOR_CREATE_SOCKET_AVAILABLE_ERROR	Failed to create socket. There is no more available buffer space.
-59983	MCHAN_CLIENT_CONNECT_ERROR	Failed to connect to remote host %1. Please check the network connection.
-59982	MCHAN_CONNECT_TO_NOT_VALID_SOCKET_ERROR	Failed to connect to remote host - %1. The remote address is not a valid address.
-59981	MCHAN_CONNECT_REJECTED_ERROR	Failed to connect to remote host - %1. Connection refused. Please check the network connection.
-59980	MCHAN_ALREADY_CONNECTED_ERROR	Failed to connect to remote host - %1. The socket is already connected. Please check the network connection.
-59979	MCHAN_CONNECT_HOST_CANT_BE_REACHED_ERROR	Failed to connect to remote host - %1. The network cannot be reached from this host at this time. Please check the network connection.
-59978	MCHAN_CONNECT_TIME_OUT_REACHED_ERROR	Failed to connect to remote host - %1. Connection timed out. Please check the network connection.

Error code	Handle	Message\Additional information
-59977	MCHAN_CLIENT_SEND_ERROR	The Client failed to send a packet.
-59976	MCHAN_SEND_CONNECTION_WAS_BROKEN_ERROR	The Client failed to send packet. The connection keep-alive is broken.
-59975	MCHAN_SEND_NOT_AVAILABLE_BUFFER_SPACE_ERROR	The Client failed to send packet. There is no available buffer space.
-59974	MCHAN_SEND_SOCKET_ISNOT_CONNECTED_ERROR	The Client failed to send packet. The socket is not connected.
-59973	MCHAN_SEND_SOCKET_HAS_BEEN_SHUT_DOWN_ERROR	The Client failed to send packet. The socket has been shut down.
-59972	MCHAN_SEND_BLOCKED_ERROR	The Client failed to send packet. The socket would block.
-59971	MCHAN_SEND_TOO_LARGE_MESSAGE_ERROR	The Client failed to send packet. The message is too big.
-59970	MCHAN_SEND_HOST_CANNOT_BE_REACHED_ERROR	The Client failed to send packet. The remote host cannot be reached from this host at this time.
-59969	MCHAN_SEND_SOCKET_HAS_NOT_BE_BOUND_ERROR	The Client failed to send packet. The socket is not bound to a valid address.
-59968	MCHAN_SEND_NETWORK_FAILURE_ERROR	The Client failed to send packet. The connection has been dropped, because of a network failure or because the system at the other end went down without notice.
-59967	MCHAN_SERVER_RECV_ERROR	The Server failed to receive message, %1.
-59966	MCHAN_RECV_CONNECTION_HAS_BEEN_BROKEN_ERROR	The server failed to receive message, %1. The connection keep-alive is broken.
-59965	MCHAN_RECV_SOCKET_HAS_BEEN_SHUT_DOWN_ERROR	The Server failed to receive message, %1. The socket has been shut down.
-59964	MCHAN_RECV_BLOCKED_ERROR	The Server failed to receive message, %1. Socket would block.
-59963	MCHAN_RECV_TOO_LARGE_MESSAGE_ERROR	The Server failed to receive message, %1. The message is too big.
-59962	MCHAN_RECV_NETWORK_FAILURE_ERROR	The Server failed to receive message, %1. Connection has been dropped, because of a network failure or because the system at the other end went down without notice.
-59961	MCHAN_SERVER_BIND_ERROR	Failed to bind socket while calling bind function.
-59960	MCHAN_ALREADY_BOUND_ADDRESS_ERROR	Failed to bind socket (on port %1). A process on the machine is already bound to the same address.
-59959	MCHAN_BIND_NOT_VALID_ADDRESS_ERROR	Failed to bind socket (on port %1). The specified address is not a valid address for this machine.
-59958	MCHAN_ALREADY_BOUND_SOCKET_ERROR	Failed to bind socket (on port %1). The socket is already bound to an address.
-59957	MCHAN_CLIENT_SELECT_ERROR	Function select failed.
-59956	MCHAN_SELECT_WSANOTINITIALISED_ERROR	Function select failed - a successful WSASStartup call must occur before using this function.
-59955	MCHAN_SELECT_WSAEFAULT_ERROR	Function select failed - the Windows Sockets implementation was unable to allocate needed resources for its internal operations, or the readfds, writefds, exceptfds or timeval parameters are not part of the user address space.
-59954	MCHAN_SELECT_WSAENETDOWN_ERROR	Function select failed - the network subsystem has failed.
-59953	MCHAN_SELECT_PARAM_INVALID_ERROR	Function select failed - the time-out value is not valid, or all three descriptor parameters were NULL.
-59952	MCHAN_SELECT_WSAEINTR_ERROR	Function select failed - a blocking Windows Socket 1.1 call was canceled through WSACancelBlockingCall.
-59951	MCHAN_SELECT_WSAEINPROGRESS_ERROR	Function select failed - a blocking Windows Sockets 1.1 call is in progress, or the service provider is still processing a callback function.
-59950	MCHAN_SELECT_WSAENOTSOCK_ERROR	Function select failed - one of the descriptor sets contains an entry that is not a socket.
-59949	MCHAN_SETSOCKOPT_ERROR	Function setsockopt failed.
-59948	MCHAN_SETSOCKOPT_WSAENETDOWN_ERROR	Function setsockopt failed - the network subsystem has failed.
-59947	MCHAN_SETSOCKOPT_WSAENETRESET_ERROR	Function setsockopt failed - connection has timed out when SO_KEEPAIVE is set.
-59946	MCHAN_SETSOCKOPT_WSAENOTCONN_ERROR	Function setsockopt failed - connection has been reset when SO_KEEPAIVE is set.
-59945	MCHAN_CLIENT_CONNECT_TO_PROXY_ERROR	Client failed to connect to a PROXY Server with the following settings:\n%1.
-59944	MCHAN_CLIENT_SEND_CONNECTION_REQUEST_VIA_PROXY_ERROR	Client failed to send the connection request through PROXY.
-59943	MCHAN_CLIENT_CONNECT_TO_PROXY_TIMEOUT_ERROR	Client failed to receive a connection acknowledge message from the proxy - timeout reached.
-59942	MCHAN_CLIENT_SEND_VIA_PROXY_ERROR	Client failed to send extra data to the server through the PROXY.
-59941	MCHAN_HTTP_CLIENT_RECEIVE_NO_ACK_FROM_PROXY_ERROR	Client received a reject connection message from the PROXY, instead of an acknowledge message.
-59940	MCHAN_CLIENT_OPEN_MUTEX_ERROR	An error occurred while trying to open mutex name - %1.
-59939	MCHAN_CLIENT_OPEN_EVENT_ERROR	An error occurred while calling the OpenEvent function.
-59938	MCHAN_CLIENT_CREATE_MAP_VIEW_ERROR	An error occurred while calling the MapViewOfFile function.
-59937	MCHAN_CLIENT_OPEN_MAP_FILE_ERROR	An error occurred while calling the OpenFileMapping function for file name - %1.
-59936	MCHAN_CLIENT_REFRESH_MAPPINT_ERROR	An error occurred while calling the mmap function.
-59935	MCHAN_CLIENT_CREATE_UX_VIRTUAL_MEMORY_ERROR	An error occurred while calling the ftruncate function.
-59934	MCHAN_CLIENT_SIGNAL_READER_ERROR	Failed to signal the reader.
-59933	MCHAN_CLIENT_CONNECTION_TO_SERVER_WAS_CLOSED_ERROR	No response from the server. The server has shut down.
-59932	MCHAN_CLIENT_RESPONSE_SELECT_REMOVE_ERROR	An error occurred while calling mic_response_remove_wait object function.
-59931	MCHAN_CLIENT_SIGPIPE_UNREGISTER_ERROR	Failed to restore the SIGPIPE signal to its default.
-59930	MCHAN_CLIENT_SIGPIPE_REGISTER_ERROR	Failed to catch SIGPIPE signal.
-59929	MCHAN_CLIENT_NOT_CONNECTED_ERROR	Failed to send message to server %1 - socket is not connected yet.
-59928	MCHAN_CLIENT_UNRESOLVE_SERVER_NAME_ERROR	Unresolved server name %1.
-59927	MCHAN_CREATE_HTTP_SERVER_ERROR	Failed to create a TCP server for the HTTP channel's server.
-59926	MCHAN_SERVER_CREATE_MAP_FILE_ERROR	An error occurred while calling the CreateFileMapping function.
-59925	MCHAN_SERVER_CREATE_MUTEX_ERROR	An error occurred while trying to create mutex.
-59924	MCHAN_SERVER_CREATE_EVENT_ERROR	An error occurred while calling the CreateEvent function.

Error code	Handle	Message\Additional information
-59923	MCHAN_SERVER_RECEIVED_BUFFER_TOO_SHORT	Server received a buffer for the next incoming that is too short.
-59922	MCHAN_SERVER_WSAEVENTSELECT_ERROR	An error occurred while calling the WSAEventSelect function.
-59921	MCHAN_SERVER_UNRESOLVE_HOST_IP_ERROR	Failed to get the server host IP by calling the gethostbyname function.
-59920	MCHAN_SERVER_UNRESOLVE_HOST_NAME_ERROR	Failed to get the server host name by calling the gethostname function.
-59919	MCHAN_SERVER_UNRESOLVE_HOST_PORT_ERROR	Failed to get the server port number by calling the getsockname function.
-59918	MCHAN_CREATE_NT_VIRTUAL_MEMORY_ERROR	An error occurred while calling the VirtualAlloc function.
-59917	MCHAN_CREATE_MMAP_ERROR	An error occurred while calling the mmap function.
-59916	MCHAN_GET_FDSTAT_ERROR	An error occurred while calling the fstat function.
-59915	MCHAN_OPEN_SHARED_MEMORY_FILE_ERROR	An error occurred while trying to open the %1 file using the open function.
-59914	MCHAN_RESPONSIVE_SELECT_ERROR	An error occurred while calling the mic_response_add function.
-59913	MCHAN_NTLM_AUTHENTICATION_TO_PROXY_ERROR	NTLM authentication to proxy server error - connection to proxy refused. (domain: %1, username: %2)
-59912	MCHAN_SOCKET_ASSOC_ERROR	1.00%
-59911	MCHAN_SSL_ERROR	1.00%
-59910	MCHAN_SSL_INITIALIZE_ERROR	SSL initialization error : %1.
-59909	MCHAN_SSL_CONNECT_REGISTER_FAILED	Failed to register on connect.
-59908	MCHAN_SSL_CONNECT_UNREGISTER_FAILED	Failed to unregister on connect.
-59907	MCHAN_SSL_CONNECT_ERROR	SSL connect error : %1.
-59906	MCHAN_SSL_ACCEPT_REGISTER_FAILED	Failed to register on accept.
-59905	MCHAN_SSL_ACCEPT_UNREGISTER_FAILED	Failed to unregister on accept.
-59904	MCHAN_SSL_ACCEPT_ERROR	SSL accept error : %1.
-59903	MCHAN_SSL_WRITE_ERROR	SSL write error : %1.
-59902	MCHAN_SSL_READ_ERROR	An error occurred while calling SSL read function : %1.
-59901	MCHAN_SSL_SHUTDOWN_ERROR	SSL shut down error : %1.
-59900	MCHAN_SHARED_MEM_NAME_ALREADY_USED	Shared memory with the same name already exists.
-59899	MCHAN_SM_VERIFICATION_ERROR	Shared memory verification failed.
-59898	MCHAN_CREATE_CLIENT_ERROR	Failed to create %1 client.
-59897	MCHAN_CREATE_SERVER_ERROR	Failed to create %1 server.
-59896	MCHAN_CREATE_TCP_CONNECTION_ERROR	Failed to create a TCP connection object for %1.
-59895	MCHAN_CREATE_TRIGGER_ERROR	An error occurred while calling the mic_response_trigger_create function.
-59894	MCHAN_GROW_BUFFER_EXCEED_MAX_ERROR	Shared memory client error: failed to grow shared memory buffer - size of buffer exceed maximum size.
-59893	MCHAN_HTTP_ERROR	http error %1
-59892	MCHAN_HTTP_CREATE_ND_CLIENT_ERROR	can't create Http ND Channel(connect not ready).
-59891	MCHAN_HTTP_CREATE_DUMMY_CLIENT_ERROR	can't create Http Dummy Channel(connect not ready).
-59890	MCHAN_HTTP_ND_BAD_RESPONSE	ND received incorrect response :\n %1.
-59889	MCHAN_HTTP_ND_SEND_NOT_READY	Message was sent when the ND channel wasn't ready.
-59888	MCHAN_HTTP_DUMMY_SEND_NOT_READY	Message was sent when the Dummy channel wasn't ready.
-59887	MCHAN_HTTP_HASH_TABLE_ERROR	can't get hash_table from tls.
-59886	MCHAN_HTTP_HASH_TABLE_VALUE_NOT_FOUND	client can't get server value from hash table.
-59885	MCHAN_HTTP_CREATE_SECONDARY_CLIENT_ERROR	can't create client.
-59884	MCHAN_HTTP_FAIL_CREATE_TIMER	fail to create timer.
-59883	MCHAN_HTTP_CREATE_CLIENT_ERROR	fail to create TCP client to HTTP channel.\n %1
-59882	MCHAN_HTTP_CREATE_TCP_SERVER_ERROR	can't create tcp secondary server to http channel.
-59881	MCHAN_HTTP_FAIL_CONNECT_TO_SERVER	Client Fail connecting to server.
-59880	MCHAN_BASIC_AUTHENTICATION_TO_PROXY_ERROR	#NAME?
-59879	MCHAN_NTLM_AUTHENTICATION_ERROR	NTLM authentication error - connection refused.
-59878	MCHAN_BASIC_AUTHENTICATION_ERROR	Basic authentication error - connection refused.
-59877	MCHAN_SERVER_AUTH_ERROR_VIA_PROXY	server authentication error via proxy.
-59876	MCHAN_HTTP_RECIEVED_BAD_RESPONSE	http channel received bad response :\n %1
-59875	MCHAN_HTTP_SERVER_WRONG_CS_FROM_DUMMY	Server Error: wrong connection string from dummy.
-59874	MCHAN_HTTP_UNKNOWN_CLIENT	Message arrived from unknown client.
-59873	MCHAN_HTTP_MESSAGE_MISSING	Message Missing.
-59872	MCHAN_HTTP_MESSAGE_MISSING_TIME_OUT	Message Missing : time out reached.
-59871	MCHAN_HTTP_CANT_CREATE_CLIENT_TO_DUMMY_ERROR	Can't open client to dummy server %1.
-59870	MCHAN_HTTP_FAIL_TO_POST_DUMMY_ERROR	fail post message to dummy server.
-59869	MCHAN_CREATE_GUID_ERROR	Error: Failed to create guid.
-59868	MCHAN_LL_SERVER_INIT_EXCEED_MAX_SERVERS_ERROR	Failed to initialize linked list server. Exceeded maximum number of servers.
-59867	MCHAN_LL_SERVER_INIT_CONTAINER_UNINITIALIZED_ERROR	Failed to initialize linked list server. Servers container is not initialized.

Error code	Handle	Message\Additional information
-59866	MCHAN REJECTION TCP CONNECTION	rejecting tcp connection without ssl.
-59865	MCHAN SHMEM REACHED MAX SHARED MEMORY SIZE	Cannot send the message since reached the shared memory buffer max size.
-59864	MCHAN FAILED TO GET MESSAGE ENCRYPTOR	Failed to get encryptor - %2
-59863	MCHAN FAILED TO GET MESSAGE DECRYPTOR	Failed to get decryptor - %2
-59862	MCHAN SSL CONNECT CLIENT CERT ERROR	The client SSL certificate is not trusted by the server.
-59861	MCHAN SSL NO CERT ERROR	The certificates required for the SSL connection could not be found. Open the Certificate Manager in order to view and change the certificates.
-59860	MCHAN_CLIENT_CONNECT_TO_PROXY_FORBIDDEN_ERROR	The proxy server you defined in the network profile has blocked communication on the specified port. Please designate another port, such as 443 which is usually open for secure communication, or contact your network administrator to open the port in the proxy.
-59859	MCHAN_CLIENT_SSL_CONNECT_FAILED_VIA_PROXY	The SSL connect via proxy failed. Please check the proxy setting and target server status.
-59858	MCHAN_SET_BROKER_LIST_ERROR	Kafka set broker list failed. %1
-59857	MCHAN_CREATE_CONSUMER_ERROR	Kafka create consumer failed. %1
-59856	MCHAN_CREATE_TOPIC_ERROR	Kafka create topic failed. %1
-59855	MCHAN_START_CONSUMER_ERROR	Kafka start consumer failed. %1
-59854	MCHAN_SET_DEFAULT_TOPIC_CONFIG_ERROR	Kafka set default topic config failed. %1
-59853	MCHAN_CREATE_PRODUCER_ERROR	Kafka create producer failed. %1
-59852	MCHAN_PRODUCER_WRITE_ERROR	Kafka producer write failed. %1
-59851	MCHAN_KAFKA_SSL_ERROR	Kafka ssl config failed. %1
-59850	MCHAN_KAFKA_PROXY_SERVER_CONNECTION_ERROR	Failed to connect to proxy server.
-59849	MCHAN_KAFKA_BROKER_ERROR	Kafka broker error. %1
mdrv_res.h		
-10800	DRIVER INFO MISSING_USR_FILE	Missing usr file after option -usr.
-10799	DRIVER INFO MISSING_RUNNING_MODE	Missing running mode after option -drv_running_mode.
-10798	DRIVER INFO WRONG_RUNNING_MODE	Running mode %1 is not acceptable (use Server or Shell).
-10797	DRIVER INFO MISSING_NO_POPUPS_FILE	Missing file name after option -no_popups.
-10796	DRIVER INFO MISSING_BIN_FILE	Missing bin file after option -file.
-10795	DRIVER INFO MISSING_OUT_DIR	Missing out dir after option -out.
-10794	DRIVER INFO NO_USR_FILE	Must have -usr option.
-10793	DRIVER INFO_USR_FILE_DIR_TOO_LONG	Usr file path's string length may exceed the maximum allowed size of 260 characters, %1.
-10792	DRIVER INFO_USR_FILE_NOT_EXIST	Cannot find usr file %1.
-10791	DRIVER INFO_OUT_DIR_NOT_EXIST	Cannot find out dir %1.
-10790	DRIVER INFO_FAIL_TO_SET_ROOT_DIR	Cannot set root dir.
-10789	DRIVER INFO_FAIL_TO_SET_ROOT_DIR_IN_SET_SECURITY_DIR	Cannot set root dir in for SecurityMode.
-10788	DRIVER_INFO_BIN_DIR_NOT_FOUND	Cannot find bin/arch directory %1.
-10787	DRIVER_INFO_INC_DIR_NOT_FOUND	Cannot find include/inc directory %1.
-10786	DRIVER_INFO_DAT_DIR_NOT_FOUND	Cannot find dat directory %1.
-10785	DRIVER_INFO_SECURITY_DIR_NOT_FOUND	Cannot find security_files directory %1.
-10784	DRIVER_INFO_NO_VUGENDAT_FILE	Data file %1 is not found.
-10783	DRIVER_INFO_NO_MAGIC	Missing session magic.
-10782	DRIVER_INFO_NO_SCRIPT_ID	Missing agent script ID.
-10781	DRIVER_INFO_ERROR_PARSING_COMMAND_LINE	Error parsing command line: %1.
-10780	DRIVER_INFO_INTERNAL_ERROR_ATTRIBS	Internal error - attrib module cannot initialize.
-10779	DRIVER_INFO_CANT_ADD_USR_FILE	Internal error in reading usr file %1.
-10778	DRIVER_INFO_CANT_ADD_CFG_ATTRIBS	Failed to add .cfg file %1 to driver attributes.
-10777	DRIVER_INFO_CANT_ADD_CFGPP_ATTRIBS	Failed to add per process .cfg file %1 to driver attributes.
-10776	DRIVER_INFO_CANT_GET_CFG_FILE	Failed to find .cfg file.
-10775	DRIVER_INFO_CANT_GET_CFGPP_FILE	Failed to find per process .cfg file.
-10774	DRIVER_INFO_CFG_TAKEN	Using CFG file %1.
-10773	DRIVER_INFO_CFGPP_TAKEN	Using CFG file %1 per process.
-10772	CFGPP_DOES_NOT_HAVE_VALUE	There is no file name after -cfgpp option in the command line.
-10771	CFG_DOES_NOT_HAVE_VALUE	There is no file name after -cfg option in the command line.
-10770	DRIVER_INFO_CANT_READ_ATTR	"%1" attribute cannot be found in section "%2" in file %3 (default: %4).
-10769	DRIVER_INFO_INVALID_TYPE_NAME	Vuser type "%1" specified in %2 cannot be found (or its section is empty) in %3.
-10768	DRIVER_INFO_MISSING_COMPILE_FLAGS_FILE	missing <compile flag file> after option -compile_flags.
-10767	DRIVER_INFO_MISSING_EXTRA_EXT_ENTRY_NAME	Missing extra extension entry name after option -extra_ext.
-10766	DRIVER_INFO_NO_EXT_SECTION	Extension %1 has no section in %2.
-10765	DRIVER_INFO_EXT_LIST	The driver extension list is %1.

Error code	Handle	Message\Additional information
-10764	DRIVER INFO CAT GET CONFIG SOURCE	Driver failed to get config source file %1.
-10763	DRIVER INFO MISSING NET DIR	Missing net directory after option -netdir.
-10762	DRIVER INFO NETDIR NOT EXIST	Cannot find controller net dir %1.
-10761	DRIVER INFO NET DIR FOUND	controller net dir is %1.
-10760	DRIVER INFO CANT GET REMOTE LOCATION	Fail to translate %1 to remote location.
-10759	DRIVER INFO COMPONENT PATH	Component to load : %1.
-10758	DRIVER INIT SAVE CONFIG	Driver config (at end of init) was saved into file %1.
-10757	DRIVER RUN SAVE CONFIG	Driver config (at end of run) was saved into file %1.
-10756	DRIVER INFO CANNOT CONVERT TO NETDIR PATH	Cannot translate local path "%1" to netdir path "%2".
-10755	DRIVER INFO NO VERIFY FLAG	Cannot find results directory: -verify option.
-10754	DRIVER INFO SECURITY DIR IS SET	driver security dir is set to %1.
-10753	DRIVER INFO IN SECURITY MODE IS SET	driver InSecurityMode attr is set to %1.
-10752	EXT LOAD UNSECURITYEXT IN SECURITYMODE	Extension %1 was not loaded. You are running under secure mode and this extension is not allowed in this mode.
-10751	DAT INFO CANT ADD LOADER CLIENTS	Failed to add loader clients for extension: %1.
-10750	DAT INFO CANT ADD LOADER BECAUSE LACK OF FUNCTION	Failed to init loader extension: %1 due to lack of exported functions.
-10749	DAT INFO CANT READ LOADER CMD LINE	Failed to read loader parameter in %1 file for loader: %2.
-10748	DAT INFO CANT FIND LOADER IN HASH	Failed to find loader: %1 in the hash table.
-10747	DAT INFO FAILED TO ADD LOADER CLIENT DATA TO LOADER	Failed to add loader client: %1 data for loader: %2.
-10746	DAT INFO CANT GET THE LOADERS FOR LOADER CLIENT	Failed to get the loaders for loader client: %1.
-10745	DAT INFO NO LOADERS	There are no loaders although there are loader clients.
-10744	DAT INFO GETTING LOADER CLIENT WITHOUT LOADERS	Get a loader client without loaders.
-10743	DRIVER INFO LOADER CLIENT LIST	Load loader client: %1 of loader: %2.
-10742	DRIVER INFO EXTENSION LIST	Load mdrv extension: %1.
-10741	DRIVER INFO CANT FIND EXT IN DAT FILE	Can't find extension: %1 in file: %2.
-10740	DRV INITIALIZER FAILED TO INITIALIZE	Driver initialization failed, reason - %1.
-10739	DRV INITIALIZER FAILED TO EXIT	Driver exiting failed, reason - %1.
-10738	DRIVER INFO MISSING TMP DIR	Can't find temp directory on the machine. Add one or use the option "-out".
-10737	DRIVER INFO CANT READ EXT DLL ATTR	Driver extension entry not found for platform %1. "%2" attribute cannot be found in section "%3" in file %4 (default: %5).
-10736	DAT INFO NO DAT FILE	Data file %1 is not found.
-10735	DAT INFO FAILED TO OPEN DAT DIR	Failed to open %1 dat directory. Reason - %2.
-10734	DAT INFO FAILED TO ADD DAT TO CONFIG	Failed to add %1 to mdrv.dat config source.
-10733	DAT INFO DUPLICATED DAT SECTION	Duplicated section in data file %1.
-10732	DRIVER INFO FAIL CREATING NO POPUPS FILE	Failed to create no popups file %1.
-10731	DRIVER WARNING INVALID ARGUMENT	Invalid parameter detected in function.
-10700	VUSER INIT EXT	Vuser failed to initialize extension %1.
-10699	VUSER RUN ENGINE	Vuser failed to run.
-10698	VUSER EXIT ENGINE	Vuser failed to terminate.
-10697	VUSER EXIT EXT	Vuser failed to terminate extension.
-10696	VUSER THRAED STARTED OK	Vuser %1 (thread %2), started OK."
-10695	VUSER THRAED ENDED OK	Vuser %1 (thread %2), ended OK."
-10694	VUSER DLL REQUEST EXIT	Action was aborted.
-10693	VUSER CANT GET CFG FILE	Vuser failed to find .cfg file.
-10692	VUSER CANT ADD CFG ATTRIBS	Vuser failed to add .cfg attribs.
-10691	VUSER CANT SET THREAD PRIORITY	Cannot set Vuser thread priority to %1. System error: %2.
-10690	VUSER CFG TAKEN	New Vuser thread using CFG file %1.
-10689	VUSER COINIT TYPE	On a Vuser thread, COM was initialized with %1.
-10688	VUSER COUNINIT TYPE	On a Vuser thread, COM was uninitialized with %1.
-10687	VUSER ASYNC SELECT FAILED	Vuser failed to Async select on socket - System error: %1.
-10686	VUSER WAIT FAILED	Vuser wait failed, System error: %1.
-10685	VUSER WAIT FAILED UNKNOWN	Vuser wait failed, unknown error.
-10684	VUSER SELECT FAILED	Vuser select failed, system error: %1.
-10683	VUSER CANNOT CALL INIT ACTION	Failed to call Vuser initialization action.
-10682	VUSER CANNOT CALL RUN ACTIONS	Failed to call Vuser run actions.
-10681	VUSER CANNOT CALL END ACTION	Failed to call Vuser end action.
-10680	VUSER THREAD EXIT UNSUCCESSFULLY	Vuser %1 (thread %2) exited unsuccessfully.
-10679	VUSER SOME VUSER EXCEPTION	Caught Vuser %1 (thread %2) exception: %3. Terminate Vuser.
-10678	VUSER ON ERROR CONTINUES	Continuing after error in Vuser script.

Error code	Handle	Message\Additional information
-10677	VUSER_NO_ACTION_LOGIC	Action logic extension not used, entering event-driven mode.
-10676	VUSER_NO_INTERPRETER	No interpreter extension was found, cannot execute action %1.
-10675	VUSER_WAIT_EVENT_FAILED	Vuser failed to wait on internal event, System error: %1
-10674	VUSER_SAVE_CONFIG	Vuser configuration was saved into file %1 .
-10673	VUSER_WAIT_ON_SOCKET_FAILED	Vuser failed to wait on socket, Response error: %1
-10672	VUSER_WAIT_ON_MULTIPLE_FD_FAILED	Vuser failed to wait on multiple fd, Response error: %1
-10671	VUSER_WAIT_ON_EVENT_FAILED	Vuser failed to wait for event, Response error: %1
-10670	VUSER_WAIT_ON_MULTIPLE_EVENTS_FAILED	Vuser failed to wait for multiple events, Response error: %1
-10669	VUSER_ON_ERROR_SKIPS_TO_NEXT_ACTION	Skipping to the next action after error in Vuser script.
-10668	VUSER_ON_ERROR_SKIPS_TO_NEXT_ITERATION	Skipping to the next iteration after error in Vuser script.
-10667	VUSER_ON_ERROR_ENDS_VUSER	Ending the Vuser after error in Vuser script (Using automatic error handling options).
-10666	VUSER_ON_ERROR_CALLS_USER_DEFINED_HANDLER	Calling user-defined error handler after error in Vuser script.
-10665	VUSER_TOO_MANY_PARAMETERS	Too many parameters to action (% 1 Id > % 2 Id)
-10664	VUSER_ILLEGAL_ERRORHANDLER_RETURN_VALUE	The value %1, returned by user-defined error handler is illegal. Script aborted.
-10600	DRV_INIT_VU_STATIC	Vusers static initializer failed.
-10599	DRV_INIT_LOAD_ALLEXTDLL	Not all extension DLLs were loaded.
-10598	DRV_INIT_ALLEXTDLL	Cannot initialize extension %1.
-10597	DRV_EXIT_ALLEXT	Cannot terminate extension.
-10596	DRV_EXIT_ENGINE	Cannot terminate engine.
-10595	DRV_EXIT_VU_STATIC	Vusers static terminator failed.
-10594	DRV_LOAD_ENGINE	Engine %1 is not loaded.
-10593	DRV_LOAD_EXT	Extension %1 is not loaded.
-10592	DRV_DISPATCH_CREATE_THREAD	Failed to create Vuser thread. System error: %1.
-10591	DRV_DISPATCH_RESUME_THREAD	Failed to resume Vuser thread. System error: %1.
-10590	DRV_LOAD_ENGINE_OK	Engine %1 is loaded OK.
-10589	DRV_LOAD_EXT_OK	Extension %1 is loaded OK.
-10588	DRV_INIT_OM	Failed to initialize object monitor module.
-10587	DRV_EXIT_OM	Failed to terminate object monitor module.
-10586	DRV_THREAD_EXITED	Vuser %1 (thread %2) terminated, exit code is %3.
-10585	DRV_INIT_ALLOC_VU	Memory allocation failed.
-10584	DRV_DISPATCH_NO_MEMORY	Cannot start Vuser thread.
-10583	DRV_RPC_INIT	Failed to initialize RPC. Exiting.
-10582	DRV_RPC_SERVER_CREATION	Failed to create RPC service. Exiting.
-10581	DRV_RPC_SHUTDOWN	Shutdown RPC server failed.
-10580	DRV_INIT_HASH_TABLE	Cannot initiate Vuser hash table, exiting.
-10579	DRV_VUSER_THREAD_TERMINATED	Terminating Vuser %1 (thread %2).
-10578	DRV_CANT_TERMINATE_THREAD	Cannot terminate Vuser %1 (thread %2).
-10577	DRV_CANT_CREATE_CLNT	Cannot create RPC client.
-10576	DRV_CANT_CONTROL_CLNT_TO	Cannot set RPC client timeout.
-10575	DRV_CANT_CONTROL_CLNT_RTO	Cannot set RPC client retries timeout.
-10574	DRV_WRONG_MAGIC	Wrong magic !, not serving.
-10573	DRV_RPC_MSG_OLD	Agent RPC lost messages: %1...%2.
-10572	DRV_RPC_MSG_RETRY	Agent RPC retried message: %1.
-10571	DRV_RPC_MSG_LOST	Agent RPC old message arrived: %1 (not serving).
-10570	DRV_NO_MASTER_MONITOR	Failed to create parent monitoring thread. System error: %1.
-10569	DRV_VESRION_NOT_SUPPORTED	Driver version %1 is not supported.
-10568	DRV_BAD_HANDSHAKE	Failed to hand shake with the agent. Exiting.
-10567	DRV_IDENTIFY_BRIDGE	Cannot monitor parent process. Process is not identified. System error: %1.
-10566	DRV_MASTER_EXITED	Master exited. Exiting too.
-10565	DRV_RPC_ERR_STR	(RPC): %1.
-10564	DRV_CLNT_CALL_FAILED	Client RPC call failed (%1).
-10563	DRV_DISPATCH_BAD_CMDLINE	Cannot set Vuser command line %1.
-10562	DRV_DISPATCH_CANT_SET_CFG_ATTRIBS	Cannot set cfg file attributes.
-10561	DRV_DETECTED_EXT_WITHOUT_THREADS	The Vuser protocol or the current test settings do not support threads.
-10560	DRV_EXIT_BY_AGENT_READY_RT	Cannot run in multi-threaded mode. Driver exists.
-10559	DRV_CLIENT_CALL	Calling RPC client function %1
-10558	DRV_CLIENT_FUNC	Calling client function %1

Error code	Handle	Message\Additional information
-10557	DRV_SERVER_CALL	Driver function %1 was called by bridge (rpc call)
-10556	DRV_SERVER_FUNC	Driver server function %1 was called
-10555	DRV_COINIT_TYPE	On the main thread, COM was initialized with %1.
-10554	DRV_COUNINIT_TYPE	On the main thread, COM was uninitialized with %1.
-10553	DRV_INIT_COM_LIBRARY	Failed to load the COM library ole32.dll.
-10552	DRV_COM_INIT_NO_SYMBOL	Failed to get symbol %1 of COM library.
-10551	DRV_INIT_SPECIAL_EXT	Cannot initialize extension "%1" on the main thread.
-10550	DRV_FAILED_XDR_MSG	Failed to encode the message :"%1" .
-10549	DRV_FAILED_DRV_RUN	Failed to call drv_run(), reason - drv_init failed or was not be called on the current thread.
-10548	DRV_FAILED_TO_FORMAT_MESSAGE	Unable to format message id [%_1_id].
-10547	DRV_FAILED_MSG_LARGER_THAN_BUFFER	Message id [%_1_id] was not saved - Auto Log cache is too small to contain the message.
-10546	DRV_AUTO_LOG_OPEN_STACK_SEPERATOR_MSG_BETWEEN_ITERATIONS	Start auto log messages stack.
-10545	DRV_AUTO_LOG_OPEN_STACK_SEPERATOR_MSG_IN_ITERATION	Start auto log messages stack - Iteration %_1_id.
-10544	DRV_AUTO_LOG_CLOSE_STACK_SEPERATOR_MSG	End auto log messages stack.
-10543	DRV_EMPTY_LINE	\\r\\n
-10542	DRV_FUNCTION_FAILED	Call to function %1 failed.
-10500	EXT_DLL_NOT_LOAD	Extension %1 is not loaded. System error: %2
-10499	EXT_CONFIG_FUNC_NAME_NOT_FOUND	GetProcAddress of %2 failed for extension library %1. System error %3
-10498	EXT_CONFIG_FUNC_FAILED	Failed to configure extension library %1 (calling function %2).
-10497	EXT_ABORT_CLEAN	Clearing extension %1 by library request.
-10496	EXT_FREE_LIB_FAILED	FreeLibrary failed for extension %1. System error: %2
-10495	EXT_LOADLIB_EXCEPTION	Exception was raised while trying to load extension %1: %2
-10494	EXT_UNLOADLIB_EXCEPTION	Exception was raised while unloading extension %1: %2
-10493	EXT_CONFIGURE_EXCEPTION	Exception was raised when calling configure function %1 in extension %2: %3
-10492	EXT_PROCESS_INIT_EXCEPTION	Exception was raised when calling per-process-init function in extension %1: %2
-10491	EXT_PROCESS_TERMINAMTE_EXCEPTION	Exception was raised when calling per-process-terminate function in extension %1: %2
-10490	EXT_THREAD_INIT_EXCEPTION	Exception was raised when calling per-thread-init function in extension %1: %2
-10489	EXT_THREAD_TERMINATE_EXCEPTION	Exception was raised when calling per-thread-terminate function in extension %1: %2
-10488	EXT_ABORT_CLEAN_EXCEPTION	Exception was raised when calling abort-cleanup function in extension %1: %2
-10487	EXT_NOTIFY_VUSER_EXCEPTION	Exception was raised when calling event-notify Vuser function in extension %1: %2
-10486	EXT_GENERIC_EXCEPTION	Exception was raised when calling_notify-generic-message function in extension %1: %2
-10485	EXT_LIB_ERROR	Extension %3 reports error %1 on call to function %2
-10484	EXT_LIB_UNLOAD_BEFORE_LOAD	Extension %1 is not loaded.
-10483	EXT_THREAD_TERMINATE_FAILED	Function per-thread-terminate failed in extension %1.
-10482	EXT_THREAD_INIT_FAILED	Function per-thread-init failed in extension %1.
-10481	EXT_THREAD_CONTEXT_NOTIFY_EXCEPTION	Exception was raised when calling thread context notify function in extension %1: %2
-10480	EXT_THREAD_CONTEXT_EVENT_NOTIFY_EXCEPTION	Exception was raised when calling thread context event notify function in extension %1: %2
-10479	EXT_CHECK_MOFW	Connection failed. If the host is a monitor, make sure to select the "Enable Monitoring over Firewall" option
-10478	EXT_DLL_HIGHER_GLIBCPP_VERSION	Some features, like JavaScript Vuser, require a higher version of libstdc++ than installed on this system. Please upgrade your glibc version, or switch to a later version of this Linux distribution.
-10477	EXT_DLL_SILK_AGENT_NOT_INSTALLED	Could not load silk_ext.dll. Please check that you have Silk Agent installed and that Runtime is configured correctly on the running machine.
-10450	ACTION_LOGIC_EXT_FUNC_NOT_FOUND	Failed to find function %2 in extension %1, system error: %3.
-10449	ACTION_LOGIC_EXCEPTION	An exception was raised while calling %1 function in extension %2: %3.
-10448	ACTION_LOGIC_FUNC_FAILED	Action logic failure of function %1 in extension %2.
-10447	ACTION_LOGIC_ABORT_CALLED	Abort was called from an action.
-10400	INTERPRETER_EXT_FUNC_NOT_FOUND	Failed to find interpreter exec function in extension %1, system error: %2
-10399	INTERPRETER_EXT_EXCEPTION	An exception was raised while calling invocation function in interpreter extension %1: %2.
-10398	INTERP_MANAGER_EXT_FUNC_NOT_FOUND	Failed to find %1 function in extension %2, system error: %3
-10350	CUSTOM_CHANNEL_SERVER_ERROR	Communication error on server %1, %2:%3
-10349	CUSTOM_CHANNEL_CLIENT_ERROR	Communication error on client %1, %2:%3
-10348	CUSTOM_CHANNEL_CLIENT_DEBUG_MESSAGE	Client %1 posted:%2
-10347	CUSTOM_CHANNEL_SERVER_DEBUG_MESSAGE	Server %1 received:%2
-10346	CUSTOM_CHANNEL_CREATE_SERVER	Failed to create communication server %1.
-10345	CUSTOM_CHANNEL_CREATE_CLIENT	Failed to create communication client %1.
-10344	CHANNEL_SERVER_ERROR	Communication error: %1
-10343	CHANNEL_CLIENT_ERROR	Communication error: %1

Error code	Handle	Message\Additional information
-10300	WORKER_THREAD_INVALID_ARGUMENTS	Invalid argument was passed to create worker thread API.
-10299	WORKER_THREAD_FAILED_TO_CREATE_LL_SERVER_FOR_MAIN_THREAD	Failed to create link list server for main thread.
-10298	WORKER_THREAD_FAILED_TO_CREATE_LL_CLIENT_TO_WORKER_THREAD	Failed to create link list client for main thread.
-10297	WORKER_THREAD_FAILED_TO_GET_MAIN_THREAD_SERVERS_CS	Failed to get connection string from main thread server.
-10296	WORKER_THREAD_FAILED_TO_CREATE_WORKER_THREAD	Failed to create worker thread. System error - %1.
-10295	WORKER_THREAD_FAILED_TO_REGISTER_ON_WORKER_THREAD_MONITORING	Failed to register worker thread for monitoring.
-10294	WORKER_THREAD_FAILED_TO_RESUME_WORKER_THREAD	Failed to resume thread.
-10293	WORKER_THREAD_FAILED_TO_INITIALIZE_WORKER_THREAD	Failed to initialize worker thread. Exit with time out - % 1 Id
-10292	WORKER_THREAD_FAILED_TO_SHUT_DOWN_WORKER_THREAD	Failed to shut down worker thread. Forcing thread to terminate.
-10291	WORKER_THREAD_FAILED_TO_DESTROY_WORKER_THREAD	Failed to destroy worker thread. System error - %1.
-10290	WORKER_THREAD_FAILED_TO_CREATE_RESPONSE_OBJECT	Failed to create response object for worker thread.
-10289	WORKER_THREAD_FAILED_TO_INIT_CHANNEL_MODULE	Failed to initialize channel module in worker thread context.
-10288	WORKER_THREAD_FAILED_TO_CREATE_SERVER_FOR_WORKER_THREAD	Failed to create link list server for worker thread.
-10287	WORKER_THREAD_FAILED_TO_CREATE_CLIENT_FOR_WORKER_THREAD	Failed to create link list client for worker thread.
-10286	WORKER_THREAD_REPORT_ERROR	Worker thread report error through its channel.
-10285	WORKER_THREAD_SENDING_DOWN_MSG_TO_WORKER_THREAD	Sending Down Message to the worker thread.
-10284	WORKER_THREAD_TERMINATE_WORKER_THREAD	Worker Thread was forcibly terminated.
-10200	THREAD_CONTEXT_USE_CLIENT_ERROR	Thread Context: Failed to use service, reason - %1.
-10199	THREAD_CONTEXT_UNUSE_CLIENT_ERROR	Thread Context: Failed to unuse service, reason - %1.
-10198	THREAD_CONTEXT_POST_VIA_SERVICE_ERROR	Thread Context: Failed to post message via launcher service, reason - %1.
-10197	THREAD_CONTEXT_CREATE_CONTEXT_ERROR	Thread Context: Failed to create thread context, reason - %1.
-10196	THREAD_CONTEXT_XDR_ERROR	Thread Context: XDR failed %1 message.
-10195	THREAD_CONTEXT_REGISTER_CLIENT_ERROR	Thread Context: Failed to register client, reason - %1.
-10194	THREAD_CONTEXT_PROVIDE_SERVICE_ERROR	Thread Context: Failed to provide service, reason - %1.
-10193	THREAD_CONTEXT_SERVICE_SET	Thread Context: Service %1 with service name %2 was set.
-10192	THREAD_CONTEXT_UNPROVIDE_SERVICE_ERROR	Thread Context: Failed to unprovide service with service name "%1", reason - %2.
-10191	THREAD_CONTEXT_LISTEN_SERVICE_ERROR	Thread Context: Failed to listen service "%1", reason - %2.
-10190	THREAD_CONTEXT_UNLISTEN_SERVICE_ERROR	Thread Context: Failed to unlisten service "%1", reason - %2.
-10189	THREAD_CONTEXT_SUBSCRIBE_SERVICE_ERROR	Thread Context: Failed to subscribe service "%1", reason - %2.
-10188	THREAD_CONTEXT_UNSUBSCRIBE_SERVICE_ERROR	Thread Context: Failed to unsubscribe service "%1", reason - %2.
-10187	THREAD_CONTEXT_CALL_CB_ERROR	Thread Context: Failed to call service callback, reason - %1.
-10186	THREAD_CONTEXT_PUBLISH_SERVICE_ERROR	Thread Context: Failed to publish service "%1", reason - %2.
-10185	THREAD_CONTEXT_UNPUBLISH_SERVICE_ERROR	Thread Context: Failed to unpublish service "%1", reason - %2.
-10184	THREAD_CONTEXT_POST_PUBLISHED_SERVICE_ERROR	Thread Context: Failed to post published service, reason - %1.
-10183	THREAD_CONTEXT_REGISTER_ON_ATTRIB_ERROR	Thread Context: Failed to register on attribute "%1", reason - %2.
-10182	THREAD_CONTEXT_UNREGISTER_ON_ATTRIB_ERROR	Thread Context: Failed to unregister on attribute "%1", reason %2.
-10181	THREAD_CONTEXT_ON_ATTRIB_CHANGE_CB_ERROR	Thread Context: Cannot notify of attribute "%1" was changed, reason - %2.
-10180	THREAD_CONTEXT_NOTIFY_CLIENT_ERROR	Thread Context: Cannot send notification to client thread, reason - %1.
-10179	THREAD_CONTEXT_FAILED_NOTIFY_ON_MESSAGE	Thread Context: Cannot notify on message, reason - %1.
-10178	THREAD_CONTEXT_FAILED_REGISTER_ON_MESSAGES	Thread Context: Cannot register on descendant generic messages.
-10177	THREAD_CONTEXT_FAILED_TO_CALL_DRIVER_SERVICE	Thread Context: Call to service "%1" failed, reason - call to the current service doesn't allowed on this type of thread.
-10176	THREAD_CONTEXT_NOT_INITIALIZED	Thread Context: Call to service of the driver failed, reason - thread context wasn't initialized on this thread.
-10175	THREAD_CONTEXT_UNREGISTER_CLIENT_ERROR	Thread Context: Failed to unset thread context, reason - %1.
-10174	THREAD_CONTEXT_SET_REENTRANCE_ERROR	Thread Context: Cannot set main thread context twice (thread context for the current thread already exists).
-10173	THREAD_CONTEXT_MAIN_DOES_NOT_EXIST	Thread Context: Call to service of the driver failed, reason - main thread context does not exist.
-10172	THREAD_CONTEXT_UNSET_ON_MDRV_THREAD	Thread Context: Attempting to unset main thread context on the mdrv-based thread.
-10171	THREAD_CONTEXT_REACHED_MAX_NUMBER	Thread Context: Failed to set main thread context (group has reached max number of threads).
-10050	LOADER_EXT_FUNC_NOT_FOUND	Failed to find function %2 in extension %1, system error: %3.
-10049	LOADER_EXT_EXCEPTION	An exception was raised while calling %1 function in extension %2: %3.
-10048	LOADER_EXT_FUNC_FAILED	Loader extension failure of function %1 in extension %2.
-10047	LOADER_EXT_FAILED_TO_LOAD_CLIENT	Failed to load client %1.
mft_msg_res.h		
-51999	TRACING	%1 %2 %3 %4

Error code	Handle	Message\Additional information
-51998	MFT_ERR_XDR_FAILED_ENCODE	File Transfer: Failure in xdr encoding : %1.
-51997	MFT_ERR_XDR_FAILED_DECODE	File Transfer: Failure in xdr decoding : %1.
-51996	MFT_ERR_FAILED_TO_CREATE_P2P_CLIENT_HANDLE	File Transfer: Failed to create client for service %1.
-51995	MFT_ERR_FAILED_TO_CREATE_P2P_SERVER_HANDLE	File Transfer: Failed to create server for service %1.
-51994	MFT_ERR_UNKNOWN_TYPE_VALUE	File Transfer: Unknown value % 1 Id for type %2.
-51993	MFT_ERR_FAILED_TO_POST_MSG	File Transfer: Failed to post message from %1 returned % 2 Id
-51992	MFT_ERR_REQUEST_FOR_FILE_THAT_DOESNT_EXIST	File Transfer: Request for %1, but the file or directory does not exist.
-51991	MFT_ERR_MEM_ALLOC_FAILURE	File Transfer: Unable to allocate memory.
-51990	MFT_ERR_THREAD_CREATION	File Transfer: Failed to create worker thread.
-51989	MFT_ERR_THREAD_CREATION_TIMEOUT	File Transfer: Timeout while creating worker thread. No response from thread for % 1 Id miliseconds.
-51988	MFT_ERR_NO_NETDIR	File Transfer: The attribute netdir_path has not been passed to the mft_server.
-51987	MFT_ERR_NO_SENDER_MONIKER	File Transfer: Failed to retrieve sender moniker in %1.
-51986	MFT_ERR_LRBR_SVC_INSTANCE_NOT_FOUND	File Transfer: CLrBrSvc instance not found for moniker %1.
-51985	MFT_ERR_FAILED_TO_OPEN_FILE	File Transfer: Failed to open file %1.
-51984	MFT_ERR_FAILED_TO_OPEN_DIR	File Transfer: Failed to open directory %1.
-51983	MFT_ERR_FAILED_TO_OPEN_DIR_FOR_COMPRESSION	File Transfer: Failed to open directory %1 for compression.
-51982	MFT_ERR_FAILED_TO_READ_FILE	File Transfer: Error in reading file %1.
-51981	MFT_ERR_FAILED_TO_READ_FILE_AT_OFFSET	File Transfer: Failed to read file %1 at offset % 2 Id.
-51980	MFT_ERR_FAILED_TO_READ_DIR_COMPRESSION_STREAM	File Transfer: Error in reading directory %1 compression stream. rc = % 2 Id.
-51979	MFT_ERR_FAILED_TO_WRITE_FILE	File Transfer: Error in writing file %1.
-51978	MFT_ERR_FAILED_TO_WRITE_DIR_COMPRESSION_STREAM	File Transfer: Error in writing directory %1 compression stream. rc = % 2 Id.
-51977	MFT_ERR_FAILED_TO_CREATE_DIR	File Transfer: Error in making directory %1. rc = % 2 Id.
-51976	MFT_ERR_FAILED_TO_CREATE_FILE	File Transfer error: Cannot create file %1. Reason : %2.
-51975	MFT_ERR_FAILED_TO_CREATE_FILE_REASON_TOO_LONG_PATH	File Transfer: Cannot create the %1 file on the load generator machine. The file name may include illegal characters or the path's string length may exceed the maximum allowed size of 260 characters.
-51974	MFT_ERR_NO_DISKSPACE	File Transfer error: There is no more disk space on %1 at %2.
-51973	MFT_ERR_NO_DISKSPACE_CONTROLLERSIDE	File Transfer error: There is no more disk space on the Controller machine at %1
-51972	MFT_ERR_DELETE_DRIVE	File Transfer: Deletion of drive is not permitted %1.
-51971	MFT_ERR_INVALID_DRIVE_NAME	File Transfer: Bad drive name %1.
-51970	MFT_ERR_SECURITY_NETDIR_NOT_SAFE	File Transfer: You are running under secure mode and netdir %1 is not safe.
-51969	MFT_ERR_FAILED_TO_CREATE_DIR_REASON_TOO_LONG_PATH	File Transfer: Cannot create the directory on the load generator machine since the path's string length exceeds the maximum allowed size of 260 characters, %1.
-51968	MFT_ERR_FAILED_OPEN_FILE_REASON_TOO_LONG_PATH	File Transfer: Failed to open file since the path's string length exceeds the maximum allowed size of 260 characters, %1.
mft_tests_res.h		
-52999	MFT_TESTS_FAILED_INIT_INIFILE	MFT Tests failed to load initialization file %1.
-52998	MFT_TESTS_FAILED_NUM_TESTS	MFT Tests: Missing number of tests in the NumberOfTests field.
-52997	MFT_TESTS_FAILED_HOST_NAME	MFT Tests: Missing host name in the RemoteHost field.
-52996	MFT_TESTS_FAILED_TO_INITIALISE_HOST	MFT Tests failed to initialize remote host %1.
-52995	MFT_TESTS_MLROOT_UNDEFINED	MFT Tests: Please define an M_LROOT environment variable.
mil_config_res.h		
-94800	MIL_CONFIG_ERR_CANT_WRITE_TO_FILE	Could not write to file %1. System error: %2To use a different path, set the environment variable %3 to the new file path, and run again.
-94799	MIL_CONFIG_AGENT_CONFIG_TITLE	MI Listener Configuration
mms_msg.h		
mms_res.h		
-235999	MMS_FUNCTION_SUCCESSFUL	%1 was successful.
-235998	MMS_ERR_EMPTY_ARGUMENT_MESSAGE	Message name is empty.
-235997	MMS_ERR_EMPTY_ARGUMENT_USERNAME	User name is empty.
-235996	MMS_ERR_EMPTY_ARGUMENT_PASSWORD	Password value is empty.

Error code	Handle	Message\Additional information
-235995	MMS_ERR_EMPTY_ARGUMENT_TRANSID	Transaction ID was not specified.
-235994	MMS_ERR_EMPTY_ARGUMENT_MP	Multipart name is empty.
-235993	MMS_ERR_EMPTY_ARGUMENT_HEADER	Header name is empty.
-235992	MMS_ERR_EMPTY_ARGUMENT_FILE	File name is empty.
-235991	MMS_ERR_EMPTY_ARGUMENT_RECIPIENT	Recipient address is empty.
-235990	MMS_ERR_EMPTY_ARGUMENT_URL	Message URL is empty.
-235989	MMS_ERR_EMPTY_ARGUMENT_DATA	Multipart data is empty.
-235988	MMS_ERR_INVALID_RECIPIENT	Recipient data is invalid: %1.
-235987	MMS_ERR_INVALID_ARG_FORMAT	Invalid argument format: %1. Required format is <header name>=<header value>.
-235986	MMS_ERR_INVALID_HEADER	Specified header is invalid.
-235985	MMS_ERR_INVALID_HEADER_VALUE	Header value is invalid: %1=%2.
-235984	MMS_ERR_FAIL_GET_HEADER	Failed to retrieve value of header '%1'. Reason: %2.
-235983	MMS_ERR_FAIL_ADD_MPS	Failed to add multipart: '%1' to message '%2'.
-235982	MMS_ERR_FAIL_ADD_MP	Failed to add multipart: '%1'.
-235981	MMS_ERR_FAIL_CREATE_MSG	Failed to create message '%1'. Reason: %2.
-235980	MMS_ERR_FAIL_DECODE	Failed to decode the message '%1'. Reason: %2.
-235979	MMS_ERR_FAIL_ENCODE	Failed to encode the message '%1'. Reason: %2.
-235978	MMS_ERR_FAIL_ADD_HEADER	Failed to add header: %1=%2.
-235977	MMS_ERR_FAIL_ADD_HEADERS	Failed to add message headers.
-235976	MMS_ERR_FAIL_ADD_RCPT	Failed to add recipient: %1.
-235975	MMS_ERR_FAIL_ADD_RCPTS	Failed to add message recipients.
-235974	MMS_ERR_FAIL_GENERATE_MESSAGE	Failed to generate MMS Message.
-235973	MMS_ERR_FAIL_CREATE_MP	Failed to create multipart, reason: %1.
-235972	MMS_ERR_FAIL_GET_MP	Failed to get multipart, reason: %1.
-235971	MMS_ERR_FAIL_GET_MP_HEADER	Failed to get multipart header. Reason: %1.
-235970	MMS_ERR_FAIL_GET_MP_COUNT	Failed to get multipart count. Reason: %1.
-235969	MMS_ERR_FAIL_SEND_MESSAGE	Failed to send MMS message. Reason: %1.
-235968	MMS_ERR_FAIL_RETRIEVE_MESSAGE	Failed to retrieve MMS message. Reason: %1.
-235967	MMS_ERR_FAIL_GET_CONFIRMATION	Failed to get confirmation message buffer.
-235966	MMS_ERR_MSG_NOT_FOUND	Message '%1' was not found.
-235965	MMS_ERR_MSG	Error in Message '%1'.
-235964	MMS_ERR_WAP_CONNECT	Failed to create WAP connection.
-235963	MMS_ERR_MSG_SERIALIZE	Message serialization failed. Reason: %1.
-235962	MMS_ERR_GET_MPS	Error in getting message '%1' multipart.
-235961	MMS_ERR_GET_MP	Error in getting multipart index %1 from message '%2'.
-235960	MMS_ERR_MP_NOT_FOUND	Warning: Multipart '%1' was not found. Skipping.
-235959	MMS_ERR_FILE_NOT_FOUND	File '%1' was not found.
-235958	MMS_ERR_RETRIEVE	Message could not be retrieved from URL: %1.
-235957	MMS_ERR_NOT_SUPPORTED_CONTENT_TYPE	Content-Type header is not supported.
-235956	MMS_ERR_HEADER_NOT_EXIST	Header %1 does not exist.
-235955	MMS_ERR_NOT_VALID_MESSAGE_TYPE	Message type is invalid for this operation
-235954	MMS_ERR_DECODE_CONF_FAILED	Failed to decode confirmation message. Reason: %1.
-235953	MMS_ERR_MP_SMIL_AND_IMAGE	Unable to add an image when SMIL is used. To add the image, include it in the SMIL file.
-235952	MMS_ERR_BIND	Failed to bind SMPP connection to user: %1.
-235951	MMS_ERR_INSTALL_LICENSE	Failed to install license. Reason: %1
-235950	MMS_ERR_TIMEOUT	Timeout received.
-235949	MMS_ERR_TIMEOUT_SMPP_CON	Timeout received on connecting to SMPP server.
-235948	MMS_ERR_TIMEOUT_SMPP_BIND	Timeout received on binding to SMPP server.
-235947	MMS_ERR_TIMEOUT_SMPP_DISCON	Timeout received on disconnecting from SMPP server.
-235946	MMS_ERR_SMPP_CON_EXIST	An active SMPP connection already exists.
-235945	MMS_ERR_SMPP_VALID_CON	SMPP error: there is no valid connection.
-235944	MMS_ERR_SOCKET	Socket error: %1.
-235943	MMS_ERR_SET_TIMEOUT	Failed to set timeout.
-235942	MMS_WRN_MESSAGE_REPLACE	Warning: Message '%1' will be replaced. Continuing.
-235941	MMS_WRN_MP_REPLACE	Warning: Multipart '%1' will be replaced. Continuing.
-235940	MMS_WRN_HEADER_REPLACE	Warning: Header '%1' will be replaced. Continuing.
-235939	MMS_WRN_WAP_DISCONNECT	Warning: failed to close WAP connection.

Error code	Handle	Message\Additional information
-235938	MMS WRN REPORT_ALLOWED	Unspecified value for 'Report Allowed'. Will be set to FALSE. Continuing.
-235937	MMS NTF NOTIFICATION_RECEIVED_INCOMPLETE	MMS Notification for recipient '%1' recieved and incomplete. Waiting for next chunk of data.
-235936	MMS ERR NOTIFICATION_DECODE_FAILED	MMS Notification decode failed for recipient '%1'. Reason %2.
-235935	MMS NTF BIND_DIFFERENT_USER	Binding SMPP connection to user: %1.
monitors_res.h		
-40999	TRACING	%1 %2 %3 %4
-40998	TRACERT_MSGS_PER_THREAD_FUNCTION_FAILED	Failed to initialize traceroute server.
-40997	TRACERT_FAILED_TO_GET_OUT_DIR	Failed to get out dir from command line.Need -out option.
-40996	TRACERT_FAILED_TO_OPEN_DEBUG_FILE	Unable to open debug file %1.
-40995	TRACERT_CREATE_SERVER_FAILURE	Failed to create a traceroute channel server.
-40994	TRACERT_CREATE_WEBTRACE_SERVER_FAILURE	Failed to create a webtrace server.
-40993	TRACERT_FAILED_TO_DECODE_MSG	Failed to decode message from client.
-40992	TRACERT_FAILED_TO_LOAD_TRACEROUTE_LIBRARY	Failed to load traceroute library %1 %2.
-40991	TRACERT_LOAD_LIBRARY_EXCEPTION	An exception was raised while attempting to load the dynamic library %1.
-40990	TRACERT_FAILED_TO_LOAD_LIBRARY_FUNC	Failed to load dynamic library %1 %2.
-40989	TRACERT_INTERNAL_VECTOR_NOT_READY	A new traceroute message has been received, but the internal data container is not ready.
-40988	TRACERT_SEND_RESULTS_FAILURE	An error occurred in the traceroute extension sending results to the transaction server.
-40987	TRACERT_GETHOSTBYNAME_FAILURE	A problem occurred resolving the destination address.
-40986	TRACERT_SERVER_FAILED_TO_GET_IP_NUMBER	Failed to change the IP string %1 to an IP net number using the function 'inet_addr'.
-40985	TRACERT_FAILED_TO_STARTUP_WS	Failed to initialize winsocket by the function 'WSAStartup'.
-40984	TRACERT_FAILED_TO_ADD_QUEUE	Failed to add client request to queue.
-40983	TRACERT_CREATE_REQUESTS_QUEUE_FAILURE	Failed to create queue for clients requests.
-40982	TRACERT_FAILED_TO_ADD_RESOURCE_FILE	Failed to add resource file %1.
-40981	TRACERT_WEBTRACE_ERROR	Webtrace error: Conduct's webtrace returned error code: % 1 _ld.
-40980	TRACERT_CREATE_HT_FAILURE	Failed to create a hash table for loop requests.
-40979	TRACERT_HASH_TABLE_ADD_FAILURE	Failed to add item to hash table.
-40978	TRACERT_STOP_LOOP_FAILED	Failed to stop traceroute loop request for destination: %1. Destination was not found in hash table.
-40977	TRACERT_DEST_EXISTS_FAILURE	TraceRoute Server cannot receive two loop-requests to the same destination: %1.
-40976	TRACERT_GET_TIMER_FAILURE	Failed to find timer handle for traceroute loop request to destination %1.
-40975	TRACERT_LAUNCH_WEBTRACE_FAILURE	Failed to launch process merc_webtrace.exe.
-40974	TRACERT_CREATE_SOCKET_FAILURE	Failed to create webtrace socket.
-40973	TRACERT_CONNECT_SOCKET_FAILURE	Failed to connect to webtrace socket.
-40972	TRACERT_REGISTER_SOCKET_FAILURE	Failed to register responsive select on webtrace socket.
-40971	TRACERT_REQUEST_NOT_FOUND	Request not found in hash table.
-40970	TRACERT_REGISTER_TIMER_FAILURE	Failed to register timer for traceroute loop request to destination %1.
-40969	TRACERT_UNREGISTER_TIMER_FAILURE	Failed to unregister timer for traceroute loop request to destination %1.
-40968	TRACERT_TIMER_HANDLE_NOT_FOUND	Failed to find timer for traceroute loop request to destination %1.
-40967	TRACERT_SET_INTERPROC_FAILURE	An error has occurred when setting interprocess temporary file full path.
-40966	TRACERT_INTERPROC_FAILURE	Failed to enter to interprocess critical section.
-40965	TRACERT_RESPONSIVE_SELECT_FAILURE	Responsive select error has occurred while waiting for disconnection acknowledgement from Conduct's webtrace.
-40964	TRACERT_RECV_FAILED	Function recv failed when trying to read data from socket.
-40963	TRACERT_SEND_FAILED	Function send failed when trying to write data on socket.
-40962	TRACERT_DISCONNECTION_ACKNOWLEDGEMENT_FAILURE	Failed to receive disconnection acknowledgement from conduct_webtrace (timeout elapsed).
-40961	TRACERT_FORMAT_REQUEST_FAILED	Failed to format traceroute request message.
-40960	TRACERT_UNFORMAT_REPLY_FAILED	Failed to unformat traceroute reply message.
-40959	TRACERT_RESPONSIVE_WAIT_FAILURE	Function DrvResponsiveWait failed.
-40958	TRACERT_FAILED_TO_REACH_DESTINATION	Failed to reach destination %1.
-40957	TRACERT_CREATE_CLIENT_FAILURE	Failed to create a traceroute channel client.
-40956	TRACERT_FAILED_TO_SEND_NOTIFICATION	Failed to send notification message to traceroute client.
-40955	TRACERT_RELOAD_WEBTRACE_FAILURE	Traceroute Server error: Failed to reload merc_webtrace.
-40954	TRACERT_RELOAD_WEBTRACE_NOTIFY	Traceroute Server: merc_webtrce process has shut down. Reloading... Note: the original order of the traceroute requests may have been changed.
-40953	TRACERT_SEND_REQUEST_ERROR	Traceroute Server error: Failed to send request with ID % 1 _ld.
-40899	MW_CREATE_WEBTRACE_SERVER_ERROR	MercWebtrace failed to initialize Webtrace driver.
-40898	MW_SEND_PROBE_ERROR	MercWebtrace failed to send request. (Function webtrace_send_probe_ex failed).

Error code	Handle	Message\Additional information
-40897	MW_UNFORMAT_REQUEST_ERROR	MercWebtrace failed to unformat request.
-40896	MW_FORMAT_REPLY_ERROR	MercWebtrace failed to format reply.
-40895	MW_RESOLVE_DESTINATION_IP_ERROR	MercWebtrace failed to resolve destination IP.
-40894	MW_SEND_REPLY_ERROR	MercWebtrace failed to send reply.
-40893	MW_COULD_NOT_OPEN_SOCKET	MercWebtrace failed to open socket. Please verify that the merc_webtrace process has root permissions.
-40892	MW_SEND_PROBE_WHILE_WEBTRACE_FAILURE_ERROR	MercWebtrace failed to initialize Webtrace driver, and therefore the probe sending failed.
-40799	TRACERT_HL_INITIALIZATION_ERROR	Network Delay Monitor (Webtrace): Failed to initialize on source machine: %1. All requests from this machine will fail. (Internal error code: % 2 _ld).
-40798	TRACERT_HL_INIT_WEBTRACE_ERROR	Network Delay Monitor (Webtrace): Failed to initialize Webtrace driver on source machine: %1 for TCP protocol. Please note that all future TCP requests for this source machine will fail. (Internal error code: % 2 _ld).
-40797	TRACERT_HL_REQUEST_ERROR	Network Delay Monitor (Webtrace): Request from source machine %1 to destination %3 failed. (Internal error code: % 2 _ld).
-40796	TRACERT_HL_REQUEST_FAILURE_DUE_TO_INIT_WT_ERROR	Network Delay Monitor (Webtrace): TCP request from source machine %1 to destination %3 failed. Reason: Failed to initialize Webtrace driver. (Internal error code: % 2 _ld).
-40795	TRACERT_HL_FAILED_TO_OPEN_SOCKET	Network Delay Monitor failed to open a socket on source machine: %1. Please verify that the merc_webtrace executable has root permissions.\n\n(For more details refer to the Network Delay Monitor section in the readme).
mosifs_msg.h		
33554433	OS_RET_CODE_OK	Ok.
33554434	OS_RET_CODE_ERROR	Unrecognizable error.
33554435	OS_RET_CODE_NOT_EXIT	No such file or directory.
33554436	OS_RET_CODE_PARAM_ILLEGAL	Illegal parameter.
33554437	OS_RET_CODE_BAD_DRIVE	Invalid drive name.
33554438	OS_RET_CODE_DELETE_FAIL	Delete operation failed.
33554439	OS_RET_CODE_OPEN_FAIL	Open operation failed.
33554440	OS_RET_CODE_WRITE_ERR	Write error.
33554441	OS_RET_CODE_INVALID_NAME	Invalid Name.
33554442	OS_RET_CODE_CREATE_FAILED	Create operation failed.
33554443	OS_RET_CODE_DEL_DRIVE	Could not delete a drive!
33554444	OS_RET_CODE_COPY_SHARED_FILE	Copy file failed. File is in use by another process.
33554445	OS_RET_CODE_MOVE_FAIL	File move operation failed.
33554446	OS_RET_CODE_NO_PERMISSION	Insufficient permission to perform the operation.
33554447	OS_RET_CODE_WRITE_PERMISSION	No write permission.
33554448	OS_RET_CODE_READ_PERMISSION	No read permission.
33554449	OS_RET_CODE_NULL_PARAM	Error: NULL parameters.
33554450	OS_RET_CODE_DST_SRC_EXIST	Destination directory or file exists.
33554451	OS_RET_CODE_DST_SRC_NOT_EXIST	Source directory or file does not exist.
33554452	OS_RET_CODE_NO_SPACE	No space left on device.
33554453	OS_RET_CODE_DIFFERENT_DEVICE	Operation on different devices.
33554454	OS_RET_CODE_MALLOC_FAIL	Memory allocation failed
33554455	OS_RET_CODE_INVALID_ENCODED_METHOOD	Invalid encoding method used.
33554456	OS_RET_CODE_NO_STR_FILE	Cannot find strings file.
33554457	OS_RET_CODE_OPEN_STR_FILE_FAIL	Cannot open strings file.
33554458	OS_RET_CODE_READ_STR_FILE_FAIL	Cannot read strings file.
33554459	OS_RET_CODE_MALLOC_STR_FILE_FAIL	Cannot allocate memory for strings array.
33554460	OS_RET_CODE_STR_TRUNCATED	String truncated.
33554461	OS_RET_CODE_FAILED_IN_DETECTION	Cannot detect encoding method.
33554462	OS_RET_CODE_EUC_OR_SJIS	Encoding method is either EUC or SJIS.
33554463	OS_RET_CODE_MSG_FILE_TOO_BIG	Strings file is too big.
33554464	OS_RET_CODE_CORRUPTED_REQUESTED_FILE	The input message file format is invalid.
33554465	OS_RET_CODE_FAILED_IN_ENCODED	The conversion operation failed.
33554466	IDS_WINEXEC_OUT_OF_MEM	System was out of memory, or the executable file was corrupt.
33554467	IDS_WINEXEC_FILE_NOT_FOUND	The executable, or one of its components was not found.
33554468	IDS_WINEXEC_PATH_NOT_FOUND	Path was not found.
33554469	IDS_WINEXEC_PROTECTION	Sharing or network-protection error, or a dynamic link to a task.
33554470	IDS_WINEXEC_SEP_DATA_SEG	Library required separate data segments for each task.
33554471	IDS_WINEXEC_INSUFFICIENT_MEM	There was insufficient memory to start the application.

Error code	Handle	Message\Additional information
33554472	IDS_WINEXEC_WINVER_INCORRECT	Windows version was incorrect.
33554473	IDS_WINEXEC_EXECUTABLE_INVALID	Executable file was invalid.
33554474	IDS_WINEXEC_OS_MISMATCH	Application was designed for a different operating system.
33554475	IDS_WINEXEC_MSDOS4	Application was designed for MS-DOS 4.0.
33554476	IDS_WINEXEC_UNKNOWN_TYPE	Type of executable file was unknown.
33554477	IDS_WINEXEC_REAL_MODE	Attempt was made to load a real-mode application.
33554478	IDS_WINEXEC_SECOND_INSTANCE	A previous instance of this program is already running.
33554479	IDS_WINEXEC_COMPRESSED	Cannot load a compressed executable file.
33554480	IDS_WINEXEC_CORRUPT	One of the DLLs required to run this application was corrupt.
33554481	IDS_WINEXEC_32BIT	Application requires Microsoft Windows 32-bit extensions.
33554482	IDS_WINEXEC_OTHER	WinExec() error %1
33554483	IDS_WINEXEC_LONG_COMMANDLINE	Command line to WinExec is too long.
33554484	IDS_WINEXEC_EMPTY_COMMAND	Empty command line for WinExec.
33554485	IDS_SE_ERR_ASSOCINCOMPLETE	The file name association is incomplete or invalid.
33554486	IDS_SE_ERR_DDEBUSY	The DDE transaction could not be completed because other DDE transactions were being processed.
33554487	IDS_SE_ERR_DDEFAIL	The DDE transaction failed.
33554488	IDS_SE_ERR_DDETIMEOUT	The DDE transaction could not be completed because the request timed out.
33554489	IDS_SE_ERR_NOASSOC	There is no application associated with the given filename extension.
33554490	IDS_SE_ERR_SHARE	A sharing violation occurred.
33554491	OS_RET_CODE_STRING_FILE_IS_TOO_LONG	The requested message file name is too long.
33554492	OS_RET_CODE_OVERLAP_BASES	Corrupted message file. The #BASE lines in the message file overlap.
33554493	OS_RET_CODE_BAD_EYECAT	Invalid pointer.
33554494	OS_RET_CODE_INTERR_BASE_GROUP	Corrupted base group structure.
33554495	OS_RET_CODE_INVALID_MESSAGE_FILE_VERSION	Wrong message file version.
33554496	OS_RET_CODE_MESSAGE_ID_NOT_FOUND	Cannot find message string for the given message id.
33554497	OS_RET_CODE_UNINSUFFICIENT_PARAMS	The requested parameter number exceeds the limit.
33554498	OS_RET_CODE_UNSUPPORTED_LANG	Message file in the requested language is not supported.
33554499	OS_RET_CODE_LINE_TRUNCATED	Corrupted message file. A message line has been truncated.
33554500	OS_RET_CODE_MISSING_EQUALS_SIGN	Corrupted message file an equal sign is missing.
33554501	OS_RET_CODE_INVALID_BASE	Corrupted message file. Invalid #BASE line.
33554502	OS_RET_CODE_INVALID_CONTROL_LINE	Corrupted message file. Invalid control line.
33554503	OS_RET_CODE_INTERR_INVALID_PARAM	Invalid parameter.
33554504	OS_RET_CODE_UNSUPPORTED_OPTION	Unsupported option.
33554505	OS_RET_CODE_MESSAGE_ID_MISMATCH	Mismatch in requested message id name.
33554506	OS_RET_CODE_FILE_IS_NOT_EXIST	The requested file does not exist.
33554507	OS_RET_CODE_IDENTIFIER_LENGTH	Error: identifier too long
33554508	OS_RET_CODE_IDENTIFIER_CHAR	Invalid identifier character: identifier character must be alphanumeric or underscore.
33554509	OS_RET_CODE_IDENTIFIER_FIRST_CHAR	Invalid identifier: first character must be a letter or underscore.
33554510	OS_RET_CODE_OUT_OF_PARAM_RANGE	Corrupted error string, one of the parameters in out of max param range.
33554511	OS_RET_CODE_MSG_NOT_SET	Message not set by os_format_msg. Call customer service.
33554512	OS_RET_CODE_INVALID_VALUE	Invalid value.
33554513	OS_RET_CODE_VALUE_TOO_LARGE	Value too large.
33554514	OS_RET_CODE_PARAM_TOO_LONG	A parameter is too long.
33554515	OS_RET_CODE_TOO_MANY_PARAMS	Too many parameters in the command line.
33554516	OS_RET_CODE_INVALID_QUOTE	Unmatched quotation marks.
33554517	OS_RET_CODE_UNSUPPORTED_PARAM_TYPE	Unsupported parameter type.
33554518	OS_RET_CODE_BUFFER_IS_TOO_SHORT	The buffer is too short to hold the data.
33554519	OS_REGISTRY_VALUE_NOT_FOUND	The value was not found in the registry.
33554520	OS_REGISTRY_KEY_NOT_FOUND	The key was not found in the registry.
33554521	OS_REGISTRY_NO_SET_PERMISSION	This user does not have set permissions for this key in the registry.
mqtt_monitor_msgs.h		
-47800	MQTT_CUSTOM_CATEGORRY	Custom
-47799	MQTT_HOST_IS_EMPTY	Host name is empty.
-47798	MQTT_NO_SYS_TOPICS	Host %1, Error: Failed to get \$SYS topics or \$SYS topic is not published.
-47797	MQTT_FAILED_DECRYPT_SETTINGS	Host %1, Error: Failed to decrypt connection settings.

Error code	Handle	Message\Additional information
-47796	MQTT_FAILED_PARSE_SETTINGS	Host %1, Error: Failed to parse connection settings.
-47795	MQTT_FAILED_CONN_CREATION	Host %1, Error: Failed to create connection.
-47794	MQTT_DETAILS_CONN_CREATION	Host %1, Error: Failed to create connection, Details:%2.
-47793	MQTT_FAILED_DISCONN_CREATION	Host %1, Error: Failed to disconnect.
-47792	MQTT_DETAILS_DISCONN_CREATION	Host %1, Error: Failed to disconnect, Details:%2.
-47791	MQTT_FAILED_TO_SUBSCRIBE	Host %1, Error: Failed to subscribe topic:%2.
-47790	MQTT_DETAILS_TO_SUBSCRIBE	Host %1, Error: Failed to subscribe topic:%2,, Details:%3.
-47789	MQTT_FAILED_TO_UNSUBSCRIBE	Host %1, Error: Failed to unsubscribe topic:%2.
-47788	MQTT_DETAILS_TO_UNSUBSCRIBE	Host %1, Error: Failed to unsubscribe topic:%2, Details:%3
-47787	MQTT_FAILED_TO_MESSAGE	Host %1, Error: Failed to retrieve incoming message.
-47786	MQTT_DETAILS_TO_MESSAGE	Host %1, Error: Failed to retrieve incoming message, Details:%2.
-47785	MQTT_FAILED_TO_FETCH	Host %1, Error: Failed to fetch incoming message.
-47784	MQTT_DETAILS_TO_FETCH	Host %1, Error: Failed to fetch incoming message, Details:%2.
-47783	MQTT_TOPIC_NOT_FOUND	Host %1, Error: Topic not found or no longer available:%2.
msg_viewer_res.h		
-92900	MV_NULL_ARG	Argument %2 was passed to function %1 as NULL.
-92899	MV_TOO_MANY_CLIENTS	Too many clients to load. Could not load client %1.
mshunra_res.h		
-77999	MSHUNRA_MSG_GENERIC	1.00%
-77998	MSHUNRA_FAILED_CREATE_PROVIDE_SERVICE	Failed to create a service provider for the OpenText Network Virtualization extension.
-77997	MSHUNRA_FAILED_DECODE_MSG	The OpenText Network Virtualization extension failed to decode a message.
-77996	MSHUNRA_UNKNOWN_MSG_ARRIVED	The OpenText Network Virtualization extension received an unknown message.
-77995	MSHUNRA_ALREADY_ACTIVE	Could not start Network Virtualization. The required resources are being used by another application.
-77994	MSHUNRA_FAILED_STOP	Could not stop Network Virtualization. OpenText NV returned the following error: %1.
-77993	MSHUNRA_FAILED_PLAY	Could not start Network Virtualization. OpenText NV returned the following error: %1.
-77992	MSHUNRA_FAILED_CANCEL	Could not cancel NV report generation. OpenText NV returned the following error: %1.
-77991	MSHUNRA_FAILED_START_REPORT_GEN	Could not start NV report generation. Error: %1.
-77990	MSHUNRA_FAILED_TO_PLAY_DRIVER_NOT_INSTALLED	Could not start Network Virtualization. OpenText NV for OpenText Load Generator version 12.50 or higher should be installed on the machine.
-77989	MSHUNRA_FAILED_TO_STOP_DRIVER_NOT_INSTALLED	Could not stop Network Virtualization. OpenText NV for OpenText Load Generator version 12.50 or higher should be installed on the machine.
-77988	MSHUNRA_PLAY_IGNORED	Network Virtualization is already running.
-77987	MSHUNRA_PLAY_SUCCESS	Network Virtualization has started successfully.
-77986	MSHUNRA_STOP_SUCCESS	Network Virtualization has stopped successfully.
-77985	MSHUNRA_ALREADY_PLAYED	Network Virtualization is already running on this machine.
-77984	MSHUNRA_STOP_WITHOUT_PLAY_ERR	Could not stop Network Virtualization that has not started.
-77983	MSHUNRA_UNKNOWN_ERR	Internal OpenText Network Virtualization module error: % 1 Id.
-77982	MSHUNRA_INIT_ERR	Could not initialize the OpenText Network Virtualization extension.
-77981	MSHUNRA_VED_INIT_ERR	Could not not initialize Network Virtualization. OpenText NV returned the following error: %1
-77980	MSHUNRA_SUPPORT_ERR	The Network Virtualization client is not installed on this machine.
-77979	MSHUNRA_EVENT_HANDLER_FAILED	Could not create the Network Virtualization event handler.
-77978	MSHUNRA_EVENT_REGISTRATION_FAILED	Could not register the Network Virtualization client event.
-77977	MSHUNRA_EVENT_STOP	The Network Virtualization client was stopped. OpenText NV returned the following error: %1
-77976	MSHUNRA_EXCLUDE_IP_ERR	Encountered a problem with an excluded IP.
-77975	MSHUNRA_EXCLUDE_IP_RESOLVE_HOST_ERR	Could not resolve the host name IP: %1
-77974	MSHUNRA_FAILED_TO_PLAY_FAILED_TO_GET_SERVICE_PORT	Could not Start Network Virtualization. Failure to get service port generated error message: %1
-77973	MSHUNRA_EVENT_START	Network Virtualization has failed to start. OpenText NV returned the following error: "%1"
-77972	MSHUNRA_INPUT_FILE_PATH_ERROR	Illegal input file path: %1
-77971	MSHUNRA_OPEN_FILE_ERROR	Failed to open vuser run result path: %1
-77970	MSHUNRA_FAILED_TO_CREATE_NV_RESULT_FOLDER	Failed to create NV report result folder: %1
-77969	MSHUNRA_START_NV_REPORT_GEN	Start NV report generation for group: %1
-77968	MSHUNRA_FAILED_TO_GENERATE_REPORT	Failed to generated NV report for group: %1. Error: %2
-77967	MSHUNRA_COMMUNICATION_WITH_NV_FAILED	Failed to communicate with NV.
-77966	MSHUNRA_FAILED_TO_ADD_ACE	Failed to add read/write privilege to vusers' result folders: %1

Error code	Handle	Message\Additional information
mw_gate_msg.h		
-73999	MW_GATE_INITIALIZE_ERROR	MercWebtrace Gate error: Failed to initialize. (Internal error code: % 1 Id).
-73998	MW_GATE_RECEIVE_REQUEST_ERROR	MercWebtrace Gate error: Failed to receive request from TraceRoute Server. (Internal error code: % 1 Id).
-73997	MW_GATE_TRS_NOT_RESPONDING_ERROR	MercWebtrace Gate error: traceroute server with ID % 1 Id is not responding.
-73996	MW_GATE_SENT_REPLY_TO_TRS_ERROR	MercWebtrace Gate error: Failed to send Webtrace reply to TraceRoute Server. (Internal error code: % 1 Id).
-73995	MW_GATE_SENT_PROGRESS_TO_TRS_ERROR	MercWebtrace Gate error: Failed to send Webtrace progress to TraceRoute Server. (Internal error code: % 1 Id).
-73994	MW_GATE_TRS_IMPROPER_SHUTDOWN_ERROR	MercWebtrace Gate error: traceroute server with ID % 1 Id shut down improperly.
-73899	MW_GATE_UNEXPECTED_2WAY_NOTIFICATION_ERROR	MercWebtrace Gate error: Unexpected 2-Way Comm notification received: % 1 Id.
-73898	MW_GATE_LOAD_RES_FILE_ERROR	MercWebtrace Gate error: Failed to load resource file.
-73897	MW_GATE_CREATE_ACCEPTOR_ERROR	MercWebtrace Gate error: Failed to create an acceptor.
-73896	MW_GATE_CREATE_HASH_ERROR	MercWebtrace Gate error: Failed to create a hash table.
-73895	MW_GATE_INITIALIZED_DEBUG	MercWebtrace Gate debug: initialized successfully.
-73894	MW_GATE_EXITING_DEBUG	MercWebtrace Gate debug: Exiting.
-73893	MW_GATE_SENT_REQUEST_TO_WEBTRACE_DEBUG	MercWebtrace Gate debug: Sent request to Webtrace for TraceRoute Server with ID % 1 Id.
-73892	MW_GATE_SENT_REQUEST_TO_WEBTRACE_ERROR	MercWebtrace Gate error: Failed to send request to Webtrace for TraceRoute Server with ID % 1 Id. Function 'webtrace_mdrv_trace' failed with error % 2 Id.
-73891	MW_GATE_SENT_MSG_TO_TRS_DEBUG	MercWebtrace Gate debug: Sent Webtrace message to TraceRoute Server with ID % 1 Id.
-73890	MW_GATE_ACCEPTED_NEW_TRS_DEBUG	MercWebtrace Gate debug: Accepted new TraceRoute Server with ID % 1 Id.
-73889	MW_GATE_TRS_DISCONNECTED_DEBUG	MercWebtrace Gate debug: TraceRoute Server with ID % 1 Id disconnected.
-73888	MW_GATE_ABORTING_DEBUG	obsolete
-73887	MW_GATE_INIT_WEBTRACE_ERROR	MercWebtrace Gate error: Failed to initialize Webtrace.
-73886	MW_GATE_XDR_ENCODE_ERROR	MercWebtrace Gate error: XDR encoding failure.
-73885	MW_GATE_XDR_DECODE_ERROR	MercWebtrace Gate error: Failed to decode Webtrace request. Function 'xdr_decode' failed with error % 1 Id.
-73884	MW_GATE_TLS_NOT_FOUND_ERROR	MercWebtrace Gate error: Failed to find MercWebtrace Gate object in TLS.
-73883	MW_GATE_FAILED_TO_FIND_POST_HANDLE_ERROR	MercWebtrace Gate error: Failed to find post handle for TraceRoute Server with id % 1 Id.
-73882	MW_GATE_POST_2WAY_MSG_ERROR	MercWebtrace Gate error: Failed to post a 2-Way Comm message.
netmon_client_msg.h		
-41999	TRACERT_CLIENT_INITIALIZE_ERROR	Traceroute client error: Failed to initialize. (Internal error code: % 1 Id).
-41998	TRACERT_CLIENT_INIT_DEBUG	Traceroute client debug: Initialized successfully.
-41997	TRACERT_CLIENT_END_DEBUG	Traceroute client debug: exiting.
-41996	TRACERT_CLIENT_SINGLE_REQUEST_ERROR	Traceroute client error: Failed to start a single request to destination %1. (Internal error code: % 2 Id).
-41995	TRACERT_CLIENT_START_LOOP_REQUEST_ERROR	Traceroute client error: Failed to start a loop request to destination %1. (Internal error code: % 2 Id).
-41994	TRACERT_CLIENT_STOP_LOOP_REQUEST_ERROR	Traceroute client error: Failed to stop a loop request to destination %1. (Internal error code: % 2 Id).
-41993	TRACERT_CLIENT_RECV_MSG_ERROR	Traceroute client error: Failed to receive a notification message from traceroute server. (Internal error code: % 1 Id).
-41992	TRACERT_CLIENT_RECEIVED_SINGLE_REQUEST_DEBUG	Traceroute client debug: Received a single request to destination %1.
-41991	TRACERT_CLIENT_RECEIVED_START_LOOP_REQUEST_DEBUG	Traceroute client debug: Received a start-loop request to destination %1.
-41990	TRACERT_CLIENT_RECEIVED_STOP_LOOP_REQUEST_DEBUG	Traceroute client debug: Received a stop-loop request.
-41989	TRACERT_CLIENT_LR_START_TRACEROTUE_ERROR	Traceroute client error: Function lr_start_traceroute() failed to destination %1. (Internal error code: % 2 Id).
-41988	TRACERT_CLIENT_LR_STOP_TRACEROTUE_ERROR	Traceroute client error: Function lr_stop_traceroute() failed to destination %1. (Internal error code: % 2 Id).
-41987	TRACERT_CLIENT_RECEIVED_LR_START_TRACEROUTE_REQUEST_DEBUG	Traceroute client debug: Received lr_start_traceroute request to destination %1.
-41986	TRACERT_CLIENT_RECEIVED_LR_STOP_TRACEROUTE_REQUEST_DEBUG	Traceroute client debug: Received lr_stop_traceroute request to destination %1.
-41899	TRACERT_CLIENT_TLS_NOT_FOUND_ERROR	Traceroute client error: Failed to find Traceroute client handle in TLS.
-41898	TRACERT_CLIENT_OPEN_HASH_ERROR	Traceroute client error: Failed to open hash table.
-41897	TRACERT_CLIENT_LOAD_RES_FILE_ERROR	Traceroute client error: Failed to load resource file.
-41896	TRACERT_CLIENT_OPEN_P2P_SERVER_ERROR	Traceroute client error: Failed to open a p2p server.
-41895	TRACERT_CLIENT_OPEN_P2P_CLIENT_ERROR	Traceroute client error: Failed to open a p2p client to server with moniker %1.
-41894	TRACERT_CLIENT_XDR_ENCODE_ERROR	Traceroute client error: XDR encoding failure.
-41893	TRACERT_CLIENT_XDR_DECODE_ERROR	Traceroute client error: XDR decoding failure.
-41892	TRACERT_CLIENT_POST_P2P_MSG_ERROR	Traceroute client error: Failed to post a p2p message to TraceRoute Server.
-41891	TRACERT_CLIENT_GET_SERVER_INFO_ERROR	Traceroute client error: Failed to get server info.
-41890	TRACERT_CLIENT_CREATE_REQUESTS_CONTAINER_ERROR	Traceroute client error: Failed to create requests container.
-41889	TRACERT_CLIENT_CREATE_SERVER_INFO_ERROR	Traceroute client error: Failed to create a server info object for Traceroute server with moniker %1.

Error code	Handle	Message\Additional information
-41888	TRACERT CLIENT SENT START REQUEST TO TRS DEBUG	Traceroute client debug: Sent start request to Traceroute server. Request ID: % 1 Id.
-41887	TRACERT CLIENT SENT END REQUEST TO TRS DEBUG	Traceroute client debug: Sent end request to Traceroute server. Request ID: % 1 Id.
-41886	TRACERT CLIENT HASH NOT FOUND IN TLS ERROR	Traceroute client error: Failed to find destinations hash table in TLS.
-41885	TRACERT CLIENT ALREADY HAS REQUEST ERROR	Traceroute client error: Already handling a request to destination %1.
-41884	TRACERT CLIENT START LOOP TRACEROUTE ERROR	Traceroute client error: API function start_loop_traceroute() failed.
-41883	TRACERT CLIENT FIND REQUEST BY DESTINATION ERROR	Traceroute client error: Failed to find request to destination %1 in destinations hash table.
-41882	TRACERT CLIENT FIND REQUEST BY ID ERROR	Traceroute client error: Failed to find request with ID % 1 Id in requests container.
-41881	TRACERT CLIENT STOP LOOP TRACEROUTE ERROR	Traceroute client error: API function stop_loop_traceroute() failed.
-41880	TRACERT CLIENT ADD TO HASH ERROR	Traceroute client error: Failed to add request to hash table.
-41879	TRACERT CLIENT RECEIVED PROGRESS DEBUG	Traceroute client debug: Received progress % 1 Id for request with ID % 2 Id.
netmon_server_msg.h		
-72999	TRACERT SERVER INITIALIZE ERROR	Traceroute server error: Failed to initialize. (Internal error code: % 1 Id).
-72998	TRACERT SERVER MW ACCEPTOR DOWN ERROR	Traceroute server error: Process merc_webtrace is down. Aborting...
-72997	TRACERT SERVER MW NOT RESPONDING ERROR	Traceroute server error: Process merc_webtrace is not responding. Aborting...
-72996	TRACERT SERVER LAUNCH STATUS ERROR	obsolete
-72995	TRACERT SERVER RECEIVE REQUEST ERROR	Traceroute server error: Failed to receive request from TraceRoute Client. (Internal error code: % 1 Id).
-72994	TRACERT SERVER RECEIVE WEBTRACE MSG_ERROR	Traceroute server error: Failed to receive message from merc_webtrace. (Internal error code: % 1 Id).
-72899	TRACERT SERVER XDR ENCODE ERROR	Traceroute server error: XDR encoding failure.
-72898	TRACERT SERVER XDR DECODE ERROR	Traceroute server error: XDR decoding failure.
-72897	TRACERT SERVER UNEXPECTED 2WAY NOTIFICATION ERROR	Traceroute server error: Unexpected 2-Way Comm notification received from merc_webtrace: % 1 Id.
-72896	TRACERT SERVER LOAD RES FILE ERROR	Traceroute server error: Failed to load resource file.
-72895	TRACERT SERVER OPEN P2P CLIENT ERROR	Traceroute server error: Failed to open a p2p client.
-72894	TRACERT SERVER OPEN P2P SERVER ERROR	Traceroute server error: Failed to open a p2p server.
-72893	TRACERT SERVER OPEN HASH ERROR	Traceroute server error: Failed to open a hash table.
-72892	TRACERT SERVER CREATE CONNECTOR ERROR	Traceroute server error: Failed to create a connector to MercWebtrace. Connection sting: %1.
-72891	TRACERT SERVER GET POST HANDLE ERROR	Traceroute server error: Failed to get connector's post handle.
-72890	TRACERT SERVER INITIALIZED DEBUG	Traceroute server debug: initialized successfully.
-72889	TRACERT SERVER CREATE REQUEST CONTAINER ERROR	Traceroute server error: Failed to create a request container.
-72888	TRACERT SERVER LAUNCH STATUS READY	obsolete
-72887	TRACERT SERVER LAUNCH MERC WEBTRACE ERROR	obsolete
-72886	TRACERT SERVER EXITING DEBUG	Traceroute server debug: Exiting.
-72885	TRACERT SERVER POST 2WAY MSG ERROR	Traceroute server error: Failed to post a 2-Way Comm message.
-72884	TRACERT SERVER SEND LOOP AFTER TIMER ERROR	Traceroute server error: Failed to resend a Webtrace loop request after timeout.
-72883	TRACERT SERVER RECEIVED START REQUEST DEBUG	Traceroute server debug: Received a new request of type % 1 Id with ID % 2 Id.
-72882	TRACERT SERVER RECEIVED STOP LOOP REQUEST DEBUG	Traceroute server debug: Received a stop-loop request with ID % 1 Id.
-72881	TRACERT SERVER FIND REQUEST ERROR	Traceroute server error: Failed to find request with ID % 1 Id.
-72880	TRACERT SERVER POST P2P MSG ERROR	Traceroute server error: Failed to post a p2p message.
-72879	TRACERT SERVER SEND REPLY TO TRASCACCT ERROR	Traceroute server error: Failed to send reply to Transaction Server (function TraceRoute_Arrived returned: % 1 Id). Request ID: % 2 Id.
-72878	TRACERT SERVER SEND REPLY TO TRASCACCT DEBUG	Traceroute server debug: Sent reply to Transaction Server. Request ID: % 1 Id.
-72877	TRACERT SERVER REQUEST NOT FOUND ERROR	Traceroute server error: Failed to find request with ID % 1 Id.
-72876	TRACERT SERVER RECEIVED WEBTRACE REPLY DEBUG	Traceroute server debug: Received Webtrace reply for request with ID % 1 Id.
-72875	TRACERT SERVER GET SOURCE NAME ERROR	obsolete
-72874	TRACERT SERVER GET SOURCE IP ERROR	obsolete
-72873	TRACERT SERVER UNEXPECTED WEBTRACE MSG_ERROR	Traceroute server error: Received an unexpected Webtrace message.
-72872	TRACERT SERVER CREATE REQUEST ERROR	Traceroute server error: Failed to create a request object.
nv_report_ext_msg.h		
-206100	NVEXT DEBUG PRINT POST	Post '%1' to '%2'.
-206099	NVEXT DEBUG PRINT RESPONSE	Reponse from '%1': %2
-206098	NVEXT WARN NULL TRANSACTION	Null transaction data received %1.
-206097	NVEXT ERROR UNKNOWN EXCEPTION	Unknown exception %1.
-206096	NVEXT ERROR STANDARD EXCEPTION	Standard exception '%1'.
-206095	NVEXT ERROR JSON PARSE EXCEPTION	Json parse exception '%1'.
-206094	NVEXT ERROR FAIL TO POST	Failed to post to '%1', retcode=% 2 Id.

Error code	Handle	Message\Additional information
-206093	NVEXT_ERROR_FAIL_TO_PARSE_JSON	Failed to parse json format response from '%1'.
-206092	NVEXT_ERROR_FAIL_TO_START_EMULATION	Failed to start NV emulation. Perhaps the NV server is not working, and therefore a NV report will not be generated.
-206091	NVEXT_ERROR_FAIL_TO_GET_EMULATION_HANDLE	Failed to get NV emulation handle.
-206090	NVEXT_ERROR_EMULATION_NOT_STARTED	NV Emulation not started.
-206089	NVEXT_ERROR_FAIL_TO_CONN_TRANS_MANAGER	Failed to connect to NV transaction manager.
-206088	NVEXT_ERROR_NOT_CONN_TRANS_MANAGER	Not connected to NV transaction manager.
-206087	NVEXT_ERROR_FAIL_TO_GET_SESSION_ID	Failed to get session identifiers from NV transaction manager.
-206086	NVEXT_ERROR_EMPTY_TRANS_NAME	The transaction name is empty or not equal.
-206085	NVEXT_WARN_ILLEGLE_CHAR_FOUND	Transaction name '%1' is illegal, will replaced with '%2'. Characters '%3' are not supported by NV.
-206084	NVEXT_ERROR_FAIL_TO_START_TRANS	Failed to start transaction '%1' on NV transaction manager.
-206083	NVEXT_ERROR_FAIL_TO_GET_TRANS_ID	Failed to get transaction identifiers for '%1' from NV transaction manager. Reason: '%2'.
-206082	NVEXT_ERROR_TRANS_NOT_STARTED	The transaction '%1' is not started on NV transaction manager.
-206081	NVEXT_ERROR_FAIL_TO_STOP_TRANS	Failed to stop transaction '%1' on NV transaction manager. Reason: '%2'.
-206080	NVEXT_ERROR_FAIL_TO_DISCONN_TRANS_MANAGER	Failed to disconnect from NV transaction manager.
-206079	NVEXT_ERROR_FAIL_TO_STOP_EMULATION	Failed to stop NV emulation.
-206078	NVEXT_ERROR_FAIL_TO_GET_RESOURCE_LOC	Failed to get analysis resources location.
-206077	NVEXT_NOTIFY_RESOURCE_LOC	The location of analysis resources from NV is '%1'.
-206076	NVEXT_ERROR_FAIL_TO_PARSE_RESPONSE	Failed to parse response from '%1', '%2'.
-206075	NVEXT_ERROR_EMPTY_TRANSACTION_DATA	Null transaction parameter received in "%1".
-206074	NVEXT_ERROR_DUPLICATE_TRANSACTION_NAME	Duplicate transaction name: "%1". A transaction with the same name has already started, and has not yet ended.
-206073	NVEXT_WARN_RESERVED_CHAR_IN_TX_NAME	Transaction "%1" contains a special character in position %_2_id. This character is reserved for use by NV. Change to an alphabetic or number character to define a unique transaction name.
-206072	NVEXT_WARN_FAILED_GET_NV_PORT	Failed to get NV port.
-206071	NVEXT_ERROR_VUSER_RUN_RESULT_NOT_FOUND	Could not find vuser run result file '%1'.
-206070	NVEXT_ERROR_HAR_GENERATOR_NOT_FOUND	HARGenerator.exe is not found from '%1'.
-206069	NVEXT_ERROR_FAILED_GENERATE_HAR_WITH_EXCEPTION	Exception thrown when calling HARGenerator.exe.
-206068	NVEXT_WARN_NO_HAR_GENEARTED	HAR file is not generated. Vuser run result may not contain any HTTP transactions.
-206067	NVEXT_ERROR_FAILED_TO_SAVE_METADATA	Failed to save metadata to file '%1'.
-206066	NVEXT_NOTIFY_HAR_GEN_EXIT	HARGenerator.exe exits with '%1'.
-206065	NVEXT_ERROR_FAILED_GENERATE_NV_REPORT_INVALID_INPUT	Failed to generate NV report for input files are invalid.
-206064	NVEXT_ERROR_FAILED_GENERATE_NV_REPORT	Failed to generate NV report for '%1'.
-206063	NVEXT_ERROR_FAILED_TO_SAVE_REPORT	Failed to save NV report to file '%1'.
-206062	NVEXT_DEBUG_PRINT_HARGEN_CMD	Command line used to generate HAR file: '%1'.
-206061	NVEXT_ERROR_FAILED_TO_PARSE_METADATA_FILE	Failed to parse ScriptUploadMetadata.xml. Error '%1'.
-206060	NVEXT_ERROR_ILLEGLE_TRANSACTION_NAME	NV only support the ASCII characters, your transaction name does not meet the rule.
oranca_res.h		
-24999	ORANCA_MSG_E_GENERAL_ERROR	%1General error occurred.%2
-24998	ORANCA_MSG_E_NOT_DISPLAYED	%1Window or object is not displayed.%2
-24997	ORANCA_MSG_E_DISABLED	%1Window or object is disabled%2
-24996	ORANCA_MSG_E_IMPROPER_CLASS	%1Object class cannot perform this operation.%2
-24995	ORANCA_MSG_E_ITEM_NOT_FOUND	%1Item in list or menu not found.%2
-24994	ORANCA_MSG_E_OUT_OF_RANGE	%1Object position is out of range.%2
-24993	ORANCA_MSG_E_ATTR_NOT_SUPPORTED	%1The selected attribute is not supported for this function.%2
-24992	ORANCA_MSG_E_ILLEGAL_OPERATION	%1Operation invalid for object.%2
-24991	ORANCA_MSG_E_DOUBLE_CONNECT	nca_connect_server: cannot establish a new connection without closing the old one!
-24990	ORANCA_MSG_E_SOCKET	nca_connect_server: cannot create tcp-ip socket.
-24989	ORANCA_MSG_E_CONNECT	nca_connect_server: cannot connect to host %1 on port %2
-24988	ORANCA_MSG_E_COMMUNICATE	nca_connect_server: cannot communicate with host %1 on port %2
-24987	ORANCA_MSG_E_INVISIBLE	%1Window or object is not visible%2
-24986	ORANCA_MSG_E_DBTRACE_TRY	Try enable DB trace...
-24985	ORANCA_MSG_E_DBTRACE_FAIL	An error occured trying enable DB trace
-24984	ORANCA_MSG_E_DBTRACE_SUCCEED	DB trace enabled
-24983	ORANCA_MSG_E_TPROC_LAUNCH	Tproc launch failed. Replay will continue
-24982	ORANCA_MSG_E_BROWSER_LAUNCH	Online Browsing launch failed, please check your setting at cfg file section [NCAOnlineBrowser]. Replay will continue
-24981	ORANCA_MSG_E_ONLINE_CFG	Wrong data at cfg file section [NCAOnlineBrowser], BROWSER=\\\"%s\\\", RELATIVE_URL=\\\"%s\\\". Replay will continue

Error code	Handle	Message\Additional information
-24980	ORANCA_MSG_E_NCA_BAD_PARAMETER	Bad parameter is given to function: %1
otlp_ext_msg.h		
-237999	OTLPTEXT_NOTIFY_LOADED	OTLP extension loaded.
-237998	OTLPTEXT_NOTIFY_OTLP_ENABLED	User %1 enabled otlp exporter.
-237997	OTLPTEXT_WARNING_NULL_TRANSACTION_DATA	Null transaction parameter received in "%1".
-237996	OTLPTEXT_NOTIFY_OTLP_TRANSACTION_START	OTLP Transaction: "%1" started.
-237995	OTLPTEXT_NOTIFY_OTLP_TRANSACTION_END	OTLP Transaction: "%1" ended.
-237994	OTLPTEXT_NOTIFY_OTLP_REPORT_TRACEPARENT	OTLP Transaction: "%1" with TraceParent: "%2".
parm_msg.h		
-13999	PRM_ENGINE_CANNOT_INIT	Cannot initialize parameter engine.
-13998	PRM_ENGINE_FAILED_TO_CREATE_PARAM	Failed to create a new parameter of type '%1'.
-13997	PRM_ENGINE_FAILED_TO_FORMAT_VALUE	Parameter '%1': Failed to format a new value. The format string is '%2'.
-13996	PRM_ENGINE_FAILED_TO_FIND_DLL_NAME	Failed to find dll name for parameter type '%1'. Type '%2' will not be supported.
-13995	PRM_ENGINE_FAILED_TO_LOAD_DLL	Failed to load dll '%1'. Error is: %3. Type '%2' will not be supported.
-13994	PRM_ENGINE_FAILED_TO_REGISTER_DLL_FUNC	Failed to register functions for parameter type '%1'.
-13993	PRM_ENGINE_TYPE_NOT_FOUND_IN_PARAM_SECTION	No type entry for parameter section '%1'. Parameter not added.
-13992	PRM_ENGINE_SUBSTITUTE_LOG	Parameter Substitution: parameter "%1" = "%2"
-13991	PRM_ENGINE_RESTRICTED_DATA_TYPE	Parameter "%1" is a restricted data type. Cannot substitute.
-13990	PRM_ENGINE_MALLOC_FAILED	malloc failed
-13989	PRM_ENGINE_ALLOCATED_STRING_TOO_SHORT	Allocated string too short
-13988	PRM_ENGINE_TABLE_DOES_NOT_EXIST	The table '%1' doesn't exist.
-13987	PRM_ENGINE_IS_NOT_PARAM	The string '%1' with parameter delimiters is not a parameter.
-13986	PRM_ENGINE_CREATE_FAILED	Creating of parameter '%1' failed ,aborting....
-13985	PRM_ENGINE_CANNOT_OPEN_PRM_FILE	Cannot open prm file: %1.
-13984	PRM_ENGINE_TYPE_NOT_SUPPORTED	Parameter type %1 not supported in this platform.
-13983	PRM_ENGINE_WRONG_PRIORITY	Parameter type %1 is not loaded in priority %2.
-13982	PRM_ENGINE_CREATE_PARAM_CONTEXT_FAILED	Creating context of parameter '%1' failed.
-13981	PRM_ENGINE_NUM_LINES_OF_DATA_NOT_FOUND_IN_PARAM_SECTION	No number lines of data entry for parameter '%1'. Context of this parameter was not set.
-13980	PRM_ENGINE_CANNOT_FIND_CURRENT_ROW	Cannot find current row of parameter '%1'. Context of parameter '%2' was not set.
-13979	PRM_ENGINE_PARAM_SCOPE_NOT_FOUND	The parameter with scope '%1' is not found.
-13978	PRM_ENGINE_PARAM_HAS_NO_VALUE	The parameter %1 has no value.
-13977	PRM_ENGINE_FORMATTED_BUF_OUT_OF_LIMIT	Parameter '%1': Failed to format a new value. The format string is '%2'. The length of the formatted buffer is limited to %3 ld bytes.
-13976	PRM_ENGINE_NOT_PARAM_REPLACED_WITH_EMPTY_STRING	The string '%1' with parameter delimiters is not a parameter and replaced by empty string.
-13900	PRM_TABLE_CANNOT_CALC_TABLE_PATH	Parameter '%1': Cannot calculate the actual path for table '%2'.
-13899	PRM_TABLE_CANNOT_OPEN_TABLE	Parameter '%1': Cannot open table '%2'.
-13898	PRM_TABLE_INVALID_RANGE	Parameter '%1': Invalid range '%2' for table '%3'. Ignoring.
-13897	PRM_TABLE_INVALID_COLUMN_NAME	Parameter '%1': Invalid column name '%2' for table '%3'.
-13896	PRM_TABLE_UNIQUE_WARP	Parameter '%1': No more unique values for this parameter in table '%2' [unique range is %3-%4].The parameter continues with last value of the range according to "When Out Of Values" policy.
-13895	PRM_TABLE_SAME_LINE_AS_CIRCLE	Parameter '%1': Unable to resolve the next parameter value. When you select next row using the "same line as" option, at least one parameter must use the Unique, Random, or Sequential option.
-13894	PRM_TABLE_SAME_LINE_AS_ERROR	Parameter '%1': Cannot find the line number from which to take the next value. This parameter is defined to use the same line as parameter '%2'.
-13893	PRM_TABLE_INVALID_SELECT_NEXT_ROW_METHOD	Parameter '%1': Invalid select next row method [internal method number %2].
-13892	PRM_TABLE_NO_DELIMITER	Parameter '%1': No delimiter was found for table '%2'.
-13891	PRM_TABLE_NO_START_LINE	Parameter '%1': No start line was found for table '%2'.
-13890	PRM_TABLE_NO_TABLE_FOUND	Parameter '%1': No table was defined for this parameter.
-13889	PRM_TABLE_NOT_EXISTS	The table '%1' does not exist.
-13888	PRM_TABLE_CANNOT_REPLACE_WITH_NEW_VALUE	Parameter '%1': Cannot replace the parameter with a value from table '%2' [column=%3, row=%4].
-13887	PRM_TABLE_PATH_TRANSLATION_FAILED	The translation of the path to table '%1' failed.
-13886	PRM_TABLE_NETDIR_PASSED_AS_NULL	Parameter '%1': The netdir value passed when looking for table '%2' was NULL.
-13885	PRM_TABLE_SETTING_PATH_FOR_TABLE	Calculating path for table '%1'.
-13884	PRM_TABLE_TABLENAME_IS_ABSOLUTE_PATH	Table '%1' is entered as absolute path.

Error code	Handle	Message\Additional information
-13883	PRM_TABLE_LOCATION	Location of table '%1' is '%2'.
-13882	PRM_TABLE_LOOKING_IN_NETDIR	Table '%1' is located in netdir '%2'.
-13881	PRM_TABLE_NETDIR_TABLE_LOCATION	Table full path in netdir is '%1'.
-13880	PRM_TABLE_DTABLE_CANNOT_OPEN_TABLE	Table '%1' cannot be opened. Error code is '%2'.
-13879	PRM_GLOBAL_DIRECTORY	Global data directory is '%1'.
-13878	PRM_LOCAL_DIRECTORY	Local directory is '%1'.
-13877	PRM_TABLE_GEN_NEW_VAL	Getting new value for parameter '%1': table = '%2' column = '%3' row = '%4'.
-13876	PRM_TABLE_SELECT_NEXT_ROW	Next row for parameter %1 = %2 [table = %3].
-13875	PRM_TABLE_UNIQUE_RANGE	Unique range for parameter %1 is '%2 - %3' [table = %4].
-13874	PRM_MESSAGE_FROM_DTABLE	1%
-13873	PRM_INTERPROC_ERROR	1%
-13872	PRM_EMPTY_TABLE_PATH	Table path for %1 is empty.
-13871	PRM_TABLE_UNIQUE_OUTOFRANGE_CYCLIC	Parameter '%1': No more unique values for this parameter in table '%2' [unique range is %3-%4]. The parameter continue to beginning of range in a cyclic manner according to "When Out Of Values" policy.
-13870	PRM_TABLE_UNIQUE_OUTOFRANGE_ABORT	Parameter '%1': No more unique values for this parameter in table '%2' [unique range is %3-%4]. The Vuser is aborted according to "When Out Of Values" policy.
-13869	PRM_TABLE_NO_ROWS_IN_INSTANCE	Parameter '%1': No number of rows in instance was found for table '%2'.
-13868	PRM_TABLE_NO_COLUMN_LIST	Parameter '%1': No column index list was found for table '%2'.
-13867	PRM_TABLE_NO_ROW_DELIMITER	Parameter '%1': No row delimiter was found for table '%2'.
-13800	PRM_VARIABLE_PARAMETER_NOT_INIT	Parameter '%1': Parameter is not initialized.
-13799	PRM_VARIABLE_PARAMETER_NOT_VALID	Parameter '%1': Parameter value is not valid.
-13798	PRM_VARIABLE_SAVING_PARAMETER	Saving Parameter "%1 = %2".
-13797	PRM_VARIABLE_FREEING_PARAMETER	Freeing Parameter '%1'.
-13796	PRM_TYPE_NOT_DYNAMIC	Parameter '%1': Cannot free parameters defined in Parameter List.
-13795	PRM_VARIABLE_PARAMETER_NOT_FOUND	Parameter '%1' either not created or already released.
-13750	PRM_LR_CONST_ATTRIBUTE_IS_NULL	Parameter '%1': The %2 attribute from the driver is NULL.
-13700	PRM_UNIQUE_BLOCK_SIZE_ZERO	Parameter '%1': Illegal value - Block size is 0.
-13699	PRM_UNIQUE_USED_ALL_VALUES_IN_BLOCK	Parameter '%1': All values in unique block already used. Block size is %2. The parameter continues with last value of the range according to "When Out Of Values" policy.
-13698	PRM_UNIQUE_USED_ALL_VALUES_IN_BLOCK_CYCLIC	Parameter '%1': All values in unique block already used. Block size is %2. The parameter continue to beginning of range in a cyclic manner according to "When Out Of Values" policy.
-13697	PRM_UNIQUE_USED_ALL_VALUES_IN_BLOCK_ABORT	Parameter '%1': All values in unique block already used. Block size is %2. The Vuser is aborted according to "When Out Of Values" policy.
-13650	PRM_USERFUNCTION_FAILED_TO_COMPUTE	Parameter '%1': Failed to compute value of function '%2' in library '%3'
-13649	PRM_USERFUNCTION_SCRIPT_FAILED_TO_COMPUTE	Parameter '%1': Failed to compute value of function '%2' in the script.
-13600	PRM_DATE_TIME_WORKING_DAYS_BAD_FORMAT	Incorrect format specified for working or non-working days.
-13599	PRM_DATE_TIME_NO_WORKING_DAYS_IN_WEEK	No working days in week.
-13598	PRM_DATE_TIME_WORKING_DAYS	Specified working days are: % 1 ld % 2 ld % 3 ld % 4 ld % 5 ld % 6 ld % 7 ld.
-13597	PRM_DATE_TIME_OFFSET_IS_NOT_WHOLE_NUMBER_OF_DAYS	Invalid offset in parameter '%1'. The offset must be a whole number of days.
-13596	PRM_DATE_TIME_GENERATION_ERROR	System error while generating date/time parameter %1.
pcoip_res.h		
-221999	PCOIP_MSG_E_INTERNAL	Internal Error: %1
-221998	PCOIP_MSG_E_OUT_OF_TIME	Operation exceeded timeout: %1
-221997	PCOIP_MSG_E_ILLEGAL_PARAMETER	An illegal parameter was passed to this function: %1
-221996	PCOIP_MSG_E_ALREADY_CONNECTED	Already connected: %1
-221995	PCOIP_MSG_E_NOT_CONNECTED	Not connected: %1
-221994	PCOIP_MSG_E_ALREADY_DISCONNECTED	Already disconnected: %1
-221993	PCOIP_MSG_INVALID_VUSERID	Invalid VUser ID value: "%1". %2
-221992	PCOIP_MSG_CANNOT_GET_VUSER_OUTDIR	Cannot get output directory of the Virtual User
-221991	PCOIP_MSG_CANNOT_GET_SCRIPTNAME	Cannot get script name
-221990	PCOIP_MSG_CANNOT_ALLOCATE_VUSER	Cannot allocate VUser % 1 ld: %2
-221989	PCOIP_MSG_CANNOT_GET_KEY_LAYOUT_NAME	Cannot get keyboard layout name
-221988	PCOIP_MSG_CANNOT_LOAD_KEY_LAYOUT	Cannot load keyboard layout %1 (error code % 2 ld), default layout will be used.
-221987	PCOIP_MSG_CANNOT_GET_SCANCODE	Cannot get scancode for key %1, ignoring it...
-221986	PCOIP_MSG_SETDISCLAIMER	Disclaimer %1
-221985	PCOIP_MSG_SETCREDS	Set credentials for connection: username=%1, domain=%2, password=*****

Error code	Handle	Message\Additional information
-221984	PCOIP_MSG_SETBROKER	Set broker address: %1:%2
-221983	PCOIP_MSG_CONNECTING	Connecting to server %1:%2 (%3, %4)...
-221982	PCOIP_MSG_CONNECTED	Connected
-221981	PCOIP_MSG_DISCONNECT	Disconnecting...
-221980	PCOIP_MSG_SET_DISPLAY	Set display resolution to % 1 _ld x % 2 _ld
-221979	PCOIP_MSG_EXEC_MOUSE_CLICK	Executing mouse click at (% 1 _ld;% 2 _ld), buttons=% 3 _ld, modifiers=% 4 _ld
-221978	PCOIP_MSG_EXEC_KEY	Executing key press %1 with modifiers=% 2 _ld
-221977	PCOIP_MSG_EXEC_TYPE	Executing type %1
-221976	PCOIP_MSG_CREATE_BROKER_ERROR	Cannot create broker (error code % 1 _ld)
-221975	PCOIP_MSG_BROKER_ADDR_NOT_SET	Broker address is not set, using address of Desktop - %1
-221974	PCOIP_MSG_BROKER_PORT_NOT_SET	Broker port is not set, using default - %1
-221973	PCOIP_MSG_SET_BROKER_ADDR_ERROR	Cannot set broker address (error code % 1 _ld)
-221972	PCOIP_MSG_SET_CLN_INFO_ERROR	Cannot set client info for broker error (error code % 1 _ld)
-221971	PCOIP_MSG_SET_CERT_IGNORE_ERROR	Cannot enable "Ignore Certificate" mode (error code % 1 _ld)
-221970	PCOIP_MSG_GET_AUTH_METHOD_ERROR	Cannot get authentication method from broker (error code % 1 _ld)
-221969	PCOIP_MSG_BROKER_AUTH_ERROR	Broker authentication failed (error code % 1 _ld)
-221968	PCOIP_MSG_CANNOT_CREATE_SNAPSHOT_DIR	Cannot create snapshot directory %1 for iteration % 2 _ld, errcode=% 3 _ld
-221967	PCOIP_MSG_SNAPSHOT_DIR_NOT_SET	Cannot save snapshot %1 - snapshot directory is not set
-221966	PCOIP_MSG_DISPLAY_BUFFER_EMPTY	Cannot save snapshot %1 - display buffer is empty
-221965	PCOIP_MSG_SNAPSHOT_CREATEFROMARRAY_ERROR	\\tError saving snapshot %1 - cannot create an image from array\\r\\n
-221964	PCOIP_MSG_SNAPSHOT_SAVE_ERROR	\\tError saving snapshot %1 - cannot write to disk\\r\\n
-221963	PCOIP_MSG_SNAPSHOT_INF_FILE_ERROR	Cannot save inf-file for snapshot %1
-221962	PCOIP_MSG_SNAPSHOT_XML_FILE_ERROR	Cannot save XML-file for snapshot %1
-221961	PCOIP_MSG_SYNC_ON_BITMAP	Entering pcoip_sync_on_bitmap()
-221960	PCOIP_MSG_SYNC_ON_BITMAP_EX	Entering pcoip_sync_on_bitmap_ex()
-221959	PCOIP_MSG_SYNC_ON_TEXT	Entering pcoip_sync_on_text()
-221958	PCOIP_MSG_GET_BITMAP_VALUE	Entering pcoip_get_bitmap_value()
perlext_msg.h		
-101999	PERLEXT_ERROR_FAILED_TO_CREATE_INTERPRETER	Failed to create Perl interpreter
-101998	PERLEXT_ERROR_NULL_SCRIPT	A NULL script name was passed to perlext_load
-101997	PERLEXT_ERROR_FAILED_TO_LOAD_SCRIPT	Failed to load Perl script file %1. Reason : %2
-101996	PERLEXT_ERROR_FAILED_TO_UNLOAD_SCRIPT	Failed to unload Perl script file %1. Reason : %2
-101995	PERLEXT_ERROR_NULL_HANDLE	A NULL handle was passed to the Perl interpreter extension
-101994	PERLEXT_ERROR_NO_INTERPRETER	No Perl interpreter was created for the current thread
-101993	PERLEXT_ERROR_NO_TRANSFORMERS	No transformers exist
-101992	PERLEXT_ERROR_NO_TRANSFORMER	No transformer exists for Perl function %1
-101991	PERLEXT_ERROR_BAD_NUMBER_OF_ARGS	Illegal number of arguments was passed to Perl function %1; Passed: % 2 _ld, expected : % 3 _ld
-101990	PERLEXT_ERROR_TOO_MANY_ARGS	Too many arguments were passed to Perl function %1; Passed: % 2 _ld, maximum allowed : % 3 _ld
-101989	PERLEXT_ERROR_FAILED_TO_TRANSFORM_ARGS	Failed to transform arguments for Perl function %1
-101988	PERLEXT_ERROR_FAILED_TO_EXECUTE_FUNC	Failed to execute Perl function %1 of script %2. Reason : %3
-101987	PERLEXT_ERROR_FAILED_TO_GET_RETVAL	Failed to get returned value of Perl function %1 of script %2
-101986	PERLEXT_ERROR_NULL_TRANSFORMERS	A null transformer list was passed to add_perl_transformers
-101985	PERLEXT_ERROR_NULL_TRANSFORMER_NAME	A transformer with a null name was defined
-101984	PERLEXT_ERROR_TRANSFORMER_ALREADY_EXISTS	A transformer named '%1' has already been defined
-101983	PERLEXT_ERROR_NULL_TRANSFORMER_FUNC	A transformer named '%1' has no arguments transformation function
-101982	PERLEXT_ERROR_SCRIPT_EXCEPTION	A system exception was thrown in func %1 of script %2. Description: %3
rdp_error_categories.h		
-202010	RDP_MSG_CAT_SYNC_STEP_FAILED	Synchronization step failed
-202009	RDP_MSG_CAT_STEP_FAILED	Step failed
-202008	RDP_MSG_CAT_CONNECTION_ERROR	Connection error
-202007	RDP_MSG_CAT_SCRIPT_ERROR	Error in script
-202006	RDP_MSG_CAT_GENERAL_ERROR	General error
rdp_res.h		
-202199	RDP_INTERNAL_ERROR	Internal Error (call customer services): %1

Error code	Handle	Message\Additional information
-202198	RDP_STEP_RDP_CALL_STARTED	RDP Call ("%1") started
-202197	RDP_STEP_STARTED	%1 started
-202196	RDP_STEP_SUCCESSFULLY_ENDED	%1 was successful
-202195	RDP_STEP_RDP_CALL_SUCCESS	RDP Call ("%1") was successful
-202194	RDP_STEP_END_STATUS	There was %1 while %2
-202193	RDP_FAILED_TO_INITIALIZE_RDP_ENCODER	Failed to initialize RDP infrastructure: %1
-202192	RDP_ILLEGAL_ARGUMENT_VALUE	Illegal argument value was found: %1
-202191	RDP_SYNC_FAILED	Image synchronization failed. No match found. Snapshot Info [MSH %1 %2]
-202190	RDP_SYNC_FAILED_IN_VUGEN	Image synchronization failed. No match found.
-202189	RDP_SYNC_APPENDED	Appending the new snapshot to the synchronization step. The step will be amended.
-202188	RDP_SYNC_APPEND_FAILED	Unable to append new snapshot to the synchronization step.
-202187	RDP_SYNC_NO_DIALOG	Unable to load the Synchronization dialog box.
-202186	RDP_SYNC_TOLERANCE_RAISED	Raising the tolerance of this step.
-202185	RDP_UPDATE_RECEIVED	%1 update received.
-202184	RDP_ORDER_UPDATE_RECEIVED	Order update received.
-202183	RDP_BITMAP_UPDATE_RECEIVED	Bitmap update received.
-202182	RDP_PALETTE_UPDATE_RECEIVED	Palette update received.
-202181	RDP_MOUSE_UPDATE_RECEIVED	mouse update received.
-202180	RDP_MOUSE_POINTER_UPDATE_RECEIVED	mouse (type=% 1 Id) update received.
-202179	RDP_SESSION_INFO_UPDATE_RECEIVED	Session info update received.
-202178	RDP_UNSUPPORTED_PDU_TYPE	Unsupported PDU%1 type: % 2 Id.
-202177	RDP_DECOMPRESSING_DATA	Decompressing %1-path data.
-202176	RDP_LICENSE_ERROR	Failed to acquire license.
-202175	RDP_CANT_RESOLVE_HOST_NAME	Unable to resolve host name: "%1".
-202174	RDP_CANT_CONNECT_TO_HOST	Unable to connect to host "%1".
-202173	RDP_SEND_TO_SOCKET_FAILED	Network failed. Unable to send buffer, error code % 1 Id.
-202172	RDP_RECV_FROM_SOCKET_FAILED	Server or network failed. Unable to receive buffer, error code % 1 Id.
-202171	RDP_VIRTUAL_DISPLAY_INITIALIZED	Virtual display was initialized with size %1
-202170	RDP_VIRTUAL_DISPLAY_SNAPSHOT_GENERATED	Generated new snapshot with name %1
-202169	RDP_VIRTUAL_CHANNEL_MESSAGE	Received message for channel %1 with size %2
-202168	RDP_CANT_CONNECT_TO_AN_EXISTING_SESSION	Connection to/from an existing session is not supported.
-202167	RDP_RECONFIGURE_SERVER	Connecting to/from an existing session is not supported.\n Hint: you can change the Terminal Services settings on the server to "End Session" when connection is broken.
-202166	RDP_SAVE_IMAGE_TO_FILE	Saving current screen snapshot to file '%1'.
-202165	RDP_DIFFERENT_DESKTOP_SIZE	Requested desktop size of %1, but received desktop size of %2
-202164	RDP_UNSUPPORTED_RASTER_OPERATION	Unsupported raster operation: % 1 Id
-202163	RDP_MOUSE_DOWN_PERFORMED	Step %1 - pressing mouse button %2 %3 down at (% 4 Id, % 5 Id)
-202162	RDP_MOUSE_UP_PERFORMED	Step %1 - releasing mouse button %2 %3 up at (% 4 Id, % 5 Id)
-202161	RDP_MOUSE_CLICK_PERFORMED	Step %1 - clicking mouse button %2 %3 at (% 4 Id, % 5 Id)
-202160	RDP_MOUSE_DOUBLE_CLICK_PERFORMED	Step %1 - double-clicking mouse button %2 %3 at (% 4 Id, % 5 Id)
-202159	RDP_MOUSE_MOVE_PERFORMED	Step %1 - moving mouse %2 to (% 3 Id, % 4 Id)
-202158	RDP_MOUSE_DRAG_PERFORMED	Step %1 - dragging mouse %2 %3 from (% 4 Id, % 5 Id) to (% 6 Id, % 7 Id)
-202157	RDP_MOUSE_WHEEL_PERFORMED	Step %1 - moving mouse wheel %2 %3 % 4 Id units at (% 5 Id, % 6 Id)
-202156	RDP_SET_LOCK_PERFORMED	Step %1 - locking key %2
-202155	RDP_RELEASE_LOCK_PERFORMED	Step %1 - releasing key %2
-202154	RDP_KEY_DOWN_PERFORMED	Step %1 - pressing key '%2' down
-202153	RDP_KEY_UP_PERFORMED	Step %1 - releasing key '%2' up
-202152	RDP_KEY_OPERATION_PERFORMED	Step %1 - pressing key %2 '%3'
-202151	RDP_TYPE_PERFORMED	Step %1 - typing characters: "%2"
-202150	RDP_SYNC_PERFORMED	Step %1 - synchronizing on image (Mode=%2, Tolerance=%3, Timeout=% 4 Id seconds)
-202149	RDP_CONNECT_PERFORMED	Connecting to the RDP Server (host: "%1", userName: "%2", domain: "%3") was successful
-202148	RDP_DISCONNECT_PERFORMED	Step %1 - session disconnected by the RDP Server
-202147	RDP_CLIENT_DISCONNECT_PERFORMED	Step %1 - session disconnected by the RDP Client
-202146	RDP_SAVE_IMAGE_PERFORMED	Saving image
-202145	RDP_PACKET_DETECTED	Detected %1 packet
-202144	RDP_IMAGE_OUT_OF_BOUNDS	Image coordinates (left=% 1 Id, top=% 2 Id, width=% 3 Id, height=% 4 Id) out of recorded image bounds (width=% 5 Id, height=% 6 Id) Snapshot Info [MSH %7 %8]

Error code	Handle	Message\Additional information
-202088	RDP_GET_ACTIVE_WINDOW_TITLE_FAILED	Failed to get the title of the active window. Snapshot Info [MSH %1 %2]
-202087	RDP_GET_ACTIVE_WINDOW_TITLE_FAILED_IN_VUGEN	Failed to get the title of the active window.
-202086	RDP_FAILED_TO_CREATE_REGULAR_EXPRESSION	Failed to create regular expression (error code=% 1 _ld).
-202085	RDP_GET_OBJECT_INFO_PERFORMED	Step %1 - getting object information (WindowTitle=%2, Ordinal=% 3 _ld, x=% 4 _ld, y=% 5 _ld, attribute=%6).
-202084	RDP_GET_OBJECT_INFO_FAILED	Failed to get object information. Snapshot Info [MSH %1 %2]
-202083	RDP_GET_OBJECT_INFO_FAILED_IN_VUGEN	Failed to get object information.
-202082	RDP_SYNC_ON_OBJECT_INFO_PERFORMED	Step %1 - Synchronizing on object information (WindowTitle=%2, Ordinal=% 3 _ld, X=% 4 _ld, Y=% 5 _ld, Attribute=%6, Value=%7).
-202081	RDP_SYNC_ON_OBJECT_INFO_FAILED	Failed to synchronize on object information. Snapshot Info [MSH %1 %2]
-202080	RDP_SYNC_ON_OBJECT_INFO_FAILED_IN_VUGEN	Failed to synchronize on object information.
-202079	RDP_SYNC_ON_OBJECT_INFO_BAD_BOOLEAN_VAL	Received illegal string representation of boolean: %1.
-202078	RDP_AGENT_NOT_RESPONDING	Failed to receive a response from the agent. It might be due to high network latency or because the agent is down. Increasing the timeout for agent response at the Runtime Settings might solve the problem.
-202077	RDP_ILLEGAL_DECIMAL_VALUE	The argument '%1' should have decimal value.
-202076	RDP_ILLEGAL_BOOLEAN_VALUE	The argument '%1' should have boolean value (TRUE or FALSE).
-202075	RDP_SYNCED_MOUSE_DOWN_PERFORMED	Step %1 - pressing mouse button %2 %3 down on synchronized object at (% 4 _ld, % 5 _ld)
-202074	RDP_SYNCED_MOUSE_UP_PERFORMED	Step %1 - releasing mouse button %2 %3 up from synchronized object at (% 4 _ld, % 5 _ld)
-202073	RDP_SYNCED_MOUSE_CLICK_PERFORMED	Step %1 - clicking mouse button %2 %3 on synchronized object at (% 4 _ld, % 5 _ld)
-202072	RDP_SYNCED_MOUSE_DOUBLE_CLICK_PERFORMED	Step %1 - double-clicking mouse button %2 %3 on synchronized object at (% 4 _ld, % 5 _ld)
-202071	RDP_SYNC_OBJECT_MOUSE_CLICK_FAILED	Failed to execute mouse click on synchronized object. Snapshot Info [MSH %1 %2]
-202070	RDP_SYNC_OBJECT_MOUSE_CLICK_FAILED_IN_VUGEN	Failed to execute mouse click on synchronized object.
-202069	RDP_SYNC_OBJECT_MOUSE_DOUBLE_CLICK_FAILED	Failed to execute mouse double-click on synchronized object. Snapshot Info [MSH %1 %2]
-202068	RDP_SYNC_OBJECT_MOUSE_DOUBLE_CLICK_FAILED_IN_VUGEN	Failed to execute mouse double-click on synchronized object.
-202067	RDP_GET_TEXT_PERFORMED	Step %1 - getting text (WindowTitle=%2, Ordinal=% 3 _ld, x=% 4 _ld, y=% 5 _ld).
-202066	RDP_SYNC_ON_TEXT_PERFORMED	Step %1 - synchronizing on text (WindowTitle=%2, Ordinal=% 3 _ld, X=% 4 _ld, Y=% 5 _ld, Text=%6).
-202065	RDP_GET_TEXT_FAILED	Failed to get text. Snapshot Info [MSH %1 %2]
-202064	RDP_GET_TEXT_FAILED_IN_VUGEN	Failed to get text.
-202063	RDP_SYNC_ON_TEXT_FAILED	Failed to synchronize on text. Snapshot Info [MSH %1 %2]
-202062	RDP_SYNC_ON_TEXT_FAILED_IN_VUGEN	Failed to synchronize on text.
-202061	RDP_MISSING_AGENT_MESSAGES	Missing % 1 _ld Message(s) from RDP Agent. This may be caused by connecting to an RDP session that is already running.
-202060	RDP_AGENT_LOG_MESSAGE	RDP Agent log message: %1.
-202059	RDP_AGENT_LOG_MESSAGE_ILLEGAL_ERROR_LEVEL	Received RDP Agent log message with illegal error level (= % 1 _ld).
-202058	RDP_WINDOW_NOT_EXIST	Failed to detect the window with the title "%1" and ordinal % 2 _ld.
-202057	RDP_COORDINATES_OUTSIDE_WINDOW	The given coordinates are outside the given window.
-202056	RDP_FAILED_TO_SEND_REQUEST_TO_AGENT	Failed to send a request to the agent.
-202055	RDP_WINDOW_IS_MINIMIZED	The window with the title "%1" and ordinal % 2 _ld is minimized.
-202054	RDP_SYNC_ON_WINDOW_FAILED	Window synchronization failed. No match found. Snapshot Info [MSH %1 %2]
-202053	RDP_SYNC_ON_WINDOW_FAILED_IN_VUGEN	Window synchronization failed. No match found.
-202052	RDP_SYNC_ON_AGENT_FAILED	Agent synchronization failed. Snapshot Info [MSH %1 %2]
-202051	RDP_SYNC_ON_AGENT_FAILED_IN_VUGEN	Agent synchronization failed.
-202050	RDP_RECEIVE_CLIPBOARD_DATA_FAILED	Failed to receive clipboard data during the specified time. Snapshot Info [MSH %1 %2]
-202049	RDP_RECEIVE_CLIPBOARD_DATA_FAILED_IN_VUGEN	Failed to receive clipboard data during the specified time.
-202048	RDP_SEND_CLIPBOARD_DATA_FAILED	Failed to receive server request for clipboard data during the specified time. Snapshot Info [MSH %1 %2]
-202047	RDP_SEND_CLIPBOARD_DATA_FAILED_IN_VUGEN	Failed to receive server request for clipboard data during the specified time.
-202046	RDP_ACTIVE_WINDOW_NOT_EXIST	No active window exists.
-202045	RDP_WINDOW_TITLE_EMPTY	Window title is empty, getting data from active window.
-202044	RDP_COMPRESSION_NOT_SUPPORTED_IN_REPLAY	Compression is not supported in Replay - the session has been disconnected.
-202043	RDP_NO_DATA_RECEIVED_FROM_SERVER	Failed to receive data from the server during the timeout - the session has been disconnected.
-202042	RDP_INFINITE_LOOP_SUSPICION	The application has encountered a loop that is most likely infinite - the session has been disconnected.
rtc_client_msg.h		
-104999	RTCC_MSG_FAILED_TO_OPEN_REQUESTS_HASH	RTC Client Error: Failed to open hash table for rtc client requests.
-104998	RTCC_MSG_FAILED_TO_GET_RTCC_PT_INSTANCE	RTC Client Error: Failed to get PT instance of RTC Client.
-104997	RTCC_MSG_INVALID_REQUEST_PTR	RTC Client Error: Invalid handle was sent to RTC Client API.
-104996	RTCC_MSG_FAILED_TO_CREATE_REQUEST_OBJECT	RTC Client Error: Failed to create request object.
-104995	RTCC_MSG_FAILED_TO_LISTEN_ON_REQUEST_SERVICE	RTC Client Error: Failed to listen to service via CE API.
-104994	RTCC_MSG_FAILED_TO_POST_COMMAND_MESSAGE_VIA_CE	RTC Client Error: Failed to post command - %1 message via CE API (error code - %2 _ld).
-104993	RTCC_MSG_FAILED_TO_ENCODE_REQUEST	RTC Client Error: Failed to encode request buffer (error code - %1 _ld).

Error code	Handle	Message\Additional information
-104992	RTCC MSG FAILED TO ENCODE BUFFER	RTC Client Error: Failed to encode buffer via XDR (error code - %1 _ld).
-104991	RTCC MSG FAILED TO DECODE BUFFER	RTC Client Error: Failed to decode buffer via XDR (error code - %1 _ld).
-104990	RTCC MSG FAILED TO OPEN SUBSCRIBER	RTC Client Error: Failed to open subscriber.
-104989	RTCC MSG FAILED TO OPEN PUBLISHER	RTC Client Error: Failed to open publisher.
run_time_context_msg.h		
-103999	RTC CM FAILED TO CREATE CM_OBJECT_ERROR	RTC Context Manager Error: Failed to create RTC Server object.
-103998	RTC CM REGISTERED DEBUG	RTC Context Manager Debug: Registered key: %1.
-103997	RTC CM UNREGISTERED DEBUG	RTC Context Manager Debug: Unregistered key: %1.
-103996	RTC CM FAILED TO OPEN HASH_ERROR	RTC Context Manager Error: Failed to open hash table.
-103899	RTC EC FAILED TO CREATE EC_OBJECT_ERROR	RTC EC Error: Failed to create EC Server object.
-103898	RTC EC FAILED TO CREATE GOHEAP_ERROR	RTC EC Error: Failed to create goheap.
-103799	RTC SERVER FAILED TO CREATE RTC_SERVER_OBJECT_ERROR	RTC Server Error: Failed to create RTC Server object.
-103798	RTC SERVER FAILED TO OPEN HASH_ERROR	RTC Server Error: Failed to open hash table.
-103797	RTC SERVER FAILED TO OPEN P2P_SERVER_ERROR	RTC Server Error: Failed to open p2p server.
-103796	RTC SERVER FAILED TO DECODE REQUEST_ERROR	RTC Server Error: Failed to decode client's request.
-103795	RTC SERVER FAILED TO ENCODE REPLY_ERROR	RTC Server Error: Failed to encode reply.
-103794	RTC SERVER FAILED ALLOCATE BUFFER FOR REPLAY_MESSAGE	RTC Server Error:Failed to allocate buffer for replay message.
-103793	RTC SERVER UNKNOWN ACTION_TYPE_ERROR	RTC Server Error: Received an unknown action type from RTC client.
-103792	RTC SERVER UNKNOWN REQUEST_TYPE_ERROR	RTC Server Error: Received an unknown request type from RTC client.
-103791	RTC SERVER FAILED TO OPEN P2P_CLIENT_ERROR	RTC Server Error: Failed to open p2p client with service name %1.
-103790	RTC SERVER FAILED TO GET CM_ERROR	RTC Server Error: Failed to get Context Manager from tls.
-103789	RTC SERVER FAILED TO POST REPLY_ERROR	RTC Server Error: Failed to post reply to RTC client.
-103788	RTC SERVER ACTIVATE_REQUEST_NOT_FOUND_ERROR	RTC Server Error: Failed to activate request. Request not found in hash table.
-103787	RTC SERVER FAILED TO GET CONTEXT FROM CM_ERROR	RTC Server Error: Failed to get context from Context Manager.
-103786	RTC SERVER FAILED TO CREATE REQUEST_OBJECT_ERROR	RTC Server Error: Failed to create RTC request object.
-103785	RTC SERVER FAILED TO OPEN PUBLISHER_ERROR	RTC Server Error: Failed to open publisher.
-103784	RTC SERVER FAILED TO OPEN SUBSCRIBER_ERROR	RTC Server Error: Failed to open subscriber.
runint_m.h		
-25999	RI_USR_NOT_FOUND	Can't find USR file %1
-25998	RI_OUTPUT_DIR_NOT_FOUND	Can't find output directory %1
-25997	RI_OUTPUT_DIR_READ_ONLY	Output directory %1 is read only
-25996	RI_COMPILER_ERROR	Compiler error : %1
-25995	RI_CI_NOT_FOUND	Can't find CI file %1
-25994	RI_DRIVER_NOT_FOUND	Can't find Driver file %1
-25993	RI_COMBINE_FILE_NOT_CREATED	Compiler error : Can't create temporary combined file %1
-25992	RI_COMBINE_FILE_NOT_CLOSED	Compiler error : Can't close temporary combined file %1
-25991	RI_DAT_DIR_NOT_FOUND	Can't find DAT directory %1
-25990	RI_DAT_FILE_NOT_FOUND	Can't find DAT file %1
-25989	RI_READ_DAT_ERROR	Can't read information from DAT file %1
-25988	RI_INC_DIR_NOT_FOUND	Can't find include/inc directory %1
-25987	RI_BIN_DIR_NOT_FOUND	Can't find arch/bin directory %1
-25986	RI_FILE_NOT_FOUND	Can't find file %1
-25985	RI_OPTIONS_FILE_NOT_CREATED	Compiler error : Can't create temporary options file %1
-25984	RI_PA_ERROR	Can't read information from file %1
-25983	RI_UNKNOWN_PLATFORM	Unknown platform
-25982	RI_CANT_RESOLVE_LRUN_ROOT_DIR	Can't resolve lrun root directory
-25981	RI_RESOURCE_FILE_NOT_FOUND	Can't found resource file %1
-25980	RI_RESOURCE_FILE_NOT_LOADED	Can't load the resource file %1
-25979	RI_CANT_CREATE_SCRIPT_DIRECTORY	Can't create script directory into global directory
-25978	RI_CANT_CREATE_CRITICAL_SECTION	Unable to create critical section
-25977	RI_CANT_ENTER_CRITICAL_SECTION	Unable to enter critical section
-25976	RI_CANT_LEAVE_CRITICAL_SECTION	Unable to leave critical section
runlogic_res.h		
-15999	RUNLOGIC_ERR_CONST_PACE_NO_TIME_ENTRY	Run-time settings pacing error: No setting for the fixed delay after the previous iteration ends.

Error code	Handle	Message\Additional information
-15998	RUNLOGIC CONST PACE TIME IS	Pacing in node %1 is set to start every %2 seconds.
-15997	RUNLOGIC CONST PACE IS NEGATIVE	Run-time settings pacing error: Fixed delay after the previous iteration is set to be a negative number (%1).
-15996	RUNLOGIC WAITING SECS FOR PACING	Waiting % 1 .4f seconds for iteration pacing.
-15995	RUNLOGIC WARNING ITERATION PACING CANNOT BE REACHED	Iteration pacing cannot be reached (pace time = % 1 .2f, actual time = % 2 .2f).
-15994	RUNLOGIC END ITERATION WITH HITS	End iteration num % 1 _ld with % 2 _ld number of hits at % 3 _ld secs.
-15993	RUNLOGIC ERR RAND PACE NO MAX TIME ENTRY	Run-time settings pacing error: No setting for maximum value at random interval pacing.
-15992	RUNLOGIC ERR BEFORE FIRST PACE NO MAX TIME ENTRY	Command line does not contain the maximal value of the pacing before first iteration.
-15991	RUNLOGIC ERR AFTER PACE NO MAX TIME ENTRY	Run-time settings pacing error: No setting for maximum range of the random delay after the previous iteration ends.
-15990	RUNLOGIC ERR RAND PACE NO MIN TIME ENTRY	Run-time settings pacing error: No setting for minimum value at random interval pacing.
-15989	RUNLOGIC ERR BEFORE FIRST NO MIN TIME ENTRY	Command line does not contain the minimal value of the pacing before first iteration.
-15988	RUNLOGIC ERR AFTER PACE NO MIN TIME ENTRY	Run-time settings pacing error: No setting for minimum range of the random delay after the previous iteration ends.
-15987	RUNLOGIC ERR RAND PACE MAX GT ZERO	Run-time settings pacing error: Maximum value of interval for the random pacing must be greater than 0.
-15986	RUNLOGIC ERR RAND PACE MIN GT ZERO	Run-time settings pacing error: Minimum value of interval for the random pacing must be greater than 0.
-15985	RUNLOGIC ERR BEFORE FIRST PACE MIN GT MAX	Run-time setting pacing error: Minimum value of the random interval for pacing is greater than maximum value.
-15984	RUNLOGIC ERR BEFORE FIRST PACE MIN GT ZERO	Minimum value for pacing before first iteration must be greater than 0.
-15983	RUNLOGIC ERR AFTER PACE MAX GT ZERO	Run-time settings pacing error: Maximum value of interval for the random delay after the previous iteration ends must be greater than 0.
-15982	RUNLOGIC ERR AFTER PACE MIN GT ZERO	Run-time settings pacing error: Minimum value of interval for the random delay after the previous iteration ends must be greater than 0.
-15981	RUNLOGIC ERR RAND PACE MIN GT MAX	Run-time setting pacing error: Minimum value of the random interval for pacing is greater than maximum value.
-15980	RUNLOGIC ERR AFTER PACE MIN GT MAX	Run-time setting pacing error: Maximum value of range for the random delay after the previous iteration ends cannot be smaller than minimum.
-15979	RUNLOGIC RAND PACE INIT DEBUG	Each iteration will be started at random interval every %1 - %2 seconds.
-15978	RUNLOGIC AFTER PACE INIT DEBUG	Each iteration will be started with random delay of %1 - %2 seconds after the previous iteration ends.
-15977	RUNLOGIC OBJECT SON TYPE UNDEFINED	Type attribute in node %1 undefined.
-15976	RUNLOGIC OBJECT SON RUN MODE UNDEFINED	Run mode of node %1 undefined.
-15975	RUNLOGIC OBJECT PACE TYPE RAND	Pace type is 'Start each iteration at random interval' in block %1.
-15974	RUNLOGIC OBJECT PACE TYPE CONST	Pace type is 'Start each iteration at fixed interval' in block %1.
-15973	RUNLOGIC OBJECT PACE TYPE HPS	Pace type is hps in block %1.
-15972	RUNLOGIC OBJECT PACE TYPE AFTER	Pace type is 'Start each iteration with random delay after the previous iteration ends' in block %1.
-15971	RUNLOGIC OBJECT ITERATIONS	Number of iterations for block %1 is %2.
-15970	RUNLOGIC OBJECT ITERATIONS WARNING	Illegal number of iterations %1 in block %2, value set to 1 iteration.
-15969	RUNLOGIC OBJECT ITERATIONS WARNING NOT EXIST	Iterations entry in block %1 does not exist, value set to 1 iteration.
-15968	RUNLOGIC OBJECT START ITERATION	Starting iteration %1.
-15967	RUNLOGIC OBJECT START SCRIPT	Virtual User Script started at: %1
-15966	RUNLOGIC OBJECT END SCRIPT	Ending Vuser...
-15965	RUNLOGIC OBJECT END ITERATION	Ending iteration %1.
-15964	RUNLOGIC OBJECT RUNNING VUSER	Running Vuser...
-15963	RUNLOGIC OBJECT VUSER TERMINATED	Vuser Terminated.
-15962	RUNLOGIC ACTION RUNNING ACTION	Running action %1.
-15961	RUNLOGIC RANDOM IS NULL	Random pool is NULL
-15960	RUNLOGIC PERCENT IS NULL	Percent for node %1 is NULL.
-15959	RUNLOGIC PERCENT ERROR	Percent error in node %1 (sum over 100).
-15958	RUNLOGIC PERCENT ERROR2	Sum of random object (%1) pct has to be 100.
-15957	RUNLOGIC ERROR CANNOT OPEN RUNLOGIC FILE	Cannot open file %1.
-15956	RUNLOGIC ERROR RUN SECTION DOES NOT EXIST	Run Section does not exist.
-15955	RUNLOGIC ERROR RAND POOL IS NULL	Random Generator is NULL
-15954	RUNLOGIC ERROR RUN MODE NOT SUPPORTED	Run mode %1 not supported.
-15953	RUNLOGIC RANDOM ORDER IS NULL	Random order pool is NULL
-15952	RUNLOGIC HPS PACE NUM OF HITS IS	Pacing in node %1 is set to % 2 _ld hits.
-15951	RUNLOGIC ERR HPS PACE NO NUM OF HIT ENTRY	No setting for number of hits in hps pace in node %1.
-15950	RUNLOGIC WARNING END ITERATION WITH LESS DPS	Warning! End iteration with % 1 _ld hits(pages) instead of % 2 _ld hits(pages). We need to speed up the Vuser.
-15949	RUNLOGIC WAITING SECS FOR DPS PACING	Waiting % 1 .2f seconds at the end of iteration in order to slow down the Vuser.
-15948	RUNLOGIC MSG THINKTIME 1	%1: % 2 .2f seconds.
-15947	RUNLOGIC MSG THINKTIME 2	%1: % 2 .2f seconds (recorded think time was % 3 .2f seconds).
-15946	RUNLOGIC MSG USING LIMIT THINK TIME	Think time - Waiting % 1 .2f seconds (according to limit).
-15945	RUNLOGIC ERR THINK TIME NO TIME OPTIONS	Think time options were not set.
-15944	RUNLOGIC TIME OPTIONS IS	Time option was set to %1.
-15943	RUNLOGIC ERR THINK TIME NO TIME HIGH DEVIATION	Missing the setting for high deviation in think time when random flag is on.
-15942	RUNLOGIC THINK TIME HIGH DEVIATION IS	When random flag is on high deviation in think time is set to %1.

Error code	Handle	Message\Additional information
-15941	RUNLOGIC_ERR_THINK_TIME_NO_TIME_LOW_DEVIATION	Missing setting for low deviation in think time when random flag is on.
-15940	RUNLOGIC_THINK_TIME_LOW_DEVIATION_IS	When random flag is on low deviation in think time is set to %1.
-15939	RUNLOGIC_ERR_THINK_TIME_NO_FACTOR	Missing setting for factor in think time when factor flag is on.
-15938	RUNLOGIC_THINK_TIME_FACTOR_IS	When factor flag is on the factor number is set to %1.
-15937	RUNLOGIC_ERR_THINK_TIME_NO_TIME_LIMIT_FLAG	No setting for limit flag in think time .
-15936	RUNLOGIC_THINK_TIME_TIME_LIMIT_FLAG_IS	The limit flag in think time is set to %1.
-15935	RUNLOGIC_ERR_THINK_TIME_NO_TIME_LIMIT	No setting for time limit in think time when limit flag is on.
-15934	RUNLOGIC_THINK_TIME_LIMIT_IS	When limit flag is on the limit number is set to %1.
-15933	RUNLOGIC_CORRECT_THINK_TIME_FACTOR	In the next iteration, each think time value will be multiplied by a factor of %_1_f factor.
-15932	RUNLOGIC_DPS_PACE_DETAILS	num of data point per second defined by the user is %_1_f.
-15931	RUNLOGIC_DPS_PACE_DETAILS_1	run_time is %_1_ld.
-15930	RUNLOGIC_DPS_PACE_DETAILS_2	Completed number of data point last iteration is %_1_ld.
-15929	RUNLOGIC_DPS_PACE_DETAILS_3	Required number of data point is %_1_ld.
-15928	RUNLOGIC_DPS_PACE_DETAILS_4	The wait_mili time is %_1_ld.
-15927	RUNLOGIC_DPS_PACE_DETAILS_5	The total think time is %_1_f.
-15926	RUNLOGIC_DPS_PACE_DETAILS_6	The factor value did not change from the previous iteration since it is very close to the result.
-15925	RUNLOGIC_DPS_PACE_DETAILS_7	run time ended at %_1_ld.
-15924	RUNLOGIC_DPS_PACE_DETAILS_8	run time begin at %_1_ld.
-15923	RUNLOGIC_DPS_PACE_USER_CANCELLED_DPS_PACING	User passed DPS(data point per second). Pacing with a zero value. DPS Pacing cancelled. Returning to Vuser default behavior.
-15922	RUNLOGIC_OBJECT_PACE_TYPE_HPS_FROM_CMDLINE	Pace type is HPS by command line with value - %1 hps.
-15921	RUNLOGIC_DPS_PACE_ERROR_DECODE_DATA	Error while decoding DPS retrieved from the Controller.
-15920	RUNLOGIC_DPS_PACE_ERROR_ENCODE_DATA	Error while encoding DPS in last iteration sent to the Controller.
-15919	RUNLOGIC_STARTING_ACTION	Starting action %1.
-15918	RUNLOGIC_ENDING_ACTION	Ending action %1.
-15917	RUNLOGIC_DPS_PACE_DETAILS_10	The number of data missing or the number of data over the limit is %_1_ld.
-15916	RUNLOGIC_DPS_PACE_DETAILS_11	The run time without the think time is %_1_ld.
-15915	RUNLOGIC_HPS_PACE_MIN_WAITING_SECS_FOR_HPS_PACING	The minimum time to wait before starting a new iteration is %_1_.2f seconds.
-15914	RUNLOGIC_HPS_PACE_MAX_WAITING_SECS_FOR_HPS_PACING	The maximum time to wait before starting a new iteration is %_1_.2f seconds.
-15913	RUNLOGIC_HPS_PACE_NUM_OF_VUSERS_FROM_CMDLINE	The number of users run by the Controller is %_1_ld.
-15912	RUNLOGIC_HPS_PACE_NUM_OF_VUSERS_NOT_DEFINE_FROM_CMDLINE_ERROR	There is no information from the Controller about the number of users that are running.
-15911	RUNLOGIC_DPS_PACE_DO_NOT_TOUCH_THINK_TIME	The Controller settings indicate to leave the recorded think time as is. Think time will be as the user request.
-15910	RUNLOGIC_DPS_PACE_DO_TOUCH_THINK_TIME	The Controller allows the think time to be modified in order to reach a goal.
-15909	RUNLOGIC_ERR_CONST_AFTER_PACE_NO_TIME_ENTRY	Run-time settings pacing error: No value was set for the fixed delay after the previous iteration ends.
-15908	RUNLOGIC_CONST_AFTER_PACE_TIME_IS	After pace interval in node %1 a constant was set to %2 seconds.
-15907	RUNLOGIC_CONST_AFTER_PACE_IS_NEGATIVE	Run-time settings error: Fixed delay after the previous iteration is a negative number (%1). The delay must be positive.
-15906	RUNLOGIC_WAITING_CONST_SECS_FOR_PACING	Waiting a constant interval of %_1_.2f seconds between iterations.
-15905	RUNLOGIC_OBJECT_PACE_TYPE_CONST_AFTER	Pace type is to wait a constant interval after the iteration in block %1.
-15904	RUNLOGIC_DPS_PACE_DETAILS_12	The total number of data received until now for this iteration by the trans ext is %_1_ld.
-15903	RUNLOGIC_DPS_PACE_WAITING_SECS_IN_BEGIN_STAGE_FOR_DPS_PACING	Waiting %_1_.2f seconds to begin iteration.
-15902	RUNLOGIC_MAX_TIME_WAIT_IN_BEGIN_FOR_DPS_PACING	The maximum time for waiting to begin an iteration is %_1_.2f seconds.
-15901	RUNLOGIC_DPS_PACE_GOAL_ORIENTED_DELAY_START_FROM_CMDLINE	The start time delay before the first iteration is %1.
-15900	RUNLOGIC_HPS_PACE_GOAL_ORIENTED_DELAY_START_FROM_CMDLINE_ERROR	There is no information from the Controller about a start time delay before the first iteration.
-15899	RUNLOGIC_HPS_PACE_WAITING_SECS_IN_BEGIN_IS_FOR_HPS_PACING	The wait_mili at begin time is %_1_.2f.
-15898	RUNLOGIC_TPS_PACE_DETAILS	The number of transactions per second defined by the user is %_1_f.
-15897	RUNLOGIC_TPS_PACE_DETAILS_1	The run_time is %_1_ld.
-15896	RUNLOGIC_TPS_PACE_DETAILS_2	The number of transactions in last iteration are %_1_ld.
-15895	RUNLOGIC_TPS_PACE_DETAILS_3	Required number of transactions are %_1_ld.
-15894	RUNLOGIC_TPS_PACE_DETAILS_4	The wait_mili time is %_1_ld.
-15893	RUNLOGIC_TPS_PACE_DETAILS_5	The total think time is %_1_f.
-15892	RUNLOGIC_TPS_PACE_DETAILS_6	The factor value did not change from the previous iteration since it is very close to the result.
-15891	RUNLOGIC_TPS_PACE_DETAILS_7	run time ended at %_1_ld.
-15890	RUNLOGIC_TPS_PACE_DETAILS_8	run time begin at %_1_ld.
-15889	RUNLOGIC_TPS_PACE_DETAILS_9	The number of transactions missing or the number of transactions over the limit is %_1_ld.

Error code	Handle	Message\Additional information
-15888	RUNLOGIC_TPS_PACE_USER_CANCELLED_TPS_PACING	User passed TPS(Transactions Per Second). Pacing with a zero value. TPS Pacing cancelled. Returning to Vuser default behavior.
-15887	RUNLOGIC_TPS_PACE_ERROR_DECODE_DATA	Error while decoding TPS retrieved from the Controller.
-15886	RUNLOGIC_TPS_PACE_ERROR_ENCODE_DATA	Error while encoding TPS in last iteration sent to the Controller.
-15885	RUNLOGIC_TPS_PACE_ERROR_POST_DATA	Error while post message regarding to notification on request of number of transactions in the last iteration.
-15884	RUNLOGIC_TPS_PACE_DO_NOT_TOUCH_THINK_TIME	The Controller settings indicate to leave the recorded think time as is. Think time will be as the user request.
-15883	RUNLOGIC_TPS_PACE_DO_TOUCH_THINK_TIME	The Controller allows the think time to be modified in order to reach a goal.
-15882	RUNLOGIC_TPS_PACE_WAITING_SECS_IN_BEGIN_STAGE_FOR_TPS_PACING	Waiting %_1_.2f seconds to begin iteration.
-15881	RUNLOGIC_TPS_PACE_MAX_TIME_WAIT_IN_BEGIN_FOR_TPS_PACING	The maximum time for waiting to begin an iteration is %_1_.2f seconds.
-15880	RUNLOGIC_TPS_PACE_GOAL_ORIENTED_DELAY_START_FROM_CMDLINE	The start time delay before the first iteration is %1.
-15879	RUNLOGIC_TPS_PACE_GOAL_ORIENTED_DELAY_START_FROM_CMDLINE_ERROR	There is no information from the Controller about a start time delay before the first iteration.
-15878	RUNLOGIC_TPS_PACE_TRANS_NAME_ERROR	There is no information from the Controller about a transaction name.
-15877	RUNLOGIC_TPS_PACE_STRUCT_TPS_DATA_ERROR1	The structure of TpsPacingData from TlsTpsPacingData in constructor is NULL.
-15876	RUNLOGIC_TPS_PACE_STRUCT_TPS_DATA_ERROR2	The structure of TpsPacingData from TlsTpsPacingData in destructor is NULL.
-15875	RUNLOGIC_TPS_PACE_STRUCT_TPS_DATA_ERROR3	Error while getting structure TpsPacingData from TlsTpsPacingData to get number of transactions.
-15874	RUNLOGIC_TPS_PACE_WARNING_END_ITERATION_WITH_LESS_TRANSACTIONS	Warning! End iteration with %_1_Id transactions instead of %_2_Id transactions.We need to speed up Vuser.
-15873	RUNLOGIC_TPS_PACE_WAITING_SECS_FOR_TPS_PACING	Waiting %_1_.2f seconds for iteration pacing in order to slow down Vuser.
-15872	RUNLOGIC_TPS_PACE_DETAILS_12	The total number of transactions received until now for this iteration by the trans ext is %_1_Id.
-15871	RUNLOGIC_OBJECT_PACE_TYPE_TPS_FROM_CMDLINE	Pace type is TPS by command line with value - %1 tps.
-15870	RUNLOGIC_OBJECT_PACE_TYPE_PPS_FROM_CMDLINE	Pace type is PPS by command line with value - %1 pps.
-15869	RUNLOGIC_GOS_PACE_DO_NOT_TOUCH_THINK_TIME	The Controller settings indicate to leave the recorded think time as is. Think time will be as the user request.
-15868	RUNLOGIC_GOS_PACE_DO_TOUCH_THINK_TIME	The Controller allows the think time to be modified in order to reach a goal.
-15867	RUNLOGIC_GOS_PACE_GOAL_ORIENTED_DELAY_START_FROM_CMDLINE	The start time delay before the first iteration is %1.
-15866	RUNLOGIC_GOS_PACE_ERROR_DECODE_DATA	Error while decoding GOS data retrieved from the Controller.
-15865	RUNLOGIC_GOS_PACE_USER_CANCELLED_GOS_PACING	The new target from user is zero.GOS Pacing cancelled. Returning to Vuser default behavior.
-15864	RUNLOGIC_GOS_PACE_ERROR_ENCODE_DATA	Error while encoding GOS data in last iteration sent to the Controller.
-15863	RUNLOGIC_GOS_PACE_MAX_TIME_WAIT_IN_BEGIN_FOR_GOS_PACING	The maximum time for waiting to begin an iteration is %_1_.2f seconds.
-15862	RUNLOGIC_GOS_PACE_WAITING_SECS_IN_BEGIN_STAGE_FOR_GOS_PACING	Waiting %_1_.2f seconds to begin iteration.
-15861	RUNLOGIC_GOS_PACE_TARGET_VALUE	The target (number of data per sec) defined by the user is %_1_f.
-15860	RUNLOGIC_GOS_PACE_RUN_TIME	The run_time is %_1_Id.
-15859	RUNLOGIC_GOS_PACE_DATA_IN_LAST_ITERATION	The number of data in last iteration are %_1_Id.
-15858	RUNLOGIC_GOS_PACE_DATA_NEED_TO_DO	Required number of data is %_1_Id.
-15857	RUNLOGIC_GOS_PACE_WAIT_TIME_MILI	The wait_mili time is %_1_Id.
-15856	RUNLOGIC_GOS_PACE_TOTAL_THINK_TIME	The total think time is %_1_f.
-15855	RUNLOGIC_GOS_PACE_SAME_FACTOR	The factor value did not change from the previous iteration since it is very close to the result.
-15854	RUNLOGIC_GOS_PACE_RUN_TIME_END	run time ended at %_1_Id.
-15853	RUNLOGIC_GOS_PACE_RUN_TIME_BEGIN	run time begin at %_1_Id.
-15852	RUNLOGIC_GOS_PACE_DATA_ADD	The number of missing data or the number of data over the limit is %_1_Id.
-15851	RUNLOGIC_GOS_PACE_PURE_RUN_TIME	The run time without the think time is %_1_Id.
-15850	RUNLOGIC_GOS_PACE_NUM_OF_DATA_ARRIVED	The total number of data received until now for this iteration by the trans ext is %_1_Id.
-15849	RUNLOGIC_GOS_WARNING_END_ITERATION_WITH_LESS_DATA	Warning! End iteration with %_1_Id data instead of %_2_Id data. We need to speed up the Vuser.
-15848	RUNLOGIC_GOS_WAITING_SECS_FOR_GOS_PACING	Waiting %_1_.2f seconds at the end of iteration in order to slow down the Vuser.
-15847	RUNLOGIC_GOS_TYPE_FROM_CMDLINE	Pace type is %1 with target - %2.
-15846	RUNLOGIC_START_ACTION_GROUP	Starting action group with action name %1.
-15845	RUNLOGIC_END_ACTION_GROUP	Ending action group with action name %1.
-15844	RUNLOGIC_START_GROUP_ITERATION	Starting iteration %1 of action %2.
-15843	RUNLOGIC_END_GROUP_ITERATION	Ending iteration %1 of action %2.
sapgui_res.h		
-79999	SAP_GUI_MSG_GENERIC	1.00%
-79998	SAP_GUI_SUCCEEDED_TO_CREATE_SCRIPTING_ENGINE	Succeeded in creating SapGui Scripting Engine
-79997	SAP_GUI_FAILED_TO_CREATE_SCRIPTING_ENGINE	Failed to create SapGui Scripting Engine. Please check your SAPGUI client installation
-79996	SAP_GUI_FAILED_TO_CREATE_SCRIPTING_ENGINE_MISMATCH_BITNESS	Go to Runtime Settings -> Miscellaneous and make sure "Replay script with 64 bit" is %1

Error code	Handle	Message\Additional information
-79995	SAP GUI FAILED TO GET SCRIPTING ENGINE	Failed to get SapGui Scripting Engine. Please check your SAPGUI client installation
-79994	SAP GUI SUCCEEDED TO SET PARAMETER VALUE	The value of parameter "%1" was set to "%2"
-79993	SAP GUI FAILED TO SET PARAMETER VALUE	Failed to set value of parameter "%1" to "%2"
-79992	SAP GUI SUCCEEDED TO FIND SAP GUI COMPONENT	Found SapGui component by ID "%1"
-79991	SAP GUI FAILED TO FIND SAP GUI COMPONENT	Failed to find SapGui component by ID "%1"
-79990	SAP GUI FAILED TO FIND SAP GUI COMPONENT IN ACTIVE WINDOW	Failed to find SapGui component by id "%1" in Active Window
-79989	SAP GUI FAILED TO FIND SAP GUI COMPONENT IN ACTIVE SESSION	Failed to find SapGui component by ID "%1" in Active Session
-79988	SAP GUI FAILED TO FIND SAP GUI COMPONENT IN ACTIVE CONNECTION	Failed to find SapGui component by ID "%1" in Active Connection
-79987	SAP GUI SUCCEEDED TO INVOKE GUI COMPONENT PROPERTY	Set property "%1" of SapGui component "%2"
-79986	SAP GUI FAILED TO INVOKE GUI COMPONENT PROPERTY	Failed to set property "%1" of SapGui component "%2" to "%3"
-79985	SAP GUI SUCCEEDED TO GET GUI COMPONENT PROPERTY VALUE	The value of property "%1" of the "%2" SapGui component is "%3"
-79984	SAP GUI SUCCEEDED TO GET GUI COMPONENT PROPERTY	The value of property "%2" of SapGui component "%3" is "%1"
-79983	SAP GUI FAILED TO GET GUI COMPONENT PROPERTY	Failed to get the "%1" property of SapGuiComponent "%2"
-79982	SAP GUI FAILED TO SAVE GUI COMPONENT PROPERTY UNSUPPORTED PROPERTY TYPE	Failed to save property "%1" of SapGui component "%2" to parameter "%3" because of unsupported property type "%d"
-79981	SAP GUI FAILED TO CREATE GUI COLLECTION	Failed to create GuiCollection
-79980	SAP GUI FAILED TO SET COLLECTION PROPERTY	Failed to set property "%1" of SapGuiComponent "%2"
-79979	SAP GUI SUCCEEDED TO SET PROPERTY	Property "%1" of SapGuiComponent "%2" set to "%3"
-79978	SAP GUI METHOD RETURNED NO OBJECT	Method "%1" of SapGuiComponent "%2" did not return object
-79977	SAP GUI PROPERTY IS NOT OBJECT	Property "%1" of SapGuiComponent "%2" is not an object
-79976	SAP GUI SUCCEEDED TO STORE ACTIVE OBJECT	Set Active Object
-79975	SAP GUI BAD MISSING ACTIVE OBJECT	Active Object was not set properly
-79974	SAP GUI FAILED TO INVOKE METHOD OF ACTIVE OBJECT	Failed to invoke method "%1" of the Active Object
-79973	SAP GUI SUCCEEDED TO INVOKE METHOD OF ACTIVE OBJECT	Invoked method "%1" of the Active Object
-79972	SAP GUI FAILED TO CHANGE PROPERTY OF ACTIVE OBJECT	Failed to change property "%1" of Active Object to "%2"
-79971	SAP GUI SUCCEEDED TO SET PROPERTY OF ACTIVE OBJECT	Property "%1" of Active Object set to "%2"
-79970	SAP GUI FAILED TO GET PROPERTY OF ACTIVE OBJECT	Failed to get property "%1" of Active Object
-79969	SAP GUI SUCCEEDED TO INVOKE GUI COMPONENT METHOD	Invoked "%1" method of "%2" SapGui component
-79968	SAP GUI FAILED TO INVOKE GUI COMPONENT METHOD	Failed to invoke "%1" method of "%2" SapGui component
-79967	SAP GUI LOG ON SUCCEEDED TO OPEN NEW CONNECTION	Opened new connection to server "%1"
-79966	SAP GUI LOG ON NO ACTIVE CONNECTION	There's no open connection available
-79965	SAP GUI LOG ON FAILED TO OPEN NEW CONNECTION	Failed to open new connection to server "%1" due to: "%2"
-79964	SAP GUI LOG ON FAILED TO OPEN NEW CONNECTION EXCEPTION	Failed to open new connection to server "%1"
-79963	SAP GUI LOG ON DETECTED USER ALREADY LOGGED ON	Logon: User "%1" is already logged on using client "%2"
-79962	SAP GUI LOG ON SUCCEEDED	Logged on as "%1"
-79961	SAP GUI LOG ON WRONG PARAMS	Logon failed. Verify that the username and password that you provided are valid
-79960	SAP GUI FAILED TO GET CLIENT NUM FIELD	Failed to find ClientNum field in Logon dialog
-79959	SAP GUI FAILED TO GET USER NAME FIELD	Failed to find UserName field in Logon dialog
-79958	SAP GUI FAILED TO GET PASSWORD FIELD	Failed to find Password field in Logon dialog
-79957	SAP GUI FAILED TO GET LANGUAGE FIELD	Failed to find Language field in Logon dialog
-79956	SAP GUI SUCCEEDED TO SET ACTIVE SSESSEION	Selected active session "%1"
-79955	SAP GUI FAILED TO SET ACTIVE SSESSEION	Failed to select active session "%1"
-79954	SAP GUI SUCCEEDED TO SET ACTIVE WINDOW	Selected active window "%1"
-79953	SAP GUI FAILED TO SET ACTIVE WINDOW	Failed to select active window "%1"
-79952	SAP GUI FAILED TO GET ACTIVE SESSION	Failed to get active session
-79951	SAP GUI FAILED TO GET ACTIVE WINDOW	Failed to get active window
-79950	SAP GUI FAILED TO GET ACTIVE CONNECTION	Failed to get active connection
-79949	SAP GUI FAILED TO GET ACTIVE USER AREA	Failed to get active user area
-79948	SAP GUI SUCCEEDED TO GET WINDOW TITLE	The title of the active window is "%1"
-79947	SAP GUI FAILED TO GET WINDOW TITLE	Failed to get title of the active window
-79946	SAP GUI SUCCEEDED TO GET STATUS BAR TEXT	The text of the status bar is "%1"
-79945	SAP GUI FAILED TO GET STATUS BAR TEXT	Failed to get the status bar text
-79944	SAP GUI UNEXPECTED EXCEPTION	Unexpected exception was thrown from "%1" SapGui object
-79943	SAP GUI HISTORY VALUE	SapGui Original History Value is % 1 Id
-79942	SAP GUI STATUS BAR TEXT ON ERROR	Additional info: the text of the status bar is "%1"
-79941	SAP GUI WINDOW TITLE ON ERROR	Additional info: the title of the active window is "%1"

Error code	Handle	Message\Additional information
-79940	SAP GUI SUCCEEDED TO SET ACTIVE CONNECTION	Selected active connection "%1"
-79939	SAP GUI FAILED TO SET ACTIVE CONNECTION	Failed to select active connection "%1"
-79938	SAP GUI CONNECTION WAS ALREADY OPENED	Connection with the name "%1" was already opened.
-79937	SAP GUI OBJECT NOT EXIST	Object "%1" does not exist
-79936	SAP GUI OBJECT EXIST	Object "%1" exists
-79935	SAP GUI SUCCEEDED TO GET STATUS BAR PARAM	The value of parameter % 1 Id in the status bar is "%2"
-79934	SAP GUI STATUS BAR PARAM OUT OF RANGE	The status bar has parameters % 1 Id to % 2 Id. Enter valid index
-79933	SAP GUI SUCCEEDED TO GET STATUS BAR TYPE	The type of the status bar is "%1"
-79932	SAP GUI TABLE COMPONENT IS NOT VALID TABLE	SapGui component "%1" is not a table
-79931	SAP GUI TABLE CANT FIND COMPONENT IN CELL	Table - Failed to find SapGui component at position (%1, %2)
-79930	SAP GUI SUCCEEDED TO FIND COMPONENT IN CELL	Table - Found SapGui component at position (%1, %2)
-79929	SAP GUI OBJECT IS NOT A VALID OBJECT	Table - SapGui component at position (%2, %3) is not a valid %1
-79928	SAP GUI TABLE FAILED TO GET ROW	Table - Failed to find row %1
-79927	SAP GUI TABLE SUCCEEDED TO GET ROW	Table - Found row %1
-79926	SAP GUI TABLE FAILED TO SET ROW SELECTED	Table - Failed to change state of row %1 to %2
-79925	SAP GUI TABLE SUCCEEDED TO SET ROW SELECTED	Table - Changed the state of row %1 to %2
-79924	SAP GUI TABLE SUCCEEDED TO INVOKE METHOD	Table - Invoked method "%2" of %1 at position (%3, %4)
-79923	SAP GUI TABLE SUCCEEDED TO SET PROPERTY	Table Set property "%2" of %1 at position (%3, %4) to "%5"
-79922	SAP GUI TABLE SUCCEEDED TO SET FOCUS	Table - Set focus on "%1"
-79921	SAP GUI TABLE FAILED TO SET FOCUS	Table - Failed to set focus on "%1"
-79920	SAP GUI TABLE SUCCEEDED TO GET PROPERTY	Table - The value of property "%1" of the %2 at position (%4, %5) is "%3"
-79919	SAP GUI TABLE FAILED TO GET ROW SELECTED	Table - Failed to get "Selected" property of row %1
-79918	SAP GUI TABLE SUCCEEDED TO GET ROW SELECTED	Table - The value of "Selected" property of row %1 is %2
-79917	SAP GUI CHANGEABLE OBJECT	Object "%1" is changeable
-79916	SAP GUI NOT CHANGEABLE OBJECT	Object "%1" is not changeable
-79915	SAP GUI SELECTED TAB	Tab "%1" is selected
-79914	SAP GUI NOT SELECTED TAB	Tab "%1" is not selected
-79913	SAP GUI GENERAL UNEXPECTED EXCEPTION	Unexpected exception was thrown from SapGui object
-79912	SAP GUI SAPGUI SCRIPTING IS DISABLED	Failed - User scripting is disabled in SAPLogon
-79911	SAP GUI SAPGUI SCRIPTING NOTIFICATION IS DISABLED	Failed - Notifications of user scripting are enabled SAPLogon
-79910	SAP GUI SNAPSHOT NOT EXIST	Snapshot "%1" does not exist
-79909	SAP GUI SUCCEEDED TO SET OK CODE	Set OKCode "%1"
-79908	SAP GUI FAILED TO SET OK CODE	Failed to set OKCode "%1"
-79907	SAP GUI SUCCEEDED TO GET OK CODE	The text of OKCode is "%1"
-79906	SAP GUI FAILED TO GET OK CODE	Failed to get OKCode
-79905	SAP GUI SUCCEEDED TO PRESS BUTTON	Pressed button "%1"
-79904	SAP GUI FAILED TO PRESS BUTTON	Failed to press button "%1"
-79903	SAP GUI SUCCEEDED TO SELECT RADIO BUTTON	Selected radio button "%1"
-79902	SAP GUI FAILED TO SELECT RADIO BUTTON	Failed to select radio button "%1"
-79901	SAP GUI SUCCEEDED TO GET RADIO BUTTON STATE	Radio button "%2" is %1
-79900	SAP GUI FAILED TO GET RADIO BUTTON STATE	Failed to get state of radio button "%1"
-79899	SAP GUI SUCCEEDED TO SET PASSWORD	Set password "%1"
-79898	SAP GUI FAILED TO SET PASSORD	Failed to set password "%1"
-79897	SAP GUI SUCCEEDED TO SET TEXT	Set text of "%1" to "%2"
-79896	SAP GUI FAILED TO SET TEXT	Failed to set text of "%1" to "%2"
-79895	SAP GUI SUCCEEDED TO GET TEXT	The text of "%2" is "%1"
-79894	SAP GUI FAILED TO GET TEXT	Failed to get text "%1"
-79893	SAP GUI SUCCEEDED TO SELECT MENU	Selected menu item "%1"
-79892	SAP GUI FAILED TO SELECT MENU	Failed to select menu item "%1"
-79891	SAP GUI SUCCEEDED TO SELECT TAB	Selected tab "%1"
-79890	SAP GUI FAILED TO SELECT TAB	Failed to select tab "%1"
-79889	SAP GUI SUCCEEDED TO SET CHECKBOX	Set checkbox "%1" to "%2"
-79888	SAP GUI FAILED TO SET CHECKBOX	Failed to set checkbox "%1" to "%2"
-79887	SAP GUI SUCCEEDED TO GET CHECKBOX STATE	Got state of checkbox "%1"
-79886	SAP GUI FAILED TO GET CHECKBOX STATE	Failed to get state of checkbox "%1"
-79885	SAP GUI SUCCEEDED TO SELECT COMBOBOX	Selected combobox entry "%1"
-79884	SAP GUI FAILED TO SELECT COMBOBOX	Failed to select combobox entry "%1"

Error code	Handle	Message\Additional information
-79883	SAP GUI SUCCEEDED TO SET FOCUS	Set focus on "%1"
-79882	SAP GUI FAILED TO SET FOCUS	Failed to set focus on "%1"
-79881	SAP GUI SUCCEEDED TO SEND VKEY	Sent virtual key "%1"
-79880	SAP GUI FAILED TO SEND VKEY	Failed to send virtual key "%1"
-79879	SAP GUI SUCCEEDED TO RESIZE WINDOW	Resized window to %1x%2
-79878	SAP GUI FAILED TO RESIZE WINDOW	Failed to resize window to %1x%2
-79877	SAP GUI FAILED TO GET OBJECT CHANGEABLE	Failed to get changeable status of "%1"
-79876	SAP GUI FAILED TO GET TAB SELECTED	Failed to get selected status of "%1"
-79875	SAP GUI GRID CLEAR SELECTION SUCCEEDED	Grid - Cleared selection
-79874	SAP GUI GRID CLEAR SELECTION FAILED	Grid - Failed to clear selection
-79873	SAP GUI GRID PRESS COLUMN HEADER SUCCEEDED	Grid - Pressed header of column "%1"
-79872	SAP GUI GRID PRESS COLUMN HEADER FAILED	Grid - Failed to press header of column "%1"
-79871	SAP GUI GRID SELECT CELL SUCCEEDED	Grid - Selected cell "%1"
-79870	SAP GUI GRID SELECT CELL FAILED	Grid - Failed to select cell "%1"
-79869	SAP GUI GRID SELECT ROWS SUCCEEDED	Grid - Selected rows "%1"
-79868	SAP GUI GRID SELECT ROWS FAILED	Grid - Failed to select rows "%1"
-79867	SAP GUI GRID SELECT COLUMNS SUCCEEDED	Grid - Selected columns "%1"
-79866	SAP GUI GRID SELECT COLUMNS FAILED	Grid - Failed to select columns "%1"
-79865	SAP GUI GRID SELECT CELLS SUCCEEDED	Grid - Selected cells "%1"
-79864	SAP GUI GRID SELECT CELLS FAILED	Grid - Failed to select cells "%1"
-79863	SAP GUI GRID SET COLUMN ORDER SUCCEEDED	Grid - Set column order "%1"
-79862	SAP GUI GRID SET COLUMN ORDER FAILED	Grid - Failed to set column order "%1"
-79861	SAP GUI GRID SELECT CELL ROW SUCCEEDED	Grid - Selected the cell in row "%1"
-79860	SAP GUI GRID SELECT CELL ROW FAILED	Grid - Failed to select the cell in row "%1"
-79859	SAP GUI GRID SELECT CELL COLUMN SUCCEEDED	Grid - Selected the cell in column "%1"
-79858	SAP GUI GRID SELECT CELL COLUMN FAILED	Grid - Failed to select the cell in column "%1"
-79857	SAP GUI GRID SCROLL TO ROW SUCCEEDED	Grid - Scrolled to row "%1"
-79856	SAP GUI GRID SCROLL TO ROW FAILED	Grid - Failed to scroll to row "%1"
-79855	SAP GUI GRID DOUBLE CLICK SUCCEEDED	Grid - Double clicked on "%1"
-79854	SAP GUI GRID DOUBLE CLICK FAILED	Grid - Failed to double click on "%1"
-79853	SAP GUI GRID CLICK SUCCEEDED	Grid - Clicked on "%1"
-79852	SAP GUI GRID CLICK FAILED	Grid - Failed to click on "%1"
-79851	SAP GUI GRID PRESS BUTTON SUCCEEDED	Grid - Pressed button "%1"
-79850	SAP GUI GRID PRESS BUTTON FAILED	Grid - Failed to press button "%1"
-79849	SAP GUI GRID PRESS TOTAL ROW SUCCEEDED	Grid - Pressed total row button "%1"
-79848	SAP GUI GRID PRESS TOTAL ROW FAILED	Grid - Failed to press total row button "%1"
-79847	SAP GUI GRID SET CELL DATA SUCCEEDED	Grid - Set cell data "%1" to "%2"
-79846	SAP GUI GRID SET CELL DATA FAILED	Grid - Failed to set cell data "%1" to "%2"
-79845	SAP GUI GRID SET CHECKBOX SUCCEEDED	Grid - Modified checkbox "%1" to "%2"
-79844	SAP GUI GRID SET CHECKBOX FAILED	Grid - Failed to modify checkbox "%1" to "%2"
-79843	SAP GUI GRID DOUBLE CLICK CURRENT SUCCEEDED	Grid - Double clicked on current cell
-79842	SAP GUI GRID DOUBLE CLICK CURRENT FAILED	Grid - Failed to double click on current cell
-79841	SAP GUI GRID CLICK CURRENT SUCCEEDED	Grid - Clicked on current cell
-79840	SAP GUI GRID CLICK CURRENT FAILED	Grid - Failed to click on current cell
-79839	SAP GUI GRID PRESS BUTTON CURRENT SUCCEEDED	Grid - Pressed button in current cell
-79838	SAP GUI GRID PRESS BUTTON CURRENT FAILED	Grid - Failed to press button in current cell
-79837	SAP GUI GRID PRESS TOTAL ROW CURRENT SUCCEEDED	Grid - Pressed total row button in current cell
-79836	SAP GUI GRID PRESS TOTAL ROW CURRENT FAILED	Grid - Failed to press total row button in current cell
-79835	SAP GUI GRID PRESS F1 SUCCEEDED	Grid - Pressed "F1" key
-79834	SAP GUI GRID PRESS F1 FAILED	Grid - Failed to press "F1" key
-79833	SAP GUI GRID PRESS F4 SUCCEEDED	Grid - Pressed "F4" key
-79832	SAP GUI GRID PRESS F4 FAILED	Grid - Failed to press "F4" key
-79831	SAP GUI GRID PRESS ENTER SUCCEEDED	Grid - Pressed "ENTER" key
-79830	SAP GUI GRID PRESS ENTER FAILED	Grid - Failed to press "ENTER" key
-79829	SAP GUI GRID PRESS TOOLBAR BUTTON SUCCEEDED	Grid - Pressed toolbar button "%1"
-79828	SAP GUI GRID PRESS TOOLBAR BUTTON FAILED	Grid - Failed to press toolbar button "%1"
-79827	SAP GUI GRID PRESS TOOLBAR CONTEXT BUTTON SUCCEEDED	Grid - Pressed toolbar context button "%1"

Error code	Handle	Message\Additional information
-79826	SAP GUI GRID PRESS TOOLBAR CONTEXT BUTTON FAILED	Grid - Failed to press toolbar context button "%1"
-79825	SAP GUI GRID OPEN CONTEXT MENU SUCCEEDED	Grid - Opened context menu
-79824	SAP GUI GRID OPEN CONTEXT MENU FAILED	Grid - Failed to open context menu
-79823	SAP GUI GRID SELECT CONTEXT MENU SUCCEEDED	Grid - Selected context menu item "%1"
-79822	SAP GUI GRID SELECT CONTEXT MENU FAILED	Grid - Failed to select context menu item "%1"
-79821	SAP GUI GRID SELECT TOOLBAR MENU SUCCEEDED	Grid - Selected toolbar menu item "%1"
-79820	SAP GUI GRID SELECT TOOLBAR MENU FAILED	Grid - Failed to select toolbar menu item "%1"
-79819	SAP GUI GRID GET CURRENT CELL ROW SUCCEEDED	Grid - Current cell row is "%1"
-79818	SAP GUI GRID GET CURRENT CELL ROW FAILED	Grid - Failed to get current cell row "%1"
-79817	SAP GUI GRID GET CURRENT CELL COLUMN SUCCEEDED	Grid - Current cell column is "%1"
-79816	SAP GUI GRID GET CURRENT CELL COLUMN FAILED	Grid - Failed to get current cell column "%1"
-79815	SAP GUI GRID GET CELL DATA SUCCEEDED	Grid - The data of cell "%2" is "%1"
-79814	SAP GUI GRID GET CELL DATA FAILED	Grid - Failed to get cell data "%1"
-79813	SAP GUI GRID GET CHECKBOX STATE SUCCEEDED	Grid - Checkbox "%2" is %1
-79812	SAP GUI GRID GET CHECKBOX STATE FAILED	Grid - Failed to get state of checkbox "%1"
-79811	SAP GUI TREE SCROLL TO NODE SUCCEEDED	Tree - Scrolled to node "%1"
-79810	SAP GUI TREE SCROLL TO NODE FAILED	Tree - Failed to scroll to node "%1"
-79809	SAP GUI TREE SET H HEADER WIDTH SUCCEEDED	Tree - Set hierarchy header width to "%1"
-79808	SAP GUI TREE SET H HEADER WIDTH FAILED	Tree - Failed to set hierarchy header width to "%1"
-79807	SAP GUI TREE SET SELECTED NODE SUCCEEDED	Tree - Selected node "%1"
-79806	SAP GUI TREE SET SELECTED NODE FAILED	Tree - Failed to select node "%1"
-79805	SAP GUI TREE DOUBLE CLICK NODE SUCCEEDED	Tree - Double clicked node "%1"
-79804	SAP GUI TREE DOUBLE CLICK NODE FAILED	Tree - Failed to double click node "%1"
-79803	SAP GUI TREE PRESS KEY SUCCEEDED	Tree - Pressed key "%1"
-79802	SAP GUI TREE PRESS KEY FAILED	Tree - Failed to press key "%1"
-79801	SAP GUI TREE PRESS BUTTON SUCCEEDED	Tree - Pressed button "%1"
-79800	SAP GUI TREE PRESS BUTTON FAILED	Tree - Failed to press button "%1"
-79799	SAP GUI TREE SET CHECKBOX SUCCEEDED	Tree - Set checkbox state "%1" to "%2"
-79798	SAP GUI TREE SET CHECKBOX FAILED	Tree - Failed to set checkbox state "%1" to "%2"
-79797	SAP GUI TREE DOUBLE CLICK ITEM SUCCEEDED	Tree - Double clicked item "%1"
-79796	SAP GUI TREE DOUBLE CLICK ITEM FAILED	Tree - Failed to double click item "%1"
-79795	SAP GUI TREE CLICK LINK SUCCEEDED	Tree - Clicked link "%1"
-79794	SAP GUI TREE CLICK LINK FAILED	Tree - Failed to click link "%1"
-79793	SAP GUI TREE OPEN DEFAULT CONTEXT MENU SUCCEEDED	Tree - Opened default context menu
-79792	SAP GUI TREE OPEN DEFAULT CONTEXT MENU FAILED	Tree - Failed to open default context menu
-79791	SAP GUI TREE OPEN NODE CONTEXT MENU SUCCEEDED	Tree - Opened context menu of node "%1"
-79790	SAP GUI TREE OPEN NODE CONTEXT MENU FAILED	Tree - Failed to open context menu of node "%1"
-79789	SAP GUI TREE OPEN HEADER CONTEXT MENU SUCCEEDED	Tree - Opened context menu of header "%1"
-79788	SAP GUI TREE OPEN HEADER CONTEXT MENU FAILED	Tree - Failed to open context menu of header "%1"
-79787	SAP GUI TREE OPEN ITEM CONTEXT MENU SUCCEEDED	Tree - Opened context menu of item "%1"
-79786	SAP GUI TREE OPEN ITEM CONTEXT MENU FAILED	Tree - Failed to open context menu of item "%1"
-79785	SAP GUI TREE SELECT ITEM SUCCEEDED	Tree - Selected item "%1"
-79784	SAP GUI TREE SELECT ITEM FAILED	Tree - Failed to select item "%1"
-79783	SAP GUI TREE SELECT NODE SUCCEEDED	Tree - Selected node "%1"
-79782	SAP GUI TREE SELECT NODE FAILED	Tree - Failed to select node "%1"
-79781	SAP GUI TREE UNSELECT NODE SUCCEEDED	Tree - Unselected node "%1"
-79780	SAP GUI TREE UNSELECT NODE FAILED	Tree - Failed to unselect node "%1"
-79779	SAP GUI TREE UNSELECT ALL SUCCEEDED	Tree - Unselected all items
-79778	SAP GUI TREE UNSELECT ALL FAILED	Tree - Failed to unselect all items
-79777	SAP GUI TREE SELECT COLUMN SUCCEEDED	Tree - Selected column "%1"
-79776	SAP GUI TREE SELECT COLUMN FAILED	Tree - Failed to select column "%1"
-79775	SAP GUI TREE UNSELECT COLUMN SUCCEEDED	Tree - Unselected column "%1"
-79774	SAP GUI TREE UNSELECT COLUMN FAILED	Tree - Failed to unselect column "%1"
-79773	SAP GUI TREE COLLAPSE NODE SUCCEEDED	Tree - Collapsed node "%1"
-79772	SAP GUI TREE COLLAPSE NODE FAILED	Tree - Failed to collapse node "%1"
-79771	SAP GUI TREE EXPAND NODE SUCCEEDED	Tree - Expanded node "%1"
-79770	SAP GUI TREE EXPAND NODE FAILED	Tree - Failed to expand node "%1"

Error code	Handle	Message\Additional information
-79769	SAP GUI TREE SCROLL TO ITEM SUCCEEDED	Tree - Scrolled to item "%1"
-79768	SAP GUI TREE SCROLL TO ITEM FAILED	Tree - Failed to scroll to item "%1"
-79767	SAP GUI TREE SET COLUMN WIDTH SUCCEEDED	Tree - Set column width to "%1"
-79766	SAP GUI TREE SET COLUMN WIDTH FAILED	Tree - Failed to set column width to "%1"
-79765	SAP GUI TREE PRESS HEADER SUCCEEDED	Tree - Pressed header "%1"
-79764	SAP GUI TREE PRESS HEADER FAILED	Tree - Failed to press header "%1"
-79763	SAP GUI TREE GET CHECKBOX STATE SUCCEEDED	Tree - Checkbox "%2" is %1
-79762	SAP GUI TREE GET CHECKBOX STATE FAILED	Tree - Failed to get state of checkbox "%1"
-79761	SAP GUI TREE GET NODE TEXT SUCCEEDED	Tree - Text of node "%2" is "%1"
-79760	SAP GUI TREE GET NODE TEXT FAILED	Tree - Failed to get text of node "%1"
-79759	SAP GUI TREE GET ITEM TEXT SUCCEEDED	Tree - Text of item "%2" is "%1"
-79758	SAP GUI TREE GET ITEM TEXT FAILED	Tree - Failed to get text of item "%1"
-79757	SAP GUI TABLE PRESS BUTTON SUCCEEDED	Table - Pressed button "%1"
-79756	SAP GUI TABLE PRESS BUTTON FAILED	Table - Failed to press button "%1"
-79755	SAP GUI TABLE SELECT RADIO BUTTON SUCCEEDED	Table - Selected radio button "%1"
-79754	SAP GUI TABLE SELECT RADIO BUTTON FAILED	Table - Failed to select radio button "%1"
-79753	SAP GUI TABLE SET PASSWORD SUCCEEDED	Table - Set password "%1"
-79752	SAP GUI TABLE SET PASSWORD FAILED	Table - Failed to set password "%1"
-79751	SAP GUI TABLE SET TEXT SUCCEEDED	Table - Set text of "%1" to "%2"
-79750	SAP GUI TABLE SET TEXT FAILED	Table - Failed to set text of "%1" to "%2"
-79749	SAP GUI TABLE SET CHECKBOX SUCCEEDED	Table - Set checkbox state "%1"
-79748	SAP GUI TABLE SET CHECKBOX FAILED	Table - Failed to set checkbox state "%1"
-79747	SAP GUI TABLE SELECT COMBO SUCCEEDED	Table - Selected combobox entry "%1"
-79746	SAP GUI TABLE SELECT COMBO FAILED	Table - Failed to select combobox entry "%1"
-79745	SAP GUI TABLE GET TEXT SUCCEEDED	Table - Text of cell "%2" is "%1"
-79744	SAP GUI TABLE GET TEXT FAILED	Table - Failed to get text of cell "%1"
-79743	SAP GUI TABLE GET RADIO STATE SUCCEEDED	Table - Radio button "%2" is %1
-79742	SAP GUI TABLE GET RADIO STATE FAILED	Table - Failed to get state of radio button "%1"
-79741	SAP GUI TABLE GET CHECKBOX STATE SUCCEEDED	Table - Checkbox "%2" is %1
-79740	SAP GUI TABLE GET CHECKBOX STATE FAILED	Table - Failed to get state of checkbox "%1"
-79739	SAP GUI TABLE GET ROW STATE SUCCEEDED	Table - Row %2 is %1
-79738	SAP GUI TABLE GET RPW STATE FAILED	Table - Failed to get state of row "%1"
-79737	SAP GUI CALENDAR FOCUS DATE SUCCEEDED	Calendar - Set focus on date "%1"
-79736	SAP GUI CALENDAR FOCUS DATE FAILED	Calendar - Failed to set focus on date "%1"
-79735	SAP GUI CALENDAR SCROLL TO DATE SUCCEEDED	Calendar - Scrolled to date "%1"
-79734	SAP GUI CALENDAR SCROLL TO DATE FAILED	Calendar - Failed to scroll to date "%1"
-79733	SAP GUI CALENDAR SELECT INTERVAL SUCCEEDED	Calendar - Selected interval "%1"
-79732	SAP GUI CALENDAR SELECT INTERVAL FAILED	Calendar - Failed to select interval "%1"
-79731	SAP GUI HTML SEND EVENT SUCCEEDED	HTML Viewer - Sent event "%1"
-79730	SAP GUI HTML SEND EVENT FAILED	HTML Viewer - Failed to send event "%1"
-79729	SAP GUI TOOLBAR PRESS BUTTON SUCCEEDED	Toolbar - Pressed button "%1"
-79728	SAP GUI TOOLBAR PRESS BUTTON FAILED	Toolbar - Failed to press button "%1"
-79727	SAP GUI TOOLBAR PRESS CONTEXT BUTTON SUCCEEDED	Toolbar - Pressed context button "%1"
-79726	SAP GUI TOOLBAR PRESS CONTEXT BUTTON FAILED	Toolbar - Failed to press context button "%1"
-79725	SAP GUI TOOLBAR SELECT MENU SUCCEEDED	Toolbar - Selected menu item "%1"
-79724	SAP GUI TOOLBAR SELECT MENU FAILED	Toolbar - Failed to select menu item "%1"
-79723	SAP GUI TOOLBAR SELECT CONTEXT MENU SUCCEEDED	Toolbar - Selected context menu item "%1"
-79722	SAP GUI TOOLBAR SELECT CONTEXT MENU FAILED	Toolbar - Failed to select context menu item "%1"
-79721	SAP GUI TABLE SET ROW SELECTED TRUE SUCCESS	Table - Selected row %1
-79720	SAP GUI TABLE SET ROW SELECTED FALSE SUCCESS	Table - Unselected row %1
-79719	SAP GUI TABLE SET ROW SELECTED TRUE FAILED	Table - Failed to select row %1
-79718	SAP GUI TABLE SET ROW SELECTED FALSE FAILED	Table - Failed to unselect row %1
-79717	SAP GUI SET CHECKBOX TRUE SUCCESS	Selected checkbox "%1"
-79716	SAP GUI SET CHECKBOX FALSE SUCCESS	Cleared checkbox "%1"
-79715	SAP GUI SET CHECKBOX TRUE FAILED	Failed to select checkbox "%1"
-79714	SAP GUI SET CHECKBOX FALSE FAILED	Failed to clear checkbox "%1"
-79713	SAP GUI GRID SET CHECKBOX TRUE SUCCESS	Grid - Selected checkbox %1

Error code	Handle	Message\Additional information
-79712	SAP GUI GRID SET CHECKBOX FALSE SUCCESS	Grid - Cleared checkbox %1
-79711	SAP GUI GRID SET CHECKBOX TRUE FAILED	Grid - Failed to select checkbox %1
-79710	SAP GUI GRID SET CHECKBOX FALSE FAILED	Grid - Failed to clear checkbox %1
-79709	SAP GUI TREE SET CHECKBOX TRUE SUCCESS	Tree - Selected checkbox "%1"
-79708	SAP GUI TREE SET CHECKBOX FALSE SUCCESS	Tree - Cleared checkbox "%1"
-79707	SAP GUI TREE SET CHECKBOX TRUE FAILED	Tree - Failed to select checkbox "%1"
-79706	SAP GUI TREE SET CHECKBOX FALSE FAILED	Tree - Failed to clear checkbox "%1"
-79705	SAP GUI TABLE SET CHECKBOX TRUE SUCCESS	Table - Selected checkbox %1
-79704	SAP GUI TABLE SET CHECKBOX FALSE SUCCESS	Table - Cleared checkbox %1
-79703	SAP GUI TABLE SET CHECKBOX TRUE FAILED	Table - Failed to select checkbox %1
-79702	SAP GUI TABLE SET CHECKBOX FALSE FAILED	Table - Failed to clear checkbox %1
-79701	SAP GUI SCROLL_USER_AREA SUCCESS	Scrolled active window to line %1
-79700	SAP GUI SCROLL_USER_AREA FAILED	Failed to scroll active window to line %1
-79699	SAP GUI SCROLL_USER_AREA_COULD_NOT_FIND_SCROLLBAR	Failed to get scrollbar of active window
-79698	SAP GUI WINDOW MAXIMIZE SUCCESS	Maximized window
-79697	SAP GUI WINDOW MAXIMIZE FAILED	Failed to maximize window
-79696	SAP GUI WINDOW RESTORE SUCCESS	Restored window
-79695	SAP GUI WINDOW RESTORE FAILED	Failed to restore window
-79694	SAP GUI WINDOW CLOSE SUCCESS	Closed window
-79693	SAP GUI WINDOW CLOSE FAILED	Failed to close window
-79692	SAP GUI SAPLOGON IS ALREADY RUNNING	SAPLogon is running
-79691	SAP GUI SAPLOGON IS NOT RUNNING	SAPLogon is not running
-79690	SAP GUI FAILED TO RUN SAPLOGON PROCESS	Failed to start SAPLogon process
-79689	SAP GUI FAILED TO CONNECT TO APP IN NEW PROCESS	Timeout reached while connecting to SAPLogon application
-79688	SAP GUI FAILED TO CONNECT TO RUNNING SAP_APP	Failed to connect to SAPLogon application
-79687	SAP GUI FAILED TO LOCATE SAPLOGON	Could not locate the SAPLogon application. To continue, run SAPLogon manually
-79686	SAP GUI APOGRID SELECT ALL SUCCEEDED	APOGrid - Selected all
-79685	SAP GUI APOGRID SELECT ALL FAILED	APOGrid - Failed to select all
-79684	SAP GUI APOGRID CLEAR SELECTION SUCCEEDED	APOGrid - Cleared selection
-79683	SAP GUI APOGRID CLEAR SELECTION FAILED	APOGrid - Failed to clear selection
-79682	SAP GUI APOGRID SELECT CELL SUCCEEDED	APOGrid - Selected cell "%1"
-79681	SAP GUI APOGRID SELECT CELL FAILED	APOGrid - Failed to select cell "%1"
-79680	SAP GUI APOGRID DESELECT CELL SUCCEEDED	APOGrid - Deselected cell "%1"
-79679	SAP GUI APOGRID DESELECT CELL FAILED	APOGrid - Failed to deselect cell "%1"
-79678	SAP GUI APOGRID SELECT ROW SUCCEEDED	APOGrid - Selected row "%1"
-79677	SAP GUI APOGRID SELECT ROW FAILED	APOGrid - Failed to select row "%1"
-79676	SAP GUI APOGRID DESELECT ROW SUCCEEDED	APOGrid - Deselected row "%1"
-79675	SAP GUI APOGRID DESELECT ROW FAILED	APOGrid - Failed to deselect row "%1"
-79674	SAP GUI APOGRID SELECT COLUMN SUCCEEDED	APOGrid - Selected column "%1"
-79673	SAP GUI APOGRID SELECT COLUMN FAILED	APOGrid - Failed to select column "%1"
-79672	SAP GUI APOGRID DESELECT COLUMN SUCCEEDED	APOGrid - Deselected column "%1"
-79671	SAP GUI APOGRID DESELECT COLUMN FAILED	APOGrid - Failed to deselect column "%1"
-79670	SAP GUI APOGRID SCROLL TO ROW SUCCEEDED	APOGrid - Scrolled to row "%1"
-79669	SAP GUI APOGRID SCROLL TO ROW FAILED	APOGrid - Failed to scroll to row "%1"
-79668	SAP GUI APOGRID DOUBLE CLICK SUCCEEDED	APOgrid - Double clicked "%1"
-79667	SAP GUI APOGRID DOUBLE CLICK FAILED	APOgrid - Failed to double click "%1"
-79666	SAP GUI APOGRID SET CELL DATA SUCCEEDED	APOGrid - Set cell data "%1"
-79665	SAP GUI APOGRID SET CELL DATA FAILED	APOGrid - Failed to set cell data "%1"
-79664	SAP GUI APOGRID GET CELL DATA SUCCEEDED	APOGrid - The data of cell "%2" is "%1"
-79663	SAP GUI APOGRID GET CELL DATA FAILED	APOGrid - Failed to get cell data "%1"
-79662	SAP GUI APOGRID GET CELL CHANGEABLE SUCCEEDED TRUE	APOGrid - Cell "%1" is changeable
-79661	SAP GUI APOGRID GET CELL CHANGEABLE SUCCEEDED FALSE	APOGrid - Cell "%1" is not changeable
-79660	SAP GUI APOGRID GET CELL CHANGEABLE FAILED	APOgrid - Failed to get changeable status of "%1"
-79659	SAP GUI APOGRID GET CELL FORMAT SUCCEEDED	APOGrid - Format of cell "%2" is "%1"
-79658	SAP GUI APOGRID GET CELL FORMAT FAILED	APOGrid - Failed to get cell format "%1"
-79657	SAP GUI APOGRID GET CELL TOOLTIP SUCCEEDED	APOGrid - Tooltip of cell "%2" is "%1"
-79656	SAP GUI APOGRID GET CELL TOOLTIP FAILED	APOGrid - Failed to get cell tooltip "%1"

Error code	Handle	Message\Additional information
-79655	SAP GUI APOGRID PRESS ENTER SUCCEEDED	APOGrid - pressed ENTER
-79654	SAP GUI APOGRID PRESS ENTER FAILED	APOGrid - Failed to press ENTER
-79653	SAP GUI APOGRID OPEN CELL CONTEXT MENU SUCCEEDED	APOGrid - opened cell context menu "%1"
-79652	SAP GUI APOGRID OPEN CELL CONTEXT MENU FAILED	APOGrid - Failed to open cell context menu "%1"
-79651	SAP GUI APOGRID FIRST VISIBLE ROW SUCCEEDED	APOGrid - Scrolled to row "%1"
-79650	SAP GUI APOGRID FIRST VISIBLE ROW FAILED	APOGrid - Failed to scroll to row "%1"
-79649	SAP GUI APOGRID SCROLL TO COLUMN SUCCEEDED	APOGrid - Scrolled to column "%1"
-79648	SAP GUI APOGRID SCROLL TO COLUMN FAILED	APOGrid - Failed to scroll to column "%1"
-79647	SAP GUI APOGRID SELECT CONTEXT MENU ITEM SUCCEEDED	APOGrid - selected context menu item
-79646	SAP GUI APOGRID SELECT CONTEXT MENU ITEM FAILED	APOGrid - Failed to select context menu item
-79645	SAP GUI GRID FILL DATA SUCCEEDED	Grid - filled with data from Table parameter "%1"
-79644	SAP GUI GRID FILL DATA FAILED	Grid - Failed to fill with data from Table parameter "%1"
-79643	SAP GUI GRID FILL DATA ARGUMENT IS NOT PARAMETER	The "data" argument should be a name of Table parameter
-79642	SAP GUI GRID FILL DATA ARGUMENT PARAMETER NOT FOUND	"%1" is not a name of valid Table parameter
-79641	SAP GUI GRID FILL DATA FAILED TO MODIFY CELL	Grid - Failed to modify cell "(%1, '%2')"
-79640	SAP GUI GRID FILL DATA ERROR WHILE SEARCHING COLUMNS	Grid - error while reading columns' titles
-79639	SAP GUI GRID FILL DATA INSUFFICIENT NUMBER OF ROWS	The number of rows in the grid is %1. The parameter data table has %2 rows. Please adjust the number of data table rows
-79638	SAP GUI GRID FILL DATA COULD NOT FIND COLUMNS	Could not find following column(s) in the grid: %1
-79637	SAP GUI TABLE FILL DATA SUCCEEDED	Table - filled with data from Table parameter "%1"
-79636	SAP GUI TABLE FILL DATA FAILED	Table - Failed to fill with data from Table parameter "%1"
-79635	SAP GUI TABLE FILL DATA ARGUMENT IS NOT PARAMETER	The "data" argument should be a name of Table parameter
-79634	SAP GUI TABLE FILL DATA ARGUMENT PARAMETER NOT FOUND	"%1" is not a name of valid Table parameter
-79633	SAP GUI TABLE FILL DATA INSUFFICIENT NUMBER OF ROWS	The number of rows in the table is %1. The parameter data table has %2 rows. Please adjust the number of data table rows
-79632	SAP GUI TABLE FILL DATA COULD NOT FIND COLUMNS	Could not find following column(s) in the table: %1
-79631	SAP GUI TABLE FILL DATA COULD NOT MODIFY CELL	Failed to modify cell "(%1, '%2')"
-79630	SAP GUI GRID SELECT ALL SUCCEEDED	Grid - Selected all
-79629	SAP GUI GRID SELECT ALL FAILED	Grid - Failed to select all
-79628	SAP GUI GRID SELECT COLUMN SUCCEEDED	Grid - Select column "%1"
-79627	SAP GUI GRID SELECT COLUMN FAILED	Grid - Failed to select column "%1"
-79626	SAP GUI GRID DESELECT COLUMN SUCCEEDED	Grid - Deselect column "%1"
-79625	SAP GUI GRID DESELECT COLUMN FAILED	Grid - Failed to deselect column "%1"
-79624	SAP GUI GRID SELECTION CHANGED SUCCEEDED	Grid - Changed selection
-79623	SAP GUI GRID SELECTION CHANGED FAILED	Grid - Failed to change selection
-79622	SAP GUI GRID GET ROWS COUNT SUCCEEDED	Grid - The number of rows is %1
-79621	SAP GUI GRID GET ROWS COUNT FAILED	Grid - Failed to retrieve rows count
-79620	SAP GUI GRID GET COLUMNS COUNT SUCCEEDED	Grid - The number of columns is %1
-79619	SAP GUI GRID GET COLUMNS COUNT FAILED	Grid - Failed to retrieve columns count
-79618	SAP GUI TREE SELECT CONTEXT MENU ITEM SUCCEEDED	Tree - Selected context menu "%1"
-79617	SAP GUI TREE SELECT CONTEXT MENU ITEM FAILED	Tree - Failed to select context menu "%1"
-79616	SAP GUI FAILED TO SELECT OPTIONAL WINDOW	Failed to find optional window "%1". Skipping all steps for this window.
-79615	SAP GUI TEXT EDIT SET FIRST VISIBLE LINE SUCCEEDED	Text Edit - Scrolled to line "%1"
-79614	SAP GUI TEXT EDIT SET FIRST VISIBLE LINE FAILED	Text Edit - Failed to scroll to line "%1"
-79613	SAP GUI TEXT EDIT SET SELECTION INDEXES SUCCEEDED	Text Edit - Set selection indexes "%1"
-79612	SAP GUI TEXT EDIT SET SELECTION INDEXES FAILED	Text Edit - Failed to set selection indexes "%1"
-79611	SAP GUI TEXT EDIT SET UNPROTECTED TEXT PART SUCCEEDED	Text Edit - Set unprotected text part "%1"
-79610	SAP GUI TEXT EDIT SET UNPROTECTED TEXT PART FAILED	Text Edit - Failed to set unprotected text part "%1"
-79609	SAP GUI TEXT EDIT GET FIRST VISIBLE LINE SUCCEEDED	Text Edit - First visible line is %1
-79608	SAP GUI TEXT EDIT GET FIRST VISIBLE LINE FAILED	Text Edit - Failed to get first visible line
-79607	SAP GUI TEXT EDIT GET SELECTION INDEX START SUCCEEDED	Text Edit - Selection index start is %1
-79606	SAP GUI TEXT EDIT GET SELECTION INDEX START FAILED	Text Edit - Failed to get selection index start
-79605	SAP GUI TEXT EDIT GET SELECTION INDEX END SUCCEEDED	Text Edit - Selection index end is %1
-79604	SAP GUI TEXT EDIT GET SELECTION INDEX END FAILED	Text Edit - Failed to get selection index end
-79603	SAP_GUI_TEXT_EDIT_GET_NUMBER_OF_UNPROTECTED_TEXT_PARTS_SUCCEEDED	Text Edit - Number of unprotected text parts is %1
-79602	SAP_GUI_TEXT_EDIT_GET_NUMBER_OF_UNPROTECTED_TEXT_PARTS_FAILED	Text Edit - Failed to get number of unprotected text parts.
-79601	SAP_GUI_TEXT_EDIT_DOUBLE_CLICK_SUCCEEDED	Text Edit - Double clicked on "%1"

Error code	Handle	Message\Additional information
-79600	SAP GUI TEXT EDIT DOUBLE CLICK FAILED	Text Edit - Failed to double click on "%1"
-79599	SAP GUI TEXT EDIT SINGLE FILE DROPPED SUCCEEDED	Text Edit - Dropped single file "%1"
-79598	SAP GUI TEXT EDIT SINGLE FILE DROPPED FAILED	Text Edit - Failed to drop single file "%1"
-79597	SAP GUI TEXT EDIT MULTIPLE FILES DROPPED SUCCEEDED	Text Edit - Dropped multiple files
-79596	SAP GUI TEXT EDIT MULTIPLE FILES DROPPED FAILED	Text Edit - Failed to drop multiple files
-79595	SAP GUI TEXT EDIT PRESS F1 SUCCEEDED	Text Edit - Pressed "F1" key
-79594	SAP GUI TEXT EDIT PRESS F1 FAILED	Text Edit - Failed to press "F1" key
-79593	SAP GUI TEXT EDIT PRESS F4 SUCCEEDED	Text Edit - Pressed "F4" key
-79592	SAP GUI TEXT EDIT PRESS F4 FAILED	Text Edit - Failed to press "F4" key
-79591	SAP GUI TEXT EDIT OPEN CONTEXT MENU SUCCEEDED	Text Edit - Opened context menu "%1"
-79590	SAP GUI TEXT EDIT OPEN CONTEXT MENU FAILED	Text Edit - Failed to open context menu "%1"
-79589	SAP GUI TEXT EDIT SELECT CONTEXT MENU SUCCEEDED	Text Edit - Selected context menu item "%1"
-79588	SAP GUI TEXT EDIT SELECT CONTEXT MENU FAILED	Text Edit - Failed to select context menu item "%1"
-79587	SAP GUI TEXT EDIT MODIFIED STATUS CHANGED SUCCEEDED	Text Edit - Succeeded to modify status changed to "%1"
-79586	SAP GUI TEXT EDIT MODIFIED STATUS CHANGED FAILED	Text Edit - Succeeded to modify status changed to "%1"
-79585	SAP GUI SUCCEEDED TO STORE ACTIVE OBJECT FROM METHOD	Set Active Object from method "%1" of SapGui Component "%2"
-79584	SAP GUI SUCCEEDED TO STORE ACTIVE OBJECT FROM PROPERTY	Set Active Object from property "%1" of SapGui Component "%2"
-79583	SAP GUI GIVEN PASSWORD IS RECORDED ASTERIKS	The password you supplied is "%1". Please verify that it is correct
-79582	SAP GUI CONTROL IS NOT VALID COMBOBOX	SapGui component "%1" is not a valid combobox
-79581	SAP GUI COULD NOT SELECT COMBOBOX ENTRY BY KEY	Could not find combobox entry by key "%1"
-79580	SAP GUI COULD NOT SELECT COMBOBOX ENTRY BY VALUE	Could not find combobox entry by value "%1"
-79579	SAP GUI TABLE FAILED TO REORDER	Table - Failed to reorder %1
-79578	SAP GUI TABLE SUCCEEDED TO REORDER	Table - Reorder succeeded %1
-79577	SAP GUI TABLE SET COLUMN SELECTED TRUE SUCCESS	Table - Selected column "%1"
-79576	SAP GUI TABLE SET COLUMN SELECTED FALSE SUCCESS	Table - Unselected column "%1"
-79575	SAP GUI TABLE SET COLUMN SELECTED TRUE FAILED	Table - Failed to select column "%1"
-79574	SAP GUI TABLE SET COLUMN SELECTED FALSE FAILED	Table - Failed to unselect column "%1"
-79573	SAP GUI TABLE FAILED TO GET COLUMN	Table - Failed to find column %1
-79572	SAP GUI TABLE SUCCEEDED TO GET COLUMN	Table - Found column %1
-79571	SAP GUI TABLE GET COLUMN STATE SUCCEEDED	Table - Column %2 is %1
-79570	SAP GUI TABLE GET CPW STATE FAILED	Table - Failed to get state of column "%1"
-79569	SAP GUI TABLE SET COLUMN WIDTH FAILED	Table - Failed to set width of column "%1" to %2
-79568	SAP GUI TABLE SET COLUMN WIDTH SUCCESS	Table - Set width of column "%1" to %2
-79567	SAP GUI TABLE GET COLUMN WIDTH FAILED	Table - Failed to get width of column "%1"
-79566	SAP GUI TABLE GET COLUMN WIDTH SUCCESS	Table - The width of column "%2" is %1
-79565	SAP GUI TABLE SCROLLED TO ROW	Table - Scrolled to row %1
-79564	SAP GUI GRID SET COLUMN WIDTH SUCCEEDED	Grid - Set width of column "%1" to %2"
-79563	SAP GUI GRID SET COLUMN WIDTH FAILED	Grid - Failed to set column width "%1"
-79562	SAP GUI TREE SET COLUMN ORDER SUCCEEDED	Tree - Set column order "%1"
-79561	SAP GUI TREE SET COLUMN ORDER FAILED	Tree - Failed to set column order "%1"
-79560	SAP GUI TREE OPTIONAL NO VALUE	Tree - No optional parameters
-79559	SAP GUI TREE OPTIONAL FAILED TO FIND PATH	Tree - Optional Parameter - Failed to find "%1" in path "%2"
-79558	SAP GUI TREE OPTIONAL FAILED TO FIND KEY FROM PATH	Tree - Optional Parameter - Failed to retrieve the key from path "%1"
-79557	SAP GUI TREE OPTIONAL SUCCEES TO FIND KEY FROM PATH	Tree - Optional Parameter - Substituting key "%2" from path "%1"
-79556	SAP GUI SUCCEEDED TO INVOKE METHOD AND GET RET VAL	Method "%2" of "%3" SapGui component returns "%1"
-79555	SAP GUI SUCCEEDED TO INVOKE METHOD OF ACTIVE OBJECT AND GET RET VAL	Method "%2" of the Active Object returns "%1"
-79554	SAP GUI SUCCEEDED TO GET PROPERTY OF ACTIVE OBJECT	The value of property "%1" of the Active Object is "%2"
-79553	SAP GUI FAILED TO CONVERT VARIANT TO BSTR	Failed to save variant value to parameter "%1". Cannot convert the variant to BSTR.
-79552	SAP GUI HTML GET DOM OBJECT DOESNT EXIST	HTML Viewer - Failed to find object "%1"
-79551	SAP GUI HTML GET DOM OBJECT SUCCESS	HTML Viewer - The value of "%1" is "%2"
-79550	SAP GUI HTML DOC COMPLETE FAILED	HTML Viewer - Failed to get "DocumentComplete" property
-79549	SAP GUI USER IS COLORED FOR BD	SAP Diagnostics is enabled for Vuser
-79548	SAP GUI FAILED TO INITIALIZE SESSION LISTENER	No SAP Diagnostics data will be reported - failed to initialize
-79547	SAP GUI NO TRANS ID PROPERTY IN SESSION OBJECT	No SAP Diagnostics data will be reported - failed to find TransID property in Session object
-79546	SAP GUI EMPTY TRANS ID	No SAP Diagnostics data will be reported - TransID property is not supported by SAP server

Error code	Handle	Message\Additional information
-79545	SAP_GUI_WARNING_SAME_TRANS_ID_IN_ITERATIONS	Same Transaction ID was generated for Dialog Steps in different iterations. This has no effect on Vuser, but may cause inaccuracy of SAP breakdown.
-79544	SAP_GUI_FAILED_TO_REPORT_ERROR	Failed to report SapGui error.
-79543	SAP_GUI_SUCCEEDED_SELECT_FILE	Selected the file "%1".
-79542	SAP_GUI_PAUSE_ON_ERROR_MSG	Error detected and script paused. \nPress OK to continue the script execution.
-79541	SAP_GUI_PAUSE_ON_ERROR_TITLE	Script Paused on Error
sdk_res.h		
-202799	SDK_INTERNAL_ERROR	Internal Error (call customer services): %1
-202798	SDK_ARG_MISSING_EMPTY	The "%1" argument is missing
-202797	SDK_CROSS_ARG_FAILED	The cross-argument verification failed
-202796	SDK_ARG_SPECIFIED_ALREADY	The "%1" argument (#% 2 _ld) was specified more than once.
-202795	SDK_ARG_UNRECOG	The "%1" argument (#% 2 _ld) is invalid or unrecognized
-202794	SDK_ARG_NOT_FOUND	"%1" is not a formal argument of this API function
-202793	SDK_ARG_NOT_BOOLEAN	The "%1" argument (#% 2 _ld) does not specify a valid Boolean value (e.g. "true", "false", "on", "off", "yes", "no", "1", "0")
-202792	SDK_ARG_NOT_NUMERIC	Failed to convert the "%1" argument (#% 2 _ld) to a number
-202791	SDK_VERIFICATION_FAILED	Verification failed for "%1" argument (#% 2 _ld)
-202790	SDK_STEP_STARTED	%1 started
-202789	SDK_STEP_SUCCESSFUL	%1 was successful
-202788	SDK_STEP_WARNING_END_STATUS	There was a warning during the %1
-202787	SDK_STEP_ERROR_END_STATUS	There was an error during the %1
-202786	SDK_ACCESSING_ARG_BEFORE_PARSING_COMPLETE	The access to argument ("%1") failed because argument parsing is not completed.
-202785	SDK_REPORT_MSG_STEP_FAILED	%1 failed
-202784	SDK_REPORT_STEP_SUCCEEDED_DETAILS	%1 was successful
security_key_res.h		
-205270	SECURITY_KEY_MESSAGE_KEY_LENGTH	Key length must be 6-16 characters.
silk_ext_msg.h		
-239999	SILK_EXT_GENERIC_MSG	1%
sps_api_res.h		
-240999	SPS_MSG_FAILED_TO_CONNECT	%1: Failed to connect to the server. Please check the protocol (http or https), server name, port number, instance name, network connectivity, or that VTS server version 11.52 or later is running.
-240998	SPS_MSG_INVALID_API_CALL	%1: Failed to get the API entry.
-240997	SPS_MSG_INVALID_ARGUMENT	%1: Invalid argument.
-240996	SPS_MSG_HANDLE_NOT_EXIST	%1: Connection handle doesn't exist.
-240995	SPS_MSG_INNER_JSON_CONVERT	%1: Cannot parse server response.
-240994	SPS_MSG_INNER_UTF8_CONVERT	%1: Can not convert between UTF8 and Locale.
-240993	SPS_MSG_COL_FORMAT_ERROR	%1: Invalid or empty column name.
-240992	SPS_MSG_COL_VALUE_NO_MATCH	%1: Unequal number of values in list of column names and messages list. Check delimiters.
-240991	SPS_MSG_LOAD_LIB_FAIL	Cannot load the library %1.
-240990	SPS_MSG_SERVER_ERROR	%1: Server error - %2
-240989	SPS_MSG_CA_VERIFY_FAILED	%1: Failed to connect to the server. The security certificate presented by this server was not issued by the specified certificate authority.
-240988	SPS_MSG_INVALID_CERT	%1: Failed to connect to the server. Please provide a valid client certificate.
-240987	SPS_MSG_SSL_CONNECT_ERROR	%1: Failed to connect to the server with SSL. Please check the protocol (http or https), server name, port number, instance name, network connectivity, and VTS server configuration.
-240986	SPS_MSG_AUTHENTICATION_ERROR	%1: Failed to connect to the server. Please check your authentication details (UserName, Password, Domain).
-240985	SPS_MSG_CERT_NOT_EXIST	%1: Failed to locate file %2. Please check if it exists.
-240984	SPS_MSG_LOW_PRIVILEGE	%1: Normal user doesn't have enough privilege to modify data, please connect with admin user.
storm_ext_is_m.h		
4000	STORM_EXT_OK	Ok
4001	STORM_EXT_SERVER_GENERAL_ERR	Index Server general error

Error code	Handle	Message\Additional information
4002	STORM_EXT_IS_INIT_FAILED	Index Server initialization failed
4003	STORM_EXT_IS_INSUFFICIENT_MEMORY	Index Server: insufficient memory
4004	STORM_EXT_INVALID_PARAMETERS	Invalid function parameters
4005	STORM_EXT_INSUFFICIENT_RECORDS	Insufficient records for parameter '%1' in table to provide the Vuser with unique data
4006	STORM_EXT_IS_ALREADY_CLOSED	Index Server is already closed
4007	STORM_EXT_CANNOT_OPEN_ANY_DT	Cannot open any data table
4008	STORM_EXT_CANNOT_OPEN_DT	Cannot open one or more data tables
4009	STORM_EXT_CANNOT_RETRIEVE_TEST_INFO	Error in retrieving test information
4010	STORM_EXT_IS_ALREADY_INIT	Index Server is already init
4011	STORM_EXT_IS_INIT_FAILED	Index Server initialization failed
4012	STORM_EXT_ERROR_CODE_OUT_OF_RANGE	Error Code is out of range
4013	STORM_EXT_UNIQUE_PARAM_ERR_DURATION	You cannot run a test using the "unique" parameter type in a scenario scheduled to run continuously (Duration option). Either change the parameter type, or run the scenario without this scheduling mode.
4014	STORM_EXT_UNIQUE_PARAM_ERR_GOAL	You cannot run a test using the "unique" parameter type in a Goal Oriented Scenario. Either change the parameter type, or run the Manual Scenario.
summary_data_res.h		
-49999	SUMMARY_DATA_MSGS_FAILED_TO_OPEN_HASH_TABLE_FOR_SUMMARY_DATA	Failed to open hash table for creating summary data for the online graphs.
-49998	SUMMARY_DATA_MSGS_FAILED_TO_SEND_SUMMARY_DATA_TO_WORKER_THREAD	Failed to send data to the summary data worker thread for processing and creating the summary data for the online graphs.
-49997	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_TRANS_DATA_INTO_HASH_TABLE_FOR_SUMMARY_DATA	Failed to insert transaction data to the summary data hash table for creating summary data for the online graphs.
-49996	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_DATA_POINT_DATA_INTO_HASH_TABLE_FOR_SUMMARY_DATA	Failed to insert data point data to the summary data hash table for creating summary data for the online graphs.
-49995	SUMMARY_DATA_MSGS_FAILED_TO_GET_SUMMARY_DATA_OBJ_BY_TLS_SO_THE_CURRENT_TRANSACTION_WILL_NOT_BE_INSERTED_TO_THE_SUMMARY_DATA	Failed to get the summary data object by TLS so the current transaction will not be inserted to the calculated summary data.
-49994	SUMMARY_DATA_MSGS_FAILED_TO_GET_SUMMARY_DATA_OBJ_BY_TLS_SO_THE_CURRENT_DATA_POINT_WILL_NOT_BE_INSERTED_TO_THE_SUMMARY_DATA	Failed to get the summary data object by TLS so the current data point will not be inserted to the calculated summary data.
-49993	SUMMARY_DATA_MSGS_FAILED_TO_GET_SUMMARY_DATA_OBJ_BY_TLS_SO_CAN_NOT_SEND_START_SCENARIO_FOR_SUMMARY_DATA	Failed to get the summary data object by TLS so can't send start scenario for creating summary data. Therefore aborting the lr_bridge.
-49992	SUMMARY_DATA_MSGS_FAILED_TO_GET_SUMMARY_DATA_OBJ_BY_TLS_SO_CAN_NOT_SEND_END_SCENARIO_FOR_SUMMARY_DATA	Failed to get the summary data object by TLS so can't send end scenario for stop sending summary data.
-49991	SUMMARY_DATA_MSGS_FAILED_TO_CREATE_DRV_WORKER_THREAD	Failed to create worker thread for summary data using a driver function.
-49990	SUMMARY_DATA_MSGS_FAILED_TO_DESTROY_DRV_WORKER_THREAD	Failed to destroy the worker thread that created the summary data using a driver function.
-49989	SUMMARY_DATA_MSGS_EVE_THREAD_IS_DOWN	The worker thread, that creates the summary data is down.
-49988	SUMMARY_DATA_MSGS_FAILED_TO_INITIALIZE_SUMMARY_DATA_OBJECTS	Failed to initialize the summary data objects, so aborting the lr_bridge.
-49987	SUMMARY_DATA_MSGS_FAILED_TO_GET_HOST_UNIQUE_ID	Failed to get host unique id from the command line for creating unique id to each new measurement.
-49986	SUMMARY_DATA_MSGS_FAILED_TO_GET_FREQUENCY_FOR_SUMMARY_DATA	Failed to get the frequency of the summary data buckets, so aborting the lr_bridge.
-49985	SUMMARY_DATA_MSGS_FAILED_TO_CREATE_TIMER_FOR_SUMMARY_DATA_FREQUENCY	Failed to create timer for the summary data frequency.
-49984	SUMMARY_DATA_MSGS_FAILED_TO_SEND_SUMMARY_DATA_TO_SUMMARY_DATA_THREAD	Failed to send data to the summary data worker thread for creating the summary data.
-49983	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_TRANSACTIONS_DATA_TO_HASH_TABLE_FOR_CREATING_SUMMARY_DATA	Failed to insert transactions data to hash table for creating summary data.
-49982	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_DATA_POINTS_DATA_TO_HASH_TABLE_FOR_CREATING_SUMMARY_DATA	Failed to insert data points data to hash table for creating summary data.
-49981	SUMMARY_DATA_MSGS_FAILED_TO_SEND_SUMMARY_DATA_BUCKETS_TO_MAIN_THREAD	Failed to send summary data buckets to the main thread from the summary data worker thread.
-49980	SUMMARY_DATA_MSGS_GETTING_AN_UNRECOGNIZED_DATA_FROM_MAIN_THREAD	Getting an unrecognized data from the main thread in the summary data worker thread.
-49979	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_SUMMARY_DATA_TO_BUCKETS	Failed to insert raw data to summary data buckets.

Error code	Handle	Message\Additional information
-49978	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_CURRENT_TRANS_DATA_INTO_HASH_TABLE_FOR_SUMMARY_DATA	Failed to insert a transaction instance to a summary data bucket.
-49977	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_CURRENT_TRANS_DATA_INTO_HASH_TABLE_FOR_SUMMARY_DATA_DUE_TO_WRONG_STATUS	Failed to insert a transaction instance to a summary data bucket since the status %_1_Id is invalid.
-49976	SUMMARY_DATA_MSGS_FAILED_TO_INSERT_CURRENT_DATA_POINT_DATA_INTO_HASH_TABLE_FOR_SUMMARY_DATA	Failed to insert a data point instance to a summary data bucket.
-49975	SUMMARY_DATA_MSGS_GET_UNRECOGNIZED_TRANSACTION_STATUS	Getting an unrecognized transaction status for creating transactions summary data.
-49974	SUMMARY_DATA_MSGS_FAILED_TO_SEND_SUMMARY_DATA_TO_THE_TRANSACTION_SERVER	Failed to send summary data to the transaction server.
-49973	SUMMARY_DATA_MSGS_FAILED_TO_OPEN_CLIENT_SERVICE	Failed to open user service for sending notification to controller about start fast analysis at end scenario.
-49972	SUMMARY_DATA_MSGS_FAILED_TO_SEND_NOTIFICATION_ABOUT_START_FAST_ANALYSIS_TO_CONTROLLER	Failed to send notification to controller about start fast analysis at end scenario.
-49971	SUMMARY_DATA_MSGS_GET_A_WRONG_FREQUENCY_FOR_SUMMARY_DATA	Getting a wrong frequency for summary data: %_1_Id.
-49970	SUMMARY_DATA_MSGS_FAILED_TO_GET_TIME_DIFF_FROM_TIME_DIFF_EXTENSION	Failed to get time diff from time diff extension by function - 'GetTimeDiff'.
-49969	SUMMARY_DATA_MSGS_FAILED_TO_GET_CURRENT_CONTROLLER_TIME	Failed to get controller current time.
-49968	SUMMARY_DATA_MSGS_FAILED_TO_GET_CURRENT_TIME	Failed to get current time.
-49967	SUMMARY_DATA_MSGS_THERE_ARE_ENTRIES_IN_PASSED_TRANSACTIONS_SUMMARY_DATA	There are still entries in passed transactions summary data hash in the destructor.
-49966	SUMMARY_DATA_MSGS_THERE_ARE_ENTRIES_IN_FAILED_TRANSACTIONS_SUMMARY_DATA	There are still entries in failed transactions summary data hash in the destructor.
-49965	SUMMARY_DATA_MSGS_THERE_ARE_ENTRIES_IN_ABORTED_TRANSACTION_S_SUMMARY_DATA	There are still entries in aborted transactions summary data hash in the destructor.
-49964	SUMMARY_DATA_MSGS_THERE_ARE_SUMMARY_DATA_OBJECT_IN_PASSED_TRANSACTIONS_SUMMARY_DATA	There are still buckets in passed transactions summary data hash in the destructor.
-49963	SUMMARY_DATA_MSGS_THERE_ARE_SUMMARY_DATA_OBJECT_IN_FAILED_TRANSACTIONS_SUMMARY_DATA	There are still buckets in failed transactions summary data hash in the destructor.
-49962	SUMMARY_DATA_MSGS_THERE_ARE_SUMMARY_DATA_OBJECT_IN_ABORTED_TRANSACTIONS_SUMMARY_DATA	There are still buckets in aborted transactions summary data hash in the destructor.
-49961	SUMMARY_DATA_MSGS_THERE_ARE_ENTRIES_IN_DATA_POINTS_SUMMARY_DATA	There are still entries in data points summary data hash in the destructor.
-49960	SUMMARY_DATA_MSGS_THERE_ARE_SUMMARY_DATA_OBJECT_IN_DATA_POINTS_SUMMARY_DATA	There are still buckets in data points summary data hash in the destructor.
-49959	SUMMARY_DATA_MSGS_FAILED_TO_TREAT_TRANS_DATA_BECAUSE_THERE_ALREADY_WAS_END_SCENARIO	Failed to treat data for creating summary data after end scenario.
-49958	SUMMARY_DATA_MSGS_THERE_ARE_ENTRIES_IN_TIMED_OUT_TRANSACTIONS_SUMMARY_DATA	There are still entries in timed out transactions summary data hash in the destructor.
-49957	SUMMARY_DATA_MSGS_THERE_ARE_SUMMARY_DATA_OBJECT_IN_TIMED_OUT_TRANSACTIONS_SUMMARY_DATA	There are still buckets in timed out transactions summary data hash in the destructor.
-49956	SUMMARY_DATA_MSGS_ERR_ABORTING_SUMMARY_DATA	The summary data extension is aborting due to the error: %_1_Id
tc2_mdrv_res.h		
-226999	TRUCLIENT2_MSGID_STATUS_LINE	
-226998	TRUCLIENT2_MSGID_INTERNAL_LOCK_TRACE	
-226997	TRUCLIENT2_MSGID_INTERNAL_FUNC_TRACE	
-226996	TRUCLIENT2_MSGID_INTERNAL_HTTP_TRACE	
-226995	TRUCLIENT2_MSGID_INTERNAL_NOTIFICATION	
-226994	TRUCLIENT2_MSGID_INTERNAL_MEASUREMENT	
-226993	TRUCLIENT2_MSGID_INTERNAL_GENERIC	
-226992	TRUCLIENT2_MSGID_HTTP_REQUEST_HEADERS	
-226991	TRUCLIENT2_MSGID_HTTP_REQUEST_BODY	
-226990	TRUCLIENT2_MSGID_HTTP_RESPONSE_HEADERS	
-226989	TRUCLIENT2_MSGID_HTTP_RESPONSE_BODY	
-226988	TRUCLIENT2_MSGID_HTTP_TRACE	
-226987	TRUCLIENT2_MSGID_NTLM_INFORMATION	
-226986	TRUCLIENT2_MSGID_SSL_INFORMATION	

Error code	Handle	Message\Additional information
-226985	TRUCLIENT2_MSGID_AUT_NON_ERROR	
-226984	TRUCLIENT2_MSGID_AUT_ERROR	
-226983	TRUCLIENT2_MSGID_PARAMETER_SUBSTITUTION	
-226982	TRUCLIENT2_MSGID_EXTENDED_GENERIC	
-226981	TRUCLIENT2_MSGID_STANDARD	
-226980	TRUCLIENT2_MSGID_WARNING	
-226979	TRUCLIENT2_MSGID_INTERNAL_PROBLEM	
-226978	TRUCLIENT2_MSGID_ERROR	Error
-226977	TRUCLIENT2_MSGID_INTERNAL_ERROR	
-226976	TRUCLIENT2_MSGID_FATAL_ERROR	
-226975	TRUCLIENT2_MSGID_INVALID_MSGTYPE	[Error: Invalid message type]
tc_platform_res.h		
-204699	HTTP_LOGGER_MSGID_REQUEST_HEADERS	Request headers for "%1" (% 2 Id byte(s)) (internal ID=% 3 Id)
-204698	HTTP_LOGGER_MSGID_REQUEST_BODY	Request body for "%1" (% 2 Id byte(s)) (internal ID=% 3 Id)
-204697	HTTP_LOGGER_MSGID_RESPONSE_HEADERS	Response headers for "%1" (% 2 Id byte(s)) (internal ID=% 3 Id)
-204696	HTTP_LOGGER_MSGID_RESPONSE_BODY	Response body for "%1" (% 2 Id byte(s), decoded) (internal ID=% 3 Id)
-204695	HTTP_LOGGER_MSGID_HTTP_0_9	The entire response is considered as body ("HTTP/0.9" - no HTTP headers) for URL="%1": the response does not start with "HTTP" within the first eight bytes
-204694	LRACTMGR_MSGID_RESPONSE_FIRST_SEGMENT	First response segment received for "%1" (internal ID=% 2 Id)
-204693	LRACTMGR_MSGID_RESPONSE_BYTES_RECEIVED	% 1 Id byte(s) received for "%2" (internal ID=% 3 Id)
-204692	LRACTMGR_MSGID_REQUEST_INITIATED_REGULAR	Request initiated for "%1" (internal ID=% 2 Id)
-204691	LRACTMGR_MSGID_RESPONSE_END	End of response for "%1" (internal ID=% 2 Id)
-204690	LRACTMGR_MSGID_REQUEST_CACHED	Browser cache entry used for "%1" (internal ID=% 2 Id)
-204689	LRACTMGR_MSGID_REQUEST_MERGED_NO_ID	Browser cache entry merged with downloaded response for "%1"
-204688	LRACTMGR_MSGID_REQUEST_MERGED	Browser cache entry merged with downloaded response for "%1" (internal ID=% 2 Id)
-204687	LRACTMGR_MSGID_REQUEST_REDIRECTED_TEMPORARY	Redirection (temporary) of "%1"%2 to "%3"%4
-204686	LRACTMGR_MSGID_REQUEST_REDIRECTED_PERMANENTLY	Redirection (permanent) of "%1"%2 to "%3"%4
-204685	LRACTMGR_MSGID_REQUEST_ENDED_NO_INFO	"%1" (internal ID=% 2 Id) ended
-204684	LRACTMGR_MSGID_REQUEST_RETRIED_NO_INFO	"%1" (internal ID=% 2 Id) is being retried
-204683	LRACTMGR_MSGID_REQUEST_ENDED_NSRESULT_ONLY	"%1" (internal ID=% 2 Id) ended with internal status %3 %4
-204682	LRACTMGR_MSGID_REQUEST_RETRIED_NSRESULT_ONLY	"%1" (internal ID=% 2 Id) retried following internal status %3 %4
-204681	LRACTMGR_MSGID_REQUEST_ENDED_HTTP_STATUS_ONLY	"%1" (internal ID=% 2 Id) ended with HTTP Status Code % 3 Id (%4) %5
-204680	LRACTMGR_MSGID_REQUEST_RETRIED_HTTP_STATUS_ONLY	"%1" (internal ID=% 2 Id) is being retried following HTTP Status Code % 3 Id (%4) %5
-204679	LRACTMGR_MSGID_REQUEST_ENDED_HTTP_STATUS_NSRESULT	"%1" (internal ID=% 2 Id) ended with HTTP Status Code % 3 Id (%4) and internal status %5 %6
-204678	LRACTMGR_MSGID_REQUEST_RETRIED_HTTP_STATUS_NSRESULT	"%1" (internal ID=% 2 Id) retried following HTTP Status Code % 3 Id (%4) and internal status %5 %6
-204677	LRACTMGR_MSGID_REQUEST_ENDED_RESOLVE_FAILED	Could not resolve address of host "%1"
-204676	LRACTMGR_MSGID_REQUEST_ENDED_CONNECT_FAILED	Failed to connect to server "%1": Connection timed out
template.h		
-300999	\$_protocolid\$ DEMO TEXT RESOURCE	This is a demo text resource for \$_protocolid\$
timediff_ext_res.h		
-43999	TIMEDIFF_FAILED_TO_OPEN_CLIENT_SERVICE	Failed to open user service for time diff extension.
-43998	TIMEDIFF_FAILED_TO_OPEN_SERVER_SERVICE	Failed to open server service for time diff extension.
-43997	TIMEDIFF_FAILED_TO_SEND_TIME_DIFF_TO_TIME_DIFF_EXTENSION	Failed to send time diff data to time diff extension.
-43996	TIMEDIFF_FAILED_TO_DECODE_TIME_DIFF_BY_XDR	Failed to decode time diff data through xdr.
-43995	TIMEDIFF_FAILED_TO_CALCULATE_FIRST_TIMEDIFF	Failed to calculate primary time diff between the Controller and the remote host.
-43994	TIMEDIFF_FAILED_TO_WRITE_TIME_DIFF_DATA	Failed to write time diff data to time diff extension.
-43993	TIMEDIFF_FAILED_TO_ENCODE_TIME_DIFF_BY_XDR	Failed to encode time diff data through xdr.
-43992	TIMEDIFF_DID_NOT_GET_TIME_FOR_AUTOMATIC_CALCULATION	time diff extension did not have time for automatic calculations of time diff.
-43991	TIMEDIFF_FAILED_TO_INITIALIZE_TIME_DIFF_EXTENSION_OBJECT	Failed to initialize time diff extension since the command line - time_diff_ext_location is incorrect - accepted values are: "cntrl", "host", or "localhost".
-43990	TIMEDIFF_FAILED_TO_GET_SENDER_MONIKER	Failed to get the sender moniker, therefore can't continue with time diff calculation.
-43989	TIMEDIFF_FAILED_TO_GET_CURRENT_TIME	Failed to get current time by the function os_double_gettimeofday().
-43988	TIMEDIFF_FAILED_ALREADY_IN_CALC	Failed to calculate time diff since the time diff extension is already in the time diff calculation.
-43987	TIMEDIFF_FAILED_TO_GET_OUT_DIR	Failed to get out dir from the command line. Please pass the -out option in command line.

Error code	Handle	Message\Additional information
-43986	TIMEDIFF FAILED TO OPEN RESULTS FILE	Cannot open output debug file: "%1".
-43985	TIMEDIFF_EXTENSION FAILED TO_INIT_TIME_DIFF	Failed to init time diff from command line.
-43984	TIMEDIFF_CAN_NOT_READ_DATA_IN_CALL_BACK_SINCE_THERE_IS_NO_CALCULATION	Cannot read data from time diff callback since there is no time diff calculation.
-43983	TIMEDIFF FAILED TO_GET_CONTROLLER_TIME	Failed to get Controller time. Aborting the Ir_bridge.
-43982	TIMEDIFF_ERR_ABORTING_TIMEDIFF	The timediff extension is aborting due to the error: % 1_ld
tracert_client_res.h		
-41499	TRACERT_CLIENT_TLS_NOT_FOUND_ERROR	Traceroute client error: %1 not found in TLS.
-41399	TRACERT_CLIENT_INITIALIZE_ERROR	Traceroute client error: Failed to initialize.
-41398	TRACERT_CLIENT_CREATE_DYN_ARRAY_ERROR	Traceroute client error: Failed to create dynamic array (function da_create failed).
-41397	TRACERT_CLIENT_CREATE_QUEUE_ERROR	Traceroute client error: Failed to create fifo queue (function mfifo_create failed).
-41396	TRACERT_CLIENT_CHANNEL_HANDLE_ERROR	Traceroute client error: Failed to create channel handle (function DrvCreateCustomChannelClient failed).
-41395	TRACERT_CLIENT_SEND_IDENTIFICATION_ERROR	Traceroute client error: Failed to send identification message to traceroute server.
-41394	TRACERT_CLIENT_CREATE_HASH_TABLE_ERROR	Traceroute client error: Failed to create hash table (function ht_open_ext failed).
-41393	TRACERT_CLIENT_OPEN_DEBUG_FILE_ERROR	Traceroute client error: Failed to open debug file.
-41299	TRACERT_CLIENT_REQUEST_ERROR	Traceroute client error: API function traceroute/traceroute_ex failed. Failed to send traceroute request to destination: %1.
-41298	TRACERT_CLIENT_START_LOOP_REQUEST_ERROR	Traceroute client error: API function Ir_start_traceroute failed. Failed to send traceroute request to destination: %1.
-41297	TRACERT_CLIENT_STOP_LOOP_REQUEST_ERROR	Traceroute client error: API function Ir_stop_traceroute failed. Failed to stop traceroute request to destination: %1.
-41296	TRACERT_CLIENT_STOP_ALL_LOOP_REQUESTS_ERROR	Traceroute client error: API function Ir_stop_all_traceroute failed.
-41295	TRACERT_CLIENT_ADD_TO_DYN_ARRAY_ERROR	Traceroute client error: Failed to add entry to dynamic array (function da_add_entry failed).
-41294	TRACERT_CLIENT_NAME_RESOLUTION_ERROR	Traceroute client error: Failed to resolve destination address.
-41293	TRACERT_CLIENT_LOOP_API_ERROR	Traceroute client error: API function Ir_start_traceroute/Ir_stop_traceroute failed. Reason: command line -traceroute_service was not passed.
-41292	TRACERT_CLIENT_SERVICE_CREATE_ERROR	Traceroute client error: A user service could not be established by the client to the traceroute server (function DrvUseService failed).
-41291	TRACERT_CLIENT_HASH_TABLE_ADD_ERROR	Traceroute client error: Failed to add moniker to hash table (function ht_add failed).
-41290	TRACERT_CLIENT_NEGATIVE_LOOP_TIME_ERROR	Traceroute client error: Time between loop-requests cannot be negative.
-41289	TRACERT_CLIENT_SINGLE_API_ERROR	Traceroute client error: API function traceroute/traceroute_ex failed. Reason: command line -traceroute_service was passed.
-41288	TRACERT_CLIENT_LLIST_CREATE_ERROR	Traceroute client error: Failed to initialize linked list (function ll_init failed).
-41287	TRACERT_CLIENT_LLIST_INSERT_ERROR	Traceroute client error: Failed to insert traceroute request to linked list.
-41286	TRACERT_CLIENT_FORMAT_REQUEST_ERROR	Traceroute client error: Failed to encode traceroute request.
-41285	TRACERT_CLIENT_POST_CHANNEL_MESSAGE_ERROR	Traceroute client error: Failed to post traceroute request message (function DrvPostMessageOnCustomChannel failed).
-41284	TRACERT_CLIENT_POST_SERVICE_MESSAGE_ERROR	Traceroute client error: Failed to post traceroute request message (function DrvPostMessageViaServiceUser failed).
-41283	TRACERT_CLIENT_DESTINATION_NOT_FOUND_ERROR	Traceroute client error: API function Ir_stop_traceroute failed. Ir_start_traceroute was not called with this destination.
-41282	TRACERT_CLIENT_MONIKER_NOT_FOUND_ERROR	Traceroute client error: Failed to find traceroute server's moniker in hash table.
-41199	TRACERT_CLIENT_RECEIVE_NOTIFICATION_ERROR	Traceroute client error: Failed to receive notification message from traceroute server.
-41198	TRACERT_CLIENT_UNFORMAT_NOTIFICATION_ERROR	Traceroute client error: Failed to decode notification message.
-41197	TRACERT_CLIENT_NOTIFICATION_HANDLE_NOT_FOUND_ERROR	Traceroute client error: Notification handle was not found in dynamic array (function da_get_entry failed).
-41196	TRACERT_CLIENT_DEL_NOTIFICATION_HANDLE_ERROR	Traceroute client error: Failed to delete notification handle from dynamic array (function da_del_entry failed).
-41195	TRACERT_CLIENT_ADD_TO_QUEUE_ERROR	Traceroute client error: Failed to add entry to fifo queue (function mfifo_add_item failed).
trans_msg.h		
-16999	TRANSACTION_MSGS_START_TRANSACTION	Transaction "%1" started.
-16998	TRANSACTION_MSGS_END_TRANSACTION	Transaction "%1" ended with a "%2" status (%3).
-16997	TRANSACTION_MSGS_END_TRANSACTION_PASS	Transaction "%1" ended successfully.
-16996	TRANSACTION_MSGS_END_TRANSACTION_FAIL	Transaction "%1" failed.
-16995	TRANSACTION_MSGS_SET_TRANSACTION_STATUS	Set LR_PASS status for transaction "%1".
-16994	TRANSACTION_MSGS_DATA_POINT	Data Point "%1" value = % 2_4f.
-16993	TRANSACTION_MSGS_TRANSACTION_NOT_ENDED	Cannot start transaction "%1". This User already started a transaction with the same name, and has not yet processed the corresponding Ir_end_transaction statement.
-16992	TRANSACTION_MSGS_TRANSACTION_NOT_STARTED	Attempt to end transaction "%1" without starting it first.
-16991	TRANSACTION_MSGS_MEMORY_ERROR	Failed to allocate memory space.
-16990	TRANSACTION_MSGS_SET_TRANSACTION_FAIL	Set Transaction "%1" failed.
-16989	TRANSACTION_MSGS_USER_DATA_POINT_FAIL	User data point "%1" failed.
-16988	TRANSACTION_MSGS_TRANS_NOT_END	No Ir_end_transaction for transaction "%1".
-16987	TRANSACTION_MSGS_TRANSACTION_PARENT_NAME_NOT_EXIST	Parent transaction "%1" does not exist. Cannot open sub-transaction "%2".
-16986	TRANSACTION_MSGS_TRANSACTION_PARENT_HANDLE_NOT_EXIST	Failed to find parent transaction with transaction handle: % 1_ld.
-16985	TRANSACTION_MSGS_END_TRANSACTION_BY_NAME_FAIL	Failed to end Transaction "%1" (by name). Please check that you made a call to start transaction operation.

Error code	Handle	Message\Additional information
-16984	TRANSACTION MSGS END TRANSACTION BY HANDLE FAIL	Failed to end Transaction: % 1 _ld (by handle). Please check that you made a call to start transaction operation.
-16983	TRANSACTION MSGS UNIQUE TRANSACTION HANDLE ERROR	Failed to set unique handle for new transaction.
-16982	TRANSACTION MSGS TRANS DPOINT INFO	%1 special report - %2.
-16981	TRANSACTION MSGS FAILED TO OPEN EVE FILE	Failed to open eve file: "%1".
-16980	TRANSACTION MSGS WRITE TO EVE FILE FAILS	Fail to write to file: "%1" - System error: %2.
-16979	TRANSACTION MSGS SET TRANSACTION	Transaction "%1" set.
-16978	TRANSACTION MSGS SET WITH TIMING FAILED	Failed to set transaction "%1".
-16977	TRANSACTION MSGS STOP TRANSACTION BY NAME FAILED	Failed to stop transaction "%1".
-16976	TRANSACTION MSGS STOP TRANSACTION BY HANDLE FAILED	Failed to stop transaction by transaction handle - % 1 _ld.
-16975	TRANSACTION MSGS ERROR MSG FROM CHANNEL	%1(error number: %2).
-16974	TRANSACTION MSGS RESUME TRANSACTION BY NAME FAILED	Failed to resume transaction "%1".
-16973	TRANSACTION MSGS RESUME TRANSACTION BY HANDLE FAILED	Failed to resume transaction by transaction instance - % 1 _ld.
-16972	TRANSACTION MSGS GET DURATION BY NAME FAIL	Failed to get duration of transaction "%1".
-16971	TRANSACTION MSGS GET DURATION BY HANDLE FAIL	Failed to get duration of transaction instance - % 1 _ld.
-16970	TRANSACTION MSGS GET THINK TIME BY NAME FAIL	Failed to get think time for transaction "%1".
-16969	TRANSACTION MSGS GET GET THINK TIME BY HANDLE FAIL	Failed to get think time for transaction instance - % 1 _ld.
-16968	TRANSACTION MSGS GET WASTED TIME BY NAME FAIL	Failed to get wasted time for transaction "%1".
-16967	TRANSACTION MSGS GET GET WASTED TIME BY HANDLE FAIL	Failed to get wasted time for transaction instance - % 1 _ld.
-16966	TRANSACTION MSGS FAILED TO LOAD DAT FILE	Failed to load the %1 file.
-16965	TRANSACTION MSGS FAILED TO INIT TRANS EXT PARAM	Failed to get "%1" extension param.
-16964	TRANSACTION MSGS EXCEPTION WAS RAISED WHILE LOAD LIB EXT	Exception was raised while loading the "%1" library.
-16963	TRANSACTION MSGS FAILED TO LOAD LIB EXT	Failed to load "%1" library.
-16962	TRANSACTION MSGS EXCEPTION WAS RAISED WHILE INIT_CFG_FUNC	Exception was raised while calling the "%1" function for extension "%2".
-16961	TRANSACTION MSGS FAILED TO INIT_CFG_FUNC	Failed to initialize "%1" configuration file for extension "%2".
-16960	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_START_FUNC	Exception was raised while calling start_transaction function in the "%1" extension.
-16959	TRANSACTION MSGS FAILED START_FUNC_RETURN_ERROR	Failed to run start_transaction function in "%1" extension.
-16958	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_END_FUNC	Exception was raised while calling end_transaction function in the "%1" extension.
-16957	TRANSACTION MSGS FAILED_END_FUNC_RETURN_ERROR	Failed to run end_transaction function in "%1" extension.
-16956	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_SET_FUNC	Exception was raised while calling set_transaction function in the "%1" extension.
-16955	TRANSACTION MSGS FAILED_SET_FUNC_RETURN_ERROR	Failed to run set_transaction function in the "%1" extension.
-16954	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_DATAPOINT_FUNC	Exception was raised while calling data_point function in "%1" extension.
-16953	TRANSACTION MSGS FAILED_DATAPOINT_FUNC_RETURN_ERROR	Failed to run data_point function in "%1" extension.
-16952	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_ADDINFO_FUNC	Exception was raised while calling add_info function in "%1" extension.
-16951	TRANSACTION MSGS FAILED_ADDINFO_FUNC_RETURN_ERROR	Failed to run add_info function in "%1" extension.
-16950	TRANSACTION MSGS INITIALIZED TRANSACTION_EXT_ONLINE_MODE	Initialized transaction extension online mode.
-16949	TRANSACTION MSGS INITIALIZED TRANSACTION_EXT_EVE_MODE	Initialized transaction extension eve mode.
-16948	TRANSACTION MSGS INITIALIZED TRANSACTION_EXT_LOG_MODE	Initialized transaction extension log mode.
-16947	TRANSACTION MSGS INITIALIZED TRANSACTION_EXT_ARM_MODE	Initialized transaction extension arm mode.
-16946	TRANSACTION MSGS LOAD TRANSACTION_EXT	Load Transaction Extension - %1.
-16945	TRANSACTION MSGS FAILED TO GET CONNECTION STRING	There is no connection string in command line for connecting to the server.
-16944	TRANSACTION MSGS FAILED TO CREATE_CUSTOM_CHANNEL_CLIENT	Failed to create custom channel client.
-16943	TRANSACTION_MSGS_INITIALIZED_TRANSACTION_SERVER_ONLINE_MODE	Initialized transaction server online mode.
-16942	TRANSACTION MSGS FAILED TO ENCODE	Failed to encode with xdr transaction data.
-16941	TRANSACTION MSGS FAILED TO GET_VUSER_ID	Failed to get Vuser id from command line.
-16940	TRANSACTION MSGS FAILED TO GET_VUSER_GROUP	Failed to get Vuser group from command line.
-16939	TRANSACTION MSGS FAILED TO GET_SCENARIO_ID	Failed to get scenario id from command line.
-16938	TRANSACTION MSGS FAILED TO GET_HOST_NAME	Failed to get host name from command line.
-16937	TRANSACTION MSGS FAILED TO GET_SCRIPT_NAME	Failed to get script name from command line.
-16936	TRANSACTION MSGS FAILED TO MREALLOC FOR ADDINFO	Failed to allocate place for adding information to transaction.
-16935	TRANSACTION MSGS FAILED TO GET_ID_MAPPING_FILE	Failed to get id mapping file from command line.
-16934	TRANSACTION MSGS FAILED TO ADD_ID_INI_FILE	Failed to add ini file "%1" to configuration.

Error code	Handle	Message\Additional information
-16933	TRANSACTION_MSGS_FAILED_TO_GET_SERVER_NAME	Failed to get server name from command line.
-16932	TRANSACTION_MSGS_FAILED_TO_FIND_VALUE_IN_INI_FILE	Cannot find value in ini file "%1", in section "%2", or in attribute "%3".
-16931	TRANSACTION_MSGS_FAILED_IN_ADD_INFO_FUNCTION	Failed to finish add info function in file trans_server_online.cpp.
-16930	TRANSACTION_MSGS_DATA_POINT_PARENT_HANDLE_NOT_EXIST	Parent transaction for data_point "%1" does not exist.
-16929	TRANSACTION_MSGS_FAILED_TO_GET_ORGANIZATION_ID	Failed to get organization id from command line.
-16928	TRANSACTION_MSGS_FAILED_TO_GET_LOCATION_ID	Failed to get location id from command line.
-16927	TRANSACTION_MSGS_FAILED_TO_GET_UNIQUE_ID	Failed to get unique id from command line.
-16926	TRANSACTION_MSGS_EMPTY_START_TRANSACTION_STRING	A transaction start name was not specified.
-16925	TRANSACTION_MSGS_EMPTY_END_TRANSACTION_STRING	A transaction end name was not specified.
-16924	TRANSACTION_MSGS_EMPTY_USER_DATA_POINT_STRING	A transaction user data point name was not specified.
-16923	TRANSACTION_MSGS_FAILED_TO_SET_DATA_POINT_PROPERTIES_FOR_AGGREGATION	Failed to open aggregated data point "%1".
-16922	TRANSACTION_MSGS_FAILED_TO_FIND_TRANSACTION_PARENT	Failed to find parent transaction object in the hash table.
-16921	TRANSACTION_MSGS_THERE_IS_NO_END_TRANSACTION	Vuser started transaction "%1", but did not reach a corresponding end transaction statement. The transaction ended automatically with status 'fail'.
-16920	TRANSACTION_MSGS_FAILED_TO_POST_MESSAGE_TO_TRANSACTION_SERVER	Failed to send data to transaction server - PostMessage failed.
-16919	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_FLUSH_FUNC	Exception was raised while calling flush_transaction function in "%1" extension.
-16918	TRANSACTION_MSGS_FAILED_FLUSH_FUNC_RETURN_ERROR	Failed to run flush_transaction function in "%1" extension.
-16917	TRANSACTION_MSGS_EMPTY_FLUSH_TRANSACTION_STRING	A flush transaction name was not specified.
-16916	TRANSACTION_MSGS_FLUSH_TRANSACTION_BY_NAME_FAIL	Failed to find the transaction "%1" in the hash table.
-16915	TRANSACTION_MSGS_FLUSH_TRANSACTION_BY_HANDLE_FAIL	Failed to find the transaction "%1" in the hash table by handle.
-16914	TRANSACTION_MSGS_FAILED_TO_CREATE_USER_SERVICE	Failed to create user service for communication to the transaction server.
-16913	TRANSACTION_MSGS_NO_OUT_COMMUNICATION_EXISTS	There is no communication. Transaction data cannot be sent.
-16912	TRANSACTION_MSGS_NO_POSSIBLE_OF_HANDLE_ZERO_OR_NEGATIVE	Invalid transaction handle - %_1_Id - handle must be a positive number.
-16911	TRANSACTION_MSGS_CAN_NOT_END_TRANSACTION_WITH_THAT_HANDLE	Cannot end transaction with handle - %_1_Id since it does not exist in the handles queue.
-16910	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_ADD_YOUR_META_DATA_FUNC	Exception was raised while calling the add_your_meta_data function in the "%1" extension.
-16909	TRANSACTION_MSGS_FAILED_ADD_YOUR_META_DATA_FUNC_RETURN_ERROR	Failed to run add_your_meta_data function in "%1" extension.
-16908	TRANSACTION_MSGS_FAILED_TO_GET_TRANS_HANDLER_OBJECT	Failed to get transaction handler object for adding meta data about the Vuser.
-16907	TRANSACTION_MSGS_FAILED_TO_FIND_PARENT_OBJECT	Failed to find the parent transaction object with handle - %_1_Id of the "%2" transaction.
-16906	TRANSACTION_MSGS_THREAD_ID	ThreadID %_1_Id.
-16905	TRANSACTION_MSGS_CAN_NOT_FIND_TRANSACTION_IN_DEQUE	Cannot find the current handle - %_1_Id in the transactions dequeue.
-16904	TRANSACTION_MSGS_FAILED_TO_SPLIT_PATH_WITH_MOSIFS	Failed to split full path by mosifs function 'os_split_path'.
-16903	TRANSACTION_MSGS_END_FAIL_TRANSACTION	Transaction "%1" ended with a failed status.
-16902	TRANSACTION_MSGS_EMPTY_SET_TRANSACTION_PROPERTY_STRING	A transaction name was not specified in set property operation.
-16901	TRANSACTION_MSGS_SET_TRANSACTION_PROPERTY_BY_NAME_FAIL	Failed to get the handle of transaction "%1".
-16900	TRANSACTION_MSGS_SET_TRANSACTION_PROPERTY_BY_HANDLE_FAIL	Failed to get the object of the current transaction from the hash table.
-16899	TRANSACTION_MSGS_FAILED_TO_CALL_TO_THE_TRANSACTION_SERVER_API_FOR_SENDING_DATA	Failed to call the 'ReportingDataToTs' operation ,for reporting data to the transaction server without using the post message operation.
-16898	TRANSACTION_MSGS_FAILED_TO_CREATE_TIMER_FOR_XDR_BUFFERING	Failed to create timer for xdr buffering optimization.
-16897	TRANSACTION_MSGS_FAILED_TO_SEND_ARRAY_OF_XDR_BUFFERS_DATA_TO_TRANSACTION_SERVER	Failed to send xdr buffers data array to the transaction server.
-16896	TRANSACTION_MSGS_FAILED_TO_CLOSE_TIMER_FOR_XDR_BUFFERING	Failed to close timer for xdr buffering optimization.
-16895	TRANSACTION_MSGS_FAILED_TO_POST_XDR_BUFFERS_DATA_ARRAY	Failed to post xdr buffers data array by post_ex.
-16894	TRANSACTION_MSGS_FAILED_TO_ADD_TRANSACTION_TO_AGGREGATE_TRANSACTIONS_ARRAY	Failed to add transaction to the transactions data array for optimization.
-16893	TRANSACTION_MSGS_FAILED_TO_SET_PROPERTY	Failed to set property to transaction "%1".
-16892	TRANSACTION_MSGS_FAILED_TO_SET_PROPERTY_SINCE_IT_WAS_ALREADY_SET	Failed to set property since it already set.
-16891	TRANSACTION_MSGS_FAILED_TO_GET_FILE_AND_LINE_OF_THE_TRANSACTION	Failed to get file name and line of the script for failed transaction "%1".
-16890	TRANSACTION_MSGS_FAILED_TO_GET_ITERATION_NUMBER	Failed to get the iteration number for adding this data to failed transactions.

Error code	Handle	Message\Additional information
-16889	TRANSACTION_MSGS_DELETE_TRANSACTION_SINCE_REAL_RESPONSE_TIME_IS_NEGATIVE	Transaction "%1" will be skipped - could not calculate the transaction time (duration=%_2_.4f, think_time=%_3_.4f, wasted_time=%_4_.4f).
-16888	TRANSACTION_MSGS_FAILED_TO_ADD_META_DATA	Failed to add data to meta data.
-16887	TRANSACTION_MSGS_FAILED_TO_ADD_META_DATA_SINCE_INPUT_KEY_NAME_IS_NULL	Failed to add meta data since the key name is null.
-16886	TRANSACTION_MSGS_FAILED_TO_ADD_META_DATA_SINCE_INPUT_VALUE_IS_NULL	Failed to add meta data since the value is NULL.
-16885	TRANSACTION_MSGS_FAILED_TO_ADD_META_DATA_SINCE_THE_TYPE_IS_NOT_VALID	Failed to add meta data since the type is not valid.
-16884	TRANSACTION_MSGS_EMPTY_SET_TRANSACTION_STATUS_STRING	A transaction name was not specified for set_transaction_status operation.
-16883	TRANSACTION_MSGS_SET_TRANSACTION_STATUS_BY_NAME_FAIL	Failed to set transaction status to transaction "%1" (by name). Please check that you made a call to start transaction operation.
-16882	TRANSACTION_MSGS_SET_TRANSACTION_STATUS_BY_HANDLE_FAIL	Failed to set transaction status to transaction "%1" (by handle). Please check that you made a call to start transaction operation.
-16881	TRANSACTION_MSGS_FAILED_TO_CREATE_TIMER_FOR_DP_AGGREGATION	Failed to create timer to data point "%1" for aggregation.
-16880	TRANSACTION_MSGS_FAILED_TO_AGGREGATE_DATA_POINT	Failed to aggregate data point.
-16879	TRANSACTION_MSGS_FAILED_TO_AGGREGATE_DATA_POINT_DUE_TO_NO_HANDLE	No handle was specified for the data point.
-16878	TRANSACTION_MSGS_FAILED_TO_REPORT_AGGREGATE_DATA_POINT_DUE_TO_NO_HANDLE	No handle was specified for reporting the aggregated data point.
-16877	TRANSACTION_MSGS_FAILED_TO_REPORT_AGGREGATED_DATA_POINTS	Failed to report aggregated data points due to unfamiliar flag in function 'report_all_aggregated_data_points'.
-16876	TRANSACTION_MSGS_FAILED_TO_GET_TRANSACTION_OBJECT_FROM_TLS	Failed to get transaction object from TLS.
-16875	TRANSACTION_MSGS_DELETE_TRANSACTION_SINCE_THERE_IS_NO_STATUS	An unfamiliar status - %_1_.ld was given to transaction "%2".
-16874	TRANSACTION_MSGS_FAILED_TO_SET_STATUS_NOT_VALID	%_1_.ld is not a valid status.
-16873	TRANSACTION_MSGS_END_TRANSACTION_ONLY_DURATION	Transaction "%1" ended with a "%2" status (Duration: %_3_.4f).
-16872	TRANSACTION_MSGS_END_TRANSACTION_ONLY_THINK_TIME	Transaction "%1" ended with a "%2" status (Duration: %_3_.4f Think Time: %_4_.4f).
-16871	TRANSACTION_MSGS_END_TRANSACTION_ONLY_WASTED_TIME	Transaction "%1" ended with a "%2" status (Duration: %_3_.4f Wasted Time: %_4_.4f).
-16870	TRANSACTION_MSGS_END_TRANSACTION_THINK_TIME_AND_WASTED_TIME	Transaction "%1" ended with a "%2" status (Duration: %_3_.4f Think Time: %_4_.4f Wasted Time: %_5_.4f).
-16869	TRANSACTION_MSGS_STOP_TRANSACTION	Transaction "%1" stopped.
-16868	TRANSACTION_MSGS_RESUME_TRANSACTION	Transaction "%1" resumed.
-16867	TRANSACTION_MSGS_FAILED_TO_ADD_DATA_TO_PB_SINCE_INPUT_KEY_NAME_OR_VALUE_IS_NULL	Failed to add data to property bag since the key name or the value is null.
-16866	TRANSACTION_MSGS_FAILED_TO_ADD_DATA_TO_PB_SINCE_THE_TYPE_IS_NOT_VALID	Failed to add data to property bag since the type is not valid.
-16865	TRANSACTION_MSGS_FAILED_TO_ADD_DATA_TO_PB_SINCE_CURRENT_PB_IS_UNFAMILIAR	Failed to copy property bag.
-16864	TRANSACTION_MSGS_DELETE_TRANSACTION_SINCE_REAL_RESPONSE_TIME_IS_NEGATIVE1	The transaction "%1" will be skipped - the response time was too short: %_2_.4f.
-16863	TRANSACTION_MSGS_GET_STATUS_BY_NAME_FAIL	Failed to get status for transaction "%1".
-16862	TRANSACTION_MSGS_GET_GET_STATUS_BY_HANDLE_FAIL	Failed to get status for transaction instance - %_1_.ld.
-16861	TRANSACTION_MSGS_FAILED_TO_ADD_DYNAMIC_META_DATA	Failed to add dynamic meta data during running.
-16860	TRANSACTION_MSGS_FAILED_TO_ADD_DYNAMIC_META_DATA_TO_AGGREGATE_TRANSACTIONS_ARRAY	Failed to add dynamic meta data to the transactions data array for optimization.
-16859	TRANSACTION_MSGS_FAILED_TO_ADD_DYNAMIC_META_DATA_SINCE_THE_INIT_META_DATA_WAS_NOT_SENT_YET	Failed to send dynamic meta data since the init meta data was not sent yet.
-16858	TRANSACTION_MSGS_EMPTY_START_DISTRIBUTED_TRANSACTION_STRING	A distributed transaction start name was not specified.
-16857	TRANSACTION_MSGS_STOP_DISTRIBUTED_TRANSACTION_SINCE_THERE_IS_NO_RIGHT_STATUS	An unfamiliar status - %_1_.ld was given to the distributed transaction with correlator "%2".
-16856	TRANSACTION_MSGS_START_DISTRIBUTED_TRANSACTION	Distributed transaction "%1" started.
-16855	TRANSACTION_MSGS_END_DISTRIBUTED_TRANSACTION	Distributed transaction with correlator "%1" ended with a "%2" status.
-16854	TRANSACTION_MSGS_FAILED_TO_GET_FILE_AND_LINE_OF_THE_DISTRIBUTED_TRANSACTION	Failed to get file name and line of the script for failed distributed transaction with correlator "%1".

Error code	Handle	Message\Additional information
-16853	TRANSACTION_MSGS_EMPTY_START_DISTRIBUTED_TRANSACTION_STRING_CORRELATOR	A correlator for distributed transaction start was not specified.
-16852	TRANSACTION_MSGS_WRONG_TIMEOUT_FOR_START_DISTRIBUTED_TRANSACTION	A timeout for distributed transaction start is not valid: %_1_id.
-16851	TRANSACTION_MSGS_EMPTY_END_DISTRIBUTED_TRANSACTION_STRING_CORRELATOR	A correlator for distributed transaction end was not specified.
-16850	TRANSACTION_MSGS_REPORT_SAMPLE	Report sample with type "%1".
-16849	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_REPORT_SAMPLE_FUNC	Exception was raised while calling report sample function in the "%1" extension.
-16848	TRANSACTION_MSGS_FAILED_REPORT_SAMPLE_FUNC_RETURN_ERROR	Failed to run report_transaction function in "%1" extension.
-16847	TRANSACTION_MSGS_FAILED_NULL_SAMPLE	Getting a wrong input: NULL sample.
-16846	TRANSACTION_MSGS_FAILED_NULL_SAMPLES	Getting a wrong input: NULL samples.
-16845	TRANSACTION_MSGS_FAILED_TO_GET_LENGTH_FOR_XDR_BUFFER	Failed to get the needed size for xdr encoding function.
-16844	TRANSACTION_MSGS_FAILED_TO_OPEN_A_RESPONDER	Failed to open a responder for java client reported samples.
-16843	TRANSACTION_MSGS_FAILED_TO_DECODE_XDR_STRUCT	Failed to decode in XDR structure: %1.
-16842	TRANSACTION_MSGS_FAILED_TO_ENCODE_XDR_STRUCT	Failed to encode in XDR structure: %1.
-16841	TRANSACTION_MSGS_FAILED_TO_SEND_A_RESPONSE	Got %1, failed to send a response.
-16840	TRANSACTION_MSGS_FAILED_EMPTY_MESSAGE_FROM_JTC	Got empty message from java transaction client.
-16839	TRANSACTION_MSGS_FAILED_TO_ATTACH_TO_TS	The transaction client failed to attach to transaction server with label "%1".
-16838	TRANSACTION_CLIENT_ATTACH_STATUS_IS_ATTACHED	Succeeded to attach to transaction server.
-16837	TRANSACTION_CLIENT_ATTACH_STATUS_IS_DETACHED	Detached from transaction server.
-16836	TRANSACTION_CLIENT_ATTACH_STATUS_IS_NOT_RESPONDING	Attached transaction server is not responding.
-16835	TRANSACTION_CLIENT_ATTACH_STATUS_IS_FAILED	Attached transaction server goes to failed status.
-16834	TRANSACTION_CLIENT_ATTACH_STATUS_IS_KILLED	Attached transaction server goes to killed status.
-16833	TRANSACTION_MSGS_NOT_SENDING_META_DATA_YET_BECAUSE_THERE_WAS_NO_ATTACH_STATUS	Not sending meta data now since attached status has not received yet.
-16832	TRANSACTION_MSGS_PRINTING_TRANS_CHAR_PROPERTY	trans_name=%1 Key=%2 Value=%_3_c
-16831	TRANSACTION_MSGS_PRINTING_TRANS_INT_PROPERTY	trans_name=%1 Key=%2 Value=%_3_id
-16830	TRANSACTION_MSGS_PRINTING_TRANS_STRING_PROPERTY	trans_name=%1 Key=%2 Value=%3
-16829	TRANSACTION_MSGS_TOO_MANY_LOADER_CLIENTS	There are too many tc loader clients.
-16828	TRANSACTION_MSGS_ERR_ABORTING_TRANSACTION	The transaction client is aborting due to the error: %_1_id
-16827	TRANSACTION_MSGS_GET_SERVERS_IP_NAME_BY_NAME_FAIL	Failed to get servers IP and name for transaction "%1".
-16826	TRANSACTION_MSGS_GET_SERVERS_IP_NAME_BY_HANDLE_FAIL	Failed to get servers IP and name for transaction instance - %_1_id.
-16825	TRANSACTION_MSGS_TIMED_DATA_POINT_EXCEEDS_ERROR_MARGIN_TIMER_IS_ON	Aggregated Data Point %1 report out of valid range - timer is running (data point timestamp: %_2_6f sec; timer start time: %_3_6f sec; timer value: %_4_6f sec; TIMED_DATA_POINT_MAX_DELAY: %_5_6f sec;TIMED_DATA_POINT_MAX_CLOCK_MISMATCH: %_6_6f sec).
-16824	TRANSACTION_MSGS_TIMED_DATA_POINT_EXCEEDS_ERROR_MARGIN_TIMER_IS_OFF	Aggregated Data Point %1 report out of valid range - timer is NOT running (data point timestamp: %_2_6f sec; current timestamp: %_3_6f sec; timer value: %_4_6f sec; TIMED_DATA_POINT_MAX_DELAY: %_5_6f sec;TIMED_DATA_POINT_MAX_CLOCK_MISMATCH: %_6_6f sec).
-16823	TRANSACTION_MSGS_SET_TRANSACTION_STANDALONE_PROPERTY_BY_HANDLE_FAIL	Failed to get the object of the current transaction.
-16822	TRANSACTION_MSGS_NEGATIVE_START_TIMESTAMP	Failed to start transaction %1 - the end timestamp is negative.
-16821	TRANSACTION_MSGS_NEGATIVE_END_TIMESTAMP	Failed to end transaction %1 - the end timestamp is negative.
-16820	TRANSACTION_MSGS_EMPTY_IDENTIFIER_DATA	A cross vuser transaction identifier data was not specified.
-16819	TRANSACTION_MSGS_END_TRANSACTION_ERROR_MESSAGE	The %4 error message associated with transaction "%1" is "Error %_3_id: %2"
-16818	TRANSACTION_MSGS_END_TRANSACTION_ERROR_MESSAGE_COUNT	Transaction "%1" has %_2_id error message(s).
trans_server_res.h		
-30999	TRANSACTION_SERVER_MSGS_PER_THREAD_FUNCTION_FAILED	Failed to initialize topaz transaction server.
-30998	TRANSACTION_SERVER_MSGS_FAILED_TO_INITIALIZE_CLIENT_PARAM	Failed to initialize transaction client param - %1 or %2.
-30997	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_CHANNEL_TRANS_SERVER	Failed to open transaction server channel.
-30996	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_CHANNEL_TRANS_CLIENT	Failed to open transaction client channel.
-30995	TRANSACTION_SERVER_FAILED_TO_OPEN_RESULTS_FILE	Cannot open output debug file - %1.
-30994	TRANSACTION_SERVER_FAILED_TO_INITIALIZE_CLIENT	There is no attribute after -topaz_online_server option or this option does not exist.
-30993	TRANSACTION_SERVER_FAILED_TO_DECODE_MSG	The transactions server failed to decode the message.
-30992	TRANSACTION_MSGS_FAILED_TO_INIT_TRANS_EXT_PARAM	Failed to get the %1 extension parameter.

Error code	Handle	Message\Additional information
-30991	TRANSACTION MSGS EXCEPTION WAS RAISED WHILE LOAD LIB EXT	Exception was raised while loading the %1 library.
-30990	TRANSACTION MSGS FAILED TO LOAD LIB EXT	Failed to load the %1 library.
-30989	TRANSACTION MSGS LOAD TRANSACTION EXT	Load Topaz Transaction Extension - %1.
-30988	TRANSACTION MSGS EXCEPTION WAS RAISED WHILE INIT_CFG_FUNC	Exception was raised while calling "%1" function.
-30987	TRANSACTION MSGS FAILED TO INIT_CFG_FUNC	Failed to initialize %1 configuration file.
-30986	TRANSACTION MSGS FAILED TO LOAD DAT_FILE	Failed to load %1 file.
-30985	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_TRANS_FUNC	Exception was raised while calling Trans_Arrived_CB function in "%1" extension.
-30984	TRANSACTION MSGS FAILED_TRANS_FUNC_RETURN_ERROR	Failed to run Trans_Arrived_CB function in "%1" extension.
-30983	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_DATA_POINT_FUNC	Exception was raised while calling DPoint_Arrived_CB function in "%1" extension.
-30982	TRANSACTION MSGS FAILED_DATA_POINT_FUNC_RETURN_ERROR	Failed to run DPoint_Arrived_CB function in "%1" extension.
-30981	TRANSACTION SERVER FAILED TO GET_OUT_DIR	Failed to get out dir from the command line. Use - out option.
-30980	TRANSACTION SERVER FAILED TO GET_FILE_OPTION	Failed to get trans_server_data_to_file attribute from the command line.
-30979	TRANSACTION MSGS FAILED TO GET_SERVER_NAME	Failed to get server name from the command line.
-30978	TRANSACTION_MSGS_FAILED_ADD_INFO_TRANS_FUNC_RETURN_ERROR	Failed to run AddInfo_Trans_Arrived_CB function in "%1" extension.
-30977	TRANSACTION_MSGS_FAILED_ADD_INFO_DATA_POINT_FUNC_RETURN_ERROR	Failed to run AddInfo_Dpoint_Arrived_CB function in "%1" extension.
-30976	TRANSACTION_MSGS_FAILED_TRACEROUTE_DATA_FUNC_RETURN_ERROR	Failed to run TraceRoute_Arrived_CB function in "%1" extension.
-30975	TRANSACTION MSGS FAILED TO INSERT META_DATA	Failed to insert meta data into the hash table. It already contains data with the same unique id - %1_id.
-30974	TRANSACTION SERVER MSGS FAILED TO OPEN_CLIENT_SERVICE	Failed to open client service 'TransClientOnline' for sending data.
-30973	TRANSACTION SERVER HAVE EXTENSIONS TO SEND DATA TO	There must be extensions to send data from the transaction server.
-30972	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_SERVICE_TRANS_SERVER	Failed to open server service 'TransServerOnline' for getting data.
-30971	TRANSACTION SERVER MSGS FAILED TO OPEN_TRANS_SERVER	Failed to open transaction server since there is no option of 'in' communication in the command line.
-30970	TRANSACTION SERVER MSGS FAILED TO OPEN_TRANS_CLIENT	Failed to open client for the transaction server since there is no option of 'out' communication.
-30969	TRANSACTION_SERVER_DOES_NOT_HAVE_ANY_CLIENT_TO_SEND_DATA	There is no client or extension to which to send data.
-30968	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_ADD_INFO_TRANS_FUNC	Exception was raised while calling AddInfo_Trans_Arrived_CB function in the "%1" extension.
-30967	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_ADD_INFO_DATA_POINT_FUNC	Exception was raised while calling AddInfo_Dpoint_Arrived_CB function in the "%1" extension.
-30966	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_TRACEROUTE_FUNC	Exception was raised while calling TraceRoute_Arrived_CB function in the "%1" extension.
-30965	TRANSACTION MSGS FAILED TO WRITE BY XDR	Failed to encode with xdr transaction data.
-30964	TRANSACTION MSGS FAILED TO GET_CLIENT_NAME	Failed to get client name from the command line.
-30963	TRANSACTION SERVER FAILED TO LAUNCH TRACEROUTE_SERVER	The Transaction server fails to launch the Traceroute server.
-30962	TRANSACTION SERVER FAILED TO KILL TRACEROUTE_SERVER	The Transaction server fails to kill the Traceroute server.
-30961	TRANSACTION SERVER LAUNCH TRACEROUTE_SERVER	The Transaction server launched the Traceroute server.
-30960	TRANSACTION SERVER DOES NOT LAUNCH TRACEROUTE_SERVER	The transaction server does not launch Traceroute server. The Traceroute is an mdrv extension.
-30959	TRANSACTION SERVER TRACEROUTE_SERVER IS LOADED	The Traceroute is loaded by the launcher.
-30958	TRANSACTION SERVER TRACEROUTE_SERVER IS KILLED	The Traceroute server was killed.
-30957	TRANSACTION_SERVER_TRACEROUTE_SERVER_FAILED_TO_BE_LOADED	The Traceroute server is not loaded.
-30956	TRANSACTION_SERVER_TRACEROUTE_SERVER IS DOWN	The Traceroute server is down.
-30955	TRANSACTION_SERVER_FAILED_TO_GET_THE_DIR_OF_TRANSACTION_SERVER	Failed to get the directory of the transaction server using the function 'os_get_my_module_dir_name' for launching the Traceroute server.
-30954	TRANSACTION_SERVER_FAILED_TO_GET_TIME_DIFF_FROM_TIME_DIFF_EXT	Failed to get time diff from time diff extension by operation - 'GetTimeDiff'.
-30953	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_ERROR_FUNC	Exception was raised while calling Error_Arrived_CB function in the "%1" extension.
-30952	TRANSACTION MSGS FAILED_ERROR_DATA_FUNC_RETURN_ERROR	Failed to run Error_Arrived_CB function in the "%1" extension.
-30951	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_START_SCENARIO_FUNC	Exception was raised while calling StartScenario_Arrived_CB function in the "%1" extension.

Error code	Handle	Message\Additional information
-30950	TRANSACTION_MSGS_FAILED_START_SCENARIO_DATA_FUNC_RETURN_ER ROR	Failed to run StartScenario_Arrived_CB function in the "%1" extension.
-30949	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_END_SC ENARIO_FUNC	Exception was raised while calling EndScenario_Arrived_CB function in the "%1" extension.
-30948	TRANSACTION_MSGS_FAILED_END_SCENARIO_DATA_FUNC_RETURN_ERRO R	Failed to run EndScenario_Arrived_CB function in the "%1" extension.
-30947	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_START_SCENARIO_SERVI CE	Failed to create service provider for getting notification about start scenario.
-30946	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_END_SCENARIO_SERVIC E	Failed to create service provider for getting notification about end scenario.
-30945	TRANSACTION_SERVER_MSGS_FAILED_TO_DECODE_SCENARIO_DATA	Failed to decode scenario data.
-30944	TRANSACTION_SERVER_MSGS_FAILED_TO_GET_NET_DIR_FOR_EVE_FILE	Failed to get the net dir for writing the .eve file.
-30943	TRANSACTION_SERVER_MSGS_FAILED_TO_GET_NET_DIR	Failed to get the network directory - the reason: This transaction server is on the local host or there is no net dir in the command line.
-30942	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_LISTENER_SERVICE_F OR_ERRORS	Failed to create listener error service.
-30941	TRANSACTION_SERVER_MSGS_FAILED_TO_DECODE_ERROR_DATA	Failed to decode error data.
-30940	TRANSACTION_SERVER_FAILED_TO_POST_MESSAGE_TO_ANOTHER_TS	Failed to post message to another transaction server.
-30939	TRANSACTION_SERVER_FAILED_TO_READ_DATA_FROM_EVE_FILE	Failed to read data from the .eve file: "%1".
-30938	TRANSACTION_SERVER_FAILED_TO_GET_TRANSACTION_SERVER_OBJECT	Failed to get the transaction server object for adding data from the .eve file to the transaction server.
-30937	TRANSACTION_SERVER_FAILED_TO_CREATE_DRV_WORKER_THREAD	Failed to create worker thread using driver function.
-30936	TRANSACTION_SERVER_FAILED_TO_DESTROY_DRV_WORKER_THREAD	Failed to destroy worker thread using driver function.
-30935	TRANSACTION_SERVER_FAILED_TO_SEND_DATA_BY_CHANNELS	Failed to send data by channels - post message failed.
-30934	TRANSACTION_SERVER_EVE_THREAD_IS_DOWN	The worker thread that writes the .eve file is down.
-30933	TRANSACTION_SERVER_FAILED_TO_GET_FULL_PATH_TO_EVE_FILE	Failed to get full path to .eve file.
-30932	TRANSACTION_SERVER_FAILED_TO_OPEN_EVE_FILE	Failed to open .eve file: "%1".
-30931	TRANSACTION_SERVER_FAILED_TO_WRITE_DATA_TO_THE_EVE_FILE	Failed to write data to the .eve file. Check that the remote host has enough disk space: system error - %1.
-30930	TRANSACTION_SERVER_FAILED_TO_FLUSH_EVE_FILE	Failed to flush .eve file (system call - fflush failed).
-30929	TRANSACTION_SERVER_CAN_NOT_START_SCENARIO_WITH_OUT_FINISHED _ANOTHER_ONE	Cannot get more then one call to start scenario - only one scenario can run at a time.
-30928	TRANSACTION_SERVER_FAILED_TO_CREATE_WRITER_OBJECT_TO_EVE_FI LE	Failed to allocate object for writing to the .eve file.
-30927	TRANSACTION_SERVER_FAILED_TO_GET_END_SCENARIO_DATA_SINCE_TH ERE_IS_NO_OBJECT	Can't get a call to end scenario since there was no start scenario.
-30926	TRANSACTION_SERVER_DOES_NOT_WRITE_DATA_TO_EVE_FILE	The transaction server does not write the current data to the .eve file.
-30925	TRANSACTION_SERVER_FAILED_TO_WRITE_FILE_HEADER_TO_EVE_FILE	Failed to write file header to the .eve file: "%1".
-30924	TRANSACTION_SERVER_FAILED_TO_WRITE_EVE_FILE_SIZE	Failed to write size of the .eve file.
-30923	TRANSACTION_SERVER_FAILED_TO_READ_EVE_FILE_HEADER	Failed to read file header from the .eve file: "%1".
-30922	TRANSACTION_SERVER_EVE_FILE_VERSION	The version of the .eve file "%1" is: %2 ld.
-30921	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_DRIVER_ ERROR_FUNC	Exception was raised while calling Driver_Error_Arrived_CB function in the "%1" extension.
-30920	TRANSACTION_MSGS_FAILED_DRIVER_ERROR_DATA_FUNC_RETURN_ERRO R	Failed to run Driver_Error_Arrived_CB function in the "%1" extension.
-30919	TRANSACTION_SERVER_FAILED_TO_FIND_META_DATA_IN_HASH	Failed to correlate meta data for the current event (transaction, data point or error) from the meta data hash table.
-30918	TRANSACTION_SERVER_EVE_FILE_IS_EMPTY	The .eve file: "%1" is empty.
-30917	TRANSACTION_SERVER_FAILED_TO_SEND_DATA_TO_THE_TS_EXTENSIONS	Failed to send data to the transaction server extensions.
-30916	TRANSACTION_SERVER_FAILED_TO_POST_MESSAGE_TO_THE_CONTROLLE R_ABOUT_COLLATING_RESULTS	Failed to send a notification to the Controller to start collating results.
-30915	TRANSACTION_SERVER_FAILED_TO_GET_EVE_FILE_SIZE	Failed to get the .eve file size for sending the data to the .eve file.
-30914	TRANSACTION_SERVER_FAILED_TO_WRITE_DATA_TO_THE_OFFLINE	Failed to write data to the offline.
-30913	TRANSACTION_SERVER_FAILED_TO_MAKE_THE_IO_BUFFER_BIGGER	Failed to increase the IO buffer size for saving writes to file.
-30912	TRANSACTION_SERVER_MSGS_GET_AN_UNRECOGNIZED_SUMMARY_DATA	Get an unrecognized summary data, so can't notify this summary event to the transaction server extensions.
-30911	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_SUMMAR Y_TRANS_FUNC	Exception was raised while calling Trans_Summary_Data_Arrived_CB function in "%1" extension.

Error code	Handle	Message\Additional information
-30910	TRANSACTION_MSGS_FAILED_SUMMARY_TRANS_FUNC_RETURN_ERROR	Failed to run Trans_Summary_Data_Arrived_CB function in "%1" extension.
-30909	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_SUMMARY_DATA_POINTS_FUNC	Exception was raised while calling Data_Points_Summary_Data_Arrived_CB function in "%1" extension.
-30908	TRANSACTION_MSGS_FAILED_SUMMARY_DATA_POINTS_FUNC_RETURN_ERROR	Failed to run Data_Points_Summary_Data_Arrived_CB function in "%1" extension.
-30907	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_SUMMARY_DATA_PROVIDER_SERVICE	Failed to open service provider for summary data.
-30906	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_SUMMARY_DATA_USER_SERVICE	Failed to open service user for summary data.
-30905	TRANSACTION_SERVER_MSGS_FAILED_TO_ENCODE_DATA_FOR_THE_EVE_FILE	Failed to encode data by xdr for the .eve file.
-30904	TRANSACTION_SERVER_FAILED_TO_ADD_META_DATA_SINCE_INPUT_VALUE_IS_NULL	Failed to add meta data since the value is NULL.
-30903	TRANSACTION_SERVER_FAILED_TO_ADD_META_DATA_SINCE_THE_TYPE_IS_NOT_VALID	Failed to add meta data since the type is not valid.
-30902	TRANSACTION_SERVER_FAILED_TO_ADD_DYNAMIC_META_DATA	Failed to add dynamic meta data.
-30901	TRANSACTION_SERVER_FAILED_TO_GET_MAIN_THREAD_CONTEXT	Failed to get main thread context through driver API.
-30900	TRANSACTION_SERVER_FAILED_TO_SET_MAIN_THREAD_CONTEXT	Failed to set main thread context through driver API.
-30899	TRANSACTION_SERVER_FAILED_TO_UNSET_MAIN_THREAD_CONTEXT	Failed to unset main thread context through driver API.
-30898	TRANSACTION_SERVER_FAILED_TO_CREATE_ERROR_DISK_SPACE_USER_SERVICE	Failed to create user service for sending disk space problem to controller.
-30897	TRANSACTION_SERVER_FAILED_TO_POST_ERROR_DISK_SPACE_BY_USER_SERVICE	Failed to post error message to controller about disk space.
-30896	TRANSACTION_SERVER_FAILED_TO_GO_BACK_TO_THE_LAST_OK_RECORD	Failed returning to the last proper record in the .eve file: "%1".
-30895	TRANSACTION_SERVER_EVE_THREAD_IS_DOWN_BECAUSE_MAIN_THREAD_IS_DOWN	The writer thread of the .eve file is down because the main thread is down.
-30894	TRANSACTION_SERVER_FAILED_TO_WRITE_EVE_FILE_HEADER	Failed to write to the .eve file its header.
-30893	TRANSACTION_SERVER_FAILED_TO_ADD_NAME_TO_HASH_OPTIMIZATION_NAMES	Failed to add name to hash table for names optimization.
-30892	TRANSACTION_SERVER_PROBLEM_IN_NAME_OPTIMIZATION	A problem occurred in map transaction names to ids optimization, aborting the bridge.
-30891	TRANSACTION_SERVER_FAILED_TO_CREATE_THREAD_CONTEXT_FOR_TS	Failed to create class object for the usage of transaction server API in different threads.
-30890	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_SAMPLE_PUBLISHER_TRANSACTION_SERVER	Failed to open publisher 'SamplesData' for sending data.
-30889	TRANSACTION_SERVER_FAILED_TO_PUBLISH_SAMPLE_DATA	Failed to publish samples data.
-30888	TRANSACTION_SERVER_MSGS_NOT_ATTACH_TO_ANOTHER_TS	The current transaction server will not attach to another transaction server.
-30887	TRANSACTION_SERVER_MSGS_FAILED_TO_ATTACH_TO_ANOTHER_TS	Failed to attach to another transaction server.
-30886	TRANSACTION_SERVER_ATTACH_STATUS_IS_ATTACHED	Succeeded to attach to another transaction server.
-30885	TRANSACTION_SERVER_ATTACH_STATUS_IS_DETACHED	Detached from another transaction server.
-30884	TRANSACTION_SERVER_ATTACH_STATUS_IS_NOT_RESPONDING	Attached transaction server is not responding.
-30883	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_TRIGGER_FOR_WAITING_TO_ATTACHED_STATUS	Failed to create trigger for waiting to attach status.
-30882	TRANSACTION_SERVER_MSGS_FAILED_TO_WAIT_ON_TRIGGER_FOR_WAITING_TO_ATTACHED_STATUS	Failed to wait on trigger for waiting to attach status.
-30881	TRANSACTION_SERVER_ATTACH_STATUS_IS_FAILED	Attached transaction server goes to failed status.
-30880	TRANSACTION_SERVER_ATTACH_STATUS_IS_KILLED	Attached transaction server goes to killed status.
-30879	TRANSACTION_SERVER_MSGS_FAILED_TO_GET_DRIVER_CONTEXT_DATA	Failed to get driver context data, so failed to report samples data.
-30878	TRANSACTION_SERVER_MSGS_FAILED_TO_WAIT_ON_TRIGGER_FOR_WAITING_TO_DETACHED_STATUS	Failed to wait on trigger for waiting to detach status.
-30877	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_TRIGGER_FOR_WAITING_TO_DETACHED_STATUS	Failed to create trigger for waiting to attach status.
-30876	TRANSACTION_SERVER_MSGS_FAILED_TO_ENCODE_SAMPLES_DATA	Failed to encode samples data.
-30875	TRANSACTION_SERVER_MSGS_FAILED_TO_INSERT_DYNAMIC_META_DATA	Failed to insert dynamic meta data with id - %_1_id.
-30874	TRANSACTION_SERVER_MSGS_FAILED_TO_ADD_PB_TO_META_DATA	Failed to add property bag to the meta data object.

Error code	Handle	Message\Additional information
-30873	TRANSACTION_SERVER_FAILED_TO_ADD_META_DATA_SINCE_INPUT_KEY_IS_ALREADY_EXISTS	Failed to add meta data, since key "%1" is already exists.
-30872	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_SUBSCRIBER_OF_SAMPLES	Failed to open subscriber for samples data.
-30871	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_PUBLISHER_OF_SAMPLES	Failed to open publisher for samples data.
-30870	TRANSACTION_SERVER_MSGS_FAILED_TO_DECODE_SAMPLES	Failed to decode samples data.
-30869	TRANSACTION_SERVER_MSGS_FAILED_TO_ENCODE_SINGLE_SAMPLE	Failed to encode sample.
-30868	TRANSACTION_SERVER_MSGS_FAILED_TO_WAIT_ON_TRIGGER_SINCE_ANOTHER_TS_IS_NOT_UP	Failed to attach to another transaction server.
-30867	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_TIMER_FOR_REATTACHING	Failed to create timer for reattaching.
-30866	TRANSACTION_SERVER_MSGS_FAILED_TO_CLOSE_TIMER_FOR_REATTACHING	Failed to close timer for reattaching.
-30865	TRANSACTION_SERVER_MSGS_GET_UNFAMILIAR_RETURN_VALUE_OF_WAIT_FOR_TRIGGER	Get an unfamiliar return value of DrvWaitForTrigger API: %_1_id.
-30864	TRANSACTION_SERVER_MSGS_TRY_TO_CREATE_ANOTHER_TIMER_ALTHOUGH_THERE_IS_ONE	Can't create another reattach timer, since there is one - maybe I got a call to 'attachstatuscb' without call to attach API.
-30863	TRANSACTION_SERVER_FAILED_TO_ALLOCATE_DISTRIBUTED_TRANSACTION_OBJECT	Failed to allocate memory for distributed transaction object.
-30862	TRANSACTION_SERVER_DISTRIBUTED_TRANS_DID_NOT_GET_CORRELATOR	Failed to get correlator for end distributed transaction.
-30861	TRANSACTION_SERVER_GET_UNNEEDED_DATA_FOR_END_DISTRIBUTED_TRANSACTION	Get an unneeded data for end distributed transaction.
-30860	TRANSACTION_SERVER_FAILED_TO_CREATE_DISTRIBUTED_TRANSACTION_OBJECT	Failed to create object of distributed transaction.
-30859	TRANSACTION_SERVER_FAILED_TO_CREATE_TIMER_FOR_DISTRIBUTED_TRANSACTION_TIMEOUT	Failed to create timer for a distributed transaction object.
-30858	TRANSACTION_SERVER_FAILED_TO_CREATE_DISTRIBUTED_TRANSACTION_OBJ_NO_NAME	Failed to create object of distributed transaction since there is no transaction name.
-30857	TRANSACTION_SERVER_FAILED_TO_CREATE_DISTRIBUTED_TRANSACTION_OBJ_NO_START_TIME	Failed to create object of distributed transaction since there is no start time.
-30856	TRANSACTION_SERVER_FAILED_TO_CREATE_TIMER_FOR_DISTRIBUTED_TRANSACTION_NO_CORRELATOR	Failed to create object of distributed transaction since there is no correlator.
-30855	TRANSACTION_SERVER_FAILED_TO_GET_DISTRIBUTED_TRANS_OBJ_FROM_HASH	Failed to get distributed transaction object. Possible causes: A call to start distributed transaction with correlator "%1" has not been executed yet or the transaction ended with timeout.
-30854	TRANSACTION_SERVER_DELETE_DISTRIBUTED_TRANS_DUE_TO_TIMEOUT	Report distributed transaction "%1" with correlator "%2" with status LR_TIMED_OUT since timeout passed.
-30853	TRANSACTION_SERVER_PROBLEM_WITH_RESPONSE_TIME_DELETE_TRANSACTION	Deleted the current transaction "%1" since response time is not accurate.
-30852	TRANSACTION_SERVER_DELETE_DISTRIBUTED_TRANS_DUE_TO_NO_END_EVENT	Deleted distributed transaction "%1" with correlator "%2" since there was no end statement.
-30851	TRANSACTION_SERVER_FAILED_TO_ADD_DISTRIBUTED_TRANS_TO_HASH_SINCE_THERE_IS_ONE	Failed to add current distributed transaction with correlator "%1" to hash since there is already such a transaction.
-30850	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_HASH_FOR_DISTRIBUTED_TRANSACTIONS	Failed to create hash table for distributed transactions.
-30849	TRANSACTION_SERVER_FAILED_TO_ADD_DISTRIBUTED_TRANS_TO_HASH_TABLE	Failed to add distributed transaction with correlator "%1" to hash.
-30848	TRANSACTION_SERVER_FAILED_TO_CREATE_DISTRIBUTED_TRANSACTION_OBJECT_NO_CORRELATOR	Failed to create distributed transaction object since there is no correlator.
-30847	TRANSACTION_SERVER_FAILED_TO_GET_META_DATA_FOR_DISTRIBUTED_TRANSACTION	Failed to get meta data for the current distributed transaction "%1" with correlator "%2".
-30846	TRANSACTION_SERVER_FAILED_TO_CREATE_DISTRIBUTED_TRANSACTION_OBJ_NO_META_DATA_UNIQUE_ID	Failed to create object of distributed transaction since there is no meta data unique id.
-30845	TRANSACTION_SERVER_MSGS_FAILED_TO_WRITE_TO_THE_EVE_FILE_SINCE_IT_ALREADY_CLOSED	Failed to write to the .eve file since it is already closed.

Error code	Handle	Message\Additional information
-30844	TRANSACTION_SERVER_FAILED_TO_WRITE_DISTRIBUTED_TRANSACTION_TO_THE_EVE_FILE	Failed to write distributed transaction "%1" with correlator "%2" to the .eve file.
-30843	TRANSACTION_MSGS_EXCEPTION_WAS_RAISED_WHILE_CALLING_SAMPLE_FUNC	Exception was raised while calling Sample_Arrived_CB function in "%1" extension.
-30842	TRANSACTION_MSGS_FAILED_SAMPLE_DATA_FUNC_RETURN_ERROR	Failed to run Sample_Arrived_CB function in the "%1" extension.
-30841	TRANSACTION_MSGS_FAILED_SAMPLE_ARRAY_DATA_FUNC_RETURN_ERROR	Failed to run SampleArray_Arrived_CB function in the "%1" extension.
-30840	TRANSACTION_SERVER_MSGS_ERR_2_LARGE_CUSTOM_CHAN_REQ	Getting too long message from the java channel.
-30839	TRANSACTION_SERVER_MSGS_ERR_DECODE_MSG_H_FAILED	Failed to decode message header.
-30838	TRANSACTION_SERVER_MSGS_ERR_CREATE_CUSTOM_CHANNEL_CLIENT_FAILED	Failed to create custom channel client with the connection string: "%1".
-30837	TRANSACTION_SERVER_MSGS_ERR_POST_MSG_ON_CUSTOM_CHANNEL_FAILED	Failed to send message on custom channel with the connection string: "%1".
-30836	TRANSACTION_SERVER_MSGS_ERR_DECODE_REQ_H_FAILED	Failed to decode request header.
-30835	TRANSACTION_SERVER_MSGS_ERR_GET_SERVICE_FAILED_REQ_H	Failed to get the service name of the header of a request.
-30834	TRANSACTION_SERVER_MSGS_ERR_WRONG_REQ_TYPE	Wrong request type (%1).
-30833	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_CUSTOM_SERVER_CHANNEL	Failed to open custom server channel on port - %_1_id.
-30832	TRANSACTION_SERVER_MSGS_FAILED_TO_DECODE	Failed to decode %1.
-30831	TRANSACTION_SERVER_MSGS_FAILED_TO_GET_DATA_FROM_MSG	Failed to get %1 from message.
-30830	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_HASH_JAVA_CLIENTS_CS_TRANSACTIONS	Failed to create hash table for java clients handles.
-30829	TRANSACTION_SERVER_FAILED_TO_ADD_JAVA_CLIENT_HANDLE_TO_HASH_TABLE	Failed to add java client handle with connection string: "%1" to hash.
-30828	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_TIMER_FOR_JAVA_CLIENTS	Failed to create a timer that is used to clean the hash of the java clients handles.
-30827	TRANSACTION_SERVER_ATTACH_STATUS_PS_POST_GUARANTEED	Got notification for guaranty delivery of messages.
-30826	TRANSACTION_SERVER_MSGS_MSG_DELIVERY_IS_NOT_GUARANTY	The message was not send since the delivery is not guaranteed.
-30825	TRANSACTION_SERVER_MSGS_ERR_BAD_CUSTOM_CHANNEL_MSG_HEADER	Bad format of custom channel message header.
-30824	TRANSACTION_SERVER_MSGS_ERR_FAILED_TO_ENCODE	Failed to encode "%1" struct by xdr.
-30823	TRANSACTION_SERVER_MSGS_ERR_FAILED_TO_GET_CURR_TIME	Failed to get the current time.
-30822	TRANSACTION_SERVER_MSGS_FAILED_TO_GET_LENGTH_FOR_XDR_BUFFER	Failed to get the needed size for xdr encoding function.
-30821	TRANSACTION_SERVER_FAILED_TO_UPDATE_TIME_DIFF	Failed to update time diff for data.
-30820	TRANSACTION_SERVER_FAILED_TO_UPDATE_TIME_DIFF_FOR_SAMPLE_NO_TIME_FIELDS	Failed to update time diff to sample of type "%1" due to absence of time fields in the sample.
-30819	TRANSACTION_SERVER_MSGS_TOO_MANY_LOADER_CLIENTS	There are too many ts loader clients.
-30818	TRANSACTION_SERVER_GET_PBAG_ON_END_DISTRIBUTED_TX	Received unexpected property bag in distributed transaction end callback.
-30817	TRANSACTION_SERVER_FAILED_TO_CLONE_PROPBAG_FOR_DISTRIBUTED_TX	Failed to clone property bag for distributed transaction due to XDR problem.
-30816	TRANSACTION_SERVER_FAILED_TO_ADD_REF_SINCE_NO_META_DATA_OBJ	Failed to add reference count for meta data since there is no existed meta data object.
-30815	TRANSACTION_SERVER_NOTIFY_START_DISTRIBUTED	Start distributed transaction "%2" with correlator "%1". Timeout value: %_3_id.
-30814	TRANSACTION_SERVER_NOTIFY_END_DISTRIBUTED	End distributed transaction "%2" with correlator "%1".
-30813	TRANSACTION_SERVER_NOTIFY_END_DISTRIBUTED_WITH_TIMEOUT	Distributed transaction "%2" with correlator "%1" ended with timeout status.
-30812	TRANSACTION_OFFLINE_SERVER_FAILED_TO_OPEN_DEBUG_FILE	Cannot open output debug file - %1.
-30811	TRANSACTION_OFFLINE_FAILED_TO_GET_END_SCENARIO_DATA_SINCE_THERE_IS_NO_OBJECT	Can't get a call to end scenario since there was no start scenario.
-30810	TRANSACTION_OFFLINE_CAN_NOT_START_SCENARIO_WITHOUT_FINISHED_ANOTHER_ONE	Offline cannot get more then one call to start scenario - only one scenario can run at a time.
-30809	TRANSACTION_OFFLINE_FAILED_TO_GET_MAIN_THREAD_CONTEXT	Offline failed to get main thread context through driver API.
-30808	TRANSACTION_OFFLINE_MSGS_FAILED_TO_OPEN_START_SCENARIO_SERVICE	Failed to create service provider for getting notification about TC start scenario.
-30807	TRANSACTION_OFFLINE_MSGS_FAILED_TO_OPEN_END_SCENARIO_SERVICE	Failed to create service provider for getting notification about end TC scenario.
-30806	TRANSACTION_OFFLINE_MSGS_FAILED_TO_DECODE_SCENARIO_DATA	Failed to decode TC scenario data.

Error code	Handle	Message\Additional information
-30805	OFFLINE_SERVER_MSGS_FAILED_TO_CREATE_EVE_FILE	Offline Writer failed to create .eve file in %1
-30804	TRANSACTION_SERVER_MSGS_ERR_ABORTING_TRANSACTION_SERVER	The transaction server is aborting due to the error: % 1 Id
-30803	TRANSACTION_MSGS_FAILED_TO_INSERT_META_DATA_INTO_HASH	=Failed to insert meta data with unique id % 1 Id into the hash table. (Stl failure).
-30802	TRANSACTION_SERVER_MSGS_FAILED_TO_CREATE_LISTENER_SERVICE_F OR_WARNINGS	Failed to create listener warning service.
-30801	TRANSACTION_SERVER_PROBLEM_WITH_NEGATIVE_RESPONSE_TIME	Detected negative response time. %1
-30800	TRANSACTION_SERVER_COMPRESSED_BUFFER_TOO_SMALL	Failed to compress raw data buffer: buffer too small.
-30799	TRANSACTION_SERVER_DECOMPRESSED_BUFFER_CORRUPTED_DATA	Failed to decompress raw data buffer: data is corrupted.
-30798	TRANSACTION_SERVER_DECOMPRESSED_BUFFER_TOO_SMALL	Failed to decompress raw data buffer: buffer too small.
-30797	TRANSACTION_SERVER_BUFFER_SIZE_TOO_BIG	Raw data buffer is too small.
-30796	TRANSACTION_SERVER_MSGS_FAILED_TO_SUBSCRIBE_TO_SCENARIO_STA RT_CONTROLLER_SERVICE	Failed to subscribe to scenario start controller service
-30795	TRANSACTION_SERVER_MSGS_FAILED_TO_SUBSCRIBE_TO_SCENARIO_EN D_CONTROLLER_SERVICE	Failed to subscribe to scenario end controller service
-30794	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_RAW_DATA_CLIENT_SER VICE	Failed to open client service 'RawDataService' for sending raw data
-30793	TRANSACTION_SERVER_MSGS_FAILED_TO_OPEN_RAW_DATA_SERVICE	Failed to open server service 'RawDataService' for getting raw data
trans_to_kafka_res.h		
-241999	TRANS_TO_KAFKA_MSGS_FAILED_TO_CREATE_PRODUCER	Failed to create Kafka producer because %1.
-241998	TRANS_TO_KAFKA_MSGS_FAILED_TO_SEND_TRANSACTION	Failed to send transaction '%1'. Error code % 2 Id.
-241997	TRANS_TO_KAFKA_MSGS_FAILED_TO_SEND_DATA_POINT	Failed to send data point '%1' Error code % 2 Id.
-241996	TRANS_TO_KAFKA_MSGS_FAILED_TO_GET_OBJ_BY_TLS_SO_THE_CURREN T_TRANSACTION_WILL_NOT_BE_SENT_TO_THE_KAFKA	Failed to get the producer object by TLS so the current transaction '%1' will not be sent to the Kafka.
-241995	TRANS_TO_KAFKA_MSGS_FAILED_TO_GET_OBJ_BY_TLS_SO_THE_CURREN T_DATA_POINT_WILL_NOT_BE_SENT_TO_THE_KAFKA	Failed to get the producer object by TLS so the current data point '%1' will not be sent to the Kafka.
tst_aes_msg.h		
-67999	TST_AES_SUCCESS	The test was successful.
-67998	TST_AES_ERR_AES_NOT_STARTING	Aes extension failed to initialize within a sensible amount of time.
-67997	TST_AES_ERR_FAILED_TO_CREATE_TEST_OUTPUT_FILE	Failed to create the test output file '%1'. This file is used by run_time sanity mechanism to check this test results.
tst_floating_license_msg.h		
-88999	FL_TEST_ERROR_NO_TEST_MODE	Floating License Test: fl_test_mode is missing in command line.
-88998	FL_TEST_ERROR_ILLEGAL_TEST_MODE	Floating License Test: Illegal test mode: %1.
-88997	FL_TEST_ERROR_CREATE_MANAGER	Floating License Test: Failed to create test manager.
-88996	FL_TEST_ERROR_CREATE_CLIENT	Floating License Test: Failed to create FL client.
-88995	FL_TEST_ERROR_XDR_ENCODE	Floating License Test: Failed to encode message.
-88994	FL_TEST_ERROR_XDR_DECODE	Floating License Test: Failed to decode message.
-88993	FL_TEST_ERROR_POST_P2P_MSG	Floating License Test: Failed to post a p2p message.
-88992	FL_TEST_ERROR_LAUNCH_PROCESS	Floating License Test: Failed to launch process %1.
-88991	FL_TEST_ERROR_OPEN_P2P_SERVER	Floating License Test: Failed to open a p2p server.
-88990	FL_TEST_ERROR_OPEN_P2P_CLIENT	Floating License Test: Failed to open a p2p client.
-88989	FL_TEST_ERROR_CREATE_TRIGGER	Floating License Test: Failed to create a trigger.
-88988	FL_TEST_ERROR_CREATE_FIFO	Floating License Test: Failed to create a fifo queue.
-88989	FL_TEST_MANAGER_ERROR_LAUNCH_SERVER	Floating License Test: Manager failed to launch FL Server.
-88988	FL_TEST_MANAGER_ERROR_LAUNCH_CLIENT	Floating License Test: Manager failed to launch FL Client.
-88897	FL_TEST_MANAGER_ERROR_LAUNCH_SERVER_CB	Floating License Test: Manager received launch status callback of FL Server with status % 1 Id.
-88896	FL_TEST_MANAGER_ERROR_LAUNCH_CLIENT_CB	Floating License Test: Manager received launch status callback of FL Client with status % 1 Id.
-88895	FL_TEST_MANAGER_ERROR_OPEN_PROTOCOL_FILE	Floating License Test: Manager failed to open protocol file.
-88894	FL_TEST_MANAGER_ERROR_SEND_REQUEST_START_TEST	Floating License Test: Manager failed to send request start test to FL Client.
-88893	FL_TEST_MANAGER_ERROR_TEST_TIMEOUT_ELAPSED	Floating License Test: Test timeout elapsed.
-88892	FL_TEST_MANAGER_ERROR_RECEIVE_MSG	Floating License Test: Manager failed to receive a message from FL Client.
-88891	FL_TEST_MANAGER_DEBUG_STATUS_FAIL	Floating License Test: Test failed.
-88890	FL_TEST_MANAGER_DEBUG_STATUS_PASS	Floating License Test: Test passed.
-88889	FL_TEST_MANAGER_ERROR_READ_CFG	Floating License Test: Manager failed to read test configuration from cfg file %1.
-88888	FL_TEST_MANAGER_ERROR_INSTALL_KEY	Floating License Test: Manager failed to install license key: %1.

Error code	Handle	Message\Additional information
-88887	FL TEST MANAGER ERROR BACKUP ORIG DIR	Floating License Test: Manager failed to backup license directory.
-88886	FL TEST MANAGER ERROR FAILED TO GET TMP DIR	Floating License Test: Manager failed to get temp directory.
-88885	FL TEST MANAGER ERROR FAILED TO CREATE BACKUP DIR	Floating License Test: Manager failed to create backup directory.
-88884	FL TEST MANAGER ERROR FAILED TO EMPTY BACKUP DIR	Floating License Test: Manager failed to empty backup directory.
-88883	FL TEST MANAGER ERROR FAILED TO BACKUP LICENSE DIR	Floating License Test: Manager failed to backup license directory.
-88882	FL TEST MANAGER ERROR FAILED TO RESTORE LICENSE DIR	Floating License Test: Manager failed to restore license directory.
-88881	FL TEST MANAGER ERROR LAUNCH INSTALLER_CB	Floating License Test: Manager received launch status callback of Installer with status % 1 _ld.
-88799	FL TEST CLIENT ERROR RECEIVE MSG	Floating License Test: Client failed to receive a message from Manager.
-88798	FL TEST CLIENT ERROR REPORT STATUS	Floating License Test: Client failed to report status to Manager.
-88797	FL TEST CLIENT DEBUG STATUS FAIL	Floating License Test: Client's status: failed.
-88796	FL TEST CLIENT DEBUG STATUS PASS	Floating License Test: Client's status: passed.
-88795	FL TEST CLIENT ERROR CREATE TEST EPISODE	Floating License Test: Client failed to create test episode.
-88794	FL TEST CLIENT ERROR BUILD TEST	Floating License Test: Client failed to build test.
-88793	FL TEST CLIENT ERROR GET WAITING SUBACTION	Floating License Test: Client failed to find a waiting sub-action when woke up on FL Client callback.
-88792	FL TEST CLIENT ERROR OPEN RESULTS_FILE	Floating License Test: Client failed to open results file.
-88791	FL TEST CLIENT ERROR READ CFG	Floating License Test: Client failed to read test configuration from cfg file %1.
-88790	FL TEST CLIENT ERROR CFG MISSING ENTRY	Floating License Test: Missing entry %1 in cfg file.
-88789	FL TEST CLIENT ERROR CFG UNKNOWN_API_FUNC	Floating License Test: Unknown API function '%1' in cfg file.
-88788	FL TEST CLIENT ERROR INIT SUBACTIONS	Floating License Test: Client failed to init sub-actions of action %1.
tst_run_action_in_server_mode_res.h		
-65900	TST_SM_FAILED_TO_CREATE_AN_OBJECT	Error in %1: Failed to create %2 object.
-65899	TST_SM_FAILED_TO_EXECUTE_ACTION	Failed to execute %1.
-65898	TST_SM_NO_ACTIONS_PATH_ATTRIB	Missing attribute "-actions_path" (which indicates the actions directory).
-65897	TST_SM_NO_STATUS_PATH_ATTRIB	Missing attribute "-status_file_path".
-65896	TST_SM_WRONG_STATUS_PATH_ATTRIB	wrong status file path: %1.
-65895	TST_SM_ACTION_EXEC_REPORT	action "%1" returned % 2 _ld.
-65894	TST_SM_ACTION_WRONG_RETURN_VALUE	Action returned wrong return value. Got: % 1 _ld, should be: % 2 _ld.
-65893	TST_SM_FUNCTION_FAILED	function "%1" failed. return value: % 2 _ld.
-65892	TST_SM_ACTION_NUM_REMOVED_FROM_QUEUE	% 1 _ld actions was removed from queue instead of % 2 _ld.
-65800	TST_SM_TEST_STATUS	Status: %1.
twc_msg.h		
-60999	TWC_CAPI_CREATE_ACCEPTOR_ERROR	Two Way Communication Error: Function two_way_comm_create_acceptor failed.
-60998	TWC_CAPI_CREATE_CONNECTOR_ERROR	Two Way Communication Error: Function two_way_comm_create_connector failed.
-60997	TWC_CAPI_DESTROY_ERROR	Two Way Communication Error: Function two_way_comm_destroy failed.
-60996	TWC_CAPI_DESTROY_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_destroy failed. Reason: invalid handle.
-60995	TWC_CAPI_CLOSE_CONNECTION_ERROR	Two Way Communication Error: Function two_way_comm_close_connection failed.
-60994	TWC_CAPI_CLOSE_INVALID_POST_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_close_connection failed. Reason: invalid handle.
-60993	TWC_CAPI_GET_CS_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_get_connection_string failed. Reason: invalid handle.
-60992	TWC_CAPI_FLUSH_ERROR	Two Way Communication Error: Function two_way_comm_flush failed.
-60991	TWC_CAPI_FLUSH_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_flush failed. Reason: invalid handle.
-60990	TWC_CAPI_POST_MSG_ERROR	Two Way Communication Error: Function two_way_comm_post_message / two_way_comm_post_message_ex failed.
-60989	TWC_CAPI_POST_MSG_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_post_message / two_way_comm_post_message_ex failed. Reason: invalid handle.
-60988	TWC_CAPI_POST_MSG_ILLEGAL_PARAM_ERROR	Two Way Communication Error: Function two_way_comm_post_message / two_way_comm_post_message_ex failed. Reason: illegal parameter.
-60987	TWC_CAPI_SET_USERDATA_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_set_userdata_on_post_handle failed. Reason: invalid handle.
-60986	TWC_CAPI_GET_POST_HANDLE_INVALID_HANDLE_ERROR	Two Way Communication Error: Function get_post_handle_for_sync_connector failed. Reason: invalid handle - This function is allowed only for connector in sync mode.
-60985	TWC_CAPI_RESOLVE_USERDATA_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_resolve_userdata failed. Reason: invalid handle.
-60984	TWC_CAPI_RESOLVE_STRING_IDENTIFIER_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_resolve_string_identifier failed. Reason: invalid handle.
-60983	TWC_CAPI_OPTION_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_set_options failed. Reason: invalid handle.
-60982	TWC_CAPI_RECV_SUSPEND_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_rcv_suspend failed. Reason: invalid handle.
-60981	TWC_CAPI_RECV_RESUME_INVALID_HANDLE_ERROR	Two Way Communication Error: Function two_way_comm_rcv_resume failed. Reason: invalid handle.
-60899	TWC_GENERAL_MSG_DEBUG	1%
-60898	TWC_GENERAL_MSG_DEBUG_WITH_INT	%1 % 2 _ld.

Error code	Handle	Message\Additional information
-60897	TWC_XDR_DECODE_ERROR	Two Way Communication Error: XDR decoding failure.
-60896	TWC_XDR_ENCODE_ERROR	Two Way Communication Error: XDR encoding failure.
-60895	TWC_CONNECTION_STRING_LEN_ERROR	Two Way Communication Error: Length of the connection string is more 1024 bytes.
-60799	TWC_UNIT_GOT_USER_MSG_FROM_QUEUE_DEBUG	Two Way Communication Debug: Unit %1 got a user message from waiting queue.
-60798	TWC_UNIT_RECV_SUSPEND_DEBUG	Two Way Communication Debug: Unit %1 is suspended.
-60797	TWC_UNIT_RECV_RESUME_DEBUG	Two Way Communication Debug: Unit %1 is resumed.
-60796	TWC_PVC_DESREGARD_DEBUG	Two Way Communication Debug: recieved pvc internal message, disregarding message.
-60795	TWC_PVC_ERROR_SEND_DEBUG	Two Way Communication Debug: recieved message with higher protocol version, disregarding message.
-60794	TWC_PVC_VERSION_MISMATCH_DEBUG	Two Way Communication Debug: remote end doesn't support our version, disregarding message.
-60793	TWC_PVC_DECODE_ERROR	Two Way Communication Error: pvc decode error, disregarding message.
-60792	TWC_PVC_INTERNAL_ERROR	Two Way Communication Error: pcv internal error, disregarding message.
-60791	TWC_PVC_REPLY_CREATE_CLIENT_ERROR	Two Way Communication Error: Failed to create client to sending pvc reply , cs: %1.
-60790	TWC_PVC_REPLY_POST_ERROR	Two Way Communication Error: Failed to create client to sending pvc reply , cs: %1.
-60789	TWC_PVC_REPLY_RECIEVED_CONNECT_ERROR	Two Way Communication Error: recieved connect error when creating client to sending pvc reply.
-60788	TWC_PVC_REPLY_SENT_DEBUG	Two Way Communication Debug: pvc reply sent successfully.
-60699	TWC_ACCEPTOR_RECV_MSG_ERROR	Two Way Communication Error: Acceptor %1 failed to receive message.
-60698	TWC_ACCEPTOR_CREATE_DYN_ARRAY_ERROR	Two Way Communication Error: Acceptor %1 failed to create dynamic array.
-60697	TWC_ACCEPTOR_CREATE_HASH_TABLE_ERROR	Two Way Communication Error: Acceptor %1 failed to create hash table.
-60696	TWC_ACCEPTOR_FAILED_TO_FIND_POST_HANDLE_ERROR	Two Way Communication Error: Acceptor %1 failed to find post handle in container.
-60695	TWC_ACCEPTOR_FAILED_TO_CREATE_POST_HANDLE_ERROR	Two Way Communication Error: Acceptor %1 failed to create a post handle with connection string: %2.
-60694	TWC_ACCEPTOR_FAILED_TO_KEEP_POST_HANDLE_ERROR	Two Way Communication Error: Acceptor %1 failed to keep post handle in container.
-60693	TWC_ACCEPTOR_POST_CONN_ACK_MSG_ERROR	Two Way Communication Error: Acceptor %1 failed to post connection acknowledgement to connector.
-60692	TWC_ACCEPTOR_POST_DOWN_MSG_ERROR	Two Way Communication Error: Acceptor %1 failed to send down notification to connector with ID % 2 Id.
-60691	TWC_ACCEPTOR_SEND_DOWN_NOTIFICATION_ERROR	Two Way Communication Error: Acceptor %1 failed to send down notifications to its connectors.
-60690	TWC_ACCEPTOR_CREATE_SERVER_ERROR	Two Way Communication Error: Acceptor %1 failed to create a Custom Channel server.
-60689	TWC_ACCEPTOR_FAILED_TO_CONNECT_ERROR	Two Way Communication Error: Acceptor %1 failed to connect to connector.
-60688	TWC_ACCEPTOR_FAIL_INIT_HEARTBEAT_CHECKER_ERROR	Two Way Communication Error: Acceptor %1 failed to initialize heartbeat checker.
-60687	TWC_ACCEPTOR_SUCCEED_INIT_HEARTBEAT_CHECKER_DEBUG	Two Way Communication Debug: Acceptor %1 initialized heartbeat checker for connector with ID % 2 Id. Timeout = % 3 Id, trials = % 4 Id.
-60686	TWC_ACCEPTOR_HB_SENDER_WORKAROUND_ERROR	Two Way Communication Error: Acceptor %1 - Heartbeat workaround failed (not all senders managed to send a heartbeat message).
-60685	TWC_ACCEPTOR_HB_SENDER_WORKAROUND_DEBUG	Two Way Communication Debug: Acceptor %1 - Heartbeat workaround: Reached % 2 Id bytes - sending heartbeat messages to connectors.
-60684	TWC_ACCEPTOR_INIT_HEARTBEAT_SENDER_ERROR	Two Way Communication Error: Acceptor %1 failed to initialize heartbeat sender.
-60683	TWC_ACCEPTOR_INIT_HEARTBEAT_SENDER_DEBUG	Two Way Communication Debug: Acceptor %1 initialized Heartbeat sender successfully.
-60682	TWC_ACCEPTOR_CREATED_DEBUG	Two Way Communication Debug: Acceptor %1 created. Options: % 2 Id.
-60681	TWC_ACCEPTOR_ACCEPTED_CONNECTOR_DEBUG	Two Way Communication Debug: Acceptor %1 accepted new connector with ID % 2 Id.
-60680	TWC_ACCEPTOR_DOWN_DEBUG	Two Way Communication Debug: Acceptor %1 going down.
-60679	TWC_ACCEPTOR_RECEIVED_DOWN_DEBUG	Two Way Communication Debug: Acceptor %1 received a down message from connector with ID % 2 Id.
-60678	TWC_ACCEPTOR_RESOLVE_CONN_STRING_ERROR	Two Way Communication Error: Acceptor %1 failed to resolve connection string from connection request.
-60677	TWC_ACCEPTOR_RESOLVE_SENDER_GUID_ERROR	Two Way Communication Error: Acceptor %1 failed to resolve sender GUID from connection request.
-60676	TWC_ACCEPTOR_ADDED_USER_MSG_TO_QUEUE_DEBUG	Two Way Communication Debug: Acceptor %1 Added a user message to waiting queue.
-60675	TWC_ACCEPTOR_ADDED_DOWN_MSG_TO_QUEUE_DEBUG	Two Way Communication Debug: Acceptor %1 received a down message from Connector, but client is not ready yet. Adding message to waiting queue.
-60674	TWC_ACCEPTOR_GOT_USER_MSG_FROM_QUEUE_DEBUG	Two Way Communication Debug: Acceptor %1 got a user message from waiting queue.
-60673	TWC_ACCEPTOR_GOT_DOWN_MSG_FROM_QUEUE_DEBUG	Two Way Communication Debug: Acceptor %1 got a down message from waiting queue.
-60672	TWC_ACCEPTOR_POST_DOWN_MSG_TO_CONNECTOR	Two Way Communication Debug: Acceptor %1 send down notification to connector with ID % 2 Id.
-60671	TWC_ACCEPTOR_FAILED_TO_RECONNECT_ERROR	Two Way Communication Error: Acceptor %1 failed to reconnect to connector.
-60670	TWC_ACCEPTOR_RECEIVED_DISCONN_REQ_DEBUG	Two Way Communication Debug: Acceptor %1 received a disconnection request message from connector with ID % 2 Id.
-60669	TWC_ACCEPTOR_SEND_READY_DEBUG	Two Way Communication Debug: Acceptor %1 got on_send_ready notification from channel.
-60668	TWC_ACCEPTOR_RENEWED_CONNECTION_DEBUG	Two Way Communication Debug: Acceptor %1 renewd connection with connector with ID % 2 Id.
-60667	TWC_ACCEPTOR_ACTIVE_DEBUG	Two Way Communication Debug: Acceptor %1 notifies: Connection with ID % 2 Id is active.
-60666	TWC_ACCEPTOR_INACTIVE_DEBUG	Two Way Communication Debug: Acceptor %1 notifies: Connection with ID % 2 Id is inactive.
-60665	TWC_ACCEPTOR_START_CONNECTION_RENEWAL_HB_DEBUG	Two Way Communication Debug: Acceptor %1 started reconnection renewal HeartBeat. Timeout = % 2 Id.
-60664	TWC_ACCEPTOR_STOP_CONNECTION_RENEWAL_HB_DEBUG	Two Way Communication Debug: Acceptor %1 stopped reconnection renewal HeartBeat.
-60663	TWC_ACCEPTOR_FAILED_TO_DECODE_CS_ERROR	=Two Way Communication Error: Acceptor %1 failed to decode the connection string in connection request of connector with ID % 2 Id.
-60662	TWC_ACCEPTOR_NO_RECONNECTION_TIMEOUT_ERROR	Two Way Communication Error: Acceptor %1 missing reconnection timeout in disconnection msg.
-60661	TWC_ACCEPTOR_SEND_DOWN_ACK_ERROR	Two Way Communication Error: Acceptor %1 failed to send a down ack message to connector with ID % 2 Id.
-60660	TWC_ACCEPTOR_SEND_DOWN_ACK_DEBUG	Two Way Communication Debug: Acceptor %1 sent a down ack message to connector with ID % 2 Id.
-60659	TWC_ACCEPTOR_UNEXPECTED_HANDSHAKE_REQ_ACK	Two Way Communication Error: Acceptor %1 received security handshake REQ/ACK message while security mode is off.

Error code	Handle	Message\Additional information
-60599	TWC CONNECTOR RECV MSG ERROR	Two Way Communication Error: Connector %1 failed to receive message.
-60598	TWC CONNECTOR FAILED TO CONNECT ERROR	Two Way Communication Error: Connector %1 failed to connect to acceptor with connection string: %2.
-60597	TWC CONNECTOR POST CONN REQ ERROR	Two Way Communication Error: Connector %1 failed to post connection request to acceptor.
-60596	TWC CONNECTOR POST DOWN MSG ERROR	Two Way Communication Error: Connector %1 failed to post down message to acceptor.
-60595	TWC CONNECTOR CREATE SERVER ERROR	Two Way Communication Error: Connector %1 failed to create a Custom Channel server.
-60594	TWC CONNECTOR FAILED TO CREATE POST HANDLE ERROR	Two Way Communication Error: Connector %1 failed to create a post handle with connection string: %2.
-60593	TWC CONNECTOR TIMEOUT ELAPSED ERROR	Two Way Communication Error: Connector %1 failed to connect - timeout elapsed.
-60592	TWC CONNECTOR REGISTER TIMER ERROR	Two Way Communication Error: Connector %1 failed to register a timer.
-60591	TWC CONNECTOR CREATE TRIGGER ERROR	Two Way Communication Error: Connector %1 failed to create a trigger.
-60590	TWC CONNECTOR NEGATIVE TIMEOUT ERROR	Two Way Communication Error: Failed to initialize connector %1 - user passed a negative connect_timeout.
-60589	TWC CONNECTOR FAIL INIT HEARTBEAT CHECKER ERROR	Two Way Communication Error: Connector %1 failed to initialize heartbeat checker.
-60588	TWC CONNECTOR SUCCEED INIT HEARTBEAT CHECKER DEBUG	Two Way Communication Debug: Connector %1 initialized heartbeat checker. Timeout = % 2 Id, trials = % 3 Id.
-60587	TWC CONNECTOR HB SENDER WORKAROUND ERROR	Two Way Communication Error: Connector %1 - Heartbeat workaround failed (sender failed to send a heartbeat message).
-60586	TWC CONNECTOR HB SENDER WORKAROUND DEBUG	Two Way Communication Debug: Connector %1 - Heartbeat workaround: Reached % 2 Id bytes - sending a heartbeat message to acceptor.
-60585	TWC CONNECTOR INIT HEARTBEAT SENDER ERROR	Two Way Communication Error: Connector %1 failed to initialize Heartbeat sender.
-60584	TWC CONNECTOR INIT HEARTBEAT SENDER DEBUG	Two Way Communication Debug: Connector %1 initialized Heartbeat sender successfully.
-60583	TWC CONNECTOR READY DEBUG	Two Way Communication Debug: Connector %1 is ready. Options: % 2 Id.
-60582	TWC CONNECTOR DOWN DEBUG	Two Way Communication Debug: Connector %1 going down.
-60581	TWC CONNECTOR RECEIVED DOWN DEBUG	Two Way Communication Debug: Connector %1 received a down message from acceptor.
-60580	TWC CONNECTOR RECEIVED CONN ACK DEBUG	Two Way Communication Debug: Connector %1 received a connection ack message from acceptor. Internal ID: % 2 Id.
-60579	TWC CONNECTOR POST DOWN MSG TO ACCEPTOR	Two Way Communication Debug: Connector %1 with ID % 2 Id sending down notification to acceptor.
-60578	TWC CONNECTOR FAILED TO RECONNECT ERROR	Two Way Communication Error: Connector %1 failed to reconnect to acceptor with connection string: %2.
-60577	TWC CONNECTOR RECEIVED RECONN ACK DEBUG	Two Way Communication Debug: Connector %1 received a reconnection ack message from acceptor.
-60576	TWC CONNECTOR DISCONNECTING DEBUG	Two Way Communication Debug: Connector %1 disconnecting.
-60575	TWC CONNECTOR SEND DISCONNECTION REQ MSG ERROR	Two Way Communication Error: Connector %1 failed to send disconnection request.
-60574	TWC CONNECTOR SEND READY DEBUG	Two Way Communication Debug: Connector %1 got on_send_ready notification from channel.
-60573	TWC CONNECTOR ACTIVE DEBUG	Two Way Communication Debug: Connector %1 is active.
-60572	TWC CONNECTOR INACTIVE DEBUG	Two Way Communication Debug: Connector %1 is inactive.
-60571	TWC CONNECTOR RECEIVED DOWN ACK DEBUG	Two Way Communication Debug: Connector %1 received a down ack message from acceptor.
-60570	TWC CONNECTOR ADDED USER MSG TO QUEUE DEBUG	Two Way Communication Debug: Connector %1 Added a user message to waiting queue.
-60569	TWC CONNECTOR UNEXPECTED HANDSHAKE REQ ACK	Two Way Communication Error: Connector %1 received security handshake REQ/ACK message while security mode is off.
-60568	TWC CONNECTOR FAILED TO CREATE SECURE CONNECTION	Two Way Communication Error: Connector failed to create secure connection. Ensure that the security keys are defined and that they match.
-60567	TWC CONNECTOR READY NOTIFY	Two Way Communication Notify: Connection string %1 has been sent to target.
-60499	TWC POST HANDLE CREATE CLIENT ERROR	Two Way Communication Error: Post handle failed to create a Custom Channel client.
-60498	TWC POST HANDLE SEND ERROR	Two Way Communication Error: Post handle failed to post a message via Custom Channel.
-60497	TWC_POST_HANDLE_INVALID_MSG_ARY_ERROR	Two Way Communication Error: Post handle failed to post message. Reason: message array does not have enough allocated space to hold a header.
-60496	TWC POST HANDLE SEND HEARTBEAT ERROR	Two Way Communication Error: Failed to send a heartbeat message. Connection ID: % 1 Id.
-60495	TWC POST HANDLE SEND HEARTBEAT DEBUG	Two Way Communication Debug: Sent a heartbeat message. Connection ID: % 1 Id.
-60494	TWC POST HANDLE CHECK HEARTBEAT DEBUG	Two Way Communication Debug: Heartbeat checker - trial % 1 Id: %2. Connection ID: % 3 Id.
-60493	TWC POST HANDLE HEARTBEAT NOT RESPONDING DEBUG	Two Way Communication Debug: Heartbeat checker - other side is not responding. Connection ID: % 1 Id.
-60492	TWC POST HANDLE FAILED TO CREATE GUID ERROR	Two Way Communication Error: Post handle failed to create a GUID. Function merc_uuid_generate_alloc() failed.
-60491	TWC POST HANDLE CREATED GUID DEBUG	Two Way Communication Debug: Post handle created a GUID: %1.
-60490	TWC POST HANDLE CREATED GD DEBUG	Two Way Communication Debug: Post handle created a Guaranty Delivery handle.
-60489	TWC POST HANDLE FAILED TO CREATE GD ERROR	Two Way Communication Error: Post handle failed to create a Guaranty Delivery handle.
-60488	TWC POST HANDLE HB CONNECTION NOT RENEWED DEBUG	Two Way Communication Debug: Heartbeat checker - Fitful connection not renewed. Other side is not responding. Connection ID: % 1 Id.
-60487	TWC POST HANDLE SEND BUSY DEBUG	Two Way Communication Debug: Post handle notifies GD: channel is busy.
-60486	TWC POST HANDLE GD POST NOTIFY DEBUG	Two Way Communication Debug: GD posts message. Connection ID: % 1 Id. Total size: % 2 Id. Message num: % 3 Id.
-60485	TWC POST HANDLE GD RECV NOTIFY DEBUG	Two Way Communication Debug: GD receives message. Connection ID: % 1 Id. Size: % 2 Id.
-60484	TWC POST HANDLE GD ON_IDLE NOTIFY DEBUG	Two Way Communication Debug: GD on idle. Connection ID: % 1 Id.
-60483	TWC POST HANDLE POST TO GD DEBUG	Two Way Communication Debug: Post handle posts message to GD. Connection ID: % 1 Id. Total size: % 2 Id. Message num: % 3 Id.
-60482	TWC POST HANDLE RECV TO GD DEBUG	Two Way Communication Debug: Post handle calls gd_on_receive. Connection ID: % 1 Id. Size: % 2 Id.
-60481	TWC POST HANDLE TO GD OPEN DEBUG	Two Way Communication Debug: Post handle calls gd_on_connection_open. Connection ID: % 1 Id.
-60480	TWC POST HANDLE TO GD READY DEBUG	Two Way Communication Debug: Post handle calls gd_on_connection_ready. Connection ID: % 1 Id.
-60479	TWC POST HANDLE TO GD CLOSE DEBUG	Two Way Communication Debug: Post handle calls gd_on_connection_close. Connection ID: % 1 Id.
-60478	TWC POST HANDLE CONNECTION CLOSED DEBUG	Two Way Communication Debug: recieved connection closed notification. Connection ID: % 1 Id.
-60477	TWC_POST_HANDLE_OPTIONS_ERROR	Two Way Communication Error: Wrong post handle options. Connection ID: % 1 Id.

Error code	Handle	Message\Additional information
-60476	TWC_POST_HANDLE_FAILED_TO_CREATE_DEC_ENC	Two Way Communication Error: Failed to create security encryptor/decryptor. Connection ID: %_1_id.
-60399	TWC_FITFUL_BATCH_CREATED_DEBUG	Two Way Communication Debug: Created fitful manager in batch mode.
-60398	TWC_FITFUL_STARTED_DEBUG	Two Way Communication Debug: Fitful started.
-60397	TWC_FITFUL_CLOSED_CONNECTION_ON_IDLE_DEBUG	Two Way Communication Debug: Fitful manager closed connection. Reason: got on idle notification.
-60396	TWC_FITFUL_OPENED_CONNECTION_BUFFER_THRESHOLD_DEBUG	Two Way Communication Debug: Fitful manager opened connection. Reason: reached buffer threshold.
-60395	TWC_FITFUL_OPENED_CONNECTION_RECONNECTION_TIMEOUT_DEBUG	Two Way Communication Debug: Fitful manager opened connection. Reason: reconnection timeout.
-60394	TWC_FITFUL_INTERACTIVE_CREATED_DEBUG	Two Way Communication Debug: Created fitful manager in interactive mode.
-60393	TWC_INTERACTIVE_OPENED_CONNECTION_ON_POST_DEBUG	Two Way Communication Debug: Fitful manager opened connection. Reason: got post notification.
-60392	TWC_INTERACTIVE_CLOSED_CONNECTION_INACTIVE_DEBUG	Two Way Communication Debug: Fitful manager closed connection. Reason: connection inactive.
-60391	TWC_INTERACTIVE_DISCONNECT_TIMEOUT_ACTIVE_DEBUG	Two Way Communication Debug: Fitful manager - disconnection timeout elapsed, but connection is still active.
-60390	TWC_INTERACTIVE_GOT_POST_NOTIFICATION_DEBUG	Two Way Communication Debug: Fitful manager got post notification.
-60389	TWC_INTERACTIVE_GOT_RECV_NOTIFICATION_DEBUG	Two Way Communication Debug: Fitful manager got recv notification.
-60388	TWC_INTERACTIVE_GOT_GD_ON_EMPTY_NOTIFICATION_DEBUG	Two Way Communication Debug: Fitful manager got gd_on_empty notification.
-60299	TWC_RECONNECT_FAILED	Reconnect: There was a network problem. Cannot restore the connection.
-60298	TWC_RECONNECT_PASSED	Reconnect: There was a network problem. The connection has been restored. Note that the result may be corrupted. The connection information is %1
-60297	TWC_RECONNECT_SSL_PASSED	Reconnect: There was a network problem. The connection has been restored. Reconnect server %1 successfully with SSL enabled.
-60296	TWC_RECONNECT_DISCONNECT	Reconnect: There was a network problem. Connection was closed.
-60249	SECURITY_PROTOCOLS_INTERNAL_ERROR_NULL_INPUT	Internal error - unexpected NULL pointer or empty argument (%1) in function %2.
-60248	SECURITY_PROTOCOLS_DC_BUILD_FAILED	Internal error - failed to build DC layer of a new %1 message.
-60247	SECURITY_PROTOCOLS_SL_BUILD_FAILED	Internal error - failed to build SL layer of a new %1 message.
-60246	SECURITY_PROTOCOLS_SL_READER_FAILED	Internal error - failed to read SL layer of a message. Please check if connector/acceptor keys match.
-60245	SECURITY_PROTOCOLS_DC_READER_FAILED	Internal error - failed to read DC layer of a message.
-60244	SECURITY_PROTOCOLS_NO_SPACE_FOR_ENCODING	Internal error - encoding buffer is too small (%_1_id while required %_2_id) at %3
-60243	SECURITY_PROTOCOLS_ENCODING_FAILED	Internal error - encoding failed (rc=%_1_id) at %2
-60242	SECURITY_PROTOCOLS_DECODING_FAILED	Internal error - decoding failed (rc=%_1_id) at %2
-60241	SECURITY_PROTOCOLS_COMMUNICATE_BEFORE_HANDSHAKE	Internal error - received %1 message before handshake at %2
-60240	SECURITY_PROTOCOLS_INVALID_DECODING	Internal error - unexpected NULL (%1)in decoded structure at %2
-60239	SECURITY_PROTOCOLS_NO_SPACE_FOR_DECODING	Internal error - decoded message buffer is too small (%_1_id while required %_2_id) at %3
-60238	SECURITY_PROTOCOLS_KEY_STORE_FAILED	Failed to store security key - %1
-60237	SECURITY_PROTOCOLS_DC_HANDSHAKE_FAILED	Handshake of DC security protocol failed - incompatible %1 numbers (%_2_id, %_3_id)
-60236	SECURITY_PROTOCOLS_DC_INVALID_SEQ_ID	Internal error - received invalid sequence ID (%_1_id)
-60235	SECURITY_PROTOCOLS_ENCRYPTION_FAILED	Internal error - encryption failed at %1
-60234	SECURITY_PROTOCOLS_DECRYPTION_FAILED	Internal error - decryption failed at %1
-60233	SECURITY_PROTOCOLS_SECURITY_MODE_STORE_FAILED	Failed to store security mode - %1
wan_emulation_res.h		
-203250	WAN_EMULATION_MSG_GENERIC	1.00%
-203249	WAN_EMULATION_MSG_ERROR_INIT	Network Virtualization: Unable to launch the Network Virtualization process.
-203248	WAN_EMULATION_MSG_ERROR_FAILED_LAUNCH_API	Network Virtualization: Failed %s. rc = %_2_id.
-203247	WAN_EMULATION_MSG_ERROR_MDRV_FAILED	Network Virtualization: The Network Virtualization process is not responding.
web_driver_res.h		
-89400	WEB_DRIVER_CANT_OPEN_MLOG_FILE	Web driver: Can't open extra log file.
-89300	WEB_DRIVER_ADD_CLIENT_GOT_EMPTY_INTERFACE	Web driver got empty interface from client.
-89299	WEB_DRIVER_ADD_CLIENT_GOT_DUPLICATE_HANDLERS	Web driver: A client tried to register '%1', but it already exists.
-89298	WEB_DRIVER_ADD_CLIENT_GOT_NULL_HANDLER	Web driver: A client tried to register a NULL handler for '%1'.
-89297	WEB_DRIVER_ADD_CLIENT_CANT_REGISTER_HANDLER	Web driver: Can't register handler for '%1'.
-89296	WEB_DRIVER_ADD_CLIENT_GOT_DUPLICATE_SERVICES	Web driver: A client tried to register '%1' service, but it already exists.
-89295	WEB_DRIVER_FAILED_TO_ADD_CLIENT_SERVICE	Web driver: Failed to add client '%1'service.
-89200	WEB_DRIVER_DISPATCHER_PT_INIT_FAILED	Web driver: Can't initialize thread.
-89199	WEB_DRIVER_DISPATCHER_CANT_READ_HANDLER_LIST	Web driver: Can't read handler table.
-89198	WEB_DRIVER_DISPATCHER_GOT_EMPTY_TYPE_NAME	Web driver: Request contained empty type.
-89197	WEB_DRIVER_DISPATCHER_GOT_UNKNOWN_HANDLER	Web driver: Request contained an unknown handler '%1'.
-89196	WEB_DRIVER_DISPATCHER_SET_CONTEXT_FAILED	Web driver: Failed to set context on thread %_1_id.
-89195	WEB_DRIVER_DISPATCHER_SET_CONTEXT_SUCCEEDED	Web driver: Thread context was set correctly on thread %_1_id.
-89194	WEB_DRIVER_DISPATCHER_CAUGHT_EXCEPTION	Web driver: Cause unhandled exception from '%1' handler.

Error code	Handle	Message\Additional information
-89100	WEB_DRIVER_HTTP_REQ_ATTEMPT_WRITE_TO_DISCONNECTED_REQUEST	Web driver: Attempt to write to a disconnected request.
-89099	WEB_DRIVER_HTTP_REQ_ATTEMPT_WRITE_BEFORE_HEADER	Web driver: Attempt to write before sending header.
-89098	WEB_DRIVER_HTTP_REQ_COULDNT_SEND_CHUNK_SIZE	Web driver: Couldn't send chunk size.
-89097	WEB_DRIVER_HTTP_REQ_COULDNT_WRITE_BUFFER	Web driver: Couldn't write buffer.
-89096	WEB_DRIVER_HTTP_REQ_COULDNT_CLOSE_CHUNK	Web driver: Couldn't close chunk.
-89095	WEB_DRIVER_HTTP_REQ_READ_POST_FROM_DISCONNECTED_CONNECTION	Web driver: Attempt to read POST message from a disconnected request.
-89094	WEB_DRIVER_HTTP_REQ_READ_POST_FROM_NON_POST_REQ	Web driver: Attempt to read post from non-POST request.
-89093	WEB_DRIVER_HTTP_REQ_MULTIPLE_SENDING_OF_HEADER	Web driver: Attempt to send the header after it was already sent.
-89092	WEB_DRIVER_HTTP_REQ_PBLOCK_ABSENT	Web driver: Attempt to read POST message with absent pblock.
-89091	WEB_DRIVER_HTTP_REQ_EMPTY_REQ_TYPE_IN_HTTP_HEADER	Web driver: Attempt to read from a request with empty type.
-89090	WEB_DRIVER_HTTP_REQ_CANT_READ_CONTENT_LENGTH	Web driver: Can't read content length in message.
-89089	WEB_DRIVER_HTTP_REQ_NEGATIVE_CONTENT_LENGTH	Web driver: Request content length is negative.
-89088	WEB_DRIVER_HTTP_REQ_CANT_ALLOCATE_BUFFER	Web driver: Can't allocate buffer for reading POST content.
-89087	WEB_DRIVER_HTTP_REQ_EMPTY_HTTP_METHOD	Web driver: Empty HTTP method in request.
-89086	WEB_DRIVER_HTTP_REQ_REQUEST_NOT_INITIALIZED	Web driver: Attempt to set content-type in an uninitialized request.
-89085	WEB_DRIVER_HTTP_REQ_FAILED_TO_SET_CONTENT_TYPE	Web driver: Failed to set content-type.
-89084	WEB_DRIVER_HTTP_REQ_FAILED_TO_READ_HEADERS	Web driver: Failed to read headers, insufficient buffer.
webservices_res.h		
-108999	LRWS_MSG_WS_CALL_STEP_SUCCEEDED	<CENTER>Web service call was successful</CENTER>
-108998	LRWS_MSG_WS_CALL_STEP_FAILED	<CENTER>Web service call failed</CENTER>
-108997	LRWS_MSG_WS_CALL_STEP_FAILED_HTTP	<CENTER>Web service call failed on HTTP request</CENTER>
-108996	LRWS_MSG_WS_CALL_STEP_FAILED_SOAP	<CENTER>Web service call failed on SOAP request</CENTER>
-108995	LRWS_MSG_WS_CALL_STEP_FAILED_BAD_SOAP	<CENTER>Web service call failed due to incorrect SOAP format</CENTER>
-108994	LRWS_MSG_WS_CALL_STEP_FAILED_WSDL	<CENTER>Web service call failed in WSDL for an unknown reason</CENTER>
-108993	LRWS_MSG_WS_CALL_STEP_FAILED_WSDL_N_FOUND	<CENTER>Web service call failed retrieving WSDL</CENTER>
-108992	LRWS_MSG_WS_CALL_STEP_FAILED_WSDL_PARSE	<CENTER>Web service call failed while parsing WSDL</CENTER>
-108991	LRWS_MSG_WS_CALL_STEP_FAILED_INVALID_PARAM	<CENTER>Web service call failed due to an invalid parameter in function</CENTER>
-108990	LRWS_MSG_WS_CALL_STEP_FAILED_ERROR_RESULT	<CENTER>Web service call failed to find requested result argument in response</CENTER>
-108989	LRWS_MSG_WS_CALL_STEP_FAILED_WSDL_ARG	<CENTER>Web service call failed because argument does not exist in WSDL</CENTER>
-108988	LRWS_MSG_SOAP_REQUEST_STEP_SUCCEEDED	<CENTER>SOAP request was successful</CENTER>
-108987	LRWS_MSG_SOAP_REQUEST_STEP_FAILED	<CENTER>SOAP request step failed</CENTER>
-108986	LRWS_MSG_SOAP_REQUEST_STEP_FAILED_HTTP	<CENTER>SOAP request failed on HTTP request</CENTER>
-108985	LRWS_MSG_SOAP_REQUEST_STEP_FAILED_SOAP	<CENTER>SOAP request failed on SOAP request</CENTER>
-108984	LRWS_MSG_SOAP_REQUEST_STEP_FAILED_WSDL	<CENTER>SOAP request failed while parsing WSDL</CENTER>
-108983	LRWS_MSG_SOAP_REQUEST_STEP_FAILED_BAD_SOAP	<CENTER>SOAP request failed due to incorrect SOAP format</CENTER>
-108982	LRWS_MSG_SOAP_REQUEST_STEP_INVALID_PARAM	<CENTER>SOAP request failed due to an invalid parameter in function</CENTER>
-108981	LRWS_MSG_SOAP_REQUEST_STEP_WARNING_HTTP	<CENTER>SOAP request passed with an HTTP warning</CENTER>
-108980	LRWS_MSG_WS_CALL_STEP_WARNING_ARG_SIMPLE	<CENTER>Web service call passed with a warning - the argument passed is missing in recorded buffer</CENTER>
-108979	LRWS_MSG_WS_CALL_STEP_WARNING_ARG_COMPLEX	<CENTER>Web service call passed with a warning - recorded buffer structure does not match the argument structure</CENTER>
-108978	LRWS_MSG_WS_CALL_STEP_WARNING_HTTP	<CENTER>Web service call passed with an HTTP warning</CENTER>
-108977	LRWS_MSG_WS_GENERIC_STRING	1%
-108976	LRWS_MSG_WS_VERSION	WebServices version: % 1 ld
-108975	LRWS_MSG_SOAP_REQUEST_FAULT_REASON	The reason for the fault is: %1
-108974	LRWS_MSG_SOAP_REQUEST_HTTP_STATUS_CODE	HTTP status code % 1 ld returned by the server
-108973	LRWS_MSG_SOAP_REQUEST_STEP_NAME_ERROR	Step name must be the first argument of the function
-108972	LRWS_MSG_SOAP_REQUEST_STEP_STARTED	SOAP request "%1" started
-108971	LRWS_MSG_SOAP_REQUEST_STEP_ERROR	There was an error during the SOAP request
-108970	LRWS_MSG_SOAP_REQUEST_STEP_ERROR_EX	There was an error during SOAP request "%1"

Error code	Handle	Message\Additional information
-108969	LRWS MSG SOAP REQUEST STEP WARNING	There was a warning during the SOAP request
-108968	LRWS MSG SOAP REQUEST STEP WARNING EX	There was a warning during SOAP request "%1"
-108967	LRWS MSG SOAP REQUEST STEP SUCCESS	SOAP request was successful
-108966	LRWS MSG SOAP REQUEST STEP SUCCESS EX	SOAP request "%1" was successful
-108965	LRWS MSG SOAP REQUEST STEP EXEC FAILED	SOAP request execution failed
-108964	LRWS MSG SOAP REQUEST STEP EXEC FAILED EX	SOAP request "%1" execution failed
-108963	LRWS MSG SOAP REQUEST STEP NOT_XML_CONTENT	The "%1" SOAP request response content is not XML
-108962	LRWS MSG WS CALL STEP STARTED	Web service call "%1" started
-108961	LRWS MSG WS CALL STEP FAILURE	Web service call execution failed
-108960	LRWS MSG WS CALL STEP FAILURE EX	Web service call "%1" execution failed
-108959	LRWS MSG WS CALL OVERRIDE RTS	"ClientEmulation" parameter overrides the Runtime Setting definition
-108958	LRWS MSG WS CALL USING CLIENT EMULATION	Using client emulation %1
-108957	LRWS MSG WS CALL HEADER NO_MATCH_EMULATION	Removed Web headers not matching the emulated client
-108956	LRWS MSG WS CALL MISSING IN BUF	The %1 argument is missing in the recorded buffer
-108955	LRWS MSG WS CALL RECORDED BUF	Recorded buffer will be sent without changes
-108954	LRWS MSG WS CALL BUF STRUCTURE	Recorded buffer structure doesn't match the argument structure
-108953	LRWS MSG WS CALL MISMATCH IGNORE	Mismatched argument will be ignored
-108952	LRWS MSG WS CALL STEP ERROR	There was an error during Web service call "%1"
-108951	LRWS MSG WS CALL STEP WARNING	There was a warning during Web service call "%1"
-108950	LRWS MSG WS CALL STEP SUCCESS	Web service call "%1" was successful
-108949	LRWS MSG WS CALL STEP WORK WSDL	Using working copy of the WSDL file "%1"
-108948	LRWS MSG WS CALL STEP ORIGINAL WSDL	Using original WSDL file "%1"
-108947	LRWS MSG WS CALL STEP NOT_XML_RESPONSE	The "%1" Web service call response content is not XML, so the output parameters cannot be stored
-108946	LRWS MSG WS SOAP FAULT	The reason for the SOAP fault is:"%1"
-108945	LRWS MSG WS ARG UNEXPECTED	Unexpected function argument "%1"
-108944	LRWS MSG WS CALL NOT RECORDED	The User cannot replay recorded traffic - no actions were recorded. Enable client emulation for a specific toolkit from the Runtime Settings.
-108943	LRWS MSG WS CALL LOCAL WSDL_LOAD_FAILED	The local WSDL file "%1" could not be loaded (%2)
-108942	LRWS_MSG_WS_CALL_SECURE_WSDL_DOWNLOAD_FAILED	The WSDL file "%1" requires secure http download which is not supported. Download and save the WSDL file locally, and use the local copy in the script. (%2)
-108941	LRWS_MSG_WS_CALL_REQUIRES_AUTHENTICATION	The WSDL file "%1" download requires authentication which is not supported. Download and save the WSDL file locally, and use the local copy in the script. (%2)
-108940	LRWS MSG WS CALL INVALID WSDL_URL	The WSDL file "%1" appears to have an invalid URL. Download and save the WSDL file locally, and use the local copy in the script. (%2)
-108939	LRWS MSG WS CALL WSDL_DOWNLOAD_FAILED	The WSDL file "%1" download failed. Download and save the WSDL file locally, and use the local copy in the script. (%2)
-108938	LRWS_MSG_WS_CALL_INVALID_WSDL_XML_STRUCTURE	The WSDL file "%1" has an invalid XML structure. If it is being downloaded from the internet, download and save the WSDL file locally, and use the local copy in the script. (%2)
-108937	LRWS MSG WS CALL NON_CONFORMANT_WSDL	The WSDL file "%1" has a non-standard WSDL structure (%2)
-108936	LRWS MSG WS CALL INVALID WSDL_NO_SERVICES	The WSDL file "%1" contains no services (%2)
-108935	LRWS_MSG_WS_CALL_INVALID_WSDL_UNKNOWN	The WSDL file "%1" download and parse failed for an unknown reason. If it is being downloaded from the internet, download and save the WSDL file locally, and use the local copy in the script.
-108934	LRWS MSG WS CALL INVALID WSDL_GENERAL_ERROR	The WSDL file "%1" has an error. (%2)
-108933	LRWS MSG WS CALL METHOD_NOT_FOUND	The requested SOAP method "%1" is either parameterized or not found in the WSDL file
-108932	LRWS MSG WS CALL INCORRECT SOAP_FORMAT	The server returned an incorrectly formatted SOAP response
-108931	LRWS MSG WS CALL RESULT_ARG_MISSING	The result argument name/query was not specified for parameter "%1"
-108930	LRWS MSG WS CALL RESULT_ARG_NOT_FOUND	The result argument "%1" was not found in the server response
-108929	LRWS MSG HTTP_TRANSPORT_PROVIDER_FAILED	HTTP Transport Provider function %1 failed: rc=% 2 Id
-108928	LRWS MSG HTTP_INVALID_PARAMETER	%1: invalid parameter %2
-108927	LRWS MSG WS_HANDLERS_PROCESS_RESPONSE_FAILED	Failed to process the response.
-108926	LRWS MSG WS_HANDLERS_PROCESS_REQUEST_FAILED	Failed to process the request.
-108925	LRWS MSG WS_OUT_OF_MEM	Out of memory.
-108924	LRWS MSG WS_LOAD_USER_HANDLER_FAILED	Loading of user handler %1 failed.
-108923	LRWS MSG WS_HENDLER_FUNC_NOT_FOUND	Service function "%1" not found in user handler library "%2".
-108922	LRWS MSG WS_LOAD_HENDLER_FAILED	Failed to load the "%1" user handler library. %2
-108921	LRWS MSG WS_HENDLER_FUNC_FAILED	The function "%1" in the user handler library "%2" failed.
-108920	LRWS MSG WS_INTERNAL_ERROR	Internal error, please call customer support. Details: %1
-108919	LRWS MSG SET_SECURITY_STEP_STARTED	Web service set security started.
-108918	LRWS MSG SET_SECURITY_STEP_FAILURE	Web service set security execution failed.
-108917	LRWS MSG SET_SECURITY_INVALID_ARGUMENT	%1 argument is invalid in web service set security.

Error code	Handle	Message\Additional information
-108916	LRWS MSG SET SECURITY SUCCESS	Web service set security was successful.
-108915	LRWS MSG SET SECURITY LOAD SECURITY HANDLER FAILED	Loading of security handler %1 failed.
-108914	LRWS MSG CANCEL SECURITY SUCCESS	Web cancel security was successful.
-108913	LRWS MSG CANCEL SECURITY STEP STARTED	Web service cancel security started.
-108912	LRWS MSG CANCEL SECURITY STEP FAILURE	Web service cancel security execution failed.
-108911	LRWS MSG CANCEL SECURITY NO SET SECURITY	Web service cancel security requires a prior Web service set security call.
-108910	LRWS MSG CANCEL SECURITY CANCEL ANY PREVIOUS SET SECURITY	web_service_cancel_security cancels any active web_service_set_security settings.
-108909	LRWS MSG SET SECURITY CANCEL ANY PREVIOUS SET SECURITY	web_service_set_security cancels any settings from previous web_service_set_security or web_service_set_security_saml calls.
-108908	LRWS MSG QT REPLAY ENGINE COM ERROR	Com error. %1. % 2 Id.
-108907	LRWS NUMBER OF ARGUMENTS UNMACHED	Number of method arguments in the script do not match number of arguments defined in the WSDL.
-108906	LRWS QT INVOKEMETHOD EXCEPTION	InvokeMethod failure: %1.
-108905	LRWS QT LASTSOAPREQUEST	Soap Request: %1
-108904	LRWS QT LASTSOAPRESPONSE	Soap Response: %1
-108903	LRWS QT EXTRACT ARG EXCEPTION	ExtractResultArg failure: %1.
-108902	LRWS QT UTF8 TO LOCAL FAILED	Fail to convert UTF-8 string to local.
-108901	LRWS AXIS INVOKEMETHOD EXCEPTION	InvokeMethod failure: %1.
-108900	LRWS MSG WS SET SECURITY PASSED	<CENTER>web_service_set_security passed</CENTER>
-108899	LRWS MSG WS SET SECURITY FAILED	<CENTER>web_service_set_security failed</CENTER>
-108898	LRWS MSG WS CANCEL SECURITY PASSED	<CENTER>web_service_cancel_security passed</CENTER>
-108897	LRWS MSG WS CANCEL SECURITY FAILED	<CENTER>web_service_cancel_security failed</CENTER>
-108896	LRWS MSG WSDL WSI VALIDATION PASSED	<CENTER>wsdl wsi validation passed</CENTER>
-108895	LRWS MSG WSDL WSI VALIDATION FAILED	<CENTER>wsdl wsi validation failed</CENTER>
-108894	LRWS MSG WSDL WSI VALIDATION FAILED COMPLIANCE	<CENTER>WSDL is not WS-I compliant</CENTER>
-108893	LRWS MSG WSDL WSI VALIDATION STEP FAILURE	WS-I execution failed
-108892	LRWS MSG WSDL WSI VALIDATION STEP ERROR	There was an error during WSDL WS-I validation
-108891	LRWS MSG WSDL WSI VALIDATION STEP WARNING	There was a warning during WSDL WS-I validation
-108890	LRWS MSG WSDL WSI VALIDATION STEP SUCCESS	WSDL WS-I validation was successful
-108889	LRWS MSG WSDL WSI VALIDATION STEP STARTED	WSDL WS-I validation for service "%1" started
-108888	LRWS MSG WSDL WSI VALIDATION STEP WSDL	Validating WSDL: "%1"
-108887	LRWS MSG WSDL WSI VALIDATION NO WSI TOOL SET	WS-I tool was not set, set it in "SOA Script -> WS-I Validation Settings" and run the script again
-108886	LRWS MSG WSDL WSI VALIDATION STEP FAILED	The service is not WS-I compliant
-108885	LRWS MSG WSDL WSI VALIDATION REPORT	For more information, see report in "%1"
-108884	LRWS MSG WSDL WSI VALIDATION SERVICE NOT EXISTS	Service does not exists in Service Management
-108883	LRWS MSG WSDL WSI VALIDATION WSDL NOT EXISTS	WSDL does not exists or not reachable
-108882	LRWS MSG SET SECURITY SAML STEP STARTED	web_service_set_security_saml started.
-108881	LRWS MSG SET SECURITY SAML STEP FAILURE	web_service_set_security_saml execution failed.
-108880	LRWS MSG SET SECURITY SAML INVALID ARGUMENT	%1 argument is invalid in web_service_set_security_saml.
-108879	LRWS MSG SET SECURITY SAML SUCCESS	web_service_set_security_saml was successful.
-108878	LRWS MSG SET SECURITY SAML_LOAD SECURITY_SAML_HANDLER_FAILED	Loading of SAML security handler %1 failed.
-108877	LRWS MSG SET SECURITY_SAML_CANCELS_ANY_PREVIOUS_SET_SECURITY	web_service_set_security_saml cancels any settings from previous web_service_set_security or web_service_set_security_saml calls.
-108876	LRWS MSG CANCEL SECURITY SAML SUCCESS	web_service_cancel_security_saml was successful.
-108875	LRWS MSG CANCEL SECURITY SAML STEP STARTED	web_service_cancel_security_saml started.
-108874	LRWS MSG CANCEL SECURITY SAML STEP FAILURE	web_service_cancel_security_saml execution failed.
-108873	LRWS MSG CANCEL SECURITY SAML NO SET SECURITY SAML	web_service_cancel_security_saml requires a prior web_service_set_security_saml call.
-108872	LRWS MSG CANCEL SECURITY_SAML_CANCELS_ANY_PREVIOUS_SET_SECURITY	web_service_cancel_security_saml cancels any active web_service_set_security_saml settings.
-108871	LRWS MSG WCF SET SECURITY SAML STEP STARTED	web_service_set_security_saml_ex started.
-108870	LRWS MSG WCF SET SECURITY SAML STEP FAILURE	web_service_set_security_saml_ex execution failed: "%1".
-108869	LRWS MSG WCF SET SECURITY SAML INVALID ARGUMENT	%1 argument is invalid in web_service_set_security_saml_ex.
-108868	LRWS MSG WCF SET SECURITY SAML SUCCESS	web_service_set_security_saml_ex was successful.
-108867	LRWS MSG WCF SET SECURITY_SAML_CANCELS_ANY_PREVIOUS_SET_SECURITY	web_service_set_security_saml_ex cancels any settings from previous web_service_set_security_saml_ex calls.
-108866	LRWS MSG WCF CANCEL SECURITY SAML SUCCESS	web_service_cancel_security_saml_ex was successful.
-108865	LRWS MSG WCF CANCEL SECURITY SAML STEP STARTED	web_service_cancel_security_saml_ex started.

Error code	Handle	Message\Additional information
-108864	LRWS MSG WCF CANCEL SECURITY SAML STEP FAILURE	web_service_cancel_security_saml_ex execution failed: "%1".
-108863	LRWS MSG WCF CANCEL SECURITY SAML NO_SET SECURITY SAML	web_service_cancel_security_saml_ex requires a prior web_service_set_security_saml call.
-108862	LRWS MSG WCF CANCEL SECURITY SAML_CANCELS_ANY_PREVIOUS_SECURITY	web_service_cancel_security_saml_ex cancels any active web_service_set_security_saml_ex settings.
-108861	LRWS MSG WS SET SECURITY SAML PASSED	<CENTER>web_service_set_security_saml passed</CENTER>
-108860	LRWS MSG WS SET SECURITY SAML FAILED	<CENTER>web_service_set_security_saml failed</CENTER>
-108859	LRWS MSG WS CANCEL SECURITY SAML PASSED	<CENTER>web_service_cancel_security_saml passed</CENTER>
-108858	LRWS MSG WS CANCEL SECURITY SAML FAILED	<CENTER>web_service_cancel_security_saml failed</CENTER>
-108857	LRWS MSG WS JMS SEND ERROR	Failed to send message %1 to %2 due to the following exception : %3
-108856	LRWS MSG WS JMS PUBLISH ERROR	Failed to publish message %1 on %2 due to the following exception : %3
-108855	LRWS MSG WS JMS SUBSCRIBE ERROR	Failed to subscribe %1 on %2 due to the following exception : %3
-108854	LRWS MSG WS JMS RECEIVE TOPIC ERROR	Failed to receive a message from %1 with subscriber %2 due to the following exception : %3
-108853	LRWS MSG WS JMS SEND RECEIVE ERROR	Failed to send message %1 to %2 and receive from %3 due to the following exception : %4
-108852	LRWS MSG WS JMS RECEIVE ERROR	Failed to receive a message from %1 due to the following exception : %2
-108851	LRWS MSG WS JMS SET PROPERTY ERROR	Failed to set property name %1 value %2 due to the following exception : %3
-108850	LRWS MSG WS JMS UNKNOWN ERROR	JMS Error occurred
-108849	LRWS MSG WS JMS ERROR	JMS Error occurred. Exception is %1.
-108848	LRWS MSG WS JMS CALL STEP FAILURE	JMS call execution failed
-108847	LRWS MSG WS JMS STEP NAME ERROR	Step name must be the first argument of the function
-108846	LRWS MSG WS JMS STEP ERROR	There was an error during JMS call
-108845	LRWS MSG WS JMS STEP WARNING	There was a warning during JMS call
-108844	LRWS MSG WS JMS STEP SUCCESS	JMS call was successful
-108843	LRWS MSG WS JMS INVALID ARGUMENT	Argument %1 is invalid
-108842	LRWS MSG WS JMS STEP STARTED	JMS call "%1" started
-108841	LRWS MSG WS JMS STEP FAILED_INVALID_PARAM	<CENTER>JMS call failed due to an invalid parameter in function</CENTER>
-108840	LRWS MSG WS JMS ARG ILLEGAL	Illegal JMS argument to web_service call. Cannot mix Topic and Queue in the same call.
-108839	LRWS MSG WS CALL_CP_ARG_NOT_FOUND	The checkpoint argument "%1" was not found in the server response
-108838	LRWS MSG_WS_CALL_STEP_FAILED_CP_XPATH	<CENTER>Checkpoint check failed due to one or more invalid XPATH</CENTER>
-108837	LRWS MSG_WS_CALL_STEP_FAILED_CP_MATCH	<CENTER>Checkpoint check failed due to one or more mismatched values</CENTER>
-108836	LRWS MSG_WS_CALL_STEP_CP_SUCCEEDED	<CENTER>Checkpoint check was successful</CENTER>
-108835	LRWS MSG_WS_CALL_CP_ARG_NOT_MATCH	Failure: checkpoint "%1" expected value="%2" actual result="%3"
-108834	LRWS MSG_WS_CALL_CP_ARG_MATCH	Success: checkpoint "%1"="%2"
-108833	LRWS MSG_WS_CALL_CP_ARG_TOTAL_FAIL	Web service call "%1" % 2 ld/% 3 ld checks failed
-108832	LRWS MSG_WS_CALL_CP_ARG_TOTAL_SKIP	Web service call "%1" % 2 ld/% 3 ld checks skipped
-108831	LRWS MSG_WS_CALL_CP_ARG_TOTAL_SUCCESS	Web service call "%1" checks succeeded
-108830	LRWS MSG ASYNC_WS_CALL_STEP WARNING	There was a warning during asynchronous Web service call "%1", event "%2" pending"
-108829	LRWS MSG ASYNC_WS_CALL_STEP SUCCESS	Asynchronous Web service call "%1" was successful, event "%2" pending
-108828	LRWS MSG WAIT FOR EVENT SUCCESS	Wait for event was successful with processed event(s): %1 .
-108827	LRWS MSG WAIT FOR EVENT STEP STARTED	Wait for event(s), step name "%1" started.
-108826	LRWS MSG WAIT FOR EVENT STEP FAILURE	Wait for event execution failed.
-108825	LRWS MSG WAIT FOR EVENT CANT_CREATE_ENGINE	Async calls are allowed only with Axis toolkit
-108824	LRWS MSG HTTP ASYNC FAILED_NO_EVENT	Asynchronous call failed, unknown event %1
-108823	LRWS MSG WAIT FOR EVENT SUCCESS REPORT	Wait for event was successful.
-108822	LRWS MSG WSA_SERVER_FAILED	WSA server failed to read the response
-108821	LRWS MSG WSA_SERVER_CREATION_FAILED	WSA server can not be created
-108820	LRWS MSG SEE_WSI_LOG_FOR_MORE_INFORMATION	For more information refer to <script directory>\WSDL\Log
-108819	LRWS MSG WS JMS SEND ERROR INIT	Failed to send message %1 to %2 due to the following error : \n JMS was not initialized properly at process start up.
-108818	LRWS MSG_WS_CALL_STEP_FAILED_EXTERNAL_TRANSPORT	<CENTER>Web service call failed in External Transport Handler</CENTER>
-108817	LRWS MSG_SOAP_REQUEST_STEP_FAILED_EXTERNAL_TRANSPORT	<CENTER>SOAP request failed in External Transport Handler</CENTER>
-108816	LRWS MSG_INVALID_EXPECTED_RESPONSE_ATTRIBUTE_VALUE	<CENTER>The 'ExpectedResponse' attribute has an invalid value: "%1"</CENTER>
-108815	LRWS_EXPECTED_RESPONSE_SOAP_FAULT	<CENTER>Negative Testing Error: expected SOAP fault, received Soap result</CENTER>
-108814	LRWS_EXPECTED_RESPONSE_SOAP_RESULT	<CENTER>Expected SOAP result, received SOAP fault</CENTER>

Error code	Handle	Message\Additional information
-108813	LRWS_MSG_CANNOT_RETRIEVE_ARGS_SOAP_FAULT	<CENTER>Failed to retrieve output arguments/checkpoints - SOAP fault occurred</CENTER>
-108812	LRWS_MSG_CANNOT_RETRIEVE_ARGS	Failed to retrieve output arguments/checkpoints
-108811	LRWS_MSG_SEE_XMLVALIDATE_LOG_FOR_MORE_INFORMATION	For more information refer to <script directory>\ISOA_XML_VALIDATE\Log
-108810	LRWS_MSG_XMLVALIDATE_STEP_ERROR	There was an error during XML validation
-108809	LRWS_MSG_XMLVALIDATE_STEP_WARNING	There was a warning during XML validation
-108808	LRWS_MSG_XMLVALIDATE_STEP_FAILED	XML validation failed
-108807	LRWS_MSG_XMLVALIDATE_STEP_SUCCESS	XML validation was successful
-108806	LRWS_MSG_XMLVALIDATE_FAILED	<CENTER>XML validation failed</CENTER>
-108805	LRWS_MSG_XMLVALIDATE_FAILED_NOT_VALID	<CENTER>XML is not valid</CENTER>
-108804	LRWS_MSG_XMLVALIDATE_PASSED	<CENTER>soa_xml_validate passed</CENTER>
-108803	LRWS_MSG_XMLVALIDATE_REPORT	For more information, see report in "%1"
-108802	LRWS_MSG_XMLVALIDATE_XML_REPORT	Xml file failure : "%1"
-108801	LRWS_MSG_XMLVALIDATE_CH_REPORT	Checkpoint failure : "%1"
-108800	LRWS_MSG_XMLVALIDATE_CALL_STEP_FAILURE_EX	Xml Validation "%1" execution failed
-108799	LRWS_MSG_XML_VALIDATION_STEP	Validating XML: "%1"
-108798	LRWS_MSG_XML_VALIDATION_Colnitalize_PR	XML execution failed (Colnitalize problem)
-108797	LRWS_MSG_XML_VALIDATE_STEP_STARTED	Xml Validation "%1" started
-108796	LRWS_MSG_XML_VALIDATE_STEP_SUCCESS	Xml Validation "%1" was successful
-108795	LRWS_MSG_XML_VALIDATE_STEP_SUCCESS_WELL_FORMED	Xml Validation "%1" Xml file is well-formed
-108794	LRWS_MSG_XML_VALIDATE_STATUS1_SUCCESS_WELL_FORMED	<CENTER>Xml file is well-formed</CENTER>
-108793	LRWS_MSG_XML_VALIDATE_STATUS2_SUCCESS_WELL_FORMED_COMPATABLE	<CENTER>Xml file is well-formed and compatible to schema</CENTER>
-108792	LRWS_MSG_XML_VALIDATE_STEP_FAILURE	Xml Validation execution failed
-108791	LRWS_MSG_XML_VALIDATE_ERR_BAD_XML	Status:XML not well-formed
-108790	LRWS_MSG_XML_VALIDATE_ERR_XML_IS_EMPTY	Status:XML Content is empty
-108789	LRWS_MSG_XML_VALIDATE_ERR_OK_XML_BAD_XSD	Status:XSD not well-formed
-108788	LRWS_MSG_XML_VALIDATE_ERR_OK_XML_XSD_BAD_VALIDATE	Status:Xml not fully validate with schema
-108787	LRWS_MSG_XML_VALIDATE_ERR_OK_FILES_VALID_BAD_CH	Status:Checkpoints validation problem
-108786	LRWS_MSG_XML_VALIDATE_ERR_XSD_NOT_EXIST	Status:XSD file does not exist
-108785	LRWS_MSG_XML_VALIDATE_ERR_XML_INTERNAL_ERROR	Status:Internal error
-108784	LRWS_MSG_XML_VALIDATE_ERR_OK_XML_BAD_XSD_BAD_CH	Status:XSD not well-formed + Checkpoints validation problem
-108783	LRWS_MSG_XML_VALIDATE_ERR_OK_XML_XSD_BAD_VALIDATE_BAD_CH	Status:Xml not fully validate with schema + Checkpoints validation problem
-108782	LRWS_MSG_XML_VALIDATE_CP_ARG_NOT_MATCH	"%1"
-108781	LRWS_MSG_XML_VALIDATE_CP_ARG_NOT_MATCH_2	"%1 %2"
-108780	LRWS_MSG_NO_SCHEMA_WARNING	Warning:Unable to locate a reference to a supported schema within the document instance
-108779	LRWS_MSG_XML_VALIDATE_STEP_CALL_Colnitalize	-----> call Colnitalize
-108778	LRWS_MSG_XML_VALIDATE_CP_ARG_TOTAL_FAIL	Check points validation : % 1 Id/% 2 Id failures
-108777	LRWS_MSG_XML_FILE_VALIDATION_FAILED	File Validation : % 1 Id failures
-108776	LRWS_MSG_XML_VALIDATION_BAD_PARAMETERS	Bad parameters in script
-108775	LRWS_MSG_XML_VALIDATION_ARG_TOTAL_SUCCESS	Xml Validation "%1" checks succeeded
-108774	LRWS_MSG_XML_VALIDATION_PARAMETER_IS_EMPTY	Cannot use empty parameter
-108773	LRWS_MSG_XML_VALIDATION_BAD_NM	Your script was created with an older version of Service Test. Please switch to Tree view and redefine the Checkpoints.
-108772	LRWS_MSG_SIGN_SAML_ASSERTION_FAILURE	ws_sign_saml assertion failed
-108771	LRWS_MSG_SIGN_SAML_ASSERTION_SUCCESS	ws_sign_saml assertion passed
-108770	LRWS_MSG_SIGN_SAML_ASSERTION_STARTED	ws_sign_saml assertion started
-108769	LRWS_MSG_SIGN_SAML_ASSERTION_EXCEPTION	ws_sign_saml assertion failure: %1.
-108768	LRWS_MSG_OUTPUTMESSAGE	<CENTER>Output message</CENTER>
-108767	LRWS_ERROR_OUTPUTMESSAGE	<CENTER>Error message</CENTER>
-108766	LRWS_MSG_HTTP_TRAFFIC	HTTP Traffic
-108765	LRWS_MSG_REPORT_FORMATTER_FAILED	Error while formatting the report
-108764	LRWS_MSG_DBManagement_Colnitalize_PR	DB Management execution failed (Colnitalize problem)
-108763	LRWS_MSG_DBCONNECTION_STEP_STARTED	DB Connection "%1" started ... Wait
-108762	LRWS_MSG_DBCONNECTION_STEP_SUCCESS	DB connection was successful
-108761	LRWS_MSG_DBCONNECTION_STEP_ERROR	There was an error during DB Connection
-108760	LRWS_MSG_DBCONNECTION_STEP_FAILURE	DB Connection execution failed

Error code	Handle	Message\Additional information
-108759	LRWS MSG DBCONNECTION_ERROR	DB Connection failed {"%1"}
-108758	LRWS REP DB CALL CONNECTION_STEP_FAILED	<CENTER>Connection failed</CENTER>
-108757	LRWS REP DB CALL CONNECTION_STEP_SUCCESS	<CENTER>Connection was successful</CENTER>
-108756	LRWS MSG DBDISCONNECTION_STEP_STARTED	DB disconnect "%1" started
-108755	LRWS MSG DBDISCONNECTION_STEP_SUCCESS	DB disconnect was successful
-108754	LRWS MSG DBDISCONNECTION_STEP_FAILURE	DB disconnect execution failed
-108753	LRWS MSG DBDISCONNECTION_ERROR	DB disconnect failed {"%1"}
-108752	LRWS MSG DBDISCONNECTION_STEP_ERROR	DB disconnect failed
-108751	LRWS REP DB CALL DISCONNECTION_STEP_FAILED	<CENTER>Disconnection failed</CENTER>
-108750	LRWS REP DB CALL DISCONNECTION_STEP_SUCCESS	<CENTER>Disconnection was successful</CENTER>
-108749	LRWS MSG DB EXEC QUERY_STEP_STARTED	SQL Statement execution "%1" started
-108748	LRWS MSG DB EXEC QUERY_STEP_SUCCESS	SQL Statement execution was successful
-108747	LRWS MSG DB EXEC QUERY_STEP_ERROR	There was an error during SQL Statement execution
-108746	LRWS MSG DB EXEC QUERY_FAILURE	SQL Statement execution failed
-108745	LRWS MSG DB EXEC QUERY_ERROR	SQL Statement failed {"%1"}
-108744	LRWS REP DB CALL EXEC QUERY_STEP_FAILED	<CENTER>SQL Statement execution failed</CENTER>
-108743	LRWS REP DB CALL EXEC QUERY_STEP_SUCCESS	<CENTER>SQL Statement execution was successful</CENTER>
-108742	LRWS MSG DB GET VALUE_STEP_STARTED	Get db value "%1" started
-108741	LRWS MSG DB GET VALUE_STEP_SUCCESS	Get db value was successful
-108740	LRWS MSG DB GET VALUE_STEP_ERROR	There was an error during getting db value
-108739	LRWS MSG DB GET VALUE_FAILURE	Getting db value failed
-108738	LRWS MSG DB GET VALUE_ERROR	Getting db failed {"%1"}
-108737	LRWS REP DB CALL GET VALUE_STEP_FAILED	<CENTER>Get db value failed</CENTER>
-108736	LRWS REP DB CALL GET VALUE_STEP_SUCCESS	<CENTER>Get db value was successful</CENTER>
-108735	LRWS MSG ASSERT_STEP_STARTED	Checkpoint validation "%1" started
-108734	LRWS MSG ASSERT_STEP_SUCCESS	Checkpoint validation was successful
-108733	LRWS MSG ASSERT_STEP_ERROR	There was an error during Checkpoint validation
-108732	LRWS MSG ASSERT_FAILURE	Checkpoint validation failed
-108731	LRWS MSG ASSERT_EMPTY_PARAMETER	Parameter is empty
-108730	LRWS MSG ASSERT_INVALID_PARAMETER	Invalid Parameter
-108729	LRWS MSG ASSERT_ERROR	Checkpoint validation failed {"%1"}
-108728	LRWS REP DB CALL ASSERT_STEP_FAILED	<CENTER>Checkpoint validation failed</CENTER>
-108727	LRWS REP DB CALL ASSERT_STEP_SUCCESS	<CENTER>Checkpoint validation was successful</CENTER>
-108726	LRWS MSG DS ACTION_STEP_STARTED	Dataset action "%1" started
-108725	LRWS MSG DS ACTION_STEP_SUCCESS	Dataset action was successful
-108724	LRWS MSG DS ACTION_STEP_ERROR	There was an error during dataset action
-108723	LRWS MSG DS ACTION_FAILURE	Dataset action action failed
-108722	LRWS MSG DS ACTION_ERROR	Dataset action failed {"%1"}
-108721	LRWS MSG PRINT_ONE_ARGUMENT	"%1"
-108720	LRWS REP DB CALL DS ACTION_STEP_FAILED	<CENTER>Dataset action failed</CENTER>
-108719	LRWS REP DB CALL DS ACTION_STEP_SUCCESS	<CENTER>Dataset action was successful</CENTER>
-108718	LRWS MSG_WSE_NOT_INSTALLED	To continue, WSE2 and WSE3 must be installed on your machine. The setup programs for WSE2.0 SP3 and WSE3.0 are included in the [Opentext Performance Engineering installation DVD]\\runner\\Common folder or can be downloaded from the Internet.
-108717	LRWS MSG_AXIS_NOT_EXIST	The Axis toolkit was removed from the installation to prevent security vulnerabilities. To continue working with the Axis toolkit, install it manually.
-108716	LRWS MSG_OPENJDK_NOT_EXIST	OpenJDK32 was removed from the installation. To continue working with the Axis or JMS, please install 32-bit java manually.
-108715	LRWS MSG REPLAY_VERSION	%1 replay version %2 for %3; Toolkit: "%4"; build %5
-108714	LRWS MSG REPLAY_RTS_FILE	Runtime Settings file: "%1"
-108713	LRW MSG REPLAY_VUSER_DIR	Vuser directory: "%1"
-108712	LRW MSG REPLAY_OUTPUT_DIR	Vuser output directory: "%1"
-108711	LRW MSG REPLAY_LOCAL_START_DATE_TIME	LOCAL start date/time : %1
-108710	LRWS MSG SET_OPTION_STEP_STARTED	Set web_service_set_option parameter "%1" value to "%2"
-108709	LRWS MSG SET_OPTION_STEP_FAILURE	web_service_set_option execution failed.
-108708	LRWS MSG SET_OPTION_STEP_INVALID_ARGUMENT	%1 argument is invalid in web_service_set_option.
-108707	LRWS MSG SET_OPTION_STEP_INVALID_VALUE	%1 value is invalid in the specified web_service_set_option %2.
-108706	LRWS MSG SET_OPTION_STEP_SUCCESS	web_service_set_option was successful.
-108705	LRWS SOAPREPLAY_JMS_INVALID_JVM_PATH	The specified JVM path "%1" is not valid; the default path will be used instead.

Error code	Handle	Message\Additional information
wsock_m.h		
7000	ID_PRG_GET_ADDRESS	%1: getting host address from the host name (%2).
9000	ID_LRS_UNKNOWN_ERROR	Error : Unknown error. Error code : %1.
9001	ID_LRS_GENERIC_ERROR	Error : Function execution failed. Error code : %1.
9002	ID_LRS_SOCKET_DOESNT_EXIST	Error : Specified socket %2 doesn't exist. Error code : %1.
9003	ID_LRS_PARAM_FAILED	Error : Parameterization of %2 failed. Error code : %1.
9004	ID_LRS_CREATE_SOCK_FAILED	Error : Unable to create socket %2. Error code : %1.
9005	ID_LRS_INVALID_FUNC_PARAM	Error : %2 parameter is invalid. Error code : %1.
9006	ID_LRS_READ_DATA_FILE_ERR	Error : Unable to read data file. Error code : %1.
9007	ID_LRS_DATA_BUFFER_ERR	Error : Reading of %2 buffer failed. Error code : %1.
9008	ID_LRS_UNKNOWN_HOST	Error : Host %2 is unknown. Error code : %1.
9009	ID_LRS_UNKNOWN_FUNC_PARAM	Error : %2 - unknown function parameter. Error code : %1.
9010	ID_LRS_DELETE_SOCK_FAILED	Error : Unable to delete socket %2. Error code : %1.
9011	ID_LRS_BUFFER_DOESNT_EXIST	Error : Specified buffer %2 doesn't exist. Error code : %1.
9012	ID_LRS_BUF_ALLOC_ERR	Error : Unable to allocate memory for %2. Error code : %1.
9013	ID_LRS_TRANSLATION_ERR	Error : Unable to translate buffer to %2. Error code : %1.
9014	ID_LRS_BUFFER_TYPE_ERR	Error : Wrong type of buffer. Expected buffer type: %2. Error code : %1.
9015	ID_LRS_SAVE_PARAM_ERR	Error : Unable to save to parameter %2. Error code : %1.
9016	ID_LRS_HOST_FIND_ERR	Error : Unable to retrieve %2 hostname for socket. Error code : %1.
9017	ID_LRS_EXIT_BY_TIMEOUT	Error : Timeout expired while trying to %2. Error code : %1.
9018	ID_LRS_SELECT_ERR	Error : Internal "select" error while trying to %2. Error code : %1.
9019	ID_LRS_NON_STREAM_SOCK	Error : Cannot start SSL on non-stream socket %2. Error code : %1.
9020	ID_LRS_NO_SSL_LISTENING	Error : Cannot start SSL on listening socket %2. Error code : %1.
10004	ID_WS_MSG_WSAEINTR	Error : %2 - Interrupted system call. Error code : %1.
10009	ID_WS_MSG_WSAEBADF	Error : %2 - Bad file number. Error code : %1.
10013	ID_WS_MSG_WSAEACCES	Error : %2 - Permission denied. Error code : %1.
10014	ID_WS_MSG_WSAEFAULT	Error : %2 - Bad address. Error code : %1.
10022	ID_WS_MSG_WSAEINVAL	Error : %2 - Invalid argument. Error code : %1.
10024	ID_WS_MSG_WSAEMFILE	Error : %2 - Too many open files. Error code : %1.
10035	ID_WS_MSG_WSAEWOULDBLOCK	Error : %2 - Resource temporarily unavailable. Error code : %1.
10036	ID_WS_MSG_WSAEINPROGRESS	Error : %2 - Operation now in progress. Error code : %1.
10037	ID_WS_MSG_WSAEALREADY	Error : %2 - Operation already in progress. Error code : %1.
10038	ID_WS_MSG_WSAENOTSOCK	Error : %2 - Socket operation on non-socket. Error code : %1.
10039	ID_WS_MSG_WSAEDESTADDRREQ	Error : %2 - Destination address required. Error code : %1.
10040	ID_WS_MSG_WSAEMSGSIZE	Error : %2 - Message too long. Error code : %1.
10041	ID_WS_MSG_WSAEPROTOTYPE	Error : %2 - Protocol wrong type for socket. Error code : %1.
10042	ID_WS_MSG_WSAENOPROTOOPT	Error : %2 - Bad protocol option. Error code : %1.
10043	ID_WS_MSG_WSAEPROTONOSUPPORT	Error : %2 - Protocol not supported. Error code : %1.
10044	ID_WS_MSG_WSAESOCKTNOSUPPORT	Error : %2 - Socket type not supported. Error code : %1.
10045	ID_WS_MSG_WSAEOPNOTSUPP	Error : %2 - Operation not supported on socket. Error code : %1.
10046	ID_WS_MSG_WSAEPFNOSUPPORT	Error : %2 - Protocol family not supported. Error code : %1.
10047	ID_WS_MSG_WSAEAFNOSUPPORT	Error : %2 - Address family not supported by protocol family. Error code : %1.
10048	ID_WS_MSG_WSAEADDRINUSE	Error : %2 - Address already in use. Error code : %1.
10049	ID_WS_MSG_WSAEADDRNOTAVAIL	Error : %2 - Can't assign requested address. Error code : %1.
10050	ID_WS_MSG_WSAENETDOWN	Error : %2 - Network is down. Error code : %1.
10051	ID_WS_MSG_WSAENETUNREACH	Error : %2 - ICMP network unreachable. Error code : %1.
10052	ID_WS_MSG_WSAENETRESET	Error : %2 - Network dropped connection on reset. Error code : %1.
10053	ID_WS_MSG_WSAECONNABORTED	Error : %2 - Software caused connection abort. Error code : %1.
10054	ID_WS_MSG_WSAECONNRESET	Error : %2 - Connection reset by peer. Error code : %1.
10055	ID_WS_MSG_WSAENOBUFS	Error : %2 - No buffer space available. Error code : %1.
10056	ID_WS_MSG_WSAEISCONN	Error : %2 - Socket is already connected. Error code : %1.
10057	ID_WS_MSG_WSAENOTCONN	Error : %2 - Socket is not connected. Error code : %1.
10058	ID_WS_MSG_WSAESHUTDOWN	Error : %2 - Can't send after socket shutdown. Error code : %1.
10059	ID_WS_MSG_WSAETOOMANYREFS	Error : %2 - Too many references. Error code : %1.
10060	ID_WS_MSG_WSAETIMEDOUT	Error : %2 - Connection timed out. Error code : %1.
10061	ID_WS_MSG_WSAECONNREFUSED	Error : %2 - Connection refused. Error code : %1.
10062	ID_WS_MSG_WSAELOOP	Error : %2 - Too many levels of symbolic links. Error code : %1.

Error code	Handle	Message\Additional information
10063	ID_WS_MSG_WSAENAMETOOLONG	Error : %2 - Name too long. Error code : %1.
10064	ID_WS_MSG_WSAEHOSTDOWN	Error : %2 - Host is down. Error code : %1.
10065	ID_WS_MSG_WSAEHOSTUNREACH	Error : %2 - No route to host. Error code : %1.
10066	ID_WS_MSG_WSAENOTEMPTY	Error : %2 - Directory not empty. Error code : %1.
10067	ID_WS_MSG_WSAEPROCLIM	Error : %2 - Too many processes. Error code : %1.
10068	ID_WS_MSG_WSAEUSERS	Error : %2 - WSAEUSERS returned. Error code : %1.
10069	ID_WS_MSG_WSAEDQUOT	Error : %2 - Disk quota exceeded. Error code : %1.
10070	ID_WS_MSG_WSAESTALE	Error : %2 - WSAESTALE returned. Error code : %1.
10071	ID_WS_MSG_WSAEREMOTE	Error : %2 - The object is remote. Error code : %1.
10091	ID_WS_MSG_WSASYSNOTREADY	Error : %2 - Network subsystem is unavailable. Error code : %1.
10092	ID_WS_MSG_WSAVERNOTSUPPORTED	Error : %2 - WINSOCK.DLL version out of range. Error code : %1.
10093	ID_WS_MSG_WSANOTINITIALISED	Error : %2 - Successful WSAStartup not yet performed. Error code : %1.
10101	ID_WS_MSG_WSAEDISCON	Error : %2 - Graceful shutdown in progress. Error code : %1.